

FCC PART 22H, PART 24E  
MEASUREMENT AND TEST REPORT

For

**MAXWEST INTERNATIONAL LIMITED.**

No.1,Longgang Road,Buji,Longgang,ShenzhenCity,Guangdong Province, P.R. China

**FCC ID: 2AEN3UNO**

|   |   |
|---|---|
| <b>Report Type:</b><br>Original Report      | <b>Product Type:</b><br>Mobile Phone  |
| <b>Test Engineer:</b> Allen Qiao            | <i>Allen Qiao</i>   |
| <b>Report Number:</b> RDG150917001-00C      |   |
| <b>Report Date:</b> 2015-09-25              |   |
| <b>Reviewed By:</b> Sula Huang<br>RF Leader | <i>Sula Huang</i>   |
| <b>Test Laboratory:</b>                     | Bay Area Compliance Laboratories Corp. (Dongguan)<br>No.69 Pulongcun, Puxinhu Industrial Zone,<br>Tangxia, Dongguan, Guangdong, China<br>Tel: +86-769-86858888<br>Fax: +86-769-86858891<br><a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a> |

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## TABLE OF CONTENTS

|   |           |
|---|-----------|
| <b>GENERAL INFORMATION.....</b>   | <b>4</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....  | 4         |
| OBJECTIVE .....   | 4         |
| RELATED SUBMITTAL(S)/GRANT(S).....  | 4         |
| TEST METHODOLOGY .....  | 4         |
| TEST FACILITY .....   | 5         |
| <b>SYSTEM TEST CONFIGURATION.....</b>   | <b>6</b>  |
| JUSTIFICATION .....   | 6         |
| EQUIPMENT MODIFICATIONS .....   | 6         |
| SUPPORT EQUIPMENT LIST AND DETAILS .....  | 6         |
| CONFIGURATION OF TEST SETUP .....   | 6         |
| BLOCK DIAGRAM OF TEST SETUP .....   | 7         |
| <b>SUMMARY OF TEST RESULTS .....</b>  | <b>8</b>  |
| <b>FCC §1.1310 &amp; §2.1093- RF EXPOSURE .....</b>   | <b>9</b>  |
| APPLICABLE STANDARD .....   | 9         |
| TEST RESULT .....   | 9         |
| <b>FCC §2.1047 - MODULATION CHARACTERISTIC .....</b>  | <b>10</b> |
| <b>FCC § 2.1046, § 22.913 (A) &amp; § 24.232 (C) - RF OUTPUT POWER.....</b>                     | <b>11</b> |
| APPLICABLE STANDARD .....   | 11        |
| TEST PROCEDURE .....  | 11        |
| TEST EQUIPMENT LIST AND DETAILS.....  | 12        |
| TEST DATA .....   | 12        |
| <b>FCC §2.1049, §22.917, §22.905 &amp; §24.238 - OCCUPIED BANDWIDTH.....</b>                    | <b>14</b> |
| APPLICABLE STANDARD .....   | 14        |
| TEST PROCEDURE .....  | 14        |
| TEST EQUIPMENT LIST AND DETAILS.....  | 14        |
| TEST DATA .....   | 14        |
| <b>FCC §2.1051, §22.917(A) &amp; §24.238(A) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS .....</b> | <b>17</b> |
| APPLICABLE STANDARD .....   | 17        |
| TEST PROCEDURE .....  | 17        |
| TEST EQUIPMENT LIST AND DETAILS.....  | 17        |
| TEST DATA .....   | 17        |
| <b>FCC §2.1053, §22.917 &amp; §24.238 - SPURIOUS RADIATED EMISSIONS .....</b>                   | <b>21</b> |
| APPLICABLE STANDARD .....   | 21        |
| TEST PROCEDURE .....  | 21        |
| TEST EQUIPMENT LIST AND DETAILS.....  | 21        |
| TEST DATA .....   | 22        |
| <b>FCC §22.917(A) &amp; §24.238(A) - BAND EDGES.....</b>  | <b>23</b> |
| APPLICABLE STANDARD .....   | 23        |
| TEST PROCEDURE .....  | 23        |
| TEST EQUIPMENT LIST AND DETAILS.....  | 23        |
| TEST DATA .....   | 23        |
| <b>FCC §2.1055, §22.355 &amp; §24.235 - FREQUENCY STABILITY.....</b>                            | <b>26</b> |
| APPLICABLE STANDARD .....   | 26        |

TEST PROCEDURE .....26  
TEST EQUIPMENT LIST AND DETAILS.....27  
TEST DATA .....27

FINAL

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The *MAXWEST INTERNATIONAL LIMITED.*'s product, model number: *UNO (FCC ID: 2AEN3UNO)* (the "EUT") in this report was a *Mobile Phone(named UNO by appliance)*, which was measured approximately: 11.3 cm (L) x4.7 cm (W) x1.3 cm (H),, rated input voltage: DC 3.7V rechargeable Li-ion battery or DC5V charging from adapter.

Adapter information: maxwest  
Input: AC100-240V, 50/60 Hz;  
Output: DC 5V, 500mAh

*All measurement and test data in this report was gathered from production sample serial number: 150917001 (Assigned by applicant). The EUT was received on 2015-09-18.*

### Objective

This report is prepared on behalf of *MAXWEST INTERNATIONAL LIMITED.* in accordance with: Part 2-Subpart J, Part 22-Subpart H, and Part 24-Subpart E of the Federal Communications Commission's rules.

The objective is to determine compliance with FCC rules for output power, modulation characteristic, occupied bandwidth, spurious emissions at antenna terminal, spurious radiated emission, frequency stability and band edge.

### Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: 2AEN3UNO  
FCC Part 15C DSS submissions with FCC ID: 2AEN3UNO

### Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

Part 22 Subpart H - Public Mobile Services  
Part 24 Subpart E - Personal Communication Services

Applicable Standards: TIA/EIA 603-D-2010.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp.(Dongguan).

### **Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FINVA

## SYSTEM TEST CONFIGURATION

### Justification

The EUT was configured for testing according to TIA/EIA-603-D-2010.

The test items were performed with the EUT operating at testing mode.


### Equipment Modifications

No modification was made to the EUT.


### Support Equipment List and Details

| Manufacturer | Description                          | Model  | Serial Number |
|--------------|--------------------------------------|--------|---------------|
| R&S          | Universal Radio Communication Tester | CMU200 | 109038        |
| N/A          | ANTENNA                              | N/A    | N/A           |

### Configuration of Test Setup



### Block Diagram of Test Setup



**SUMMARY OF TEST RESULTS**

| <b>FCC Rules</b>                         | <b>Description of Test</b>   | <b>Result</b>  |
|--|--|----------------|
| §1.1310, §2.1093                         | RF Exposure  | Compliance     |
| §2.1046;<br>§ 22.913 (a); § 24.232 (c)   | RF Output Power  | Compliance     |
| § 2.1047                                 | Modulation Characteristics   | Not Applicable |
| § 2.1049; § 22.905<br>§ 22.917; § 24.238 | Occupied Bandwidth   | Compliance     |
| § 2.1051,<br>§ 22.917 (a); § 24.238 (a)  | Spurious Emissions at Antenna Terminal                                 | Compliance     |
| § 2.1053<br>§ 22.917 (a); § 24.238 (a)   | Field Strength of Spurious Radiation                                   | Compliance     |
| § 22.917 (a); § 24.238 (a)               | Out of band emission, Band Edge  | Compliance     |
| § 2.1055<br>§ 22.355; § 24.235           | Frequency stability vs. temperature<br>Frequency stability vs. voltage | Compliance     |



---

## **FCC §1.1310 & §2.1093- RF EXPOSURE**

---

### **Applicable Standard**

FCC§1.1310 and §2.1093.

### **Test Result**

Compliant, please refer to the SAR report: RDG150917001-20.

FINAL

## **FCC §2.1047 - MODULATION CHARACTERISTIC**

---

According to FCC § 2.1047(d), Part 22H & 24E, there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

FINAL

## **FCC § 2.1046, § 22.913 (a) & § 24.232 (c) - RF OUTPUT POWER**

### **Applicable Standard**

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (C), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications..

According to §24.232 (d) Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

### **Test Procedure**

#### **GSM/GPRS**

Function: Menu select > GSM Mobile Station > GSM 850/1900

Press Connection control to choose the different menus

Press RESET > choose all the reset all settings

Connection Press Signal Off to turn off the signal and change settings

Network Support > GSM + GPRS or GSM + EGSM

Main Service > Packet Data

Service selection > Test Mode A – Auto Slot Config. off

MS Signal Press Slot Config Bottom on the right twice to select and change the number of time slots and power setting

> Slot configuration > Uplink/Gamma

> 33 dBm for GPRS 850

> 30 dBm for GPRS 1900

BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel

Frequency Offset > + 0 Hz

Mode > BCCH and TCH

BCCH Level > -85 dBm (May need to adjust if link is not stable)

BCCH Channel > choose desire test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]

Channel Type > Off

P0 > 4 dB

Slot Config > Unchanged (if already set under MS signal)

TCH > choose desired test channel

Hopping > Off

Main Timeslot > 3

Network Coding Scheme > CS4 (GPRS)

Bit Stream > 2E9-1 PSR Bit Stream

AF/RF Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input

Connection Press Signal on to turn on the signal and change settings

#### *Radiated method:*

ANSI/TIA 603-D section 2.2.17

**Test Equipment List and Details**

| Manufacturer   | Description               | Model      | Serial Number | Calibration Date | Calibration Due Date |
|----------------|---------------------------|------------|---------------|------------------|----------------------|
| R&S            | EMI Test Receiver         | ESCI       | 100224        | 2015-05-09       | 2016-05-09           |
| Sunol Sciences | Antenna                   | JB3        | A060611-3     | 2014-11-06       | 2017-11-05           |
| HP             | Amplifier                 | 8447E      | 2434A02181    | 2015-09-01       | 2016-09-01           |
| R&S            | Spectrum Analyzer         | FSEM       | DE31388       | 2015-05-09       | 2016-05-09           |
| ETS LINDGREN   | Horn Antenna              | 3115       | 000 527 35    | 2013-09-06       | 2016-09-06           |
| Mini-Circuit   | Amplifier                 | ZVA-213-S+ | 054201245     | 2015-02-19       | 2016-02-19           |
| Giga           | Signal Generator          | 1026       | 320408        | 2015-05-09       | 2016-05-09           |
| EMCO           | Adjustable Dipole Antenna | 3121C      | 9109-753      | N/A              | N/A                  |
| TDK RF         | Horn Antenna              | HRN-0118   | 130 084       | 2013-09-06       | 2016-09-06           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 25.7 °C   |
| <b>Relative Humidity:</b> | 55%       |
| <b>ATM Pressure:</b>      | 100.3 kPa |

*The testing was performed by Allen Qiao on 2015-09-21.*

**Conducted Power****Cellular Band (Part 22H) & PCS Band (Part 24E)**

| Band     | Channel No. | Peak Output Power (dBm) |                |                |                |                |
|----------|-------------|-------------------------|----------------|----------------|----------------|----------------|
|          |             | GSM                     | GPRS 1 TX Slot | GPRS 2 TX Slot | GPRS 3 TX Slot | GPRS 4 TX Slot |
| Cellular | 128         | 31.60                   | 31.32          | 30.31          | 28.26          | 26.31          |
|          | 190         | 31.50                   | 31.11          | 30.01          | 27.87          | 26.01          |
|          | 251         | 31.30                   | 31.05          | 29.76          | 27.55          | 25.67          |
| PCS      | 512         | 29.30                   | 29.28          | 27.11          | 24.91          | 23.05          |
|          | 661         | 29.00                   | 28.98          | 26.62          | 24.38          | 22.41          |
|          | 810         | 28.90                   | 28.91          | 26.37          | 24.08          | 21.91          |

**ERP & EIRP****Part 22H**

| Frequency (MHz)               | Polar (H/V) | Receiver Reading (dB $\mu$ V) | Substituted Method |                        |                 | Absolute Level (dBm) | Limit (dBm) | Margin (dB) |
|-------------------------------|-------------|-------------------------------|--------------------|------------------------|-----------------|----------------------|-------------|-------------|
|                               |             |                               | S.G. Level (dBm)   | Antenna Gain (dBd/dBi) | Cable Loss (dB) |                      |             |             |
| <b>GSM 850_Middle Channel</b> |             |                               |                    |                        |                 |                      |             |             |
| 836.600                       | H           | 94.52                         | 19.6               | 0.0                    | 1               | 18.6                 | 38.50       | 19.9        |
| 836.600                       | V           | 103.43                        | 31.6               | 0.0                    | 1               | 30.6                 | 38.50       | 7.9         |

**Part 24E**

| Frequency (MHz)                | Polar (H/V) | Receiver Reading (dB $\mu$ V) | Substituted Method |                        |                 | Absolute Level (dBm) | Limit (dBm) | Margin (dB) |
|--------------------------------|-------------|-------------------------------|--------------------|------------------------|-----------------|----------------------|-------------|-------------|
|                                |             |                               | S.G. Level (dBm)   | Antenna Gain (dBd/dBi) | Cable Loss (dB) |                      |             |             |
| <b>PCS 1900_Middle Channel</b> |             |                               |                    |                        |                 |                      |             |             |
| 1880.000                       | H           | 87.58                         | 16                 | 11.7                   | 1.4             | 26.3                 | 33.0        | 6.7         |
| 1880.000                       | V           | 89.73                         | 18.3               | 11.7                   | 1.4             | 28.6                 | 33.0        | 4.4         |

**Note:**

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = SG Level - Cable loss + Antenna Gain
- 3) Margin = Limit-Absolute Level

**FCC §2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH**


**Applicable Standard**

FCC §2.1049, §22.917 and §22.905, §24.238.

**Test Procedure**

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The 26 dB & 99% bandwidth was recorded.



**Test Equipment List and Details**

| Manufacturer | Description                          | Model  | Serial Number | Calibration Date | Calibration Due Date |
|--------------|--------------------------------------|--------|---------------|------------------|----------------------|
| R&S          | Spectrum Analyzer                    | FSP 38 | 100478        | 2015-05-09       | 2016-05-09           |
| R&S          | Universal Radio Communication Tester | CMU200 | 109 038       | 2015-05-09       | 2016-05-09           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data**

**Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 26.4 °C   |
| <b>Relative Humidity:</b> | 59 %      |
| <b>ATM Pressure:</b>      | 100.3 kPa |


*The testing was performed by Allen Qiao on 2015-09-22.*

*Test Mode: Transmitting*

*Test Result: Compliant. Please refer to the following table and plots.*


| Band     | Channel No. | Mode | 99% Occupied Bandwidth (kHz) | 26 dB Occupied Bandwidth (kHz) |
|----------|-------------|------|------------------------------|--------------------------------|
| Cellular | 190         | GSM  | 244                          | 310                            |
| PCS      | 661         | PCS  | 244                          | 312                            |

**GMSK 850 Cellular Band**



Date: 22.SEP.2015 18:37:25

### GMSK PCS Band



Date: 22.SEP.2015 18:43:43





## FCC §2.1051, §22.917(a) & §24.238(a) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


### Applicable Standard

FCC §2.1051, §22.917(a) and §24.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

### Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. Sufficient scans were taken to show any out of band emissions up to 10<sup>th</sup> harmonic.



### Test Equipment List and Details

| Manufacturer | Description                          | Model  | Serial Number | Calibration Date | Calibration Due Date |
|--------------|--------------------------------------|--------|---------------|------------------|----------------------|
| R&S          | Spectrum Analyzer                    | FSP 38 | 100478        | 2015-05-09       | 2016-05-09           |
| R&S          | Universal Radio Communication Tester | CMU200 | 109 038       | 2015-05-09       | 2016-05-09           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data



#### Environmental Conditions

|                           |         |
|---------------------------|---------|
| <b>Temperature:</b>       | 26.4 °C |
| <b>Relative Humidity:</b> | 59 %    |
| <b>ATM Pressure:</b>      | 100 kPa |



*The testing was performed by Allen Qiao on 2015-09-24.*


Please refer to the following plots.

**GSM850\_Middle Channel**



PCS 1900\_ Middle Channel





## **FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS**

### **Applicable Standard**

FCC § 2.1053, §22.917 and § 24.238.

### **Test Procedure**

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = 10 lg (TXpwr in Watts/0.001) – the absolute level

Spurious attenuation limit in dB = 43 + 10 Log<sub>10</sub> (power out in Watts)

### **Test Equipment List and Details**

| <b>Manufacturer</b> | <b>Description</b>        | <b>Model</b> | <b>Serial Number</b> | <b>Calibration Date</b> | <b>Calibration Due Date</b> |
|---------------------|---------------------------|--------------|----------------------|-------------------------|-----------------------------|
| R&S                 | EMI Test Receiver         | ESCI         | 100224               | 2015-05-09              | 2016-05-09                  |
| Sunol Sciences      | Antenna                   | JB3          | A060611-3            | 2014-07-28              | 2017-07-27                  |
| HP                  | Amplifier                 | 8447E        | 2434A02181           | 2015-09-01              | 2016-09-01                  |
| R&S                 | Spectrum Analyzer         | FSEM         | DE31388              | 2015-05-09              | 2016-05-09                  |
| ETS LINDGREN        | Horn Antenna              | 3115         | 000 527 35           | 2015-09-06              | 2018-09-06                  |
| Mini-Circuit        | Amplifier                 | ZVA-213-S+   | 054201245            | 2015-02-19              | 2016-02-19                  |
| Giga                | Signal Generator          | 1026         | 320408               | 2015-05-09              | 2016-05-09                  |
| EMCO                | Adjustable Dipole Antenna | 3121C        | 9109-753             | N/A                     | N/A                         |
| TDK RF              | Horn Antenna              | HRN-0118     | 130 084              | 2015-09-06              | 2018-09-06                  |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 27.3 °C   |
| <b>Relative Humidity:</b> | 46 %      |
| <b>ATM Pressure:</b>      | 100.4 kPa |

The testing was performed by Allen Qiao on 2015-09-16.

EUT Operation Mode: Transmitting

**Cellular Band****30 MHz-10 GHz:**

| Frequency (MHz)      | Polar (H/V) | Receiver Reading (dB $\mu$ V) | Substituted Method |                        |                 | Absolute Level (dBm) | Limit (dBm) | Margin (dB) |
|----------------------|-------------|-------------------------------|--------------------|------------------------|-----------------|----------------------|-------------|-------------|
|                      |             |                               | S.G. Level (dBm)   | Antenna Gain (dBd/dBi) | Cable Loss (dB) |                      |             |             |
| Frequency: 836.6 MHz |             |                               |                    |                        |                 |                      |             |             |
| 1673.200             | H           | 70.77                         | -30.3              | 10.6                   | 1.5             | -21.2                | -13.0       | 8.2         |
| 1673.200             | V           | 64.02                         | -37.4              | 10.6                   | 1.5             | -28.3                | -13.0       | 15.3        |
| 2509.800             | H           | 73.43                         | -24.6              | 13.1                   | 2.8             | -14.3                | -13.0       | 1.3         |
| 2509.800             | V           | 69.07                         | -28                | 13.1                   | 2.8             | -17.7                | -13.0       | 4.7         |

For below 1GHz, all spurious emissions are 20dB below the limit or are on the system noise floor level.

**PCS Band****30 MHz-20 GHz:**

| Frequency (MHz)     | Polar (H/V) | Receiver Reading (dB $\mu$ V) | Substituted Method |                        |                 | Absolute Level (dBm) | Limit (dBm) | Margin (dB) |
|---------------------|-------------|-------------------------------|--------------------|------------------------|-----------------|----------------------|-------------|-------------|
|                     |             |                               | S.G. Level (dBm)   | Antenna Gain (dBd/dBi) | Cable Loss (dB) |                      |             |             |
| Frequency: 1880 MHz |             |                               |                    |                        |                 |                      |             |             |
| 3760.000            | H           | 55.64                         | -38.7              | 13.8                   | 2.9             | -27.8                | -13.0       | 14.8        |
| 3760.000            | V           | 57.36                         | -35.7              | 13.8                   | 2.9             | -24.8                | -13.0       | 11.8        |

For below 1GHz, all spurious emissions are 20dB below the limit or are on the system noise floor level.

Note:

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = SG Level - Cable loss + Antenna Gain
- 3) Margin = Limit - Absolute Level

## FCC §22.917(a) & §24.238(a) - BAND EDGES

### Applicable Standard


According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

### Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency.



### Test Equipment List and Details

| Manufacturer | Description                          | Model  | Serial Number | Calibration Date | Calibration Due Date |
|--------------|--------------------------------------|--------|---------------|------------------|----------------------|
| R&S          | Spectrum Analyzer                    | FSP 38 | 100478        | 2015-05-09       | 2016-05-09           |
| R&S          | Universal Radio Communication Tester | CMU200 | 109 038       | 2015-05-09       | 2016-05-09           |

**\* Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions


|                    |           |
|--------------------|-----------|
| Temperature:       | 26.4 °C   |
| Relative Humidity: | 59 %      |
| ATM Pressure:      | 100.3 kPa |

*The testing was performed by Allen Qiao on 2015-09-22.*

*Test Mode: Transmitting*


*Test Result: Compliant. Please refer to the following plots.*

### GSM 850, Left Band Edge



Date: 22.SEP.2015 18:38:40


### GSM 850, Right Band Edge



Date: 22.SEP.2015 18:39:33




### GSM 1900, Left Band Edge



Date: 22.SEP.2015 18:44:33

### GSM 1900, Right Band Edge



Date: 22.SEP.2015 18:45:11

## FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY

### Applicable Standard

FCC § 2.1055 (a), § 2.1055 (d), §22.355, §24.235

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

| Frequency Range (MHz) | Base, fixed (ppm) | Mobile ≤ 3 watts (ppm) | Mobile ≤ 3 watts (ppm) |
|-----------------------|-------------------|------------------------|------------------------|
| 25 to 50              | 20.0              | 20.0                   | 50.0                   |
| 50 to 450             | 5.0               | 5.0                    | 50.0                   |
| 450 to 512            | 2.5               | 5.0                    | 5.0                    |
| 821 to 896            | 1.5               | 2.5                    | 2.5                    |
| 928 to 929.           | 5.0               | N/A                    | N/A                    |
| 929 to 960.           | 1.5               | N/A                    | N/A                    |
| 2110 to 2220          | 10.0              | N/A                    | N/A                    |


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

### Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: An external variable DC power supply was connected to the battery terminals of the equipment under test. The voltage was set from 85% to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the battery end point. The output frequency was recorded for each battery voltage.



**Test Equipment List and Details**

| Manufacturer | Description                          | Model  | Serial Number | Calibration Date | Calibration Due Date |
|--------------|--------------------------------------|--------|---------------|------------------|----------------------|
| Dongzhixu    | High Temperature Test Chamber        | DP1000 | 201105083-3   | 2015-08-01       | 2016-08-01           |
| R&S          | Universal Radio Communication Tester | CMU200 | 109 038       | 2015-05-09       | 2016-05-09           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data**

**Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 25.7 °C   |
| <b>Relative Humidity:</b> | 55%       |
| <b>ATM Pressure:</b>      | 100.3 kPa |

The testing was performed by Allen Qiao on 2015-09-22.

**Cellular Band (Part 22H)**

| GMSK, Middle Channel, $f_c = 836.6$ MHz |                 |                 |                 |       |
|---|-----------------|-----------------|-----------------|-------|
| Temperature                             | Voltage         | Frequency Error | Frequency Error | Limit |
| °C                                      | V <sub>DC</sub> | Hz              | ppm             | ppm   |
| -30                                     | 3.7             | -13             | -0.016          | 2.5   |
| -20                                     |                 | -11             | -0.013          |       |
| -10                                     |                 | -14             | -0.017          |       |
| 0                                       |                 | -15             | -0.018          |       |
| 10                                      |                 | -12             | -0.014          |       |
| 20                                      |                 | -18             | -0.022          |       |
| 30                                      |                 | -11             | -0.013          |       |
| 40                                      |                 | -15             | -0.018          |       |
| 50                                      |                 | -16             | -0.019          |       |
| 25                                      |                 | 3.5             | -19             |       |
|   | 4.2             | -17             | -0.020          |       |

**PCS Band (Part 24E)**

| <b>GMSK, Middle Channel, <math>f_c = 1880.0</math> MHz</b> |                       |                        |                        |               |
|--|-----------------------|------------------------|------------------------|---------------|
| <b>Temperature</b>   | <b>Voltage</b>        | <b>Frequency Error</b> | <b>Frequency Error</b> | <b>Result</b> |
| <b>°C</b>  | <b>V<sub>DC</sub></b> | <b>Hz</b>              | <b>ppm</b>             |               |
| -30  | 3.7                   | -14                    | -0.007                 | Compliance    |
| -20  |                       | -15                    | -0.008                 |               |
| -10  |                       | -11                    | -0.006                 |               |
| 0  |                       | -14                    | -0.007                 |               |
| 10   |                       | -19                    | -0.010                 |               |
| 20   |                       | -12                    | -0.006                 |               |
| 30   |                       | -10                    | -0.005                 |               |
| 40   |                       | -18                    | -0.010                 |               |
| 50   |                       | -10                    | -0.005                 |               |
| 25   |                       | 3.5                    | -16                    |               |
|  | 4.2                   | -11                    | -0.006                 |               |

**\*\*\*\*\* END OF REPORT \*\*\*\*\***