

RF exposure report

For

Shenzhen Imaginevision Technology Limited

1205,Block A,Cadre headquarter center,168 tongsha
road,xili,Nanshan,Shenzhen,china

FCC ID:2AENNUHD

Trade:Z

This Report Concerns: Original Report	Equipment Type: 4K UHD video camera
Test Engineer:	Lisa Chen <i>Lisa Chen</i>
Report No.:	BSL20150723-2
Receive EUT Date/Test Date:	July 13, 2015/ July 13- July 23, 2015
Reviewed By:	Mike moo <i>Mike moo</i>
Prepared By:	BSL Testing Co.,LTD. NO. 24, ZH Park, Nantou, Shenzhen, 518000 China Tel: 86- 755-26508703 Fax: 86- 755-26508703

FCC §15.247 (i) & §2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance v05r02

Result

According to FCC KDB 447498 D01 General RF Exposure Guidance v05r02 generic portable criteria

The distance between antenna and test point is 5 mm

The max. technical average output power:9.15 dBm=8.222 mW)

According to the Appendix A of KDB 447498 D01 General RF Exposure Guidance v05r02, the exclusion thresholds for 2450 MHz is 10 mW.

Conclusion:

The max. technical average output power is 8.222 mW <the exclusion thresholds 10 mW, so stand-alone SAR evaluation is not required.