



SAR exemption evaluation

Applicant	Montblanc-Simplo GmbH
FCC ID	2AENP-MBTW4810
Product	Montblanc TWIN
Brand	Montblanc
Marketing Name	MBTW-4810
Model	MBTW-4810
Report No.	RXA1712-0445SAR01R1
Issue Date	June 6, 2018

Jiang peng Lan

Approved by: Jiangpeng Lan

Kai Xu

Reviewed by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Conducted Power

Network Standards	Carrier frequency (MHz)	Output Power (dBm)
Bluetooth (Low Energy)	2402	-2.01
	2440	-2.31
	2480	-1.89

Per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Bluetooth	Distance (mm)	MAX Power (dBm)	Frequency (MHz)	Ratio	Evaluation
Body	5	-1.89	2480	0.20	No
Limb	5	-1.89	2480	0.20	No