

RASTAR GROUP

# TEST REPORT

**SCOPE OF WORK**

FCC TESTING— MODEL: 80445A52019(98340)

**REPORT NUMBER**

GZHH00440229-001

**ISSUE DATE**

April 6, 2022

**PAGES**

26

**DOCUMENT CONTROL NUMBER**

FCC ID 249\_C

© 2017 INTERTEK



**RASTAR GROUP**

Application for Certification

**FCC ID: 2AENTXH804000TX****Model R/C Car****Model: 80445A52019(98340)  
Additional Model: See Page 5**

2.4GHz Transceiver

Report No.: GZHH00440229-001

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-20]

Prepared and Checked by:

Approved by:

Sign on file

*Maura Wang*  
Engineer

---

*Peter Kang*  
Technical Supervisor  
Date: April 6, 2022

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**Intertek Testing Service Shenzhen Ltd. Longhua Branch**

101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community GuanHu Subdistrict, LongHua District, Shenzhen, People's Republic of China  
Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751

**MEASUREMENT/TECHNICAL REPORT**

This report concerns (check one:)      Original Grant       Class II Change

Equipment Type: DXX - Part 15 Low Power Communication Device Transmitter

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)?      Yes       No

If yes, defer until: \_\_\_\_\_  
date

Company Name agrees to notify the Commission by: \_\_\_\_\_  
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37?      Yes       No

If no, assumed Part 15, Subpart C for intentional radiator – the new 47 CFR [10-1-20 Edition] provision.

Report prepared by:

Maura Wang  
Intertek Testing Services Shenzhen Ltd. Longhua Branch  
101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing  
Community GuanHu Subdistrict, LongHua District, Shenzhen,  
People's Republic of China  
Tel / Fax: 86-755-8601 6288/86-755-8601 6751

## Table of Contents

<b>1.0 Summary of Test Result</b> .....	4
<b>2.0 General Description</b> .....	5
2.1 Product Description .....	5
2.2 Related Submittal(s) Grants .....	7
2.3 Test Methodology .....	7
2.4 Test Facility .....	7
<b>3.0 System Test Configuration</b> .....	8
3.1 Justification .....	8
3.2 EUT Exercising Software .....	8
3.3 Special Accessories .....	8
3.4 Equipment Modification .....	8
3.5 Measurement Uncertainty .....	8
3.6 Support Equipment List and Description .....	8
<b>4.0 Emission Results</b> .....	9
4.1 Radiated Test Results .....	9
4.1.1 Field Strength Calculation .....	9
4.1.2 Radiated Emission Configuration Photograph .....	10
4.1.3 Radiated Emissions .....	10
4.1.4 Transmitter Spurious Emissions .....	13
<b>5.0 Equipment Photographs</b> .....	17
<b>6.0 Product Labelling</b> .....	17
<b>7.0 Technical Specifications</b> .....	17
<b>8.0 Instruction Manual</b> .....	17
<b>9.0 Miscellaneous Information</b> .....	18
9.1 Bandedge Plot .....	18
9.2 20dB Bandwidth .....	20
9.3 Discussion of Pulse Desensitization .....	21
9.4 Calculation of Average Factor .....	21
9.5 Emissions Test Procedures .....	24
<b>10.0 Test Equipment List</b> .....	26

## 1.0 Summary of Test Result

Applicant: RASTAR GROUP

Applicant Address: Xinghui Industrial Park, Xiadao Road,Shanghua,Chenghai,Shantou,GuangDong,China.

Manufacturer: RASTAR GROUP

Manufacturer Address: Xinghui Industrial Park, Xiadao Road,Shanghua,Chenghai,Shantou,GuangDong,China.

MODEL: 80445A52019(98340)

FCC ID: 2AENTXH804000TX

Test Specification	Reference	Results
Transmitter Radiated Emission Bandedge	15.249 &15.209 &15.205	Pass
20dB Bandwidth	15.215(c)	Pass

Notes: The EUT uses an Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

## 2.0 General Description

### 2.1 Product Description

The equipment under test (EUT) is an Model R/C Car operating at 2.4G Band. The EUT can be powered by DC 3.0V (2 x 1.5V AA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna

Modulation Type: GFSK

Antenna Gain: 0dBi

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

The additional controller Models are the same as the Model: 80445A52019(98340) in hardware and electrical aspect. The difference in appearance, model number and names serve as marketing strategy.

Additional name:	Additional model:
BMW i4	80445A52019 (98340)
BMW i8	80442447986 (71040-1)
BMW M4 Coupe	80442447987 (70940-1)
BMW i8	80442447986(71040)
BMW M4 Coupe	80442447987(70940)
BMW Z4	80442447988(40340)
BMW 6 Series	80442454831(42640)
BMW i8	71070
Ferrari LaFerrari	50160
Lamborghini Huracan STO	98760
Lamborghini Sián FKP 37	97760
Lamborghini Sián FKP 37	97700
Bugatti Divo	98000
Bugatti Divo	98060
BMW i4	98300
BMW i4	98340
BMW i4	98360
Mercedes-Benz F1 W11	98400
Mercedes-Benz F1 W11	98460
Ferrari SF90 Stradale	97300
Ferrari FXX K EVO	79200
Ferrari FXX K EVO	79200-6
McLaren Senna	96600
McLaren Senna	96660
BMW M8 GTE	97100
BMW i8	71040-1
BMW Z4	40340-1
BMW 6 Series	42640-1
BMW M4 Coupe	70940-1
Lamborghini Aventador LP700-4	52600
Porsche GT3 RS	42800-8
Lamborghini Aventador LP700	43000-8
Ferrari 458 Italia	47300-8
Audi R8 LMS	47510-8
Mercedes SLS	47600-8
Range Rover Evoque	47900-8

BMW M3	48000-8
BMW I8	49600-8
Ferrari LaFerrari	50100-8
Ferrari 458 Speciale A	73400-8
JEEP Wrangler Rubicon	79400
JEEP Wrangler Rubicon	79400-1
JEEP Wrangler Rubicon	79410
BMW I8	95500
BMW Z4 Roadster	95600
BMW Z4 Roadster	95610
Mercedes-Benz G63	95700
Lamborghini Aventador SVJ Performance	96000
Lamborghini Aventador SVJ Performance	96010
Lamborghini Aventador SVJ Performance	96010-6
MINI COOPER S	21800
LANDROVER DISCOVERY 3	21900
Audi Q7	27400
Range Rover Sport	28200
Mercedes-Benz G55 AMG	30400
BMW X6	31400
Volvo XC60	31600
Pagani Zonda R	38110
Murcielago LP670-4	38900
Murcielago LP670-4	38901
BMW Z4	40300
Mercedes-Benz SLR	42400
BMW 6 Series	42600
Porsche GT3	42800
Porsche Cayenne Turbo	42900
Aventador LP700	43000
Ferrari 599 GTO	47100
Ferrari California	47200
Ferrari 458 Italia	47300
AUDI R8	47500
AUDI R8 LMS Performance	47510
Mercedes-Benz SLS AMG	47600
Porsche 911 Carrera S	47700
Range Rover Evoque	47900
BMW M3	48000
Ferrari F12	49100
Lamborghini Sesto	49200
Ford Shelby GT500	49400
BMW I8	49600
BMW I8	49600-11
Range Rover Sport 2013 Version	49700
Bentley Continental GT speed convertible	49900
Ferrari LaFerrari	50100
Ferrari F1	57400
Lamborghini Aventador J	57500
Lamborghini Aventador J	57500-6
Bugatti Grand Sport Vitesse	70400
Bentley Continental GT3	70600
PORSCHE 918 Spyder	70700
PORSCHE 918 Spyder Performance	70710
Lamborghini HURACÁN LP 610-4	70800

BMW M4 Coupe	70900
BMW I8	71000
BMW I8	71060
BMW I8	71060-1
BMW I8	71060-2
BMW I8	71000-6
BMW I8	71010
Mini Countryman	72500
Lamborghini URUS	73000
Porsche Macan	73300
Ferrari 458 Speciale A	73400
Volvo XC90	73700
Mercedes AMG GT	74000
Mercedes AMG GT	74010
Mercedes AMG GT3 Performance	74100
AUDI R8 2015 Version	74400

## 2.2 Related Submittal(s) Grants

This is an application for certification of controller unit for the Model R/C Car, and the corresponding receiver unit which associated with this EUT is subjected to FCC SDOC and FCC certification with FCC ID: 2AENTXH983401RX.

## 2.3 Test Methodology

Radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). Radiated emission measurement was performed in Semi-anechoic chamber. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

## 2.4 Test Facility

The Semi-anechoic chamber used to collect the radiated data is **Intertek Testing Services Shenzhen Ltd. Longhua Branch** and located at 101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community GuanHu Subdistrict, LongHua District, Shenzhen, People's Republic of China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: CN1188).



### 3.0 System Test Configuration

#### 3.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The EUT was powered by DC 3.0V (2 x 1.5V AA batteries) during the test, only the worst data was reported in this report.

For maximizing emissions below 30 MHz, the EUT was rotated through 360°, the bottom of the loop antenna was placed 1 meter above the ground, and the antenna polarization was changed. For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Section 4.

The EUT was operated standalone and placed in the central of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on a turn table, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

#### 3.2 EUT Exercising Software

There was no special software to exercise the device.

#### 3.3 Special Accessories

No special accessories used.

#### 3.4 Equipment Modification

Any modifications installed previous to testing by RASTAR GROUP will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd Longhua Branch.

#### 3.5 Measurement Uncertainty

When determining the test conclusion, the Measurement Uncertainty of test has been considered.

#### 3.6 Support Equipment List and Description

Description	Manufacturer	Model No.
N/A	N/A	N/A

## 4.0 Emission Results

Data is included worst-case configuration (the configuration which resulted in the highest emission levels).

### 4.1 Radiated Test Results

A sample calculation, configuration photographs and data tables of the emissions are included.

#### 4.1.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

Where

- FS = Field Strength in dB $\mu$ V/m
- RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB
- PD = Pulse Desensitization in dB
- AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

Assume a receiver reading of 62.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

$$\begin{aligned} RA &= 62.0 \text{ dB}\mu\text{V} \\ AF &= 7.4 \text{ dB} \\ CF &= 1.6 \text{ dB} \\ AG &= 29.0 \text{ dB} \\ PD &= 0 \text{ dB} \\ AV &= -10 \text{ dB} \\ FS &= 62 + 7.4 + 1.6 - 29 + 0 = 42 \text{ dB}\mu\text{V/m} \end{aligned}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm} [(42 \text{ dB}\mu\text{V/m})/20] = 125.9 \mu\text{V/m}$$

## 4.1.2 Radiated Emission Configuration Photograph

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

## 4.1.3 Radiated Emissions

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Worst Case Radiated Emission  
at  
501.298750 MHz

Judgement: Passed by 25.6 dB

### ***TEST PERSONNEL:***

*Sign on file*

Maura Wang, Engineer  
*Typed/Printed Name*

March 22, 2022  
*Date*


Applicant: RASTAR GROUP

Date of Test: March 22, 2022

Model: 80445A52019(98340)

Worst Case Operating Mode: Transmitting(2410.000MHz)

ANT Polarity: Horizontal



Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
290.081250	13.7	1000.0	120.000	H	16.0	32.3	46.0
336.641250	15.6	1000.0	120.000	H	17.7	30.4	46.0
501.298750	20.5	1000.0	120.000	H	22.0	25.6	46.0

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. QuasiPeak (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Limit Line (dBuV/m) – Level (dBuV/m)


Applicant: RASTAR GROUP

Date of Test: March 22, 2022

Model: 80445A52019(98340)

Worst Case Operating Mode: Transmitting(2410.000MHz)

ANT Polarity: Vertical



Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
148.218750	12.3	1000.0	120.000	V	11.3	31.2	43.5
154.281250	12.1	1000.0	120.000	V	11.7	31.4	43.5
160.343750	10.5	1000.0	120.000	V	12.1	33.0	43.5

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. QuasiPeak (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Limit Line (dBμV/m) – Level (dBμV/m)

## 4.1.4 Transmitter Spurious Emissions (Radiated)

Worst Case Radiated Emission  
at  
2483.500 MHz

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 6.5 dB

**TEST PERSONNEL:**

*Sign on file*

Maura Wang, Engineer  
*Typed/Printed Name*

March 22, 2022  
*Date*

Applicant: RASTAR GROUP  
 Date of Test: March 22, 2022  
 Model: 80445A52019(98340)  
 Worst Case Operating Mode: Transmitting

Table 1

**Radiated Emissions**  
(2410 MHz)

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Peak Limit at 3m (dBµV/m)	Margin (dB)
Horizontal	2410.000	105.8	36.7	28.1	97.2	114.0	-16.8
Horizontal	4820.000	40.5	36.7	35.5	39.3	74.0	-34.7

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (-dB)	Net at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
Horizontal	2410.000	105.8	36.7	28.1	22.9	74.3	94.0	-19.7
Horizontal	4820.000	40.5	36.7	35.5	22.9	16.4	54.0	-37.6

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna is used for the emission over 1000MHz.

Applicant: RASTAR GROUP  
 Date of Test: March 22, 2022  
 Model: 80445A52019(98340)  
 Worst Case Operating Mode: Transmitting

Table 2

**Radiated Emissions**  
 (2442 MHz)

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Peak Limit at 3m (dBµV/m)	Margin (dB)
Horizontal	2442.000	107.9	36.7	28.3	99.5	114.0	-14.5
Horizontal	4884.000	39.5	36.7	35.7	38.5	74.0	-35.5

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (-dB)	Net at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
Horizontal	2442.000	107.9	36.7	28.3	22.9	76.6	94.0	-17.4
Horizontal	4884.000	39.5	36.7	35.7	22.9	15.6	54.0	-38.4

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna is used for the emission over 1000MHz.



Applicant: RASTAR GROUP  
 Date of Test: March 22, 2022  
 Model: 80445A52019(98340)  
 Worst Case Operating Mode: Transmitting

Table 3

**Radiated Emissions**  
 (2473 MHz)

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBµV/m)	Peak Limit at 3m (dBµV/m)	Margin (dB)
Horizontal	2473.000	106.3	36.7	28.5	98.1	114.0	-15.9
Horizontal	4946.000	39.0	36.7	35.9	38.2	74.0	-35.8

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (-dB)	Net at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
Horizontal	2473.000	106.3	36.7	28.5	22.9	75.2	94.0	-18.8
Horizontal	4946.000	39.0	36.7	35.9	22.9	15.3	54.0	-38.7

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna is used for the emission over 1000MHz.

## 5.0 Equipment Photographs

For electronic filing, the photographs of the tested EUT are saved with filename: external photos.pdf & internal photos.pdf.

## 6.0 Product Labelling

For electronic filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

## 7.0 Technical Specifications

For electronic filing, the block diagram and schematics of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

## 8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

## 9.0 Miscellaneous Information

This miscellaneous information includes details of the measured bandedge, 20dB Bandwidth, the test procedure and calculation of factor such as pulse desensitization.


### 9.1 Bandedge Plot

The test plots are attached as below. From the plot, the field strength of any emissions outside of the specified frequency band are attenuated to the general radiated emission limits in section 15.209. It fulfils the requirement of 15.249(d).

#### Peak Measurement

Restricted-band band-edge tests shall be performed as radiated measurements, i.e (Band-edge Plot).

#### (i) Lower channel 2410.000 MHz:




Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	2400.000	64.3	36.7	28.1	55.7	74.0	-18.3

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	2400.000	52.8	36.7	28.1	44.2	54.0	-9.8

The resultant field strength meets the general radiated emission limit in section

15.209, which does not exceed 74dB $\mu$ v/m (Peak Limit) and 54dB $\mu$ v/m (Average Limit).

**(ii) Upper channel 2473.000 MHz:**





Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	2483.500	64.8	36.8	29.1	57.1	74.0	-16.9

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	2483.500	55.2	36.8	29.1	47.5	54.0	-6.5

The resultant field strength meets the general radiated emission limit in section 15.209, which does not exceed 74dB $\mu$ v/m (Peak Limit) and 54dB $\mu$ v/m (Average Limit).

## 9.2 20dB Bandwidth

Pursuant to FCC part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered. The test plots are reported as below.



## 9.3 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period ( $T_{eff}$ ) is approximately 869.6 $\mu$ s for a digital "1" bit, as shown in the plots of Section 9.4. With a resolution bandwidth (3 dB) of 100 kHz, the pulse desensitivity factor was 0 dB.

## 9.4 Calculation of Average Factor

Averaging factor in dB =  $20 \log(\text{duty cycle})$

The specification for output field strengths in accordance with the FCC rules specify measurements with an average detector. During testing, a spectrum analyzer incorporating a peak detector was used. Therefore, a reduction factor can be applied to the resultant peak signal level and compared to the limit for measurement instrumentation incorporating an average detector.

The time period over which the duty cycle is measured is 100 milliseconds, or the repetition cycle, whichever is a shorter time frame. The worst case (highest percentage on) duty cycle is used for the calculation. The duty cycle is measured by placing the spectrum analyzer in zero scan (receiver mode) and linear mode at maximum bandwidth (3 MHz at 3 dB down) and viewing the resulting time domain signal output from the analyzer on a Tektronix oscilloscope. The oscilloscope is used because of its superior time base and triggering facilities.

The duty cycle is simply the on-time divided by the period:



The duration of one cycle = 12.087ms


Effective period of the cycle =  $869.6\mu\text{s} \times 1 = 0.8696\text{ms}$

DC =  $0.8696\text{ms} / 12.087\text{ms} = 0.0719$  or 7.19%

Therefore, the averaging factor is found by  $20 \log_{10}(0.0719) = -22.9\text{dB}$

The test plots are attached as below.







## 9.5 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.10 - 2013.

The transmitting equipment under test (EUT) is placed on a styrene turntable which is four feet in diameter and approximately 0.8 meter up to 1GHz and 1.5 meter above 1GHz in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Section 9.4.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

## 9.5 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Section 9.2). Above 1000 MHz, a resolution bandwidth of 1 MHz is used, RBW 5MHz used for fundamental emission.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

**10.0 Test Equipment List**

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ061-13	BiConiLog Antenna	ETS	3142E	00217919	10-Jun-2019	10-Jun-2022
SZ185-01	EMI Receiver	R&S	ESCI	100547	12-Jul-2021	12-Jul-2022
SZ061-09	Horn Antenna	ETS	3115	00092346	17-Oct-2020	17-Oct-2022
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	18-May-2021	18-May-2023
SZ061-15	Double-Ridged Waveguide Horn Antenna	ETS	3116C-PA	00224718	1-Nov-2020	1-Nov-2022
SZ056-06	Spectrum Analyzer	R&S	FSV40	101101	20-Dec-2021	20-Dec-2022
SZ181-04	Preamplifier	Agilent	8449B	3008A02474	10-May-2021	10-May-2022
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	12-Dec-2021	12-Dec-2024
SZ062-02	RF Cable	RADIALL	RG 213U	--	1-Nov -2021	1-May-2022
SZ062-05	RF Cable	RADIALL	0.04-26.5GHz	--	1-Nov -2021	1-May-2022
SZ062-12	RF Cable	RADIALL	0.04-26.5GHz	--	1-Nov -2021	1-May-2022
SZ067-04	Notch Filter	Micro-Tronics	BRM5070 2-02	--	11-May-2021	11-May-2022