

MPE Test Report

Report No.: AGC01284180501FH07

FCC ID : 2AEOCPC202

PRODUCT

DESIGNATION

: CB RADIO

BRAND NAME : PRESIDENT

TEST MODEL : BILL FCC

CLIENT: President Electronics USA

DATE OF ISSUE : May 22, 2018

STANDARD(S) : CFR 47 Part 2.1091

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

CAUTION: This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true www.ago. gent.com.

Attestation of Global Compliance

Tel: +86-755 2908 1955 Fax: +86-755 2600 8484 E-mail: agc@agc-cert.com @ 400 089 2118 Add: 2/F., Building 2, No.1-4,Chaxi Sanwei Technical Industrial Park,Gushu, Xixiang, Baoan District, Shenzhen, Guangdong China



Page 2 of 9

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	May 22, 2018	Valid	Initial Release

The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by KGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.agc.gett.com.

Attestation of Global Compliance



Page 3 of 9

TABALE OF CONTENTS

1. TEST RESULT CERTIFICATION		4
2. TECHNICAL INFORMATION		
3. RF EXPOSURE MEASUREMENT	The second secon	
3.1 INTRODUCTION		
3.2 FCC LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)	B. The S. T. T. T.	o Marine de Company
4. CLASSIFICATION OF THE ASSESSMENT METHODS	<u></u>	
5. EUT OPERATION CONDITION		
6. TEST RESULTS	E AND COLOR	Julian of Car

The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.cett.com.



Page 4 of 9

1. TEST RESULT CERTIFICATION

Annliagnation of columbia	President Electronics USA				
Applicant:	1007 Collier Center Way, Naples, Florida 34110, USA				
Manufacturer:	GROUPE PRESIDENT ELECTRONICS				
ivianuiacturer:	ROUTE DE SETE, BP100 34540 BALARUC-LES-BAINS FRANCE				
Product Designation:	CB RADIO				
Brand Name:	PRESIDENT				
Test Model	BILL FCC				
Hardware Version	BILL-FCC-RF-V2				
Software Version	V1.0				
Date of Test:	May16, 2018 to May 22, 2018				

We Attestation of Global Compliance (Shenzhen) Co., for compliance with the requirements set forth in the CFR 47 Part 2.1091. The results of testing in this report apply to the product/system which was tested only.

Steven Zhou Steven Zhou Steven Zhou Steven Zhou (Zhou Pengyun) May .22, 2018

Approved By

Forrest Lei(Lei Yonggang) May .22, 2018

Authorized Officer

The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true; //www.agc.gett.com.

Attestation of Global Compliance



Page 5 of 9

2. TECHNICAL INFORMATION

Note: the following data is based on the information by the applicant.

EUT DESCRIPTION

The EUT is a CB RADIO designed for voice communication. It is designed by way of utilizing the AM modulation achieves the system operating.

A major technical description of EUT is described as following:

Operation Frequency	26.965 MHz -27.405 MHz
Modulation	AM AM
Output power	4W
Antenna type	Detachable
Antenna gain	0dBi
Power Supply	DC12V

The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 6 of 9

3. RF EXPOSURE MEASUREMENT


3.1 INTRODUCTION

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

The 1992 ANSI/IEEE standard (See Listed limit table) specifies a minimum separation distance of 20 cm for performing reliable field measurements to determine adherence to MPE limits.

If the minimum separation distance between a transmitter and nearby persons is more than 20 cm under normal operating conditions, compliance with MPE limits may be determined at such distance from the transmitter. When applicable, operation instructions and prominent warning labels may be used to alert the exposed persons to maintain a specified distance from the transmitter or to limit their exposure durations and usage conditions to ensure compliance.

The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.





Page 7 of 9

3.2 FCC LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time E ², H ² or S (Minutes)
0.3 1.34	614	1.63	(100)*	30
1.34 30	824/f	2.19/f	(180/f ²)*	30
30 300	27.5	0.073	0.2	30
300 1500	· 12	The Company - 0 Mar.	f/1500	30
1500 100,000	S # Jahor of Clobata	and	1.0	30

*Note:

- 1. f= Frequency in MHz * Plane-wave Equivalent Power Density
- 2. The averaging time for General Population/Uncontrolled exposure to fixed transmitters is not applicable for mobile and portable transmitters. See 47 CFR §§2.1091 and 2.1093 on source-based time-averaging requirement for mobile and portable transmitters.

The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true www.ago.gent.com.



Page 8 of 9

4. CLASSIFICATION OF THE ASSESSMENT METHODS

According to user manual, The antenna of the product, under normal use condition is at least 25.76 cm away from the body of the user. Warning statement to the user for keeping at least 25.76 cm separation distance and the prohibition of operating to a person has been printed on the user's manual. So, this product under normal use is located on electromagnetic far field between the human body.

S=PG/4πR²

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator R=distance to the center of radiation of the antenna

5. EUT OPERATION CONDITION

Make the EUT to transmit at lowest, middle and highest channel individually.

The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gott.com.



Page 9 of 9

6. TEST RESULTS

Note: report the worst result in this part

Antenna Gain=0dBi (Numeric 1.0), π=3.141, Duty cycle=50%

Frequency	Output Power	Output Power	Correct Power	Power Density	Power Density Limit	Result
MHz	dBm	mW	mW	mW/cm ²	mW/cm ²	Pass/Fail
27.405	36.02	4000	2000	0.237	0.24	Pass

Note: The output power is refer to AGC01284180501FE10.

Correct Power=Output Power*Duty cycle.

According to the user manual, the minimum separate distance which used for MPE calculate is 25.76cm.

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.