

# RF Exposure Evaluation

## FCC ID: 2AEP6-RP-2LR

### 1. Client Information

<b>Applicant</b>	:	HangZhou XiongMai Technology CO., LTD
<b>Address</b>	:	9th Floor, Building 9, Yinhu Innovation Center, No.9 FuXian Road, YinHu Street, Hangzhou, China
<b>Manufacturer</b>	:	HangZhou XiongMai Technology CO., LTD
<b>Address</b>	:	9th Floor, Building 9, Yinhu Innovation Center, No.9 FuXian Road, YinHu Street, Hangzhou, China

### 2. General Description of EUT

<b>EUT Name</b>	:	ROBOT CAMERA
<b>Models No.</b>	:	RP-2LR, XM-JPR1C-R, XM-JPR13X-R, XM-JPR2C-R, XM-JPR-2LR, XM-JPR-3LR, XM-JPR-3CR, XM-JPR3C-R, XM-JPR-4LR, XM-JPR1-R X, XM-JPR2-MX, XM-JPR2C-LX, XM-JPR2X-RX, XM-JPR2C-MX, XM-JPR2-3LX, XM-JPR2-LX4G, R2-LX4G
<b>Model Difference</b>	:	All these models are in the same PCB, layout and electrical circuit, the only difference is the model name
<b>Product Description</b>	Operation Frequency:	<b>2.4G:</b> 802.11b/g/n(HT20): 2412MHz~2462MHz 802.11n(HT40): 2422MHz~2452MHz
	Modulation Type:	802.11b: DSSS(CCK, DQPSK, DBPSK) 802.11g/n: OFDM(BPSK, QPSK, 16QAM, 64QAM)
<b>Power Rating</b>	:	Adapter Model: TPA-46050150VU Input: AC 100-240V~50/60Hz, 0.3A    Output: DC 5.0V-1500mA
<b>Software Version</b>	:	V1.0
<b>Hardware Version</b>	:	XMJP-PZ-WIFI-USB-18EV-ETH V2.01
<b>Connecting I/O Port(S)</b>	:	Please refer to the User's Manual
<b>Remark</b>	:	The antenna gain provided by the applicant, the verified for the RF conduction test provided by TOBY test lab.

**Note:** More test information about the EUT please refer the RF Test Report.



## MPE Calculations for WIFI

### 1. Antenna Gain:

PCB Ant:	Model	Frequency Range
	N/A	2400~2483.5MHz 3dBi

### 2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### 3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=(PG)/4\pi R^2$$

Where

**S:** power density

**P:** power input to the antenna

**G:** power gain of the antenna in the direction of interest relative to an isotropic radiator.

**R:** distance to the center of radiation of the antenna

### 4. Test Result:

#### 2.4G WIFI&BLE

Mode	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm <sup>2</sup> ) [S]	Limit of Power Density (mW/ cm <sup>2</sup> ) (S)
802.11B	17.74	17±1	18	3.0	20	0.0250	1
802.11G	16.10	16±1	17	3.0	20	0.0199	1
802.11N(HT20)	16.71	16±1	17	3.0	20	0.0199	1
802.11N(HT40)	14.82	14±1	15	30	20	0.0126	1

**5. Conclusion:**

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

**Limits for General Population/ Uncontrolled Exposure**

Frequency Range (MHz)	Power density (mW/ cm <sup>2</sup> )
300-1,500	F/1500
1,500-100,000	1.0

For BT&BLE:2402~2480 MHz

For WIFI: 802.11b/g/n(HT20): 2412MHz~2462MHz

802.11n(HT40): 2422MHz~2452MHz

MPE limit S: 1mW/ cm<sup>2</sup>

The MPE is calculated as **0.0250mW / cm<sup>2</sup> < limit 1mW / cm<sup>2</sup>**. So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

**Note**

For a more detailed features description, please refer to the RF Test Report.

-----END OF REPORT-----