



RF TEST REPORT

Product Name: T-BOX

Model Name: ZDCB01

FCC ID: 2AEQT-DSTBX002

Issued For : Huizhou Desay SV Automotive Co., Ltd.

No. 103, Hechang 5th Road West, Zhongkai National Hi-tech
Industrial Development Zone, Huizhou City, Guangdong Province,
P.R. China

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Zhenxiong Industrial Park,
No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan
District, Shenzhen, Guangdong, China

Report Number: LGT24D091HA01

Sample Received Date: Apr. 17, 2024

Date of Test: Apr. 17, 2024 – Apr. 26, 2024

Date of Issue: Apr. 26, 2024

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



TEST REPORT CERTIFICATION

Applicant: Huizhou Desay SV Automotive Co., Ltd.
Address: No. 103, Hechang 5th Road West, Zhongkai National Hi-tech Industrial Development Zone, Huizhou City, Guangdong Province, P.R. China

Manufacture: Huizhou Desay SV Automotive Co., Ltd.
Address: No. 103, Hechang 5th Road West, Zhongkai National Hi-tech Industrial Development Zone, Huizhou City, Guangdong Province, P.R. China

Product Name: T-BOX

Trademark: DESAY SV

Model Name: ZDCB01

Sample Status: Normal

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47 CFR §2.1091 KDB 447498 D01 General RF Exposure Guidance v06	PASS

Prepared by:

Zane Shan

Zane Shan
Engineer

Approved by:

Vita Li

Vita Li
Technical Director





TABLE OF CONTENTS

1 . GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST LABORATORY	5
2 . FCC 47CFR §2.1091 REQUIREMENT	6
2.1 TEST STANDARDS	6
2.2 LIMIT	6
2.3 EUT OPERATION CONDITION	6
2.4 CLASSIFICATION	6
2.5 TEST RESULT	7



Revision History

Rev.	Issue Date	Revisions
00	Apr. 26, 2024	Initial Issue



1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF THE EUT

Product Name:	T-BOX	
Trademark:	DESAY SV	
Model Name:	ZDCB01	
Series Model:	N/A	
Model Difference:	N/A	
Frequency Bands:	GSM:	850: 824 MHz ~ 849MHz 1900: 1850 MHz ~ 1910MHz
	WCDMA:	Band V: 824 MHz ~ 849 MHz Band II: 1850 MHz ~ 1910 MHz Band IV: 1710 MHz ~ 1755 MHz
	LTE:	FDD LTE Band 5: 824~849MHz FDD LTE Band 7: 2500-2570 MHz FDD LTE Band 38: 2570-2620 MHz
Rating:	Input: DC 9~16V 0.5A	
Hardware Version:	0.0.3	
Software Version:	DSW01.01	

1.2 TEST LABORATORY

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China
Accreditation Certificate	A2LA Certificate No.: 6727.01
	FCC Registration No.: 746540
	CAB ID: CN0136



2. FCC 47CFR §2.1091 REQUIREMENT

2.1 TEST STANDARDS

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

2.2 LIMIT

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)
Limits for Occupational / controlled Exposures			
300 - 1500	--	--	F/300
1500 – 100000	--	--	5.0
Limits for General population / Uncontrolled Exposure			
300 - 1500	--	--	F/1500
1500 – 100000	--	--	1.0

F= Frequency in MHz

Friss Formula

Friss Transmission Formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.

2.3 EUT OPERATION CONDITION

EUT was enabled to transmit and receive at lowest, middle and highest channels.

2.4 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance from the antenna should be included in the User manual. So, this device is classified as Mobile device.



2.5 TEST RESULT

Turn up Result

Mode	Turn up Power
GSM 850	33.5±1dBm
GSM 1900	30±1dBm
WCDMA B2	23±1dBm
WCDMA B4	23±1dBm
WCDMA B5	23±1dBm
LTE B2	23.5±1dBm
LTE B4	23.5±1dBm
LTE B5	23.5±1dBm
LTE B7	23.5±1dBm



The MPE result of worst mode:

RF Function	Frequency (MHz)	Max Turn up Power (dBm)	Duty cycle factor	Max Power (dBm)	Max Power (mW)	ANT Gain (dBi)	ANT Gain (gain of antenna in linear scale)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Ratio	Result
GPRS (1Slot)	836.6	34.5	-9.03	25.47	352.37	1.2	1.32	0.092	0.56	0.166	Pass
WCDMA	1907.6	24	0	24	251.19	1.95	1.57	0.078	1	0.078	Pass
LTE	1732.5	24.5	0	24.5	281.84	2.31	1.70	0.095	1	0.095	Pass

Note:

1. The Maximum Power Density is less than the limit, complies with the exemption requirements.

※※※※※END OF THE REPORT※※※※※