



FCC RF EXPOSURE REPORT

For

CAR MULTIMEDIA

MODEL NUMBER: M3GL06L, M3GL06R

FCC ID: 2AEQT-M3GL06L

REPORT NUMBER: 4790583817-RF-5

ISSUE DATE: March 2, 2023

Prepared for

**Huizhou Desay SV Automotive Co., Ltd.
NO.103, Hechang 5th Road West, Zhongkai National Hi-tech Industrial
Development Zone, Huizhou, Guangdong, P.R. China**

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V0	March 2, 2023	Initial Issue	



TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. REQUIREMENT	6



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Huizhou Desay SV Automotive Co., Ltd.
Address: NO.103, Hechang 5th Road West, Zhongkai National Hi-tech Industrial Development Zone, Huizhou, Guangdong, P.R. China

Manufacturer Information

Company Name: Huizhou Desay SV Automotive Co., Ltd.
Address: NO.103, Hechang 5th Road West, Zhongkai National Hi-tech Industrial Development Zone, Huizhou, Guangdong, P.R. China

EUT Information

EUT Name: CAR MULTIMEDIA
Model: M3GL06L, M3GL06R
Model Difference: The difference lies only the touch screen buttons of the front panel of the host are opposite, and the front panel Layout is opposite for these two models.
Brand: DESAY SV
Sample Received Date: February 6, 2023
Sample ID: NA
Date of Tested: February 15, 2023 to March 2, 2023

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47CFR§2.1091	PASS

Prepared By:

Denny Huang
Senior Project Engineer

Checked By:

Kebo Zhang
Senior Project Engineer

Approved By:

Stephen Guo
Operations Manager



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 and KDB 447498 D01v06.

3. FACILITIES AND ACCREDITATION

<p>Accreditation Certificate</p>	<p>A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p>FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p>ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B , the VCCI registration No. is C-20012 and T-20011</p>
----------------------------------	--

Note: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China.



4. REQUIREMENT

LIMIT AND CALCULATION METHOD

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

RF EXPOSURE LIMIT

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (Minutes)
0.3 -- 1.34	614	1.63	(100)*	30
1.34 -- 30	824/f	2.19/f	(180/f ²)*	30
30 -- 300	27.5	0.073	0.2	30
300 -- 1500	--	--	f/1500	30
1500 -- 100,000	--	--	1.0	30

CALCULATION METHOD

$$S = PG / 4\pi R^2$$

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna



CALCULATED RESULTS

2.4G WiFi Mode					
Frequency	Output Power	Output Power	Power Density	Power Density Limit	Test Result
MHz	dBm	mW	mW/cm ²	mW/cm ²	--
2412-2462	17	50.12	0.008	1.0	Complies

5G WiFi Mode					
Frequency	Output Power	Output Power	Power Density	Power Density Limit	Test Result
MHz	dBm	mW	mW/cm ²	mW/cm ²	--
5150-5250 5725-5850	16	39.81	0.01	1.0	Complies

BT Mode					
Frequency	Output Power	Output Power	Power Density	Power Density Limit	Test Result
MHz	dBm	mW	mW/cm ²	mW/cm ²	--
2402-2480	9	7.94	0.001	1.0	Complies

- Note: 1. 2.4G WiFi Antenna Gain=-0.759 dBi, 5G WiFi Antenna Gain=1.049 dBi, BT Antenna Gain=-1.336 dBi (Numeric 25.12), $\pi=3.141$.
 2. The Power comes from report operation description.
 3. The minimum separation distance of the device is greater than 20 cm.
 4. Calculate by WORST-CASE mode.
 5. EUT does not support simultaneous transmission.

END OF REPORT