

## RADIO FREQUENCY EXPOSURE

EUT Specification

|                                   |   |
|-----------------------------------|---|
| <b>EUT</b>                        | CH18  |
| <b>Frequency band (Operating)</b> | <input checked="" type="checkbox"/> WLAN: 2.400GHz ~ 2.460GHz<br><input type="checkbox"/> Others  |
| <b>Device category</b>            | <input checked="" type="checkbox"/> Portable (<20cm separation)<br><input type="checkbox"/> Mobile (>20cm separation)<br><input type="checkbox"/> Others  |
| <b>Exposure classification</b>    | <input type="checkbox"/> Occupational/Controlled exposure ( $S = 5\text{mW/cm}^2$ )<br><input checked="" type="checkbox"/> General Population/Uncontrolled exposure ( $S=1\text{mW/cm}^2$ )   |
| <b>Antenna diversity</b>          | <input checked="" type="checkbox"/> Single antenna<br><input type="checkbox"/> Multiple antennas<br><input type="checkbox"/> Tx diversity<br><input type="checkbox"/> Rx diversity<br><input checked="" type="checkbox"/> Tx/Rx diversity |
| <b>Max. output power</b>          | 2.400-2.460GHz: 0.24mW  |
| <b>Antenna gain (Max)</b>         | 0 dBi   |
| <b>Evaluation applied</b>         | <input type="checkbox"/> MPE Evaluation*<br><input type="checkbox"/> SAR Evaluation<br><input checked="" type="checkbox"/> N/A  |

**Remark:**

1. The maximum output power is 0.24mW at 2460MHz (with 1 numeric antenna gain.)
2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.
3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm<sup>2</sup> even if the calculation indicates that the power density would be larger.

**TEST RESULTS**

No non-compliance noted.

$$\text{eirp} = \text{ptx} \times \text{gt} = (\text{Exd})^2/30$$

Where:

Pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, ---  $10^{(\text{dBuV/m})/20}/10^6$

d = measurement distance in meters (m) --- 3m

So Pt = (Exd)<sup>2</sup>/30×gt

Maximum Field strength: 89.02 dBuV/m @3m –Channel high:2460MHz

Refer to FCC Part 15C 15.249 Test Report page 12.

Ant gain = 0dBi; so Ant numeric gain=1

$$\text{So, Pt} = \{[(10^{(89.02/20)}/10^6) \times 3^2]/30 \times 1\} \times 1000\text{mW} = 0.24 \text{mW}$$

**Standard Requirement:**

According to 447498 D01 General RF Exposure Guidance v05

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f_{(\text{GHz})}} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}^{16} \text{ where}$

- $f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

|      |                                  |       |
|------|----------------------------------|-------|
|      | Tune-up Maximum rated power (mW) | 0.24  |
| Body | Antenna to user (mm)             | 5     |
|      | Frequency(GHz)                   | 2.460 |
|      | Test result                      | 0.075 |
|      | SAR exclusion threshold          | 3     |

Per KDB 447498 D01v05r01 exclusion thresholds is  $0.075 < 3$ , RF exposure evaluation is not required.