RF EXPOSURE REPORT



Report No.: 18070475-FCC-H

Supersede Report No.: N/A Applicant Hale Devices, Inc. **Product Name Bluetooth Headphone** Model No. Aiwa Arc-1-US, Arc-1-XX (X=blank, 0~9, A~Z) Serial No. N/A FCC 2.1093 **Test Standard Test Date** April 29 to May 10, 2018 **Issue Date** May 11, 2018 Pass **Test Result** Fail 7 Equipment complied with the specification Equipment did not comply with the specification ion Aform L David Huang Aaron Liang **David Huang Test Engineer Checked By** This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108 Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn



Test Report18070475-FCC-HPage2 of 8

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Accreditations for Conformity Assessment



 Test Report
 18070475-FCC-H

 Page
 3 of 8

This page has been left blank intentionally.



Test Report18070475-FCC-HPage4 of 8

CONTENTS

1.	REPORT REVISION HISTORY	5
2.	CUSTOMER INFORMATION	5
3.	TEST SITE INFORMATION	5
4.	EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5.	FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES.	7
5.1	RF EXPOSURE	7
5.2	TEST RESULT	8



Test Report	18070475-FCC-H
Page	5 of 8

1. Report Revision History

Report No.	Report Version	Description	Issue Date
18070475-FCC-H	NONE	Original	May 11, 2018

2. Customer information

Applicant Name	Hale Devices, Inc.
Applicant Add	650 W. Lake St. Suite#220, Chicago, IL, 60661, USA
Manufacturer	Hale Devices, Inc.
Manufacturer Add	650 W. Lake St. Suite#220, Chicago, IL, 60661, USA

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park
Lab Address	South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China
	518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0



4. Equipment under Test (EUT) Information

Description of EUT:	Bluetooth Headphone
Main Model:	Aiwa Arc-1-US, Arc-1-XX (X=blank, 0~9, A~Z)
Serial Model:	N/A
Date EUT received:	April 28, 2018
Test Date(s):	April 29 to May 10, 2018
Antenna Gain:	Bluetooth/BLE: 0dBi
Antenna Type:	PIFA Antenna
Type of Modulation:	Bluetooth: GFSK, π /4DQPSK, 8DPSK BLE: GFSK
RF Operating Frequency (ies):	Bluetooth& BLE: 2402-2480 MHz
Number of Channels:	Bluetooth: 79CH BLE: 40CH
Port:	Please refer to the user' s manual
Input Power:	Model: 652035 Spec: 3.7V, 420mAh
Trade Name :	AIWA
FCC ID:	2AERPAIWAARC-1



 Test Report
 18070475-FCC-H

 Page
 7 of 8

5. <u>FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable</u> devices.

5.1 RF Exposure

Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission' s guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)].

- $[\sqrt{f_{(GHz)}}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,¹⁶ where
- f_(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is \leq 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

result = $P\sqrt{F}/D$

P= Maximum turn-up power in mW

- F= Channel frequency in GHz
- D= Minimum test separation distance in mm



Test Report18070475-FCC-HPage8 of 8

5.2 Test Result

Bluetooth Mode:

Modulation	СН	Freque ncy	Conducted Power	Tune Up Power	Max Tune Up Power	Max Tune Up Power	Result	Limit
		(MHz)	(dBm)	(dBm)	(dBm)	(mW)		
	Low	2402	3.242	3±1	4	2.512	0.78	3
GFSK	Mid	2441	3.748	3±1	4	2.512	0.78	3
	High	2480	3.884	3±1	4	2.512	0.79	3
π /4 DQPSK	Low	2402	3.157	3±1	4	2.512	0.78	3
	Mid	2441	3.451	3±1	4	2.512	0.78	3
	High	2480	2.632	3±1	4	2.512	0.79	3
8-DPSK	Low	2402	3.608	3±1	4	2.512	0.78	3
	Mid	2441	3.793	3±1	4	2.512	0.78	3
	High	2480	3.986	3±1	4	2.512	0.79	3

BLE Mode:

Modulation	СН	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	2.17	2±1	3	1.995	0.62	3
	Mid	2440	1.61	2±1	3	1.995	0.62	3
	High	2480	1.82	2±1	3	1.995	0.63	3

Result: Compliance

No SAR measurement is required.