

LIMIT Modular approval Declaration letter

We , GALAXYWIND Network System Co., Ltd. apply limited modular approval for
Product Name: W Module

Model : W Module, W0, W1, W2, W3, W4, W5, W6, W7, W8, W9

FCC ID: 2AES6WMODULE

According to 996369 D01 Module Equip Auth Guide v01r04 and 15.212 requirement:

1) The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly;

Answer: No, Modular is not shielded

2) The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal;

Answer : Yes ; The EUT has buffered data inputs; it is integrated in chip U12 AS2930M5

3)The modular transmitter must have its own power supply regulation.

Answer : Yes ; The EUT interface provides 3.3VDC, and on board IC U12 AS2930M5 has its own VCO inside.

4) The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per Sections 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b);

Answer : Yes ; Device is equipped with PCB antenna.

(5) The module must demonstrate compliance in a stand-alone configuration;

Answer : NO , distance between modular and all AEs are shorter than 10cm , refer to setup photo.

(6) The module must be labelled with its permanently affixed FCC ID label, or use an electronic display (See KDB Publication 784748 about labelling requirements);

Answer : Yes ; The modular has a permanent fixed label, and below statement was listed in the User Manual ;The host device must be labelled to display the FCC ID of the module
Contains FCC ID: 2AES6WMODULE

(7) The module must comply with all specific rules applicable to the transmitter including all the conditions provided in the integration instructions by the grantee;

Answer : Yes ; The module comply with all specific rules applicable to the transmitter including all the conditions provided in the integration instructions by the grantee, Refer to test report and user manual .

(8) The module must comply with RF exposure requirements

Answer : Yes ; Transmitter meets MPE calculation of 47 CFR 1.1307 . Refer to MPE Reports and Refer to modular installation manual

Dated this July 02, 2015

Agency agreement expiration date: Usually Give 8 - 12 Months

By: Yu Zeng Yu Zeng
Signature *Printed*

Title: General Manager

On behalf of : GALAXYWIND Network System Co., Ltd.

Telephone: 86-755- 83400088