



## FCC PART 27

### MEASUREMENT AND TEST REPORT

For

### Quectel Wireless Solutions Company Limited

Room501,Building 13,No.99 TianZhou Road, Xuhui District, Shanghai, China

**Test Model: EC25-A**  
**FCC ID: XMR201605EC25A**

<b>Report Type:</b> CIIPC	<b>Product Type:</b> LTE Module
<b>Test Engineer:</b> <u>David. Hsu</u>	<i>David. Hsu</i>
<b>Report Number:</b> <u>RKS160908001-00A</u>	
<b>Report Date:</b> <u>2016-09-08</u>	
<b>Reviewed By:</b> <u>Jerry.Chang</u>	<i>Jerry.Chang</i>
<b>Prepared By:</b>	Bay Area Compliance Laboratories Corp. (Taiwan) 70, Lane 169, Sec. 2, Datong Road, Xizhi Dist., New Taipei City 22183, Taiwan, R.O.C. Tel: +886 (02)27206758 Fax: +886 (02)27206722 <a href="http://www.bacl.com.tw">www.bacl.com.tw</a>

**Note:** This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

---

---

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION</b> .....	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE .....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY .....	4
TEST FACILITY .....	5
<b>SYSTEM TEST CONFIGURATION</b> .....	<b>6</b>
JUSTIFICATION .....	6
EQUIPMENT MODIFICATIONS .....	6
SPECIFIC ACCESSORY EQUIPMENT .....	6
SUPPORT EQUIPMENT LIST AND DETAILS .....	6
EXTERNAL CABLE LIST AND DETAILS .....	7
BLOCK DIAGRAM OF TEST SETUP .....	7
<b>SUMMARY OF TEST RESULTS</b> .....	<b>8</b>
<b>FCC §1.1310</b>	

---

APPLICABLE STANDARDS.....	31
TEST PROCEDURE .....	31
TEST EQUIPMENT LIST AND DETAILS.....	32
TEST DATA .....	32

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The Quectel Wireless Solutions Company Limited's product, model number: EC25-A (FCC ID: XMR201605EC25A) or the "EUT" in this report was a LTE Module , which was measured approximately 32mm(L) × 29mm(W) × 2.4mm(H). Rated with input voltage: DC3.8 V, EUT Operating Voltage Range: 3.3~4.3V.

*\* Note: The product ' s series model number: EC25-A and EC25-A MiniPCle The difference between them was explained in the attached declaration letter.*

*\* All measurement and test data in this report was gathered from production sample serial number: 20160519001 (Assigned by BACL, Taiwan).The EUT supplied by the applicant was received on 2016-05-19.*

### Objective

This type approval report is prepared on behalf of Quectel Wireless Solutions Company Limited in accordance with Part 2, Part 27 of the Federal Communication Commission's rules.

The objective is to determine the compliance of EUT with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability, and band edge.

This is a CIIPC base on the original report RTWK160705001-00 with FCC ID: XMR201605EC25A which was granted on 2016-07-18, the differences between the original device and the current one are as follows:

- 1.Add new Band (WCDMA Band IV)
- 2.Update RF Exposure Evaluation (MPE)

For the changes made to the device, according to Part 27-Subpart, the test items were performed.

### Related Submittal(s)/Grant(s)

N/A

### Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-Part J as well as the following parts:

Part 27 – Miscellaneous wireless communications services

Applicable Standards: TIA/EIA 603-D.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp. (Taiwan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.81 dB for 30MHz-1GHz.and 4.88 dB for above 1GHz, 1.95dB for conducted measurement.

### **Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp.(Taiwan) 70, Lane 169, Sec. 2, Datong Road, Xizhi Dist., New Taipei City 22183, Taiwan, R.O.C.

Test site at Bay Area Compliance Laboratories Corp. (Taiwan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on October 31, 2103. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 431084. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

## SYSTEM TEST CONFIGURATION

### Justification

The EUT was configured for testing according to TIA/EIA-603-D.

The final qualification test was performed with the EUT operating at normal mode.

### Equipment Modifications

No modifications were made to the EUT.

### Specific Accessory Equipment

Description	Parameter	Serial Number
WCDMA antenna	PCB antenna with typical gain:1.0dBi	N/A


### Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891
Dell	Notebook	E6410	N/A
Quectel	Test Fixer	N/A	N/A
Shanghai Jingsai Electronic Technology Co.,Ltd.	ADAPATER I/P: AC 100-240V, 50-60Hz O/P: DC 5V, 2A, 12W	JS-400K	N/A
Quectel Wireless Solutions	Control Board	S2-W2231	MP76121D4000228

**External Cable List and Details**

Cable Description	Length (m)	From Port	To
/	/	/	/

**Block Diagram of Test Setup**



**SUMMARY OF TEST RESULTS**

FCC Rules	Description of Test	Result
§1.1310, §2.1091  §2.1046;	MAXIMUM PERMISSIBLE EXPOSURE (MPE)	Compliant



**FCC §1.1310**

To meet MPE requirement, the allowed maximal gain for each band is below:

Mode	Frequency Range (MHz)	Antenna Gain		Target Power		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
		(dBi)	(Numeric)	(dBm)	(mW)			
WCDMA (Band V)	826.4-846.6	10.92	12.36	23.5	223.87	20	0.551	0.551
WCDMA (Band II)	1852.4-1907.6	13.51	22.44	23.5	223.87	20	1.0	1.0
WCDMA (Band IV)	1712.4-1752.6	13.51	22.44	23.5	223.87	20	1.0	1.0
LTE (Band II)	1850.7-1909.3	13.01	20.00	24	251.19	20	1.0	1.0
LTE (Band IV)	1710.7-1754.3	13.01	20.00	24	251.19	20	1.0	1.0
LTE (Band XII)	699.7-715.3	9.69	9.31	24	251.19	20	0.465	0.466

Note:

1. The device meets FCC MPE at 20 cm distance.
2. Target Power =the max power including Tune-up tolerance, the tune up power declared by manufacture as:

WCDMA Bands: 22.5±1

---

## **FCC §2.1047 - MODULATION CHARACTERISTIC**

---

According to FCC § 2.1047(d) , Part 27 there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

**FCC**

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Interval
Rohde & Schwarz	EMI Test Receiver	ESCI	100540	2016-07-25	2017-07-24
Agilent	Signal Generator	8648C	3537A01810	2016-07-04	2017-07-03
Sunol Sciences	Broadband Antenna	JB6	A050115	2016-06-15	2017-06-14
EMCO	Horn Antenna	3115	9311-4158	2016-05-08	2017-05-07
ETS	Horn Antenna	3115	6431	2015-11-07	2016-11-06
Rohde & Schwarz	Spectrum Analyzer	FSU 26	200268	2016-07-29	2017-08-28
EMCO	Turn Table	2081-1.21	9709-1885	N.C.R	N.C.R
EMCO	Antenna Tower	2075-2	9707-2060	N.C.R	N.C.R
Controller	EMCO	2090	9709-1256	N.C.R	N.C.R
R&S	Software	EMC32	V9.10.00	NCR	NCR
BACL	RF cable	KS-LAB-012	KS-LAB-012	2015-12-16	2016-12-15
BACL	RF cable	KS-LAB-010	KS-LAB-010	2015-12-16	2016-12-15
Mini	Attenuator	10dB	N/A	2016-01-11	2017-01-10

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Taiwan) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	50 %
<b>ATM Pressure:</b>	101.0kPa

*The testing was performed by David. Hsu on 2016-09-07.*

**Conducted Power**

**WCDMA Band IV**

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band IV)	Normal	Rel99	1	22.53	22.33	22.40
		HSDPA	1	22.33	22.42	22.45
			2	22.52	22.32	22.58
			3	22.36	22.45	22.58
			4	22.44	22.53	22.42
		HSUPA	1	22.35	22.36	22.46
			2	22.40	22.45	22.40
			3	22.30	22.32	22.49
			4	22.41	22.52	22.53
			5	22.34	22.47	22.59
		HSPA+	1	22.37	22.44	22.51

**EIRP:**

Frequency (MHz)	Receiver Reading (dBµV)	Turn table Angle Degree	RX Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable (dB)	Antenna Gain (dB)			
WCDMA Band IV Mode, Middle channel										
1732.40	78.52	233	2.1	H	4.69	0.31	10.40	14.78	30	15.22
1732.40	84.65	358	1.3	V	11.52	0.31	10.40	21.61	30	15.39

**Note:**

1) The unit of antenna gain is dBd for frequency below 1GHz and dBi for frequency above 1

**Peak-to-average ratio (PAR)****WCDMA Band IV**

<b>Mode</b>	<b>Channel</b>	<b>PAR (dB)</b>	<b>Limit (dB)</b>
Rel99	Low	2.65	13
	Middle	2.64	13
	High	2.61	13
HSDPA	Low	2.45	13
	Middle	2.43	13
	High	2.52	13
HSUPA	Low	2.41	13
	Middle	2.44	13
	High	2.47	13

**FCC §2.1049**



**Test Data****Environmental Conditions**

<b>Temperature:</b>	21 °C
<b>Relative Humidity:</b>	49 %
<b>ATM Pressure:</b>	101.0kPa

*The testing was performed by David. Hsu on 2016-09-07.*


*EUT operation mode: Transmitting*

*Test Result: Compliance. Please refer to the following tables and plots.*


**WCDMA Band IV**

<b>Mode</b>	<b>Test Condition</b>	<b>Test Mode</b>	<b>OCCUPIED BANDWIDTH (MHz)</b>	<b>26dB BANDWIDTH (MHz)</b>
WCDMA (Band IV)	Normal	Rel99	4.13	4.73
		HSDPA	4.15	4.75
		HSUPA	4.13	4.75


**99% Occupied & 26 dB Emissions Bandwidth for Rel99 Mode**



**99% Occupied & 26 dB Emissions Bandwidth for HSDPA Mode**



**99% Occupied & 26 dB Emissions Bandwidth for HSUPA Mode**



**FCC**

**Test Data**

**Environmental Conditions**


<b>Temperature:</b>	20~23 °C
<b>Relative Humidity:</b>	48~50 %
<b>ATM Pressure:</b>	100.5~101.0kPa

The testing was performed by David. Hsu on 2016-09-07.


Please refer to the following plots.

**WCDMA Band IV**


**30 MHz – 1 GHz**



### 1 GHz – 2 GHz



### 2 GHz – 20 GHz



**FCC §2.1053**

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Interval
Sonoma	Amplifier	310N	130601	2016-07-02	2017-07-01
Rohde & Schwarz	EMI Test Receiver	ESCI	100540	2016-07-25	2017-07-24
Sunol Sciences	Broadband Antenna	JB6	A050115	2016-06-15	2017-06-14
Sunol Sciences	Broadband Antenna	JB3	A090314-1	2015-11-07	2016-11-06
Mini	Amplifier	ZVA-213-S+	460901516	2016-08-21	2017-08-21
EMCO	Horn Antenna	3115	9311-4158	2016-05-08	2017-05-07
ETS	Horn Antenna	3115	6431	2015-11-07	2016-11-06
Rohde & Schwarz	Spectrum Analyzer	FSU 26	200268	2016-07-29	2017-08-28
EMCO	Turn Table	2081-1.21	9709-1885	N.C.R	N.C.R
EMCO	Antenna Tower	2075-2	9707-2060	N.C.R	N.C.R
Controller	EMCO	2090	9709-1256	N.C.R	N.C.R
R&S	Software	EMC32	V9.10.00	NCR	NCR
HP	Signal Generator	E4421B	3426A01336	2015-11-04	2016-11-03
BACL	RF cable	KS - LAB - 012	KS - LAB - 012	2015-12-16	2016-12-15
BACL	RF cable	KS - LAB - 010	KS - LAB - 010	2015-12-16	2016-12-15

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Taiwan) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	48 %
<b>ATM Pressure:</b>	101.0kPa

*The testing was performed by David. Hsu on 2016-09-07.*

*Test mode: Transmitting*



Test mode: Transmitting (Pre-scan with Low, Middle, High channel, and the worse case data as below)

**30 MHz ~ 18 GHz:**

**WCDMA Band IV**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
<b>Middle Channel: 1732.400 MHz</b>								
3464.800	H	61.4	-48.6	13.9	1.9	-36.6	-13.0	23.6
3464.800	V	64.0	-46.0	13.9	1.9	-34.0	-13.0	21.0
5197.200	H	62.0	-45.2	14.0	2.3	-33.5	-13.0	20.5
5197.200	V	63.8	-43.4	14.0	2.3	-31.7	-13.0	18.7
239.200	H	28.6	-69.6	0.0	0.5	-70.1	-13.0	57.1
281.300	V	31.2	-67.0	0.0	0.5	-67.5	-13.0	54.5

## FCC §27.53 (h) - BAND EDGES

### Applicable Standards


According to FCC §27.53 (c)(h), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

For mobile digital stations, the attenuation factor shall be not less than  $40 + 10 \log(P)$  dB on all frequencies between the channel edge and 5 megahertz from the channel edge,  $43 + 10 \log(P)$  dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and  $55 + 10 \log(P)$  dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than  $43 + 10 \log(P)$  dB on all frequencies between 2490.5 MHz and 2496 MHz and  $55 + 10 \log(P)$  dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

### Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency



**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde &Schwarz	Signal Analyzer	FSIQ26	8386001028	2015-12-11	2016-12-11
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891	2015-11-23	2016-11-23
Mini	Splitter	ZFRSC-14-S+	SF019411452	2016-07-11	2016-12-10
BACL	RF cable	KS-LAB-020	KS-LAB-020	2016-07-11	2016-12-10
Mini	Attenuator	10dB	N/A	2016-07-11	2016-12-10

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Taiwan) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**


<b>Temperature:</b>	20~23 °C
<b>Relative Humidity:</b>	48~52 %
<b>ATM Pressure:</b>	100.5~101.0kPa

*The testing was performed by David. Hsu on 2016-09-07.*


*EUT operation mode: Transmitting*

*Test Result: Compliance. Please refer to the following plots.*


### Left Band Edge for Rel99 Mode




### Right Band Edge for Rel99 Mode




**Left Band Edge for HSDPA Mode**




**Right Band Edge for HSDPA Mode**



### Left Band Edge for HSUPA Mode



### Right Band Edge for HSUPA Mode



**FCC §2.1055**

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde &Schwarz	Signal Analyzer	FSIQ26	8386001028	2015-12-11	2016-12-11
BACL	Temperature Chamber	BTH - 150	30023	2015-11-12	2016-11-11
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891	2015-11-23	2016-11-23
Mini	Splitter	ZFRSC-14-S+	SF019411452	2016-07-11	2016-12-10
BACL	RF cable	KS-LAB-020	KS-LAB-020	2016-07-11	2016-12-10
Mini	attenuator	10dB	N/A	2016-07-11	2016-12-10

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Taiwan) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

**Test Data**

**Environmental Conditions**

<b>Temperature:</b>	23 °C
<b>Relative Humidity:</b>	50 %
<b>ATM Pressure:</b>	101.0kPa

*The testing was performed by David. Hsu on 2016-09-07.*

*EUT operation mode: Transmitting*

*Test Result: Compliance. Please refer to the following tables.*



**WCDMA Band IV Rel99 Mode**

Middle Channel, $f_0=1732.4\text{MHz}$				
Temperature (°C)	Power Supplied (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.8	7	0.0040	pass
-20		9	0.0052	pass
-10		7	0.0040	pass
0		8	0.0046	pass
10		7	0.0040	pass
20		9	0.0052	pass
30		13	0.0075	pass
40		13	0.0075	pass
50		11	0.0063	pass
25	$V_{\min.}= 3.5$	13	0.0075	pass
25	$V_{\max.}= 4.2$	11	0.0063	pass

**WCDMA Band IV HSDPA Mode**

Middle Channel, $f_0=1732.4\text{MHz}$				
Temperature (°C)	Power Supplied (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.8	12	0.0069	pass
-20		11	0.0063	pass
-10		11	0.0063	pass
0		14	0.0081	pass
10		15	0.0087	pass
20		6	0.0035	pass
30		12	0.0069	pass
40		8	0.0046	pass
50		7	0.0040	pass
25	$V_{\min.}= 3.5$	13	0.0075	pass
25	$V_{\max.}= 4.2$	10	0.0058	pass

**WCDMA Band IV HSUPA Mode**

Middle Channel, $f_0 = 1732.4$ MHz				
Temperature (°C)	Power Supplied (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.8	6	0.0035	pass
-20		9	0.0052	pass
-10		14	0.0081	pass
0		12	0.0069	pass
10		5	0.0029	pass
20		10	0.0058	pass
30		14	0.0081	pass
40		7	0.0040	pass
50		12	0.0069	pass
25	$V_{min.} = 3.5$	14	0.0081	pass
25	$V_{max.} = 4.2$	11	0.0063	pass

**\*\*\*\*\* END OF REPORT \*\*\*\*\***