

RF Exposure Evaluation Report

Product : WIFI Module
Trade mark : N/A
Model/Type reference : SD06-S14PXX000NV3
Serial Number : N/A
Report Number : EED32I00265502
FCC ID : 2AEU8SD06
Date of Issue : Mar. 24, 2017
Test Standards : 47 CFR Part 1.1307(2015)
47 CFR Part 1.1310(2015)
KDB447498D01v06
Test result : PASS

Prepared for:

Ittim Technology Co., Ltd.
Room 1215, 5th building, No.1988, Jiamei Road, Nanxiang town,
Jiading district, Shanghai, China

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Tested By:

Tom chen
Tom chen (Test Project)

Compiled by:

Ware xin
Ware xin (Project Engineer)

Reviewed by:

Kevin Yang
Kevin yang (Reviewer)

Approved by:

Sheek Luo
Sheek Luo (Lab supervisor)

Date:

Mar. 24, 2017

Check No.: 2496598453



2 Version

| Version No. | Date | Description |
|-------------|---------------|-------------|
| 00 | Mar. 24, 2017 | Original |
| | | |
| | | |

3 Contents

| | Page |
|--|----------|
| 1 COVER PAGE..... | 1 |
| 2 VERSION..... | 2 |
| 3 CONTENTS..... | 3 |
| 4 GENERAL INFORMATION..... | 4 |
| 4.1 CLIENT INFORMATION..... | 4 |
| 4.2 GENERAL DESCRIPTION OF EUT..... | 4 |
| 4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD..... | 4 |
| 4.4 TEST LOCATION..... | 4 |
| 4.5 TEST FACILITY..... | 5 |
| 4.6 DEVIATION FROM STANDARDS..... | 6 |
| 4.7 ABNORMALITIES FROM STANDARD CONDITIONS..... | 6 |
| 4.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER..... | 6 |
| 5 RF EXPOSURE EVALUATION..... | 7 |
| 5.1 RF EXPOSURE COMPLIANCE REQUIREMENT..... | 7 |
| 5.1.1 Limits..... | 7 |
| 5.1.2 Test Procedure..... | 8 |
| 5.1.3 EUT RF Exposure Evaluation..... | 8 |
| PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS..... | 9 |

4 General Information

4.1 Client Information

| | |
|--------------------------|---|
| Applicant: | Ittim Technology Co., Ltd. |
| Address of Applicant: | Room 1215, 5th building, No.1988, Jiamei Road, Nanxiang town, Jiading district, Shanghai, China |
| Manufacturer: | Ittim Technology Co., Ltd. |
| Address of Manufacturer: | Room 1215, 5th building, No.1988, Jiamei Road, Nanxiang town, Jiading district, Shanghai, China |

4.2 General Description of EUT

| | |
|----------------------------------|-------------------------------|
| Product Name: | WIFI Module |
| Model No.: | SD06-S14PXX000NV3 |
| Trade Mark: | N/A |
| EUT Supports Radios application: | Wlan 2.4GHz 802.11b/g/n(HT20) |
| Power Supply: | DC 5V |

4.3 Product Specification subjective to this standard

| | |
|--|--|
| Operation Frequency: | IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz |
| Channel Numbers: | IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels |
| Type of Modulation: | IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g :OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20) : OFDM (64QAM, 16QAM, QPSK,BPSK) |
| Test Software of EUT: | CDM v2.12.00 |
| Max Conducted Output Power: | 17.26dBm |
| Antenna Type: | Chip antenna |
| Antenna Gain: | 0dBi |
| Sample Received Date: | Mar. 14, 2017 |
| Sample tested Date: | Mar. 14, 2017 to Mar. 24, 2017 |
| The tested sample and the sample information are provided by the client. | |

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd.

Hongwei Industrial Zone, Bao'an 70 District, Shenzhen, Guangdong, China 518101

Telephone: +86 (0) 755 3368 3668 Fax:+86 (0) 755 3368 3385

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L1910

Centre Testing International Group Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories..

A2LA-Lab Cert. No. 3061.01

Centre Testing International Group Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 886427

Centre Testing International Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 886427.

IC-Registration No.: 7408A-2

The 3m Alternate Test Site of Centre Testing International Group Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 7408A-2 .

IC-Registration No.: 7408B-1

The 10m Alternate Test Site of Centre Testing International Group Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 7408B-1.

NEMKO-Aut. No.: ELA503

Centre Testing International Group Co., Ltd. has been assessed the quality assurance system, the testing facilities, qualifications and testing practices of the relevant parts of the organization. The quality assurance system of the Laboratory has been validated against ISO/IEC 17025 or equivalent. The laboratory also fulfils the conditions described in Nemko Document NLA-10.

VCCI

The Radiation 3 & 10 meters site of Centre Testing International Group Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-4096.

Main Ports Conducted Interference Measurement of Centre Testing International Group Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: C-4563.

Telecommunication Ports Conducted Disturbance Measurement of
Centre Testing International Group

Report No. : EESZG04210004

Page 6 of 9

Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: T-2146.

The Radiation 3 meters site of Centre Testing International Group Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-758

4.6 Deviation from Standards

None.

4.7 Abnormalities from Standard Conditions

None.

4.8 Other Information Requested by the Customer

None.

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposures | | | | |
| 0.3–3.0 | 614 | 1.63 | *(100) | 6 |
| 3.0–30 | 1842/f | 4.89/f | *(900/f ²) | 6 |
| 30–300 | 61.4 | 0.163 | 1.0 | 6 |
| 300–1500 | | | f/300 | 6 |
| 1500–100,000 | | | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3–1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34–30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30–300 | 27.5 | 0.073 | 0.2 | 30 |
| 300–1500 | | | f/1500 | 30 |
| 1500–100,000 | | | 1.0 | 30 |

A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation:

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R= distance to the centre of radiation of the antenna

EIRP = P*G

The antenna of the product, under normal use condition is at least 20 cm away from the body of the user.

Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to

a person has been printed on the user's manual. Therefore, the S of the device is calculated with R=20cm, and if it is below the limit S, then we can conclude the device complies with the rules.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually.

5.1.3 EUT RF Exposure Evaluation

Antenna Gain: 0dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

| Channel | Frequency (MHz) | Max Conducted Peak Output Power(dBm) | Gain (dBi) | EIRP* (dBm) | EIRP (mW) | R (cm) | S (mW/cm ²) | Limit (mW/cm ²) | Result |
|---------|-----------------|--------------------------------------|------------|-------------|-----------|--------|-------------------------|-----------------------------|--------|
| Middle | 2437 | 17.26 | 0 | 17.26 | 53.21 | 20 | 0.011 | 1.0 | Pass |

Note: Refer to report No. EED32100265501 for EUT test Max Conducted Peak Output Power value.

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32I00265501 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.