

ONE WORLD O OUR APPROVAL

Wireless Test Report – 1R368533-11TRFWL

Applicant: **Ring LLC** Product name: Ring Model: **Base Station NA** FCC ID: 2AEUPBHABN002

ISED Registration number: 20271-BHABN002

Specifications:

FCC 47 CFR Part 15 Subpart E, §15.407(h)(2)

Radar Detection Function of Dynamic Frequency Selection (DFS)

RSS-247, Issue 2, Feb 2017, Section 6.3

Dynamic frequency selection for devices operating in the bands 5250-5350 MHz, 5470-5600 MHz and 5650-5725 MHz

Date of issue: April 2, 2019

Test engineer(s): Mark Libbrecht, EMC/Wireless Specialist

Kevin Rose, Wireless/EMC Specialist Reviewed by:

e: Mark tillredet

Signature:

Signature:

www.nemko.com

Nemko Canada Inc., a testing laboratory, is accredited by the Standards Council of Canada. The tests included in this report are within the scope of this accreditation





Lab and Test location(s)

Company name	Nemko Canada Inc. (Can	bridge)	
Facility	130 Saltsman Drive, Uni	#1	
	Cambridge, ON		
	Canada, N3E 0B2		
	Tel: +1 519 680 4811		
	Test Firm Registration N	mber: 332406	
Test site registration	Organization	Designation Number	
	FCC/ISED	CA0101	
Website	www.nemko.com		

Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contain in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

Copyright notification

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. © Nemko Canada Inc.



Table of contents

Table of o	contents3	
Section 1	. Report summary4	
1.1	Applicant and manufacturer 4	
1.2	Test specifications	
1.3	Test methods 4	
1.4	Statement of compliance 4	
1.5	Exclusions 4	
1.6	Test report revision history 4	
Section 2	. Summary of test results5	
2.1	FCC §15.407(h)(2), test results	
2.2	RSS-247 Issue 1, test results	
Section 3	. Equipment under test (EUT) details6	
3.1	Sample information	
3.2	EUT information	
3.3	Technical information	
3.4	Product description and theory of operation	
3.5	EUT exercise details	
Section 4	. Engineering considerations	
4.1	Modifications incorporated in the EUT7	
4.2	Technical judgment	
4.3	Deviations from laboratory tests procedures	
Section 5	. Test conditions	
5.1	Atmospheric conditions	
5.2	Power supply range	
5.3	Uncertainty of measurement	
Section 6	. Test equipment9	
6.1	Test equipment list	
Section 7	. Test rules and requirements	
7.1	FCC 15.407(h)(2) Radar Detection Function of Dynamic Frequency Selection (DFS) 10	
Section 8	. Testing data	
8.1	Channel closing transmission and move time	
8.2	Non-occupancy period	
Section 9	. Block diagrams of test set-ups	
9.1	Test set-up diagram	



Section 1. Report summary

1.1 Applicant and manufacturer

Company name	Ring LLC
Address	1523 26 th Street, Santa Monica, CA, United States, 90404
1.2 Test specifications	
FCC 47 CFR Part 15, Subpart E, Clause 15.407	Unlicensed National Information Infrastructure Devises
FCC 47 CFR Part 15, Subpart E, Clause 15.407 RSS-247 Issue 1, May 2015, Section 6.3	Unlicensed National Information Infrastructure Devises Licence-Exempt Local Area Network (LE-LAN) Devices
FCC 47 CFR Part 15, Subpart E, Clause 15.407 RSS-247 Issue 1, May 2015, Section 6.3	Unlicensed National Information Infrastructure Devises Licence-Exempt Local Area Network (LE-LAN) Devices

1.3 Test methods

789033 D02 General UNII Test Procedures New Rules v02r01	Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices Part 15, Subpart E
905462 D02 Client Without DFS New Rules v01r02	U-NII client devices without radar detection capability
905462 D02 UNII DFS Compliance Procedures New Rules v02	Compliance measurement procedures for unlicensed – national information infrastructure devices operating in the 5250–5350 MHz and 5470–5725 MHz bands incorporating dynamic frequency selection

1.4 Statement of compliance

In the configuration tested, the EUT was found compliant.

Testing was completed against all relevant requirements of the test standard. Results obtained indicate that the product under test complies in full with the requirements tested. The test results relate only to the items tested.

See "Summary of test results" for full details.

1.5 Exclusions

None

1.6 Test report revision history

 Table 1.6-1: Test report revision history

Revision #	Date of issue	Details of changes made to test report
TRF	March 29, 2019	Original report issued
R1	April 2, 2019	Remove model variant, update DFS block diagram



Section 2. Summary of test results

2.1 FCC §15.407(h)(2), test results

KDB Section	Test description	Verdict
5.2	DFS detection threshold	Not applicable
7.8.1	U-NII detection bandwidth	Not applicable
7.8.2.1	Initial Channel Availability Check (CAC) time	Not applicable
7.8.2.2	In-service monitoring, radar burst at the beginning of the CAC	Not applicable
7.8.2.3	In-service monitoring, radar burst at the end of the CAC	Not applicable
7.8.3	Channel move time	Pass
7.8.3	Channel closing transmission time	Pass
7.8.3	Non-occupancy period	Pass
7.8.4.1	Statistical performance with short pulse radar test	Not applicable
7.8.4.2	Statistical performance with long pulse radar test	Not applicable
7.8.4.3	Statistical performance with frequency hopping radar test	Not applicable

Note:

2.2 RSS-247 Issue 1, test results

Section	Test description	Verdict
RSS-247 6.3(1)	DFS radar signal detection threshold	Not applicable
KDB Section 7.8.1	U-NII detection bandwidth	Not applicable
RSS-247 6.3(2)(ii)	Initial Channel Availability Check (CAC) time	Not applicable
RSS-247 6.3(2)(i)	In-service monitoring, radar burst at the beginning of the CAC	Not applicable
RSS-247 6.3(2)(i)	In-service monitoring, radar burst at the end of the CAC	Not applicable
RSS-247 6.3(2)(iii)	Channel move time	Pass
RSS-247 6.3(2)(iv)	Channel closing transmission time	Pass
RSS-247 6.3(2)(v)	Non-occupancy period	Pass
KDB Section7.8.4.1	Statistical performance with short pulse radar test	Not applicable
KDB Section7.8.4.2	Statistical performance with long pulse radar test	Not applicable
KDB Section7.8.4.3	Statistical performance with frequency hopping radar test	Not applicable

Note:



Section 3. Equipment under test (EUT) details

3.1 Sample information

Receipt date	February 1, 2019
Nemko sample ID number	Item # 3

3.2 EUT information

Product name	Ring
Model	Base Station NA
Serial number	BHBN21851PG000052

3.3 Technical information

Operating band	5250–5350 MHz
Operating frequencies	20 MHz channel: 5260–5320 MHz; 40 MHz channel: 5270–5310 MHz
Modulation type	802.11a/n
Channel bandwidth	20 MHz, 40 MHz
Power requirements	5 V _{DC} (via external 100-240 VAC, 50/60 Hz power adapter)
Antonna information	Antenna Gain is 5.6 dBi (inverted F)
Antenna mormation	The EUT uses a unique antenna coupling/ non-detachable antenna to the intentional radiator.

3.4 Product description and theory of operation

Communications Hub for Home Security Products

3.5 EUT exercise details

The EUT was setup in continuous transmit state



Section 4. Engineering considerations

4.1 Modifications incorporated in the EUT

There were no modifications performed to the EUT during this assessment.

4.2 Technical judgment

None

4.3 Deviations from laboratory tests procedures

No deviations were made from laboratory procedures.



Section 5. Test conditions

5.1 Atmospheric conditions

Temperature	15–30 °C
Relative humidity	20–75 %
Air pressure	860–1060 mbar

When it is impracticable to carry out tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests shall be recorded and stated.

5.2 Power supply range

The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage, or any of the declared voltages ±5 %, for which the equipment was designed.

5.3 Uncertainty of measurement

Nemko Canada Inc. has calculated measurement uncertainty and is documented in EMC/MUC/001 "Uncertainty in EMC measurements." Measurement uncertainty was calculated using the methods described in CISPR 16-4 Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC measurements; as well as described in UKAS LAB34: The expression of Uncertainty in EMC Testing. Measurement uncertainty calculations assume a coverage factor of K=2 with 95% certainty.



Section 6. Test equipment

6.1 Test equipment list

Equipment	Manufacturer	Model no.	Asset no.	Cal cycle	Next cal.	
DFS test box	Aeroflex	PXI	FA002628	-	VOU	
Spectrum analyzer	Rohde & Schwarz	FSW43	FA002971	1 year	June 1/19	
50 Ω coax cable	Huber + Suhner	None	FA003047	1 year	Nov 12/19	
50 Ω coax cable	Huber + Suhner	None	FA003044	1 year	Nov 12/19	
1 – 18 GHz Horn	ETS-Lindgren	3115	FA000649	1 year	Nov 28/19	

Table 6.1-1: Equipment list



Section 7. Test rules and requirements

7.1 FCC 15.407(h)(2) Radar Detection Function of Dynamic Frequency Selection (DFS)

(2) Radar Detection Function of Dynamic Frequency Selection (DFS). U-NII devices operating with any part of its 26 dB emission bandwidth in the 5.25– 5.35 GHz and 5.47–5.725 GHz bands shall employ a DFS radar detection mechanism to detect the presence of radar systems and to avoid co-channel operation with radar systems. Operators shall only use equipment with a DFS mechanism that is turned on when operating in these bands. The device must sense for radar signals at 100 percent of its emission bandwidth. The minimum DFS detection threshold for devices with a maximum e.i.r.p. of 200 mW to 1 W (23–30 dBm) is –64 dBm. For devices that operate with less than 200 mW (23 dBm) e.i.r.p. and a power spectral density of less than 10 dBm in a 1 MHz band, the minimum detection threshold is –62 dBm. The detection threshold is the received power averaged over 1 microsecond referenced to a 0 dBi antenna. For the initial channel setting, the manufacturers shall be permitted to provide for either random channel selection or manual channel selection.

(i) Operational Modes. The DFS requirement applies to the following operational modes:

(A) The requirement for channel availability check time applies in the master operational mode.

(B) The requirement for channel move time applies in both the master and slave operational modes.

(ii) Channel Availability Check Time. A U-NII device shall check if there is a radar system already operating on the channel before it can initiate a transmission on a channel and when it has to move to a new channel. The U-NII device may start using the channel if no radar signal with a power level greater than the interference threshold values listed in paragraph (h)(2) of this section, is detected within 60 seconds.

(iii) Channel Move Time. After a radar's presence is detected, all transmissions shall cease on the operating channel within 10 seconds. Transmissions during this period shall consist of normal traffic for a maximum of 200 ms after detection of the radar signal. In addition, intermittent management and control signals can be sent during the remaining time to facilitate vacating the operating channel.

(iv) Non-occupancy Period. A channel that has been flagged as containing a radar system, either by a channel availability check or in-service monitoring, is subject to a non-occupancy period of at least 30 minutes. The non-occupancy period starts at the time when the radar system is detected.

Parameter Value Non-occupancy period Minimum 30 minutes Channel Availability Check Time 60 seconds Channel Move Time 10 seconds¹ Channel Closing Transmission Time 200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period^{1 and 2} U-NII Detection Bandwidth Minimum 100% of the 99% power bandwidth³

 Table 7.1-1: DFS Response Requirement Values

Notes: ¹The instant that the *Channel Move Time* and the *Channel Closing Transmission Time* begins is as follows:

• For the Short pulse radar Test Signals this instant is the end of the Burst.

• For the Frequency Hopping radar Test Signal, this instant is the end of the last radar Burst generated.

• For the Long Pulse radar Test Signal this instant is the end of the 12 second period defining the radar transmission.

² The *Channel Closing Transmission Time* is comprised of 200 milliseconds starting at the beginning of the *Channel Move Time* plus any additional intermittent control signals required to facilitate Channel changes (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

³ During the *U-NII Detection Bandwidth* detection test, radar type 0 is used and for each frequency step the minimum percentage of detection is 90%. Measurements are performed with no data traffic.

Table 7.1-2: Summary of the requirements

Description	Radar type	Requirement	Notes
7.8.3 Channel Move Time	Type 0	≤10 s	Widest BW
7.8.3 Channel Closing Transmission Time	Type 0	≤260 ms	Widest BW
7.8.3 Non-Occupancy Period	Type 0	>30 min	



Section 8. Testing data

8.1 Channel closing transmission and move time

8.1.1 Definitions and limits

Maximum channel closing transmission time is 200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. Maximum channel move time is 10 seconds.

8.1.2 Test summary

Test date	March 20, 2019	Temperature	23 °C
Test engineer	Mark Libbrecht	Air pressure	985 mbar
Verdict	Pass	Relative humidity	28 %

8.1.3 Observations, settings and special notes

The test was performed on the widest channel BW, which is 40 MHz with the use of Radar type 0.

8.1.4 Test data

Table 8.1-1: Channel closing transmission time results

Measured closing transmission time, ms	Limit, ms	Margin, ms
225.7	260.0	34.3

Table 8.1-2: Channel move time results

Measured move time, s	Limit, s	Margin, s
1.5	10.0	8.5

Table 8.1-3: Channel closing transmission and move time measurement results

Region	Start, s	End, s	Measured, ms	Limit, ms
0	0	0.2	0.7	200
1	0.2	10	10.6	60
2	10	12	0.0	0

Section 8	Testing data
Test name	Channel closing transmission and move time
Specification	KDB 905462 Section 7.8.3





Figure 8.1-1: Channel closing transmission and move time



8.2 Non-occupancy period

8.2.1 Definitions and limits

Non-occupancy period minimum is 30 minutes.

8.2.2 Test summary

Test date	March 20, 2019	Temperature	23 °C
Test engineer	Mark Libbrecht	Air pressure	985 mbar
Verdict	Pass	Relative humidity	28 %

8.2.3 Observations, settings and special notes

The EUT was monitored for more than 30 minutes following instant T_2 (the end of Radar pulses) to verify that the EUT does not resume any transmissions on this Channel. This test was performed once on the widest channel BW, which is 40 MHz with the use of Radar type 0.

8.2.4 Test data



Measured Non-occupancy period, min	Minimum limit, min	Margin, min
30.06	30	0.06

tt RG:VID Zero Span	10 dB • SWT 2	200 s VBW :	3 MHz				O1AP Clrv
						M1	1] -65,49 dB 23,77
0 dBm						DI	1] 0.82 1806.63
0 dBm							
0 dBm							
0 dBm							
J ubm	TPC - 59 000 dam -						
0 dBm	In the study of the		and a family strange	the state of the state of the		D1	former the second state of the second

13:24:45 20.03.2019





Section 9. Block diagrams of test set-ups

9.1 Test set-up diagram

