



FCC RF Test Report

APPLICANT : Ring LLC
EQUIPMENT : Ring Car Cam
BRAND NAME : Ring
MODEL NAME : 5B28S9
FCC ID : 2AEUPBHACC001
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DSS) Spread Spectrum Transmitter
TEST DATE(S) : Nov. 16, 2021 ~ Feb. 21, 2022

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

Alex Wang

Approved by: Alex Wang / Manager



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION..... 5

 1.1 Applicant 5

 1.2 Manufacturer 5

 1.3 Product Feature of Equipment Under Test..... 5

 1.4 Product Specification of Equipment Under Test..... 5

 1.5 Modification of EUT 5

 1.6 Testing Location 5

 1.7 Test Software 6

 1.8 Applicable Standards..... 6

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST..... 7

 2.1 Carrier Frequency Channel 7

 2.2 Test Mode 8

 2.3 Connection Diagram of Test System..... 9

 2.4 Support Unit used in test configuration and system 9

 2.5 EUT Operation Test Setup 9

 2.6 Measurement Results Explanation Example..... 10

3 TEST RESULT 11

 3.1 Number of Channel Measurement 11

 3.2 Hopping Channel Separation Measurement 15

 3.3 Dwell Time Measurement..... 21

 3.4 20dB and 99% Bandwidth Measurement 25

 3.5 Output Power Measurement..... 36

 3.6 Conducted Band Edges Measurement..... 37

 3.7 Conducted Spurious Emission Measurement 44

 3.8 Radiated Band Edges and Spurious Emission Measurement 54

 3.9 Antenna Requirements 58

4 LIST OF MEASURING EQUIPMENT 59

5 UNCERTAINTY OF EVALUATION..... 60

APPENDIX A. CONDUCTED TEST RESULTS

APPENDIX B. RADIATED SPURIOUS EMISSION

APPENDIX C. DUTY CYCLE PLOTS

APPENDIX D. SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR1O0826D	Rev. 01	Initial issue of report	Apr. 22, 2022



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)(i)	Number of Channels	≥ 50Chs	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	≥ 20dB Bandwidth	Pass	-
3.3	15.247(a)(1)(i)	Dwell Time of Each Channel	≤ 0.4sec in 20sec period	Pass	-
3.4	15.247(a)(1)(i)	20dB Bandwidth	≤ 500 kHz	Pass	-
3.4	-	99% Bandwidth	-	Pass	-
3.5	15.247(b)(2)	Peak Output Power	≤ 1 W	Pass	-
3.6	15.247(d)	Conducted Band Edges	≤ 20dBc	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	≤ 20dBc	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.05 dB at 960.100 MHz
-	15.207	AC Conducted Emission	15.207(a)	Pass	1
3.9	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

Remark 1: Not required means after assessing, test item is not necessary to carry out.

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Applicant

Ring LLC
1523 26th Street, Santa Monica CA 90404, USA

1.2 Manufacturer

Ring LLC
1523 26th Street, Santa Monica, CA 90404 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Ring Car Cam
Brand Name	Ring
Model Name	5B28S9
FCC ID	2AEUPBHACC001
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	902 MHz ~ 928 MHz
Number of Channels	129
Bandwidth / Spreading Factor	125kHz / 7, 8, 9
Maximum Output Power to Antenna	SF7 : 26.29 dBm (0.4256 W) SF8 : 25.93 dBm (0.3917 W) SF9 : 26.18 dBm (0.4150 W)
99% Occupied Bandwidth	SF7 : 0.131MHz SF8 : 0.131MHz SF9 : 0.131MHz
Antenna Type / Gain	Monopole Antenna with gain 0.60 dBi
Type of Modulation	LoRa-FHSS

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for



Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH06-KS TH01-KS	CN1257	314309

1.7 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH06-KS	AUDIX	E3	6.2009-8-24al

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
902-928 MHz	1	902.2	44	910.8	87	919.4
	2	902.4	45	911	88	919.6
	3	902.6	46	911.2	89	919.8
	4	902.8	47	911.4	90	920
	5	903	48	911.6	91	920.2
	6	903.2	49	911.8	92	920.4
	7	903.4	50	912	93	920.6
	8	903.6	51	912.2	94	920.8
	9	903.8	52	912.4	95	921
	10	904	53	912.6	96	921.2
	11	904.2	54	912.8	97	921.4
	12	904.4	55	913	98	921.6
	13	904.6	56	913.2	99	921.8
	14	904.8	57	913.4	100	922
	15	905	58	913.6	101	922.2
	16	905.2	59	913.8	102	922.4
	17	905.4	60	914	103	922.6
	18	905.6	61	914.2	104	922.8
	19	905.8	62	914.4	105	923
	20	906	63	914.6	106	923.2
	21	906.2	64	914.8	107	923.4
	22	906.4	65	915	108	923.6
	23	906.6	66	915.2	109	923.8
	24	906.8	67	915.4	110	924
	25	907	68	915.6	111	924.2
	26	907.2	69	915.8	112	924.4
	27	907.4	70	916	113	924.6
	28	907.6	71	916.2	114	924.8
	29	907.8	72	916.4	115	925
	30	908	73	916.6	116	925.2
	31	908.2	74	916.8	117	925.4
	32	908.4	75	917	118	925.6
	33	908.6	76	917.2	119	925.8
	34	908.8	77	917.4	120	926
	35	909	78	917.6	121	926.2
	36	909.2	79	917.8	122	926.4
	37	909.4	80	918	123	926.6
	38	909.6	81	918.2	124	926.8
	39	909.8	82	918.4	125	927
	40	910	83	918.6	126	927.2
	41	910.2	84	918.8	127	927.4
	42	910.4	85	919	128	927.6
	43	910.6	86	919.2	129	927.8

Note: The above EUT's information was declared by manufacturer.




2.2 Test Mode

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower) For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report,

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases			
Test Item	Modulation / Spreading Factor		
	LoRa FHSS / SF7	LoRa FHSS / SF8	LoRa FHSS / SF9
Conducted Test Cases	Mode 1: CH1_902.2 MHz	Mode 4: CH1_902.2 MHz	Mode 7: CH1_902.2 MHz
	Mode 2: CH65_915 MHz	Mode 5: CH65_915 MHz	Mode 8: CH65_915 MHz
	Mode 3: CH129_927.8 MHz	Mode 6: CH129_927.8 MHz	Mode 9: CH129_927.8 MHz
Radiated Test Cases	Mode 1: CH1_902.2 MHz	Mode 4: CH1_902.2 MHz	Mode 7: CH1_902.2 MHz
	Mode 2: CH65_915 MHz	Mode 5: CH65_915 MHz	Mode 8: CH65_915 MHz
	Mode 3: CH129_927.8 MHz	Mode 6: CH129_927.8 MHz	Mode 9: CH129_927.8 MHz

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	DC Power Supply	N/A	N/A	N/A	N/A	N/A
2.	OBD cable	Ring	5B29S1	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For LoRa FHSS function, the engineering test program was provided and enabled to make EUT continuous transmit.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.5 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.5 + 10 = 14.5 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW = 50kHz; VBW = 100KHz; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup




3.1.5 Test Result of Number of Hopping Frequency

Please refer to Appendix A.




SF7:

Number of Hopping Channel Plot on Channel 1 - 129



Date: 24.NOV.2021 07:56:50




Date: 24.NOV.2021 08:00:36




SF8:

Number of Hopping Channel Plot on Channel 1 - 129



Date: 30.NOV.2021 20:16:27




Date: 30.NOV.2021 20:19:13




SF9:

Number of Hopping Channel Plot on Channel 1 - 129



Date: 30.NOV.2021 20:25:38



Date: 30.NOV.2021 20:24:09

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels;
RBW = 50kHz; VBW = 100KHz; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup




3.2.5 Test Result of Hopping Channel Separation

Please refer to Appendix A.




SF7:

Channel Separation Plot on Channel 1 - 2



Date: 16 NOV.2021 22:33:58


Channel Separation Plot on Channel 64 - 65



Date: 16 NOV.2021 22:10:56




Channel Separation Plot on Channel 128 - 129



Date: 16 NOV.2021 22:31:25

SF8:


Channel Separation Plot on Channel 1 - 2



Date: 23 NOV.2021 13:55:44




Channel Separation Plot on Channel 64 - 65



Date: 23.NOV.2021 14:13:21

Channel Separation Plot on Channel 128 - 129




Date: 23.NOV.2021 14:33:13




SF9:

Channel Separation Plot on Channel 1 - 2



Date: 16 NOV 2021 23:37:25


Channel Separation Plot on Channel 64 - 65



Date: 16 NOV 2021 23:28:56



Channel Separation Plot on Channel 128 - 129



Date: 16 NOV 2021 23:46:56

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 20 KHz; VBW = 20KHz; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup






3.3.5 Test Result of Dwell Time

Please refer to Appendix A.

SF7:

DT on-time and Hops over 20 sec period



Date: 17.NOV.2021 01:02:14


Remark:

$$\begin{aligned}
 \text{Dwell Time(s)} &= \text{Hops Over Occupancy Time (hops)} \times \text{Package Transfer Time} \\
 &= 1 \text{ (hop)} \times 283.343 \text{ (ms)} \\
 &= 0.283 \text{ (sec)}
 \end{aligned}$$



SF8:

DT on-time and Hops over 20 sec period



Date: 30.NOV.2021 20:02:01


Remark:

$$\begin{aligned} \text{Dwell Time(s)} &= \text{Hops Over Occupancy Time (hops)} \times \text{Package Transfer Time} \\ &= 1 \text{ (hop)} \times 364.679 \text{ (ms)} \\ &= 0.365 \text{ (sec)} \end{aligned}$$



SF9:

DT on-time and Hops over 20 sec period



Date: 30.NOV.2021 20:28:08

Remark:

$$\begin{aligned}
 \text{Dwell Time(s)} &= \text{Hops Over Occupancy Time (hops)} \times \text{Package Transfer Time} \\
 &= 1 \text{ (hop)} \times 367.346 \text{ (ms)} \\
 &= 0.367 \text{ (sec)}
 \end{aligned}$$

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
RBW \geq 1% of the 20 dB bandwidth; VBW \geq RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
RBW \geq 1% of the 99% bandwidth; VBW \geq RBW; Sweep = auto; Detector function = sample;
Trace = max hold.
6. Measure and record the results in the test report.

3.4.4 Test Setup




3.4.5 Test Result of 20dB Bandwidth

Please refer to Appendix A.




SF7:

20 dB Bandwidth Plot on Channel 1



Date: 16 NOV, 2021 22:25:21


20 dB Bandwidth Plot on Channel 65



Date: 16 NOV, 2021 22:05:28




20 dB Bandwidth Plot on Channel 129



Date: 16 NOV 2021 22:26:47

SF8:


20 dB Bandwidth Plot on Channel 1



Date: 23 NOV 2021 13:02:23




20 dB Bandwidth Plot on Channel 65



Date: 23.NOV.2021 13:57:53

20 dB Bandwidth Plot on Channel 129




Date: 23.NOV.2021 14:19:37



SF9:

20 dB Bandwidth Plot on Channel 1



Date: 16 NOV, 2021 23:35:24


20 dB Bandwidth Plot on Channel 65



Date: 16 NOV, 2021 22:48:45



20 dB Bandwidth Plot on Channel 129



Date: 16 NOV 2021 23:45:20




3.4.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

SF7:

99% Occupied Bandwidth Plot on Channel 1



99% Occupied Bandwidth Plot on Channel 65






99% Occupied Bandwidth Plot on Channel 129



Date: 16 NOV 2021 22:27:38

SF8:


99% Occupied Bandwidth Plot on Channel 1



Date: 23 NOV 2021 13:01:37




99% Occupied Bandwidth Plot on Channel 65



Date: 23.NOV.2021 13:58:51

99% Occupied Bandwidth Plot on Channel 129



Date: 23.NOV.2021 14:20:20




SF9:

99% Occupied Bandwidth Plot on Channel 1



Date: 16 NOV. 2021 23:33:50


99% Occupied Bandwidth Plot on Channel 65



Date: 16 NOV. 2021 22:49:38



99% Occupied Bandwidth Plot on Channel 129



Date: 16 NOV 2021 23:44:49

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.5 Output Power Measurement

3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:
For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup



3.5.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

3.6.4 Test Setup







3.6.5 Test Result of Conducted Band Edges

SF7:

Low Band Edge Plot on Channel 1




High Band Edge Plot on Channel 129






SF8:

Low Band Edge Plot on Channel 1



Date: 23.NOV.2021 12:57:56

High Band Edge Plot on Channel 129




Date: 23.NOV.2021 14:28:33




SF9:

Low Band Edge Plot on Channel 1



High Band Edge Plot on Channel 129







3.6.6 Test Result of Conducted Hopping Mode Band Edges

SF7:

Hopping Mode Low Band Edge Plot




Hopping Mode High Band Edge Plot






SF8:

Hopping Mode Low Band Edge Plot



Date: 23.NOV.2021 13:45:57

Hopping Mode High Band Edge Plot




Date: 23.NOV.2021 13:41:25




SF9:

Hopping Mode Low Band Edge Plot



Hopping Mode High Band Edge Plot



3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.7.4 Test Setup







3.7.5 Test Result of Conducted Spurious Emission

SF7:

CSE Plot on Ch 1 between 30MHz ~ 1 GHz




CSE Plot on Ch 1 between 800 MHz ~ 10 GHz






CSE Plot on Ch 65 between 30MHz ~ 1 GHz



Date: 16 NOV. 2021 23:56:32


CSE Plot on Ch 65 between 800 MHz ~ 10 GHz



Date: 16 NOV. 2021 23:58:06




CSE Plot on Ch 129 between 30MHz ~ 1 GHz



Date: 16 NOV. 2021 23:54:26

CSE Plot on Ch 129 between 800 MHz ~ 10 GHz




Date: 16 NOV. 2021 23:51:38




SF8:

CSE Plot on Ch 1 between 30MHz ~ 1 GHz



Date: 23.NOV.2021 13:01:04


CSE Plot on Ch 1 between 800 MHz ~ 10 GHz



Date: 23.NOV.2021 13:49:57




CSE Plot on Ch 65 between 30MHz ~ 1 GHz



Date: 23.NOV.2021 14:10:11


CSE Plot on Ch 65 between 800 MHz ~ 10 GHz




Date: 23.NOV.2021 14:03:24



CSE Plot on Ch 129 between 30MHz ~ 1 GHz




CSE Plot on Ch 129 between 800 MHz ~ 10 GHz






SF9:

CSE Plot on Ch 1 between 30MHz ~ 1 GHz



Date: 16 NOV, 2021 23:33:21


CSE Plot on Ch 1 between 800 MHz ~ 10 GHz



Date: 16 NOV, 2021 23:30:47




CSE Plot on Ch 65 between 30MHz ~ 1 GHz



Date: 16 NOV 2021 22:53:33


CSE Plot on Ch 65 between 800 MHz ~ 10 GHz



Date: 16 NOV 2021 22:52:07




CSE Plot on Ch 129 between 30MHz ~ 1 GHz



Date: 16 NOV. 2021 23:43:20

CSE Plot on Ch 129 between 800 MHz ~ 10 GHz



Date: 16 NOV. 2021 23:44:20



3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.8.3 Test Procedures


1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz, RBW=1MHz for $f > 1$ GHz ; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.8.7 Duty Cycle

Please refer to Appendix C.

3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.



3.9 Antenna Requirements

3.9.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.9.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.9.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 14, 2021	Nov. 16, 2021~ Nov. 30, 2021	Oct. 13, 2022	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 05, 2022	Nov. 16, 2021~ Nov. 30, 2021	Jan. 04, 2023	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 05, 2022	Nov. 16, 2021~ Nov. 30, 2021	Jan. 04, 2023	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz;Max 30dBm	Oct. 16, 2021	Feb. 21, 2022	Oct. 15, 2022	Radiation (03CH06-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz-44GHz	Apr. 12, 2021	Feb. 21, 2022	Apr. 11, 2022	Radiation (03CH06-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 30, 2021	Feb. 21, 2022	Oct. 29, 2022	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	49921	30MHz-1GHz	May 27, 2021	Feb. 21, 2022	May 26, 2022	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218652	1GHz~18GHz	Apr. 25, 2021	Feb. 21, 2022	Apr. 24, 2022	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	187289	9KHz ~1GHZ	Apr. 12, 2021	Feb. 21, 2022	Apr. 11, 2022	Radiation (03CH06-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2025788	1Ghz-18Ghz	Jul. 30, 2021	Feb. 21, 2022	Jul. 29, 2022	Radiation (03CH06-KS)
Amplifier	Keysight	83017A	MY53270203	500MHz~26.5GHz	Apr. 13, 2021	Feb. 21, 2022	Apr. 12, 2022	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Feb. 21, 2022	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Feb. 21, 2022	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Feb. 21, 2022	NCR	Radiation (03CH06-KS)

NCR: No Calibration Required.



5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.94dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0dB
---	-------



Appendix A. Conducted Test Results

Test Engineer:	Kib Shi	Temperature:	20~26	°C
Test Date:	2021/11/16~2021/11/30	Relative Humidity:	40~51	%

LoRa-FHSS-Spreading Factor 7**TEST RESULTS DATA****20dB and 99% Occupied Bandwidth and Hopping Channel Separation**

Mod.		NTX	CH.	Freq. (MHz)	20db BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
SF7		1	1	902.2	0.148	0.130	0.271	0.148	Pass
SF7		1	65	915	0.152	0.131	0.205	0.152	Pass
SF7		1	129	927.8	0.150	0.130	0.269	0.150	Pass

TEST RESULTS DATA**Dwell Time**

Mod.	CH.	DT On-time per hop (ms)	Total hops over 20sec	Dwell Time (sec)	Limits (sec)	Pass/Fail
SF7	hopping	283.343	1.00	0.28	0.4	Pass

TEST RESULTS DATA**Peak Power Table**

mode	Freq. (MHz)	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
SF7	902.2	1	26.21	30.00	Pass
	915	1	26.11	30.00	Pass
	927.8	1	26.29	30.00	Pass

TEST RESULTS DATA**Number of Hopping Frequency**

Number of Hopping (Channel)	Limits (Channel)	Pass/Fail
129	> 50	Pass

LoRa-FHSS-Spreading Factor 8**TEST RESULTS DATA*****20dB and 99% Occupied Bandwidth and Hopping Channel Separation***

Mod.	NTX	CH.	Freq. (MHz)	20db BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
SF8	1	1	902.2	0.154	0.130	0.234	0.154	Pass
SF8	1	65	915	0.151	0.131	0.278	0.151	Pass
SF8	1	129	927.8	0.151	0.131	0.313	0.151	Pass

TEST RESULTS DATA***Dwell Time***

Mod.	CH.	DT On-time per hop (ms)	Total hops over 20sec	Dwell Time (sec)	Limits (sec)	Pass/Fail
SF8	hopping	364.679	1.00	0.36	0.4	Pass

TEST RESULTS DATA***Peak Power Table***

mode	Freq. (MHz)	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
SF8	902.2	1	25.88	30.00	Pass
	915	1	25.93	30.00	Pass
	927.8	1	25.87	30.00	Pass

TEST RESULTS DATA***Number of Hopping Frequency***

Number of Hopping (Channel)	Limits (Channel)	Pass/Fail
129	> 50	Pass

LoRa-FHSS-Spreading Factor 9**TEST RESULTS DATA****20dB and 99% Occupied Bandwidth and Hopping Channel Separation**

Mod.	NTX	CH.	Freq. (MHz)	20db BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
SF9	1	1	902.2	0.149	0.131	0.224	0.149	Pass
SF9	1	65	915	0.151	0.131	0.221	0.151	Pass
SF9	1	129	927.8	0.149	0.131	0.236	0.149	Pass

TEST RESULTS DATA**Dwell Time**

Mod.	CH.	DT On-time per hop (ms)	Total hops over 20sec	Dwell Time (sec)	Limits (sec)	Pass/Fail
SF9	hopping	367.346	1.00	0.37	0.4	Pass

TEST RESULTS DATA**Peak Power Table**

mode	Freq. (MHz)	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
SF9	902.2	1	26.06	30.00	Pass
	915	1	26.18	30.00	Pass
	927.8	1	26.13	30.00	Pass

TEST RESULTS DATA**Number of Hopping Frequency**

Number of Hopping (Channel)	Limits (Channel)	Pass/Fail
129	> 50	Pass



Appendix B. Radiated Spurious Emission

902~928MHz

LORA FHSS SF=7 (Band Edge @ 3m)

Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
902.2MHz	120.21	32.73	-10.77	43.5	45.86	17.4	1.63	32.16	150	349	P	H
	263.77	31.51	-14.49	46	41.46	20	2.22	32.17	150	349	P	H
	902.03	119.53	-	-	118.3	28.94	4.49	32.2	150	349	P	H
	120.21	30.03	-13.47	43.5	43.16	17.4	1.63	32.16	155	327	P	V
	240.49	29.8	-16.2	46	42.59	17.3	2.09	32.18	155	327	P	V
	902.03	114.08	-	-	112.85	28.94	4.49	32.2	155	327	P	V
915MHz	120.21	30.5	-13	43.5	43.63	17.4	1.63	32.16	155	334	P	H
	263.77	29.84	-16.16	46	39.79	20	2.22	32.17	155	334	P	H
	914.64	120.34	-	-	118.73	29.3	4.51	32.2	155	334	P	H
	120.21	29.14	-14.36	43.5	42.27	17.4	1.63	32.16	158	321	P	V
	240.1	28.45	-17.55	46	41.24	17.3	2.09	32.18	158	321	P	V
	914.64	112.62	-	-	111.01	29.3	4.51	32.2	158	321	P	V
927.8MHz	120.21	31.41	-12.09	43.5	44.54	17.4	1.63	32.16	150	332	P	H
	928.22	121.07	-	-	119.27	29.46	4.54	32.2	150	332	P	H
	960.23	47.68	-6.32	54	44.15	31.1	4.61	32.18	150	332	P	H
	120.21	29.17	-14.33	43.5	42.3	17.4	1.63	32.16	158	314	P	V
	928.22	115.44	-	-	113.64	29.46	4.54	32.2	158	314	P	V
	960.23	45.63	-8.37	54	42.1	31.1	4.61	32.18	158	314	P	V
Remark	<ol style="list-style-type: none"> No other spurious found. All results are PASS against Peak and Average limit line. 											



LORA FHSS SF=7 (Harmonic @ 3m)

	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
902.2MHz		1804	35.87	-63.66	99.53	63.65	30.6	6.34	64.72	100	360	P	H
		2706	40.91	-33.09	74	65.84	32.3	7.86	65.09	100	360	P	H
		1804	36.73	-57.35	94.08	64.51	30.6	6.34	64.72	300	360	P	V
		2706	39.38	-34.62	74	64.31	32.3	7.86	65.09	300	360	P	V
915MHz		1828	36.26	-64.08	100.34	63.8	30.78	6.4	64.72	0	0	P	H
		2746	42.58	-31.42	74	67.43	32.3	7.96	65.11	100	0	P	H
		1828	36.23	-56.39	92.62	63.77	30.78	6.4	64.72	0	360	P	V
		2746	46.12	-27.88	74	70.97	32.3	7.96	65.11	300	360	P	V
927.8MHz		1855	36.92	-64.15	101.07	64.33	30.88	6.43	64.72	100	360	P	H
		2782	49.52	-24.48	74	74.32	32.3	8.02	65.12	100	360	P	H
		1855	39.21	-56.23	95.44	66.62	30.88	6.43	64.72	300	0	P	V
		2782	44.78	-29.22	74	69.58	32.3	8.02	65.12	300	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



LORA FHSS SF=8 (Band Edge @ 3m)

	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
902.2MHz		120.21	31.4	-12.1	43.5	44.53	17.4	1.63	32.16	156	341	P	H
		263.77	30.67	-15.33	46	40.62	20	2.22	32.17	156	341	P	H
		902.03	120.52	-	-	119.29	28.94	4.49	32.2	156	341	P	H
		120.21	30.48	-13.02	43.5	43.61	17.4	1.63	32.16	147	312	P	V
		240.49	28.08	-17.92	46	40.87	17.3	2.09	32.18	147	312	P	V
		902.03	113.9	-	-	112.67	28.94	4.49	32.2	147	312	P	V
915MHz		120.21	31.29	-12.21	43.5	44.42	17.4	1.63	32.16	155	350	P	H
		263.77	31.45	-14.55	46	41.4	20	2.22	32.17	155	350	P	H
		914.64	121.79	-	-	120.18	29.3	4.51	32.2	155	350	P	H
		120.21	29.02	-14.48	43.5	42.15	17.4	1.63	32.16	157	321	P	V
		249.52	28.68	-17.32	46	40.51	18.28	2.09	32.2	157	321	P	V
		914.64	114.7	-	-	113.09	29.3	4.51	32.2	157	321	P	V
927.8MHz		120.21	31.04	-12.46	43.5	44.17	17.4	1.63	32.16	142	321	P	H
		928.22	122.72	-	-	120.92	29.46	4.54	32.2	142	321	P	H
		960.23	50.12	-3.88	54	46.59	31.1	4.61	32.18	142	321	P	H
		120.21	30.2	-13.3	43.5	43.33	17.4	1.63	32.16	154	318	P	V
		928.22	115.49	-	-	113.69	29.46	4.54	32.2	154	318	P	V
		960.23	43.96	-10.04	54	40.43	31.1	4.61	32.18	154	318	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



LORA FHSS SF=8 (Harmonic @ 3m)

	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
902.2MHz		1804	36.2	-64.32	100.52	63.98	30.6	6.34	64.72	100	360	P	H
		2707	46.11	-27.89	74	71.04	32.3	7.86	65.09	100	360	P	H
		1801	36.72	-57.18	93.9	64.5	30.6	6.34	64.72	100	360	P	V
		2710	42.43	-31.57	74	67.34	32.3	7.89	65.1	100	360	P	V
915MHz		1828	36.17	-65.62	101.79	63.71	30.78	6.4	64.72	300	0	P	H
		2746	44.26	-29.74	74	69.11	32.3	7.96	65.11	300	0	P	H
		1828	35.56	-59.14	94.7	63.1	30.78	6.4	64.72	100	360	P	V
		2746	40.33	-33.67	74	65.18	32.3	7.96	65.11	100	360	P	V
927.8MHz		1855	36.95	-65.77	102.72	64.36	30.88	6.43	64.72	300	0	P	H
		2782	47.16	-26.84	74	71.96	32.3	8.02	65.12	300	0	P	H
		1855	36.64	-58.85	95.49	64.05	30.88	6.43	64.72	100	360	P	V
		2782	45.73	-28.27	74	70.53	32.3	8.02	65.12	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



LORA FHSS SF=9 (Band Edge @ 3m)

	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
902.2MHz		120.21	31.22	-12.28	43.5	44.35	17.4	1.63	32.16	155	344	P	H
		263.77	32.36	-13.64	46	42.31	20	2.22	32.17	155	344	P	H
		902.03	121.19	-	-	119.96	28.94	4.49	32.2	155	344	P	H
		120.21	29.19	-14.31	43.5	42.32	17.4	1.63	32.16	155	322	P	V
		240.117	29.92	-16.08	46	42.71	17.3	2.09	32.18	155	322	P	V
		902.03	113.96	-	-	112.73	28.94	4.49	32.2	155	322	P	V
915MHz		120.21	30.73	-12.77	43.5	43.86	17.4	1.63	32.16	150	350	P	H
		263.77	31.3	-14.7	46	41.25	20	2.22	32.17	150	350	P	H
		914.64	122.35	-	-	120.74	29.3	4.51	32.2	150	350	P	H
		120.21	28.59	-14.91	43.5	41.72	17.4	1.63	32.16	159	314	P	V
		240.12	29.68	-16.32	46	42.47	17.3	2.09	32.18	159	314	P	V
		914.64	114.72	-	-	113.11	29.3	4.51	32.2	159	314	P	V
927.8MHz		120.21	30.53	-12.97	43.5	43.66	17.4	1.63	32.16	152	341	P	H
		928.22	122.73	-	-	120.93	29.46	4.54	32.2	152	341	P	H
		960.1	50.95	-3.05	54	47.42	31.1	4.61	32.18	152	341	P	H
		265.71	28.67	-17.33	46	38.81	19.8	2.23	32.17	150	329	P	V
		928.22	115.52	-	-	113.72	29.46	4.54	32.2	150	329	P	V
		960.23	45.63	-8.37	54	42.1	31.1	4.61	32.18	150	329	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



LORA FHSS SF=9 (Harmonic @ 3m)

	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
902.2MHz		1805	36.35	-64.84	101.19	64.13	30.6	6.34	64.72	300	360	P	H
		2706	44.39	-29.61	74	69.32	32.3	7.86	65.09	300	360	P	H
		1805	36.54	-57.42	93.96	64.32	30.6	6.34	64.72	100	360	P	V
		2707	43.16	-30.84	74	68.09	32.3	7.86	65.09	100	360	P	V
915MHz		1828	36.6	-65.75	102.35	64.14	30.78	6.4	64.72	100	360	P	H
		2746	43.73	-30.27	74	68.58	32.3	7.96	65.11	100	360	P	H
		1828	35.98	-58.74	94.72	63.52	30.78	6.4	64.72	300	0	P	V
		2746	40.81	-33.19	74	65.66	32.3	7.96	65.11	300	0	P	V
927.8MHz		1855	35.87	-66.86	102.73	63.28	30.88	6.43	64.72	300	0	P	H
		2782	49.67	-24.33	74	74.47	32.3	8.02	65.12	300	0	P	H
		1855	35.77	-59.75	95.52	63.18	30.88	6.43	64.72	100	360	P	V
		2782	44.95	-29.05	74	69.75	32.3	8.02	65.12	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
2402MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:


1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.




Appendix C. Duty Cycle Plots

SF7 on time Plot



Date: 16.NOV.2021 22:06:22


SF8 on time Plot



Date: 23.NOV.2021 14:17:05



SF9 on time Plot



Date: 16.NOV.2021 23:27:03

Note: Duty cycle = 100%