ring

Ring 1523 26th Street Santa Monica CA 90404 USA

2020/09/10

FCC C2PC / ISED C3PC Permissive change letter

Federal Communications Commission 7435 Oakland Mills Road Columbia, MD 21046

Certification and Engineering Bureau ISED Canada 3701 Carling Avenue (Building 94) Ottawa, Ontario K2H 8S2

To whom it may concern,

We, Ring LLC. apply for certification of the below described changes to the following existing certifications:

FCC-ID: 2AEUPBHARB001, initial grant data: 2019-01-21

IC: 20271-BHARB001, HVIN: 5B01S8, approval date: 2019-01-29

under FCC Class 2 Permissive Change rules according to FCC §2.1043 (b)(2) and ISED Class 3 Permissive Change rules according to ISED RSP-100, issue 12, section 10.

For ISED, the updated products will be identified with the following dedicated FVIN: 0.7.5-33 (IC ID and HVIN remain unchanged).

The purpose of this application is to add the following hopping modes by SW activation, to the existing initial certification which was for non-hopping mode (DTS) only: LoRa FHSS 250KHz: 902.3-926.7MHz (Channel Separation:400KHz)---61channels LoRa FHSS 125KHz 902.2-927.8MHz (Channel Separation:200KHz)---129channels FSK FHSS 5Kbps 902.2-927.8MHz (Channel Separation:200KHz)---129channels FSK FHSS 50Kbps 902.2-927.8MHz (Channel Separation:200KHz)---129channels FSK FHSS 150Kbps 902.2-927.6MHz (Channel Separation:200KHz)---64channels FSK FHSS 150Kbps 902.4-927.6MHz (Channel Separation:400KHz)---64channels FSK FHSS 250Kbps 902.5-927.5MHz (Channel Separation:500KHz)---51channels

ring

Ring 1523 26th Street Santa Monica CA 90404 USA

In addition, we introduce the following HW modification for further production units. HW modification:

(1)C84 and C85 changed from 8pF to Not Connect (Remove SX1262 32MHz crystal load capacitors)

In SX1262 datasheet explain this:

The SX1261/2 does not require the user to set external foot capacitors on the XTAL supplying the 32 MHz clock. Indeed, the device is fitted with internal programmable capacitors connected independently to the pins XTA and XTB of the device. The added functionality and HW update will not increase maximum RF output power as initially reported and certified.

Ongoing compliance with all limits according to FCC 15.247 and ISED RSS-247 issue 2 for non-hopping and hopping modes has been verified by testing in accredited and recognized laboratories of DEKRA Testing & Certification (Suzhou) Co., Ltd. and is documented in related test reports, as listed below:

Test Report number 2080843R-RF-CA-P06V01 Test Report number 1922002R-RF-US-P06V01

We confirm, that all changes are within the boundaries of the FCC C2PC and ISED C3PC rules.

Sincerely,

Cano haieh

Hand signed signature

Printed name title

Carro Hsieh Engineer

Company name and address

Ring LLC 1523 26th St, Santa Monica, CA 90404, USA