

FCC Radio Test Report

FCC ID: 2AEUPBHARG031

This report concerns (check one): Original Grant Class II Change

Project No. : 1512192
Equipment : Ring
Model Name : Video Doorbell
Applicant : Bot Home Automation, Inc.
Address : 1523 26th Street Santa Monica California United States 90404

Date of Receipt : Dec. 24, 2015
Date of Test : Dec. 24, 2015 ~ Jan. 05, 2016
Issued Date : Jan. 06, 2016
Tested by : BTL Inc.

Testing Engineer : Rush Kao
(Rush Kao)

Technical Manager : Jeff Yang
(Jeff Yang)

Authorized Signatory : Andy Chiu
(Andy Chiu)

B T L I N C .

B1, No.37, Lane 365, Yang Guang St.,
Nei-Hu District, Taipei City 114, Taiwan.
TEL:+886-2-2657-3299 FAX: +886-2- 2657-3331

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **R.O.C**, or National Institute of Standards and Technology (**NIST**) of **U.S.A**.

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

BTL's report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL's** authorized written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

| Table of Contents | Page |
|--|-------------|
| 1 . CERTIFICATION | 6 |
| 2 . SUMMARY OF TEST RESULTS | 7 |
| 2.1 TEST FACILITY | 7 |
| 2.2 MEASUREMENT UNCERTAINTY | 8 |
| 3 . GENERAL INFORMATION | 9 |
| 3.1 GENERAL DESCRIPTION OF EUT | 9 |
| 3.2 DESCRIPTION OF TEST MODES | 10 |
| 3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING | 11 |
| 3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED | 11 |
| 3.5 DESCRIPTION OF SUPPORT UNITS | 11 |
| 4 . EMC EMISSION TEST | 12 |
| 4.1 CONDUCTED EMISSION MEASUREMENT | 12 |
| 4.1.1 POWER LINE CONDUCTED EMISSION LIMITS | 12 |
| 4.1.2 TEST PROCEDURE | 12 |
| 4.1.3 DEVIATION FROM TEST STANDARD | 12 |
| 4.1.4 TEST SETUP | 13 |
| 4.1.5 EUT OPERATING CONDITIONS | 13 |
| 4.1.6 EUT TEST CONDITIONS | 13 |
| 4.1.7 TEST RESULTS | 13 |
| 4.2 RADIATED EMISSION MEASUREMENT | 14 |
| 4.2.1 RADIATED EMISSION LIMITS | 14 |
| 4.2.2 TEST PROCEDURE | 15 |
| 4.2.3 DEVIATION FROM TEST STANDARD | 15 |
| 4.2.4 TEST SETUP | 16 |
| 4.2.5 EUT OPERATING CONDITIONS | 17 |
| 4.2.6 EUT TEST CONDITIONS | 17 |
| 4.2.7 TEST RESULTS (9KHZ TO 30MHZ) | 18 |
| 4.2.8 TEST RESULTS (30MHZ TO 1000 MHZ) | 18 |
| 4.2.9 TEST RESULTS (ABOVE 1000 MHZ) | 18 |
| 5 . BANDWIDTH TEST | 19 |
| 5.1 APPLIED PROCEDURES | 19 |
| 5.1.1 TEST PROCEDURE | 19 |
| 5.1.2 DEVIATION FROM STANDARD | 19 |
| 5.1.3 TEST SETUP | 19 |
| 5.1.4 EUT OPERATION CONDITIONS | 19 |
| 5.1.5 EUT TEST CONDITIONS | 19 |
| 5.1.6 TEST RESULTS | 19 |
| 6 . MAXIMUM PEAK CONDUCTED OUTPUT POWER TEST | 20 |

| Table of Contents | Page |
|--|-------------|
| 6.1 APPLIED PROCEDURES / LIMIT | 20 |
| 6.1.1 TEST PROCEDURE | 20 |
| 6.1.2 DEVIATION FROM STANDARD | 20 |
| 6.1.3 TEST SETUP | 20 |
| 6.1.4 EUT OPERATION CONDITIONS | 20 |
| 6.1.5 EUT TEST CONDITIONS | 20 |
| 6.1.6 TEST RESULTS | 20 |
| 7 . ANTENNA CONDUCTED SPURIOUS EMISSION | 21 |
| 7.1 APPLIED PROCEDURES / LIMIT | 21 |
| 7.1.1 TEST PROCEDURE | 21 |
| 7.1.2 DEVIATION FROM STANDARD | 21 |
| 7.1.3 TEST SETUP | 21 |
| 7.1.4 EUT OPERATION CONDITIONS | 21 |
| 7.1.5 EUT TEST CONDITIONS | 21 |
| 7.1.6 TEST RESULTS | 21 |
| 8 . POWER SPECTRAL DENSITY TEST | 22 |
| 8.1 APPLIED PROCEDURES / LIMIT | 22 |
| 8.1.1 TEST PROCEDURE | 22 |
| 8.1.2 DEVIATION FROM STANDARD | 22 |
| 8.1.3 TEST SETUP | 22 |
| 8.1.4 EUT OPERATION CONDITIONS | 22 |
| 8.1.5 EUT TEST CONDITIONS | 22 |
| 8.1.6 TEST RESULTS | 22 |
| 9 . MEASUREMENT INSTRUMENTS LIST | 23 |
| 10 . EUT TEST PHOTO | 25 |
| ATTACHMENT A - CONDUCTED EMISSION | 29 |
| ATTACHMENT B - RADIATED EMISSION (9KHZ TO 30MHZ) | 32 |
| ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ) | 35 |
| ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ) | 40 |
| ATTACHMENT E - BANDWIDTH | 113 |
| ATTACHMENT F – MAXIMUM PEAK CONDUCTED OUTPUT POWER | 120 |
| ATTACHMENT G - ANTENNA CONDUCTED SPURIOUS EMISSION | 122 |
| ATTACHMENT H - POWER SPECTRAL DENSITY | 132 |

REPORT ISSUED HISTORY

| Issued No. | Description | Issued Date |
|--------------------|-----------------|---------------|
| BTL-FCCP-1-1512192 | Original Issue. | Jan. 06, 2016 |

1. CERTIFICATION

Equipment : Ring
Brand Name : N/A
Model Name : Video Doorbell
Applicant : Bot Home Automation, Inc.
Manufacturer : GOLDTEK TECHNOLOGY CO., Ltd.
Address : 3F, No.10 Jiankang Rd., Zhonghe Dist., New Taipei City 23586, Taiwan
Factory : GOLDTEK TECHNOLOGY CO., Ltd.
Address : 3F, No.10 Jiankang Rd., Zhonghe Dist., New Taipei City 23586, Taiwan
Date of Test : Dec. 24, 2015 ~ Jan. 05, 2016
Test Sample : Engineering Sample
Standard(s) : FCC Part15, Subpart C (15.247) / ANSI C63.10-2013

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-1-1512192) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

| Applied Standard(s): FCC Part15 (15.247) , Subpart C | | | |
|--|-------------------------------------|----------|--------|
| Standard(s) Section | Test Item | Judgment | Remark |
| 15.207 | Conducted Emission | PASS | |
| 15.247(d) | Antenna conducted Spurious Emission | PASS | |
| 15.247(a)(2) | 6dB Bandwidth | PASS | |
| 15.247(b)(3) | Peak Output Power | PASS | |
| 15.247(e) | Power Spectral Density | PASS | |
| 15.203 | Antenna Requirement | PASS | |
| 15.209/15.205 | Transmitter Radiated Emissions | PASS | |

NOTE:

(1) "N/A" denotes test is not applicable in this test report.

2.1 TEST FACILITY

The test facilities used to collect the test data in this report:

Conducted emission Test:

C05: (VCCI RN: C-4742; FCC RN:965108; FCC DN:TW1082)

No. 68-1, Ln. 169, Sec.2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan

Radiated emission Test (Below 1 GHz):

CB08: (FCC RN: 614388; FCC DN: TW1054; IC Assigned Code: 4428C-1)

1F., No. 61, Ln. 77, Sing-ai Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

Radiated emission Test (Above 1 GHz):

CB08: (VCCI RN: G-91; FCC RN: 614388; FCC DN: TW1054; IC Assigned Code: 4428C-1)

1F., No. 61, Ln. 77, Sing-ai Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. The BTL measurement uncertainty is less than the CISPR 16-4-2 U_{CISPR} requirement.

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

A. Conducted emission test:

| Test Site | Method | Measurement Frequency Range | U, (dB) |
|-----------|--------|-----------------------------|---------|
| C05 | CISPR | 150 kHz~30MHz | 2.04 |

B. Radiated emission test:

| Test Site | Method | Measurement Frequency Range | U,(dB) |
|--------------|--------|-----------------------------|--------|
| CB08 (3m) | CISPR | 9kHz ~ 150kHz | 4.00 |
| | | 150kHz ~ 30MHz | 4.00 |

| Test Site | Method | Measurement Frequency Range | Ant. H / V | U,(dB) |
|--------------|--------|-----------------------------|---------------|--------|
| CB08 (3m) | CISPR | 30MHz ~ 200MHz | V | 3.06 |
| | | 30MHz ~ 200MHz | H | 2.58 |
| | | 200MHz ~ 1,000MHz | V | 3.50 |
| | | 200MHz ~ 1,000MHz | H | 3.10 |

| Test Site | Method | Measurement Frequency Range | Ant. H / V | U,(dB) |
|--------------|--------|-----------------------------|---------------|--------|
| CB08 (3m) | CISPR | 1GHz ~ 6GHz | V | 4.14 |
| | | 1GHz ~ 6GHz | H | 4.14 |
| | | 6GHz ~ 18GHz | V | 5.34 |
| | | 6GHz ~ 18GHz | H | 5.34 |

Our calculated Measurement Instrumentation Uncertainty is shown in the tables above. These are our U_{lab} values in CISPR 16-4-2 terminology.

Since Table 1 of CISPR 16-4-2 has values of measurement instrumentation uncertainty, called U_{CISPR} , as follows:

Conducted Disturbance (mains port) – 150 kHz – 30 MHz : 3.6 dB

Radiated Disturbance (electric field strength on an open area test site or alternative test site) – 30 MHz – 1000 MHz : 5.2 dB

It can be seen that our U_{lab} values are smaller than U_{CISPR} .

Note: unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

| | | |
|---------------------|---|---|
| Equipment | Ring | |
| Brand Name | N/A | |
| Model Name | Video Doorbell | |
| Model Difference | N/A | |
| Product Description | Operation Frequency | 2412~2462 MHz |
| | Modulation Technology | 802.11b:DSSS 802.11g:OFDM 802.11n:OFDM |
| | Bit Rate of Transmitter | 802.11b: 11/5.5/2/1 Mbps 802.11g: 54/48/36/24/18/12/9/6 Mbps 802.11n up to 65.0 Mbps |
| | Output Power (Max.) | 802.11b: 15.85dBm 802.11g: 18.41dBm 802.11n(20MHz): 17.82dBm |
| Power Source | #1 Supplied from USB port. #2 Supplied from Battery. Model:B15169 | |
| Power Rating | #1 DC 5V #2 3.75V 5000mAh 18.75Wh | |

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. Channel List:

| CH01 – CH11 for 802.11b, 802.11g, 802.11n(20MHz) | | | | | | | |
|--|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 01 | 2412 | 04 | 2427 | 07 | 2442 | 10 | 2457 |
| 02 | 2417 | 05 | 2432 | 08 | 2447 | 11 | 2462 |
| 03 | 2422 | 06 | 2437 | 09 | 2452 | | |

3. Table for Filed Antenna

| Ant. | Manufacturer | Model Name | Antenna Type | Connector | Gain (dBi) |
|------|--------------|------------|--------------|-----------|------------|
| 1 | Goldtek | N/A | PCB | N/A | 3.46 |
| 2 | Goldtek | N/A | Chip | N/A | 0.84 |

Only "one" antenna is selected for use at any one time, through the on-board Transmit-Receive / Diversity RF switch.

3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

| Pretest Mode | Description |
|--------------|----------------------------------|
| Mode 1 | TX B MODE CHANNEL 01/06/11 |
| Mode 2 | TX G MODE CHANNEL 01/06/11 |
| Mode 3 | TX N-20MHZ MODE CHANNEL 01/06/11 |
| Mode 4 | TX Mode |

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

| For Conducted Test | |
|--------------------|-------------|
| Final Test Mode | Description |
| Mode 4 | TX Mode |

| For Radiated Test | |
|-------------------|----------------------------------|
| Final Test Mode | Description |
| Mode 1 | TX B MODE CHANNEL 01/06/11 |
| Mode 2 | TX G MODE CHANNEL 01/06/11 |
| Mode 3 | TX N-20MHZ MODE CHANNEL 01/06/11 |

Note:


- (1) The measurements are performed at the high, middle, low available channels.
- (2) 802.11b mode: DBPSK (1Mbps)
802.11g mode: OFDM (6Mbps)
802.11n HT20 mode : BPSK (6.5Mbps)
For radiated emission tests, the highest output powers were set for final test.
- (3) For radiated below 1G test, the 802.11b is found to be the worst case and recorded.
- (4) The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.
- (5) Both PCB & Chip antennas are evaluated for Radiated while the PCB antenna is evaluated for conducted.

3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN

| | | | |
|-----------------------|--|------|------|
| Test software version | CC3100/CC3200 Radio Tool v1.1.5686.29375 | | |
| Frequency (MHz) | 2412 | 2437 | 2462 |
| 802.11b | 0 | 0 | 0 |
| 802.11g | 0 | 0 | 0 |
| 802.11n (20MHz) | 1 | 1 | 1 |

3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment | Mfr/Brand | Model/Type No. | FCC ID | Series No. |
|------|-------------|-----------|----------------|--------|------------|
| A | Notebook PC | DELL | PP18L | DOC | PF329 A01 |

| Item | Shielded Type | Ferrite Core | Length | Note |
|------|---------------|--------------|--------|-----------|
| 1 | NO | NO | 1M | USB Cable |

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION LIMITS (Frequency Range 150KHz-30MHz)

| Frequency of Emission (MHz) | Conducted Limit (dB μ V) | |
|-----------------------------|------------------------------|-----------|
| | Quasi-peak | Average |
| 0.15 -0.5 | 66 to 56* | 56 to 46* |
| 0.50 -5.0 | 56 | 46 |
| 5.0 -30.0 | 60 | 50 |

Note:

- (1) The limit of " * " decreases with the logarithm of the frequency
- (2) The test result calculated as following:
 Measurement Value = Reading Level + Correct Factor
 Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor(if use)
 Margin Level = Measurement Value - Limit Value

The following table is the setting of the receiver

| Receiver Parameters | Setting |
|---------------------|----------|
| Attenuation | 10 dB |
| Start Frequency | 0.15 MHz |
| Stop Frequency | 30 MHz |
| IF Bandwidth | 9 KHz |


4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

4.1.5 EUT OPERATING CONDITIONS

The EUT was placed on the test table and programmed in normal function.

4.1.6 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 58% Test Voltage: AC 120V/60Hz

4.1.7 TEST RESULTS

Please refer to the Attachment A.

4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (9KHz-1000MHz)

| Frequency (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-----------------|-----------------------------------|-------------------------------|
| 0.009~0.490 | 2400/F(KHz) | 300 |
| 0.490~1.705 | 24000/F(KHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| 960~1000 | 500 | 3 |

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

| Frequency (MHz) | (dBuV/m) (at 3 meters) | |
|-----------------|------------------------|---------|
| | PEAK | AVERAGE |
| Above 1000 | 74 | 54 |

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).
- (4) The test result calculated as following:
 Measurement Value = Reading Level + Correct Factor
 Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use)
 Margin Level = Measurement Value - Limit Value

| Spectrum Parameter | Setting |
|--|---|
| Attenuation | Auto |
| Start Frequency | 1000 MHz |
| Stop Frequency | 10th carrier harmonic |
| RBW / VBW (Emission in restricted band) | 1MHz / 3MHz for Peak, 1MHz / 1/T for Average |

| Receiver Parameter | Setting |
|------------------------|-----------------------------------|
| Attenuation | Auto |
| Start ~ Stop Frequency | 9KHz~90KHz for PK/AVG detector |
| Start ~ Stop Frequency | 90KHz~110KHz for QP detector |
| Start ~ Stop Frequency | 110KHz~490KHz for PK/AVG detector |
| Start ~ Stop Frequency | 490KHz~30MHz for QP detector |
| Start ~ Stop Frequency | 30MHz~1000MHz for QP detector |

4.2.2 TEST PROCEDURE


- a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8 m or 1.5m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
- f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1GHz)
- h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1GHz)
- i. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



(C) For Radiated Emissions Below 30MHz



4.2.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

4.2.6 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 65% Test Voltage: AC 120V/60Hz

4.2.7 TEST RESULTS (9KHZ TO 30MHZ)

Please refer to the Attachment B

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB).
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

4.2.8 TEST RESULTS (30MHZ TO 1000 MHZ)

Please refer to the Attachment C.

4.2.9 TEST RESULTS (ABOVE 1000 MHZ)

Please refer to the Attachment D.

Remark:

- (1) No limit: This is fundamental signal, the judgment is not applicable.
For fundamental signal judgment was referred to Peak output test.

5. BANDWIDTH TEST

5.1 APPLIED PROCEDURES

| FCC Part15 (15.247) , Subpart C | | | |
|---------------------------------|-----------|-----------------------|--------|
| Section | Test Item | Frequency Range (MHz) | Result |
| 15.247(a)(2) | Bandwidth | 2400-2483.5 | PASS |

5.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = 2.5 ms.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

5.1.5 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 60% Test Voltage: AC 120V/60Hz

5.1.6 TEST RESULTS

Please refer to the Attachment E.

6. MAXIMUM PEAK CONDUCTED OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C | | | | |
|---------------------------------|----------------------|-----------------|-----------------------|--------|
| Section | Test Item | Limit | Frequency Range (MHz) | Result |
| 15.247(b)(3) | Maximum Output Power | 1 Watt or 30dBm | 2400-2483.5 | PASS |

6.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,
- b. The maximum peak conducted output power was performed in accordance with method 9.1.2 of FCC KDB 558074 D01 DTS Meas Guidance v03r03.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

6.1.5 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 60% Test Voltage: AC 120V/60Hz

6.1.6 TEST RESULTS

Please refer to the Attachment F.

7. ANTENNA CONDUCTED SPURIOUS EMISSION

7.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.


7.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = Auto.
- c. Offset=antenna gain+cable loss

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

7.1.5 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 60% Test Voltage: AC 120V/60Hz

7.1.6 TEST RESULTS

Please refer to the Attachment G.

8. POWER SPECTRAL DENSITY TEST

8.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C | | | | |
|---------------------------------|------------------------|---------------------|-----------------------|--------|
| Section | Test Item | Limit | Frequency Range (MHz) | Result |
| 15.247(e) | Power Spectral Density | 8 dBm (in any 3KHz) | 2400-2483.5 | PASS |

8.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW=3KHz, VBW=10KHz, Sweep time = Auto.

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP



8.1.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

8.1.5 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 60% Test Voltage: AC 120V/60Hz

8.1.6 TEST RESULTS

Please refer to the Attachment H.

9. MEASUREMENT INSTRUMENTS LIST

| Conducted Emission Measurement | | | | | |
|--------------------------------|----------------------|--------------|-------------------------|------------|------------------|
| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
| 1 | TWO-LINE V-NETWORK | R&S | ENV216 | 101050 | Jun. 01, 2016 |
| 2 | Test Cable | TIMES | CFD300-NL | C03 | Mar. 04, 2016 |
| 3 | EMI Test Receiver | R&S | ESR3 | 101854 | Dec. 08, 2016 |
| 4 | Measurement Software | EZ | EZ_EMG (Version NB-03A) | N/A | N/A |

| Radiated Emission Measurement | | | | | |
|-------------------------------|-------------------------|--------------------|--------------|------------|------------------|
| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
| 1 | Spectrum Analyzer | Agilent | N9020A | MY51160196 | Jan. 06, 2017 |
| 2 | Horn Antenna | Schwarzbeck | BBHA 9120 | D-325 | Apr. 20, 2016 |
| 3 | Microwave Pre_amplifier | Agilent | 8449B | 3008A01714 | Apr. 13, 2016 |
| 4 | Microflex Cable | Harbour industries | 27478LL142 | 1m | Apr. 13, 2016 |
| 5 | Microflex Cable | EMC | S104-SMA | 8m | May 14, 2016 |
| 6 | Microflex Cable | Harbour industries | 27478LL142 | 3m | May 13, 2016 |
| 7 | Test Cable | LMR | LMR-400 | 10m | May 13, 2016 |
| 8 | Test Cable | LMR | LMR-400 | 3m | May 13, 2016 |
| 9 | Pre-Amplifier | Anritsu | MH648A | M92649 | Jun. 16, 2016 |
| 10 | Log-Bicon Antenna | Schwarzbeck | VULB9168-352 | 9168-352 | Jul. 30, 2016 |
| 11 | Loop Antenna | EMCO | 6502 | 00042960 | Nov. 05, 2016 |

| 6dB Bandwidth Measurement | | | | | |
|---------------------------|-------------------|--------------|----------|------------|------------------|
| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
| 1 | Spectrum Analyzer | Agilent | N9010A | MY54200240 | Aug. 26, 2016 |

| Peak Output Power Measurement | | | | | |
|-------------------------------|--------------------|--------------|----------|------------|------------------|
| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
| 1 | Power Meter | Anritsu | ML2487A | 6K00004714 | May 19, 2016 |
| 2 | Power Meter Sensor | Anritsu | MA2491A | 034138 | May 18, 2016 |

| Antenna Conducted Spurious Emission Measurement | | | | | |
|---|-------------------|--------------|----------|------------|------------------|
| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
| 1 | Spectrum Analyzer | Agilent | N9010A | MY54200240 | Aug. 26, 2016 |

| Power Spectral Density Measurement | | | | | |
|------------------------------------|-------------------|--------------|----------|------------|------------------|
| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
| 1 | Spectrum Analyzer | Agilent | N9010A | MY54200240 | Aug. 26, 2016 |

Remark: "N/A" denotes no model name, serial no. or calibration specified.
 All calibration period of equipment list is one year.



10. EUT TEST PHOTO

Conducted Measurement Photos





Radiated Measurement Photos

9KHz to 30MHz





Radiated Measurement Photos

30MHz to 1000MHz



Radiated Measurement Photos


Above 1000MHz



ATTACHMENT A - CONDUCTED EMISSION

Test Mode : TX Mode


Line



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV | Limit dBuV | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|--------------|----------|---------|
| 1 | * | 0.1766 | 47.70 | 9.66 | 57.36 | 64.64 | -7.28 | QP | |
| 2 | | 0.1766 | 32.10 | 9.66 | 41.76 | 54.64 | -12.88 | AVG | |
| 3 | | 0.2459 | 37.60 | 9.66 | 47.26 | 61.89 | -14.63 | QP | |
| 4 | | 0.2459 | 22.40 | 9.66 | 32.06 | 51.89 | -19.83 | AVG | |
| 5 | | 0.3047 | 33.20 | 9.66 | 42.86 | 60.11 | -17.25 | QP | |
| 6 | | 0.3047 | 16.90 | 9.66 | 26.56 | 50.11 | -23.55 | AVG | |
| 7 | | 5.0000 | 25.80 | 9.89 | 35.69 | 56.00 | -20.31 | QP | |
| 8 | | 5.0000 | 13.50 | 9.89 | 23.39 | 46.00 | -22.61 | AVG | |
| 9 | | 17.0500 | 24.20 | 9.85 | 34.05 | 60.00 | -25.95 | QP | |
| 10 | | 17.0500 | 16.60 | 9.85 | 26.45 | 50.00 | -23.55 | AVG | |
| 11 | | 22.8000 | 31.50 | 9.90 | 41.40 | 60.00 | -18.60 | QP | |
| 12 | | 22.8000 | 23.00 | 9.90 | 32.90 | 50.00 | -17.10 | AVG | |

Test Mode : TX Mode

Neutral



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV | Limit dBuV | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|--------------|----------|---------|
| 1 | * | 0.1507 | 44.80 | 9.66 | 54.46 | 65.96 | -11.50 | QP | |
| 2 | | 0.1507 | 20.00 | 9.66 | 29.66 | 55.96 | -26.30 | AVG | |
| 3 | | 0.3068 | 30.80 | 9.67 | 40.47 | 60.05 | -19.58 | QP | |
| 4 | | 0.3068 | 12.50 | 9.67 | 22.17 | 50.05 | -27.88 | AVG | |
| 5 | | 0.4881 | 23.50 | 9.68 | 33.18 | 56.20 | -23.02 | QP | |
| 6 | | 0.4881 | 13.30 | 9.68 | 22.98 | 46.20 | -23.22 | AVG | |
| 7 | | 5.0000 | 25.20 | 9.88 | 35.08 | 56.00 | -20.92 | QP | |
| 8 | | 5.0000 | 13.20 | 9.88 | 23.08 | 46.00 | -22.92 | AVG | |
| 9 | | 17.2500 | 23.10 | 9.87 | 32.97 | 60.00 | -27.03 | QP | |
| 10 | | 17.2500 | 15.80 | 9.87 | 25.67 | 50.00 | -24.33 | AVG | |
| 11 | | 22.8000 | 29.90 | 9.93 | 39.83 | 60.00 | -20.17 | QP | |
| 12 | | 22.8000 | 21.00 | 9.93 | 30.93 | 50.00 | -19.07 | AVG | |

ATTACHMENT B - RADIATED EMISSION (9KHZ TO 30MHZ)

For PCB Antenna

| | |
|------------|----------------------|
| Test Mode: | TX B MODE CHANNEL 01 |
|------------|----------------------|

| Frequency (MHz) | Ant 0°/90° | Read level dBuV/m | Factor (dB) | Measured(FS) (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Note |
|-----------------|------------|-------------------|-------------|-----------------------|----------------|-------------|------|
| 0.015 | 0° | 32.240 | 22.275 | 54.515 | 104.082 | -49.567 | AVG |
| 0.015 | 0° | 43.200 | 22.275 | 65.475 | 124.082 | -58.607 | PK |
| 0.026 | 0° | 28.990 | 22.013 | 51.003 | 99.473 | -48.471 | AVG |
| 0.026 | 0° | 33.250 | 22.013 | 55.263 | 119.473 | -64.211 | PK |
| 0.037 | 0° | 24.870 | 21.735 | 46.605 | 96.335 | -49.730 | AVG |
| 0.037 | 0° | 32.650 | 21.735 | 54.385 | 116.335 | -61.950 | PK |
| 0.060 | 0° | 24.680 | 21.240 | 45.920 | 92.041 | -46.121 | AVG |
| 0.060 | 0° | 34.920 | 21.240 | 56.160 | 112.041 | -55.881 | PK |
| 1.265 | 0° | 33.580 | 20.335 | 53.915 | 65.562 | -11.647 | QP |
| 1.135 | 0° | 38.540 | 20.465 | 59.005 | 66.502 | -7.498 | QP |

| Frequency (MHz) | Ant 0°/90° | Read level dBuV/m | Factor (dB) | Measured(FS) (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Note |
|-----------------|------------|-------------------|-------------|-----------------------|----------------|-------------|------|
| 0.013 | 90° | 33.650 | 22.320 | 55.970 | 105.193 | -49.223 | AVG |
| 0.013 | 90° | 48.840 | 22.320 | 71.160 | 125.193 | -54.033 | PK |
| 0.026 | 90° | 27.160 | 22.008 | 49.168 | 99.406 | -50.238 | AVG |
| 0.026 | 90° | 42.480 | 22.008 | 64.488 | 119.406 | -54.918 | PK |
| 0.035 | 90° | 26.130 | 21.788 | 47.918 | 96.848 | -48.930 | AVG |
| 0.035 | 90° | 35.930 | 21.788 | 57.718 | 116.848 | -59.130 | PK |
| 0.063 | 90° | 22.850 | 21.189 | 44.039 | 91.590 | -47.551 | AVG |
| 0.063 | 90° | 38.160 | 21.189 | 59.349 | 111.590 | -52.241 | PK |
| 1.251 | 90° | 34.420 | 20.349 | 54.769 | 65.659 | -10.890 | QP |
| 1.650 | 90° | 36.340 | 19.950 | 56.290 | 63.255 | -6.965 | QP |

For Chip Antenna

| | |
|------------|----------------------|
| Test Mode: | TX B MODE CHANNEL 01 |
|------------|----------------------|

| Frequency (MHz) | Ant 0°/90° | Read level dBuV/m | Factor (dB) | Measured(FS) (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Note |
|-----------------|------------|-------------------|-------------|-----------------------|----------------|-------------|------|
| 0.0150 | 0° | 32.4800 | 22.2750 | 54.7550 | 104.0824 | -49.3274 | AVG |
| 0.0150 | 0° | 43.5600 | 22.2750 | 65.8350 | 124.0824 | -58.2474 | PK |
| 0.0255 | 0° | 29.2500 | 22.0125 | 51.2625 | 99.4734 | -48.2109 | AVG |
| 0.0255 | 0° | 33.1500 | 22.0125 | 55.1625 | 119.4734 | -64.3109 | PK |
| 0.0366 | 0° | 24.4800 | 21.7350 | 46.2150 | 96.3346 | -50.1196 | AVG |
| 0.0366 | 0° | 32.5500 | 21.7350 | 54.2850 | 116.3346 | -62.0496 | PK |
| 0.0600 | 0° | 24.5700 | 21.2400 | 45.8100 | 92.0412 | -46.2312 | AVG |
| 0.0600 | 0° | 34.8500 | 21.2400 | 56.0900 | 112.0412 | -55.9512 | PK |
| 1.2650 | 0° | 33.2400 | 20.3350 | 53.5750 | 65.5624 | -11.9874 | QP |
| 1.1353 | 0° | 37.9500 | 20.4648 | 58.4148 | 66.5024 | -8.0876 | QP |


| Frequency (MHz) | Ant 0°/90° | Read level dBuV/m | Factor (dB) | Measured(FS) (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Note |
|-----------------|------------|-------------------|-------------|-----------------------|----------------|-------------|------|
| 0.013 | 90° | 33.510 | 22.320 | 55.830 | 105.193 | -49.363 | AVG |
| 0.013 | 90° | 48.620 | 22.320 | 70.940 | 125.193 | -54.253 | PK |
| 0.026 | 90° | 27.280 | 22.008 | 49.288 | 99.406 | -50.118 | AVG |
| 0.026 | 90° | 42.580 | 22.008 | 64.588 | 119.406 | -54.818 | PK |
| 0.035 | 90° | 26.240 | 21.788 | 48.028 | 96.848 | -48.820 | AVG |
| 0.035 | 90° | 35.860 | 21.788 | 57.648 | 116.848 | -59.200 | PK |
| 0.063 | 90° | 22.760 | 21.189 | 43.949 | 91.590 | -47.641 | AVG |
| 0.063 | 90° | 38.260 | 21.189 | 59.449 | 111.590 | -52.141 | PK |
| 1.251 | 90° | 34.250 | 20.349 | 54.599 | 65.659 | -11.060 | QP |
| 1.650 | 90° | 36.240 | 19.950 | 56.190 | 63.255 | -7.065 | QP |

ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)

For PCB Antenna

Test Mode: TX MODE 2437MHz


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | * | 42.1250 | 36.90 | -14.29 | 22.61 | 40.00 | -17.39 | peak | |
| 2 | | 114.8750 | 35.90 | -17.15 | 18.75 | 43.50 | -24.75 | peak | |
| 3 | | 393.7500 | 34.36 | -11.31 | 23.05 | 46.00 | -22.95 | peak | |
| 4 | | 599.8750 | 30.43 | -7.13 | 23.30 | 46.00 | -22.70 | peak | |
| 5 | | 786.6000 | 30.44 | -4.15 | 26.29 | 46.00 | -19.71 | peak | |
| 6 | | 944.2250 | 29.94 | -1.94 | 28.00 | 46.00 | -18.00 | peak | |

Test Mode: TX MODE 2437MHz

Horizontal




| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | * | 42.1250 | 35.45 | -14.29 | 21.16 | 40.00 | -18.84 | peak | |
| 2 | | 114.8750 | 35.54 | -17.15 | 18.39 | 43.50 | -25.11 | peak | |
| 3 | | 243.4000 | 32.05 | -15.21 | 16.84 | 46.00 | -29.16 | peak | |
| 4 | | 393.7500 | 36.09 | -11.31 | 24.78 | 46.00 | -21.22 | peak | |
| 5 | | 599.8750 | 29.17 | -7.13 | 22.04 | 46.00 | -23.96 | peak | |
| 6 | | 801.1500 | 30.64 | -3.88 | 26.76 | 46.00 | -19.24 | peak | |

For Chip Antenna

Test Mode: TX MODE 2437MHz


Vertical



| No. Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measurement dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|---------|-----------|--------------------|-------------------|--------------------|--------------|-----------|----------|---------|
| 1 | 42.1250 | 35.20 | -14.29 | 20.91 | 40.00 | -19.09 | peak | |
| 2 | 114.8750 | 34.20 | -17.15 | 17.05 | 43.50 | -26.45 | peak | |
| 3 | 393.7500 | 33.56 | -11.31 | 22.25 | 46.00 | -23.75 | peak | |
| 4 | 599.8750 | 29.53 | -7.13 | 22.40 | 46.00 | -23.60 | peak | |
| 5 | 786.6000 | 30.04 | -4.15 | 25.89 | 46.00 | -20.11 | peak | |
| 6 * | 944.2250 | 28.94 | -1.94 | 27.00 | 46.00 | -19.00 | peak | |

Test Mode: TX MODE 2437MHz

Horizontal




| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | * | 42.1250 | 35.25 | -14.29 | 20.96 | 40.00 | -19.04 | peak | |
| 2 | | 114.8750 | 35.04 | -17.15 | 17.89 | 43.50 | -25.61 | peak | |
| 3 | | 243.4000 | 31.45 | -15.21 | 16.24 | 46.00 | -29.76 | peak | |
| 4 | | 393.7500 | 35.19 | -11.31 | 23.88 | 46.00 | -22.12 | peak | |
| 5 | | 599.8750 | 28.37 | -7.13 | 21.24 | 46.00 | -24.76 | peak | |
| 6 | | 801.1500 | 30.04 | -3.88 | 26.16 | 46.00 | -19.84 | peak | |

ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)

For PCB Antenna

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2412MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | | 2390.000 | 25.97 | 31.96 | 57.93 | 74.00 | -16.07 | peak | |
| 2 | | 2390.000 | 14.55 | 31.96 | 46.51 | 54.00 | -7.49 | AVG | |
| 3 | X | 2411.250 | 66.46 | 32.03 | 98.49 | 74.00 | 24.49 | peak | NO LIMIT |
| 4 | * | 2411.250 | 61.65 | 32.03 | 93.68 | 54.00 | 39.68 | AVG | NO LIMIT |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2412MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4824.075 | 47.80 | 5.79 | 53.59 | 74.00 | -20.41 | peak | |
| 2 | * | 4824.075 | 41.69 | 5.79 | 47.48 | 54.00 | -6.52 | AVG | |
| 3 | | 7233.050 | 42.15 | 13.87 | 56.02 | 74.00 | -17.98 | peak | |
| 4 | | 7233.050 | 28.05 | 13.87 | 41.92 | 54.00 | -12.08 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2412MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | | 2390.000 | 25.60 | 31.96 | 57.56 | 74.00 | -16.44 | peak | |
| 2 | | 2390.000 | 15.48 | 31.96 | 47.44 | 54.00 | -6.56 | AVG | |
| 3 | X | 2411.250 | 68.72 | 32.03 | 100.75 | 74.00 | 26.75 | peak | NO LIMIT |
| 4 | * | 2411.250 | 63.89 | 32.03 | 95.92 | 54.00 | 41.92 | AVG | NO LIMIT |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2412MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4823.800 | 47.51 | 5.79 | 53.30 | 74.00 | -20.70 | peak | |
| 2 | * | 4823.800 | 42.22 | 5.79 | 48.01 | 54.00 | -5.99 | AVG | |
| 3 | | 7227.700 | 41.06 | 13.86 | 54.92 | 74.00 | -19.08 | peak | |
| 4 | | 7227.700 | 30.19 | 13.86 | 44.05 | 54.00 | -9.95 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2437MHz |


Vertical



| No. | Mk. | Freq. | Reading | Correct | Measure- | Limit | Margin | | |
|-----|-----|----------|---------|---------|----------|--------|--------|----------|----------|
| | | MHz | Level | Factor | ment | | | Detector | Comment |
| | | | dBuV | dB | dBuV/m | dBuV/m | dB | | |
| 1 | X | 2436.250 | 67.38 | 32.12 | 99.50 | 74.00 | 25.50 | peak | NO LIMIT |
| 2 | * | 2436.250 | 62.48 | 32.12 | 94.60 | 54.00 | 40.60 | AVG | NO LIMIT |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2437MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4874.000 | 48.27 | 5.84 | 54.11 | 74.00 | -19.89 | peak | |
| 2 | * | 4874.000 | 42.79 | 5.84 | 48.63 | 54.00 | -5.37 | AVG | |
| 3 | | 7306.650 | 41.40 | 14.05 | 55.45 | 74.00 | -18.55 | peak | |
| 4 | | 7306.650 | 30.60 | 14.05 | 44.65 | 54.00 | -9.35 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2437MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | X | 2436.250 | 74.12 | 32.12 | 106.24 | 74.00 | 32.24 | peak | NO LIMIT |
| 2 | * | 2436.250 | 69.31 | 32.12 | 101.43 | 54.00 | 47.43 | AVG | NO LIMIT |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2437MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4873.950 | 50.33 | 5.84 | 56.17 | 74.00 | -17.83 | peak | |
| 2 | * | 4873.950 | 45.57 | 5.84 | 51.41 | 54.00 | -2.59 | AVG | |
| 3 | | 7302.150 | 41.31 | 14.05 | 55.36 | 74.00 | -18.64 | peak | |
| 4 | | 7302.150 | 30.61 | 14.05 | 44.66 | 54.00 | -9.34 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2462MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | X | 2462.750 | 67.84 | 32.23 | 100.07 | 74.00 | 26.07 | peak | NO LIMIT |
| 2 | * | 2462.750 | 63.05 | 32.23 | 95.28 | 54.00 | 41.28 | AVG | NO LIMIT |
| 3 | | 2483.500 | 27.10 | 32.30 | 59.40 | 74.00 | -14.60 | peak | |
| 4 | | 2483.500 | 15.97 | 32.30 | 48.27 | 54.00 | -5.73 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2462MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4924.000 | 48.39 | 5.90 | 54.29 | 74.00 | -19.71 | peak | |
| 2 | * | 4924.000 | 42.84 | 5.90 | 48.74 | 54.00 | -5.26 | AVG | |
| 3 | | 7393.650 | 41.03 | 14.25 | 55.28 | 74.00 | -18.72 | peak | |
| 4 | | 7393.650 | 30.56 | 14.25 | 44.81 | 54.00 | -9.19 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2462MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | X | 2461.250 | 72.27 | 32.22 | 104.49 | 74.00 | 30.49 | peak | NO LIMIT |
| 2 | * | 2461.250 | 67.47 | 32.22 | 99.69 | 54.00 | 45.69 | AVG | NO LIMIT |
| 3 | | 2483.500 | 28.76 | 32.30 | 61.06 | 74.00 | -12.94 | peak | |
| 4 | | 2483.500 | 17.35 | 32.30 | 49.65 | 54.00 | -4.35 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2462MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4924.000 | 50.38 | 5.90 | 56.28 | 74.00 | -17.72 | peak | |
| 2 | * | 4924.000 | 45.65 | 5.90 | 51.55 | 54.00 | -2.45 | AVG | |
| 3 | | 7382.600 | 40.90 | 14.22 | 55.12 | 74.00 | -18.88 | peak | |
| 4 | | 7382.600 | 30.44 | 14.22 | 44.66 | 54.00 | -9.34 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2412MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | | 2390.000 | 25.65 | 31.96 | 57.61 | 74.00 | -16.39 | peak | |
| 2 | | 2390.000 | 14.29 | 31.96 | 46.25 | 54.00 | -7.75 | AVG | |
| 3 | X | 2413.000 | 67.64 | 32.04 | 99.68 | 74.00 | 25.68 | peak | NO LIMIT |
| 4 | * | 2413.000 | 49.39 | 32.04 | 81.43 | 54.00 | 27.43 | AVG | NO LIMIT |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2412MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4825.900 | 43.17 | 5.80 | 48.97 | 74.00 | -25.03 | peak | |
| 2 | | 4825.900 | 30.73 | 5.80 | 36.53 | 54.00 | -17.47 | AVG | |
| 3 | | 7233.400 | 41.38 | 13.87 | 55.25 | 74.00 | -18.75 | peak | |
| 4 | * | 7233.400 | 30.01 | 13.87 | 43.88 | 54.00 | -10.12 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2412MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | | 2390.000 | 27.15 | 31.96 | 59.11 | 74.00 | -14.89 | peak | |
| 2 | | 2390.000 | 14.60 | 31.96 | 46.56 | 54.00 | -7.44 | AVG | |
| 3 | X | 2411.000 | 70.25 | 32.03 | 102.28 | 74.00 | 28.28 | peak | NO LIMIT |
| 4 | * | 2411.000 | 52.07 | 32.03 | 84.10 | 54.00 | 30.10 | AVG | NO LIMIT |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2412MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4825.725 | 42.67 | 5.80 | 48.47 | 74.00 | -25.53 | peak | |
| 2 | | 4825.725 | 30.74 | 5.80 | 36.54 | 54.00 | -17.46 | AVG | |
| 3 | | 7226.550 | 41.45 | 13.86 | 55.31 | 74.00 | -18.69 | peak | |
| 4 | * | 7226.550 | 30.36 | 13.86 | 44.22 | 54.00 | -9.78 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2437MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | X | 2438.000 | 70.15 | 32.14 | 102.29 | 74.00 | 28.29 | peak | NO LIMIT |
| 2 | * | 2438.000 | 53.66 | 32.14 | 85.80 | 54.00 | 31.80 | AVG | NO LIMIT |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2437MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4876.100 | 44.78 | 5.85 | 50.63 | 74.00 | -23.37 | peak | |
| 2 | | 4876.100 | 32.52 | 5.85 | 38.37 | 54.00 | -15.63 | AVG | |
| 3 | | 7301.650 | 41.06 | 14.04 | 55.10 | 74.00 | -18.90 | peak | |
| 4 | * | 7301.650 | 30.64 | 14.04 | 44.68 | 54.00 | -9.32 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2437MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | X | 2436.000 | 77.27 | 32.12 | 109.39 | 74.00 | 35.39 | peak | NO LIMIT |
| 2 | * | 2436.000 | 60.26 | 32.12 | 92.38 | 54.00 | 38.38 | AVG | NO LIMIT |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2437MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4870.850 | 49.46 | 5.84 | 55.30 | 74.00 | -18.70 | peak | |
| 2 | | 4870.850 | 33.79 | 5.84 | 39.63 | 54.00 | -14.37 | AVG | |
| 3 | | 7302.850 | 41.14 | 14.05 | 55.19 | 74.00 | -18.81 | peak | |
| 4 | * | 7302.850 | 30.61 | 14.05 | 44.66 | 54.00 | -9.34 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2462MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | X | 2463.250 | 67.70 | 32.24 | 99.94 | 74.00 | 25.94 | peak | NO LIMIT |
| 2 | * | 2463.250 | 51.01 | 32.24 | 83.25 | 54.00 | 29.25 | AVG | NO LIMIT |
| 3 | | 2483.500 | 26.79 | 32.30 | 59.09 | 74.00 | -14.91 | peak | |
| 4 | | 2483.500 | 14.88 | 32.30 | 47.18 | 54.00 | -6.82 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2462MHz |


Vertical



| No. Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measurement dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|---------|-----------|--------------------|-------------------|--------------------|--------------|-----------|----------|---------|
| 1 | 4921.750 | 43.83 | 5.90 | 49.73 | 74.00 | -24.27 | peak | |
| 2 | 4921.750 | 31.26 | 5.90 | 37.16 | 54.00 | -16.84 | AVG | |
| 3 | 7371.125 | 40.66 | 14.20 | 54.86 | 74.00 | -19.14 | peak | |
| 4 * | 7371.125 | 30.20 | 14.20 | 44.40 | 54.00 | -9.60 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2462MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | X | 2463.250 | 72.43 | 32.24 | 104.67 | 74.00 | 30.67 | peak | NO LIMIT |
| 2 | * | 2463.250 | 55.60 | 32.24 | 87.84 | 54.00 | 33.84 | AVG | NO LIMIT |
| 3 | | 2483.500 | 31.78 | 32.30 | 64.08 | 74.00 | -9.92 | peak | |
| 4 | | 2483.500 | 16.11 | 32.30 | 48.41 | 54.00 | -5.59 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2462MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4927.050 | 47.36 | 5.91 | 53.27 | 74.00 | -20.73 | peak | |
| 2 | | 4927.050 | 31.93 | 5.91 | 37.84 | 54.00 | -16.16 | AVG | |
| 3 | | 7383.100 | 41.17 | 14.23 | 55.40 | 74.00 | -18.60 | peak | |
| 4 | * | 7383.100 | 30.28 | 14.23 | 44.51 | 54.00 | -9.49 | AVG | |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2412MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | | 2390.000 | 25.17 | 31.96 | 57.13 | 74.00 | -16.87 | peak | |
| 2 | | 2390.000 | 14.07 | 31.96 | 46.03 | 54.00 | -7.97 | AVG | |
| 3 | X | 2413.250 | 65.06 | 32.05 | 97.11 | 74.00 | 23.11 | peak | NO LIMIT |
| 4 | * | 2413.250 | 48.51 | 32.05 | 80.56 | 54.00 | 26.56 | AVG | NO LIMIT |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2412MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4824.950 | 41.55 | 5.79 | 47.34 | 74.00 | -26.66 | peak | |
| 2 | | 4824.950 | 30.73 | 5.79 | 36.52 | 54.00 | -17.48 | AVG | |
| 3 | | 7226.500 | 39.98 | 13.86 | 53.84 | 74.00 | -20.16 | peak | |
| 4 | * | 7226.500 | 30.46 | 13.86 | 44.32 | 54.00 | -9.68 | AVG | |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2412MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | | 2390.000 | 26.97 | 31.96 | 58.93 | 74.00 | -15.07 | peak | |
| 2 | | 2390.000 | 14.34 | 31.96 | 46.30 | 54.00 | -7.70 | AVG | |
| 3 | X | 2410.500 | 67.00 | 32.03 | 99.03 | 74.00 | 25.03 | peak | NO LIMIT |
| 4 | * | 2410.500 | 50.62 | 32.03 | 82.65 | 54.00 | 28.65 | AVG | NO LIMIT |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2412MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4814.100 | 41.80 | 5.79 | 47.59 | 74.00 | -26.41 | peak | |
| 2 | | 4814.100 | 30.49 | 5.79 | 36.28 | 54.00 | -17.72 | AVG | |
| 3 | | 7228.100 | 41.68 | 13.86 | 55.54 | 74.00 | -18.46 | peak | |
| 4 | * | 7228.100 | 30.44 | 13.86 | 44.30 | 54.00 | -9.70 | AVG | |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2437MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | X | 2435.750 | 69.08 | 32.12 | 101.20 | 74.00 | 27.20 | peak | NO LIMIT |
| 2 | * | 2435.750 | 53.17 | 32.12 | 85.29 | 54.00 | 31.29 | AVG | NO LIMIT |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2437MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4872.250 | 46.79 | 5.84 | 52.63 | 74.00 | -21.37 | peak | |
| 2 | | 4872.250 | 32.24 | 5.84 | 38.08 | 54.00 | -15.92 | AVG | |
| 3 | | 7303.800 | 41.10 | 14.04 | 55.14 | 74.00 | -18.86 | peak | |
| 4 | * | 7303.800 | 30.60 | 14.04 | 44.64 | 54.00 | -9.36 | AVG | |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2437MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | X | 2438.250 | 75.42 | 32.14 | 107.56 | 74.00 | 33.56 | peak | NO LIMIT |
| 2 | * | 2438.250 | 59.39 | 32.14 | 91.53 | 54.00 | 37.53 | AVG | NO LIMIT |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2437MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4876.500 | 48.16 | 5.85 | 54.01 | 74.00 | -19.99 | peak | |
| 2 | | 4876.500 | 33.34 | 5.85 | 39.19 | 54.00 | -14.81 | AVG | |
| 3 | | 7303.350 | 39.85 | 14.05 | 53.90 | 74.00 | -20.10 | peak | |
| 4 | * | 7303.350 | 30.53 | 14.05 | 44.58 | 54.00 | -9.42 | AVG | |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2462MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | X | 2463.250 | 65.42 | 32.24 | 97.66 | 74.00 | 23.66 | peak | NO LIMIT |
| 2 | * | 2463.250 | 49.52 | 32.24 | 81.76 | 54.00 | 27.76 | AVG | NO LIMIT |
| 3 | | 2483.500 | 26.55 | 32.30 | 58.85 | 74.00 | -15.15 | peak | |
| 4 | | 2483.500 | 14.55 | 32.30 | 46.85 | 54.00 | -7.15 | AVG | |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2462MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4921.900 | 43.39 | 5.90 | 49.29 | 74.00 | -24.71 | peak | |
| 2 | | 4921.900 | 30.17 | 5.90 | 36.07 | 54.00 | -17.93 | AVG | |
| 3 | | 7391.350 | 42.01 | 14.25 | 56.26 | 74.00 | -17.74 | peak | |
| 4 | * | 7391.350 | 30.45 | 14.25 | 44.70 | 54.00 | -9.30 | AVG | |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2462MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | X | 2463.500 | 72.71 | 32.24 | 104.95 | 74.00 | 30.95 | peak | NO LIMIT |
| 2 | * | 2463.500 | 56.17 | 32.24 | 88.41 | 54.00 | 34.41 | AVG | NO LIMIT |
| 3 | | 2483.500 | 30.49 | 32.30 | 62.79 | 74.00 | -11.21 | peak | |
| 4 | | 2483.500 | 16.21 | 32.30 | 48.51 | 54.00 | -5.49 | AVG | |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2462MHz |

Horizontal




| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4921.250 | 41.42 | 5.90 | 47.32 | 74.00 | -26.68 | peak | |
| 2 | | 4921.250 | 30.16 | 5.90 | 36.06 | 54.00 | -17.94 | AVG | |
| 3 | | 7377.300 | 40.77 | 14.21 | 54.98 | 74.00 | -19.02 | peak | |
| 4 | * | 7377.300 | 30.21 | 14.21 | 44.42 | 54.00 | -9.58 | AVG | |

For Chip Antenna

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2412MHz |


Vertical



| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Margin | Detector | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------|----------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | | |
| 1 | | 2390.000 | 25.64 | 31.96 | 57.60 | 74.00 | -16.40 | peak | |
| 2 | | 2390.000 | 14.26 | 31.96 | 46.22 | 54.00 | -7.78 | AVG | |
| 3 | X | 2411.250 | 65.26 | 32.03 | 97.29 | 74.00 | 23.29 | peak | NO LIMIT |
| 4 | * | 2411.250 | 60.25 | 32.03 | 92.28 | 54.00 | 38.28 | AVG | NO LIMIT |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2412MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4824.075 | 46.33 | 5.79 | 52.12 | 74.00 | -21.88 | peak | |
| 2 | * | 4824.075 | 41.25 | 5.79 | 47.04 | 54.00 | -6.96 | AVG | |
| 3 | | 7233.050 | 41.85 | 13.87 | 55.72 | 74.00 | -18.28 | peak | |
| 4 | | 7233.050 | 27.86 | 13.87 | 41.73 | 54.00 | -12.27 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2412MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | | 2390.000 | 25.12 | 31.96 | 57.08 | 74.00 | -16.92 | peak | |
| 2 | | 2390.000 | 15.13 | 31.96 | 47.09 | 54.00 | -6.91 | AVG | |
| 3 | X | 2411.250 | 68.32 | 32.03 | 100.35 | 74.00 | 26.35 | peak | NO LIMIT |
| 4 | * | 2411.250 | 63.72 | 32.03 | 95.75 | 54.00 | 41.75 | AVG | NO LIMIT |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2412MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4824.000 | 46.23 | 5.79 | 52.02 | 74.00 | -21.98 | peak | |
| 2 | * | 4824.000 | 41.25 | 5.79 | 47.04 | 54.00 | -6.96 | AVG | |
| 3 | | 7226.900 | 40.36 | 13.86 | 54.22 | 74.00 | -19.78 | peak | |
| 4 | | 7226.900 | 30.04 | 13.86 | 43.90 | 54.00 | -10.10 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2437MHz |


Vertical



| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Margin | Detector | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------|----------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | | |
| 1 | X | 2436.250 | 67.05 | 32.12 | 99.17 | 74.00 | 25.17 | peak | NO LIMIT |
| 2 | * | 2436.250 | 62.14 | 32.12 | 94.26 | 54.00 | 40.26 | AVG | NO LIMIT |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2437MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4874.000 | 47.56 | 5.84 | 53.40 | 74.00 | -20.60 | peak | |
| 2 | * | 4874.000 | 42.52 | 5.84 | 48.36 | 54.00 | -5.64 | AVG | |
| 3 | | 7311.000 | 40.95 | 14.06 | 55.01 | 74.00 | -18.99 | peak | |
| 4 | | 7311.000 | 30.24 | 14.06 | 44.30 | 54.00 | -9.70 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2437MHz |


Horizontal



| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Margin | Detector | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------|----------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | | |
| 1 | X | 2436.250 | 73.68 | 32.12 | 105.80 | 74.00 | 31.80 | peak | NO LIMIT |
| 2 | * | 2436.250 | 68.86 | 32.12 | 100.98 | 54.00 | 46.98 | AVG | NO LIMIT |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2437MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4874.000 | 49.35 | 5.84 | 55.19 | 74.00 | -18.81 | peak | |
| 2 | * | 4874.000 | 44.86 | 5.84 | 50.70 | 54.00 | -3.30 | AVG | |
| 3 | | 7311.000 | 40.68 | 14.06 | 54.74 | 74.00 | -19.26 | peak | |
| 4 | | 7311.000 | 30.15 | 14.06 | 44.21 | 54.00 | -9.79 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2462MHz |


Vertical



| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Margin | Detector | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------|----------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | | |
| 1 | X | 2462.750 | 67.66 | 32.23 | 99.89 | 74.00 | 25.89 | peak | NO LIMIT |
| 2 | * | 2462.750 | 62.31 | 32.23 | 94.54 | 54.00 | 40.54 | AVG | NO LIMIT |
| 3 | | 2483.500 | 26.56 | 32.30 | 58.86 | 74.00 | -15.14 | peak | |
| 4 | | 2483.500 | 15.48 | 32.30 | 47.78 | 54.00 | -6.22 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2462MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4924.000 | 48.15 | 5.90 | 54.05 | 74.00 | -19.95 | peak | |
| 2 | * | 4924.000 | 42.17 | 5.90 | 48.07 | 54.00 | -5.93 | AVG | |
| 3 | | 7394.000 | 40.58 | 14.25 | 54.83 | 74.00 | -19.17 | peak | |
| 4 | | 7394.000 | 30.18 | 14.25 | 44.43 | 54.00 | -9.57 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2462MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | X | 2461.250 | 71.69 | 32.22 | 103.91 | 74.00 | 29.91 | peak | NO LIMIT |
| 2 | * | 2461.250 | 66.58 | 32.22 | 98.80 | 54.00 | 44.80 | AVG | NO LIMIT |
| 3 | | 2483.500 | 27.95 | 32.30 | 60.25 | 74.00 | -13.75 | peak | |
| 4 | | 2483.500 | 16.95 | 32.30 | 49.25 | 54.00 | -4.75 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX B MODE 2462MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4924.000 | 50.14 | 5.90 | 56.04 | 74.00 | -17.96 | peak | |
| 2 | * | 4924.000 | 45.38 | 5.90 | 51.28 | 54.00 | -2.72 | AVG | |
| 3 | | 7386.000 | 40.21 | 14.23 | 54.44 | 74.00 | -19.56 | peak | |
| 4 | | 7386.000 | 31.37 | 14.23 | 45.60 | 54.00 | -8.40 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2412MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | | 2390.000 | 25.34 | 31.96 | 57.30 | 74.00 | -16.70 | peak | |
| 2 | | 2390.000 | 14.25 | 31.96 | 46.21 | 54.00 | -7.79 | AVG | |
| 3 | X | 2413.000 | 67.24 | 32.04 | 99.28 | 74.00 | 25.28 | peak | NO LIMIT |
| 4 | * | 2413.000 | 48.93 | 32.04 | 80.97 | 54.00 | 26.97 | AVG | NO LIMIT |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2412MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4824.000 | 42.15 | 5.79 | 47.94 | 74.00 | -26.06 | peak | |
| 2 | | 4824.000 | 30.24 | 5.79 | 36.03 | 54.00 | -17.97 | AVG | |
| 3 | | 7236.000 | 41.18 | 13.87 | 55.05 | 74.00 | -18.95 | peak | |
| 4 | * | 7236.000 | 29.64 | 13.87 | 43.51 | 54.00 | -10.49 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2412MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | | 2390.000 | 26.54 | 31.96 | 58.50 | 74.00 | -15.50 | peak | |
| 2 | | 2390.000 | 14.28 | 31.96 | 46.24 | 54.00 | -7.76 | AVG | |
| 3 | X | 2411.000 | 69.64 | 32.03 | 101.67 | 74.00 | 27.67 | peak | NO LIMIT |
| 4 | * | 2411.000 | 51.38 | 32.03 | 83.41 | 54.00 | 29.41 | AVG | NO LIMIT |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2412MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4825.000 | 41.68 | 5.80 | 47.48 | 74.00 | -26.52 | peak | |
| 2 | | 4825.000 | 30.38 | 5.80 | 36.18 | 54.00 | -17.82 | AVG | |
| 3 | | 7226.000 | 41.28 | 13.86 | 55.14 | 74.00 | -18.86 | peak | |
| 4 | * | 7226.000 | 29.58 | 13.86 | 43.44 | 54.00 | -10.56 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2437MHz |


Vertical



| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Margin | Detector | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------|----------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | | |
| 1 | X | 2438.000 | 69.76 | 32.14 | 101.90 | 74.00 | 27.90 | peak | NO LIMIT |
| 2 | * | 2438.000 | 53.15 | 32.14 | 85.29 | 54.00 | 31.29 | AVG | NO LIMIT |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2437MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4874.000 | 44.68 | 5.84 | 50.52 | 74.00 | -23.48 | peak | |
| 2 | | 4874.000 | 32.15 | 5.84 | 37.99 | 54.00 | -16.01 | AVG | |
| 3 | | 7311.000 | 40.85 | 14.06 | 54.91 | 74.00 | -19.09 | peak | |
| 4 | * | 7311.000 | 30.38 | 14.06 | 44.44 | 54.00 | -9.56 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2437MHz |


Horizontal



| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Margin | Detector | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------|----------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | | |
| 1 | X | 2436.000 | 76.48 | 32.12 | 108.60 | 74.00 | 34.60 | peak | NO LIMIT |
| 2 | * | 2436.000 | 59.35 | 32.12 | 91.47 | 54.00 | 37.47 | AVG | NO LIMIT |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2437MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4872.000 | 48.68 | 5.84 | 54.52 | 74.00 | -19.48 | peak | |
| 2 | | 4872.000 | 32.58 | 5.84 | 38.42 | 54.00 | -15.58 | AVG | |
| 3 | | 7318.000 | 40.85 | 14.08 | 54.93 | 74.00 | -19.07 | peak | |
| 4 | * | 7318.000 | 30.28 | 14.08 | 44.36 | 54.00 | -9.64 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2462MHz |


Vertical



| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Margin | Detector | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------|----------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | | |
| 1 | X | 2463.250 | 67.24 | 32.24 | 99.48 | 74.00 | 25.48 | peak | NO LIMIT |
| 2 | * | 2463.250 | 50.24 | 32.24 | 82.48 | 54.00 | 28.48 | AVG | NO LIMIT |
| 3 | | 2483.500 | 26.34 | 32.30 | 58.64 | 74.00 | -15.36 | peak | |
| 4 | | 2483.500 | 14.24 | 32.30 | 46.54 | 54.00 | -7.46 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2462MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4924.000 | 43.26 | 5.90 | 49.16 | 74.00 | -24.84 | peak | |
| 2 | | 4924.000 | 30.35 | 5.90 | 36.25 | 54.00 | -17.75 | AVG | |
| 3 | | 7371.125 | 40.26 | 14.20 | 54.46 | 74.00 | -19.54 | peak | |
| 4 | * | 7371.125 | 29.68 | 14.20 | 43.88 | 54.00 | -10.12 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2462MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | X | 2463.250 | 71.44 | 32.24 | 103.68 | 74.00 | 29.68 | peak | NO LIMIT |
| 2 | * | 2463.250 | 55.28 | 32.24 | 87.52 | 54.00 | 33.52 | AVG | NO LIMIT |
| 3 | | 2483.500 | 31.34 | 32.30 | 63.64 | 74.00 | -10.36 | peak | |
| 4 | | 2483.500 | 15.76 | 32.30 | 48.06 | 54.00 | -5.94 | AVG | |

| | |
|-------------------|-------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX G MODE 2462MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4924.000 | 47.58 | 5.90 | 53.48 | 74.00 | -20.52 | peak | |
| 2 | | 4924.000 | 31.15 | 5.90 | 37.05 | 54.00 | -16.95 | AVG | |
| 3 | | 7384.000 | 40.25 | 14.23 | 54.48 | 74.00 | -19.52 | peak | |
| 4 | * | 7384.000 | 30.05 | 14.23 | 44.28 | 54.00 | -9.72 | AVG | |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2412MHz |


Vertical



| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Margin | Detector | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------|----------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | | |
| 1 | | 2390.000 | 24.68 | 31.96 | 56.64 | 74.00 | -17.36 | peak | |
| 2 | | 2390.000 | 13.82 | 31.96 | 45.78 | 54.00 | -8.22 | AVG | |
| 3 | X | 2413.250 | 64.84 | 32.05 | 96.89 | 74.00 | 22.89 | peak | NO LIMIT |
| 4 | * | 2413.250 | 48.03 | 32.05 | 80.08 | 54.00 | 26.08 | AVG | NO LIMIT |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2412MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4824.000 | 40.25 | 5.79 | 46.04 | 74.00 | -27.96 | peak | |
| 2 | | 4824.000 | 29.48 | 5.79 | 35.27 | 54.00 | -18.73 | AVG | |
| 3 | | 7236.000 | 39.97 | 13.87 | 53.84 | 74.00 | -20.16 | peak | |
| 4 | * | 7236.000 | 30.45 | 13.87 | 44.32 | 54.00 | -9.68 | AVG | |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2412MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | | 2390.000 | 26.85 | 31.96 | 58.81 | 74.00 | -15.19 | peak | |
| 2 | | 2390.000 | 14.24 | 31.96 | 46.20 | 54.00 | -7.80 | AVG | |
| 3 | X | 2410.500 | 66.83 | 32.03 | 98.86 | 74.00 | 24.86 | peak | NO LIMIT |
| 4 | * | 2410.500 | 50.18 | 32.03 | 82.21 | 54.00 | 28.21 | AVG | NO LIMIT |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2412MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4824.000 | 40.25 | 5.79 | 46.04 | 74.00 | -27.96 | peak | |
| 2 | | 4824.000 | 29.48 | 5.79 | 35.27 | 54.00 | -18.73 | AVG | |
| 3 | | 7236.000 | 40.58 | 13.87 | 54.45 | 74.00 | -19.55 | peak | |
| 4 | * | 7236.000 | 29.54 | 13.87 | 43.41 | 54.00 | -10.59 | AVG | |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2437MHz |


Vertical



| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Margin | Detector | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------|----------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | | |
| 1 | X | 2435.750 | 68.56 | 32.12 | 100.68 | 74.00 | 26.68 | peak | NO LIMIT |
| 2 | * | 2435.750 | 52.38 | 32.12 | 84.50 | 54.00 | 30.50 | AVG | NO LIMIT |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2437MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4874.000 | 46.13 | 5.84 | 51.97 | 74.00 | -22.03 | peak | |
| 2 | | 4874.000 | 31.48 | 5.84 | 37.32 | 54.00 | -16.68 | AVG | |
| 3 | | 7311.000 | 40.55 | 14.06 | 54.61 | 74.00 | -19.39 | peak | |
| 4 | * | 7311.000 | 30.14 | 14.06 | 44.20 | 54.00 | -9.80 | AVG | |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2437MHz |


Horizontal



| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Margin | | |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------|----------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | Detector | Comment |
| 1 | X | 2438.250 | 74.86 | 32.14 | 107.00 | 74.00 | 33.00 | peak | NO LIMIT |
| 2 | * | 2438.250 | 58.67 | 32.14 | 90.81 | 54.00 | 36.81 | AVG | NO LIMIT |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2437MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4874.000 | 47.68 | 5.84 | 53.52 | 74.00 | -20.48 | peak | |
| 2 | | 4874.000 | 32.48 | 5.84 | 38.32 | 54.00 | -15.68 | AVG | |
| 3 | | 7311.000 | 38.48 | 14.06 | 52.54 | 74.00 | -21.46 | peak | |
| 4 | * | 7311.000 | 30.15 | 14.06 | 44.21 | 54.00 | -9.79 | AVG | |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2462MHz |


Vertical



| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Margin | Detector | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------|----------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | | |
| 1 | X | 2463.250 | 64.86 | 32.24 | 97.10 | 74.00 | 23.10 | peak | NO LIMIT |
| 2 | * | 2463.250 | 48.68 | 32.24 | 80.92 | 54.00 | 26.92 | AVG | NO LIMIT |
| 3 | | 2483.500 | 26.13 | 32.30 | 58.43 | 74.00 | -15.57 | peak | |
| 4 | | 2483.500 | 14.21 | 32.30 | 46.51 | 54.00 | -7.49 | AVG | |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2462MHz |


Vertical



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4924.000 | 42.48 | 5.90 | 48.38 | 74.00 | -25.62 | peak | |
| 2 | | 4924.000 | 29.43 | 5.90 | 35.33 | 54.00 | -18.67 | AVG | |
| 3 | | 7386.000 | 41.25 | 14.23 | 55.48 | 74.00 | -18.52 | peak | |
| 4 | * | 7386.000 | 29.58 | 14.23 | 43.81 | 54.00 | -10.19 | AVG | |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2462MHz |


Horizontal



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|----------|
| 1 | X | 2463.500 | 72.15 | 32.24 | 104.39 | 74.00 | 30.39 | peak | NO LIMIT |
| 2 | * | 2463.500 | 55.85 | 32.24 | 88.09 | 54.00 | 34.09 | AVG | NO LIMIT |
| 3 | | 2483.500 | 29.86 | 32.30 | 62.16 | 74.00 | -11.84 | peak | |
| 4 | | 2483.500 | 15.35 | 32.30 | 47.65 | 54.00 | -6.35 | AVG | |

| | |
|-------------------|-----------------------|
| Orthogonal Axis : | X |
| Test Mode : | TX N-20M MODE 2462MHz |

Horizontal




| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1 | | 4924.000 | 41.24 | 5.90 | 47.14 | 74.00 | -26.86 | peak | |
| 2 | | 4924.000 | 29.58 | 5.90 | 35.48 | 54.00 | -18.52 | AVG | |
| 3 | | 7386.000 | 40.48 | 14.23 | 54.71 | 74.00 | -19.29 | peak | |
| 4 | * | 7386.000 | 29.38 | 14.23 | 43.61 | 54.00 | -10.39 | AVG | |

ATTACHMENT E - BANDWIDTH


Test Mode : TX B Mode_CH01/06/11

| Frequency (MHz) | 6dB Bandwidth (MHz) | 99% Occupied BW (MHz) | Min. Limit (kHz) | Test Result |
|-----------------|---------------------|-----------------------|------------------|-------------|
| 2412 | 9.56 | 13.96 | 500 | Complies |
| 2437 | 9.56 | 13.98 | 500 | Complies |
| 2462 | 9.10 | 13.97 | 500 | Complies |


TX CH01



TX CH06




TX CH11




Test Mode: TX G Mode_CH01/06/11

| Frequency (MHz) | 6dB Bandwidth (MHz) | 99% Occupied BW (MHz) | Min. Limit (kHz) | Test Result |
|-----------------|---------------------|-----------------------|------------------|-------------|
| 2412 | 15.11 | 16.24 | 500 | Complies |
| 2437 | 15.12 | 16.28 | 500 | Complies |
| 2462 | 15.12 | 16.23 | 500 | Complies |


TX CH01



TX CH06




TX CH11




Test Mode : TX N-20MHz Mode_CH01/06/11

| Frequency (MHz) | 6dB Bandwidth (MHz) | 99% Occupied BW (MHz) | Min. Limit (kHz) | Test Result |
|-----------------|---------------------|-----------------------|------------------|-------------|
| 2412 | 15.11 | 17.37 | 500 | Complies |
| 2437 | 15.11 | 17.38 | 500 | Complies |
| 2462 | 15.12 | 17.37 | 500 | Complies |


TX CH01



TX CH06



TX CH11



**ATTACHMENT F – MAXIMUM PEAK CONDUCTED OUTPUT
POWER**

| Test Mode :TX B Mode_CH01/06/11 | | | | | |
|---------------------------------|-----------------------|---------------------|------------------|----------------|----------|
| Frequency (MHz) | Conducted Power (dBm) | Conducted Power (W) | Max. Limit (dBm) | Max. Limit (W) | Result |
| 2412 | 14.73 | 0.0297 | 30.00 | 1.00 | Complies |
| 2437 | 15.85 | 0.0385 | 30.00 | 1.00 | Complies |
| 2462 | 15.35 | 0.0343 | 30.00 | 1.00 | Complies |


| Test Mode :TX G Mode_CH01/06/11 | | | | | |
|---------------------------------|-----------------------|---------------------|------------------|----------------|----------|
| Frequency (MHz) | Conducted Power (dBm) | Conducted Power (W) | Max. Limit (dBm) | Max. Limit (W) | Result |
| 2412 | 17.82 | 0.0605 | 30.00 | 1.00 | Complies |
| 2437 | 18.41 | 0.0693 | 30.00 | 1.00 | Complies |
| 2462 | 17.89 | 0.0615 | 30.00 | 1.00 | Complies |

| Test Mode :TX N20 Mode_CH01/06/11 | | | | | |
|-----------------------------------|-----------------------|---------------------|------------------|----------------|----------|
| Frequency (MHz) | Conducted Power (dBm) | Conducted Power (W) | Max. Limit (dBm) | Max. Limit (W) | Result |
| 2412 | 17.57 | 0.0571 | 30.00 | 1.00 | Complies |
| 2437 | 17.82 | 0.0605 | 30.00 | 1.00 | Complies |
| 2462 | 17.62 | 0.0578 | 30.00 | 1.00 | Complies |


**ATTACHMENT G - ANTENNA CONDUCTED SPURIOUS
EMISSION**

Test Mode : TX B Mode

TX B mode CH01



TX B mode CH11



TX B mode CH01 (10 Harmonic of the frequency)



TX B mode CH06 (10 Harmonic of the frequency)




TX B mode CH11 (10 Harmonic of the frequency)




Test Mode : TX G Mode

TX G mode CH01



TX G mode CH11



TX G mode CH01 (10 Harmonic of the frequency)



TX G mode CH06 (10 Harmonic of the frequency)



TX G mode CH11 (10 Harmonic of the frequency)




Test Mode : TX N-20M Mode

TX HT20 mode CH01



TX HT20 mode CH11



TX HT20 mode CH01 (10 Harmonic of the frequency)



TX HT20 mode CH06 (10 Harmonic of the frequency)



TX HT20 mode CH11 (10 Harmonic of the frequency)



ATTACHMENT H - POWER SPECTRAL DENSITY


Test Mode :TX B Mode_CH01/06/11

| Frequency (MHz) | Power Density (dBm/3kHz) | Power Density (mW/3kHz) | Max. Limit (dBm/3kHz) | Result |
|-----------------|--------------------------|-------------------------|-----------------------|----------|
| 2412 | -11.22 | 0.08 | 8.00 | Complies |
| 2437 | -9.12 | 0.12 | 8.00 | Complies |
| 2462 | -10.52 | 0.09 | 8.00 | Complies |


TX CH01



TX CH06




TX CH11




Test Mode :TX G Mode_CH01/06/11

| Frequency (MHz) | Power Density (dBm/3kHz) | Power Density (mW/3kHz) | Max. Limit (dBm/3kHz) | Result |
|-----------------|--------------------------|-------------------------|-----------------------|----------|
| 2412 | -14.88 | 0.03 | 8.00 | Complies |
| 2437 | -12.34 | 0.06 | 8.00 | Complies |
| 2462 | -14.76 | 0.03 | 8.00 | Complies |


TX CH01



TX CH06




TX CH11




Test Mode : TX N-20M Mode_CH01/06/11

| Frequency (MHz) | Power Density (dBm/3kHz) | Power Density (mW/3kHz) | Max. Limit (dBm/3kHz) | Result |
|-----------------|--------------------------|-------------------------|-----------------------|----------|
| 2412 | -16.68 | 0.02 | 8.00 | Complies |
| 2437 | -14.05 | 0.04 | 8.00 | Complies |
| 2462 | -15.87 | 0.03 | 8.00 | Complies |

TX CH01



TX CH06



TX CH11

