

Report No.: SABAOZ-WTW-P21030111B

FCC ID: 2AEUPBHASC071

Test Model: 5UM7E5

Received Date: May 29, 2019

Test Date: June 17, 2019

Issued Date: Oct. 04, 2021

Applicant: Ring LLC

Address: 1523 26th Street, Santa Monica, CA 90404 United States

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

**FCC Registration /
Designation Number:** 723255 / TW2022

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result of Maximum Conducted Power.....	6

Report Issue History Record of EUT

Attachment No.	Issue Date	Description
SA190529E02	July 09, 2019	Original release.
SA190529E02A	Aug. 22, 2019	Changed the product name from "Stick Up Cam Lite" to "Stick Up Cam Plug-In, Stick Up Cam Battery"
SA190529E02C	Mar. 25, 2020	Add case of black color.
SABAOZ-WTW-P21030111B	Oct. 04, 2021	<ol style="list-style-type: none"> 1. Added new antenna for Bluetooth. 2. Added 2nd source component list, more detailed information, please refer to Report No.: RFBAOZ-WTW-P21030111B section 3.1.

Release Control Record

Issue No.	Description	Date Issued
SABAOZ-WTW-P21030111B	Original release.	Oct. 04, 2021

1 Certificate of Conformity

Product: Stick Up Cam Plug-In, Stick Up Cam Battery

Brand: Ring

Test Model: 5UM7E5

Sample Status: Engineering sample

Applicant: Ring LLC

Test Date: June 17, 2019

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Phoenix Huang , **Date:** Oct. 04, 2021
Phoenix Huang / Specialist

Approved by : Clark Lin , **Date:** Oct. 04, 2021
Clark Lin / Technical Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Original						
WLAN						
Brand	Model	Antenna Gain (dBi)	Frequency range (GHz)	Antenna Type	Connector Type	Cable Length (cm)
RF LINK	RF11C02698S	2.7	2.4~2.4835	FPC	i-pex(MHF)	10
Bluetooth						
Brand	Model	Antenna Gain (dBi)	Frequency range (GHz)	Antenna Type	Connector Type	
ACX	AT3216-A2R4PAA	2.9	2.4~2.4835	Chip	None	
Newly						
Bluetooth						
Brand	Model	Antenna Gain (dBi)	Frequency range (GHz)	Antenna Type	Connector Type	
Unictron	AA055M	2.2	2.4~2.4835	Chip	None	

2.5 Calculation Result of Maximum Conducted Power

Note:

1. This report is issued as a duplicate report of BV CPS report no.: SA190529E02C. The difference compared with the original report are add new antenna for Bluetooth and add 2nd source component list (more detail please refer to Report No.: RFBAOZ-WTW-P21030111B section 3.1); therefore all test data was copied from the original test report.
2. The test data are copied which have obtained authorization from applicant and brand company both of the original test report (Report No.: SA190529E02C).

Operation Mode	Evaluation Frequency (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN 2.4GHz	2437	302.691	2.7	20	0.11213	1
Bluetooth	2402	3.236	2.9	20	0.00126	1

--- END ---