

RF Exposure Report

Report No.: SABAOZ-WTW-P21030111B

FCC ID: 2AEUPBHASC071

Test Model: 5UM7E5

Received Date: July 21, 2021

Test Date: July 31, 2021

Issued Date: Aug. 13, 2021

Applicant: Ring LLC

Address: 1523 26th Street, Santa Monica, CA 90404 United States

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,

Taiwar

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,

Taiwan

FCC Registration / Designation Number:

723255 / TW2022





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Report No.: SABAOZ-WTW-P21030111B Reference No.: BAOZ-WTW-P21070753 Page No. 1 / 6

Report Format Version: 6.1.1



Table of Contents

Relea	ase Control Record	. 3
1	Certificate of Conformity	. 4
2	RF Exposure	. 5
2.1	Limits for Maximum Permissible Exposure (MPE)	. 5
	MPE Calculation Formula	
	Classification	
	Antenna Gain	
2.5	Calculation Result of Maximum Conducted Power	. 6



Release Control Record

Issue No.	Description	Date Issued
SABAOZ-WTW-P21030111B	Original release.	Aug. 13, 2021

Report No.: SABAOZ-WTW-P21030111B Page No. 3 / 6 Report Format Version: 6.1.1 Reference No.: BAOZ-WTW-P21070753



1 Certificate of Conformity

Product: Stick Up Cam Plug-in, Stick Up Cam Battery

Brand: Ring

Test Model: 5UM7E5

Sample Status: Engineering sample

Applicant: Ring LLC

Test Date: July 31, 2021

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by: herry onuo, Date: Aug. 13, 2021

Cherry Chue / Specialist

Approved by : , Date: Aug. 13, 2021

Clark Lin / Technical Manager



2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time (minutes)				
Limits For General Population / Uncontrolled Exposure								
0.3-1.34	614	1.63	(100)*	30				
1.34-30	824/f	2.19/f	(180/f ²)*	30				
30-300	27.5	0.073	0.2	30				
300-1500			f/1500	30				
1500-100,000			1.0	30				

f = Frequency in MHz; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20 cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

WLAN									
Brand	Model	Antenna Gain (dBi)		rar	uency nge Antenna ⁻ Hz)		Гуре	Connector Type	Cable Length (cm)
RF LINK	RF11C02698S		2.7 2.4~2		2.4835	FPC		i-pex(MHF)	10
	Bluetooth								
Brand	Model				ncy range SHz)	Ant	enna Type	Connector Type	
Walsin Technology Corporation			3.37	7	2.4~	2.4835		Chip	None

^{*}The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

Report No.: SABAOZ-WTW-P21030111B Reference No.: BAOZ-WTW-P21070753



2.5 Calculation Result of Maximum Conducted Power

The Maximum average power was refer to original report (Report No: RF190529E02 & RF190529E02-1).

Operation Mode	Evaluation Frequency (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
WiFi 2.4GHz	2412-2462	73.451	2.7	20	0.02721	1
Bluetooth	2402-2480	3.214	3.37	20	0.00139	1

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

	END	
--	------------	--