

<b>Prüfbericht-Nr.:</b> <i>Test report No.:</i>	<b>50329128 001</b>	<b>Auftrags-Nr.:</b> <i>Order No.:</i>	168145634	Seite 1 von 22 <i>Page 1 of 22</i>	
<b>Kunden-Referenz-Nr.:</b> <i>Client reference No.:</i>	N/A	<b>Auftragsdatum:</b> <i>Order date:</i>	20.12.2019		
<b>Auftraggeber:</b> <i>Client:</i>	<b>Ring LLC</b> 1523 26th St, Santa Monica, CA 90404, USA				
<b>Prüfgegenstand:</b> <i>Test item:</i>	Solar Steplight				
<b>Bezeichnung / Typ-Nr.:</b> <i>Identification / Type No.:</i>	5AT1S7				
<b>Auftrags-Inhalt:</b> <i>Order content:</i>	FCC/IC testing				
<b>Prüfgrundlage:</b> <i>Test specification:</i>	CFR47 FCC Part 15: Subpart C Section 15.247 CFR47 FCC Part 15: Subpart C Section 15.209 RSS-247 Issue 2 February 2017 RSS-Gen Issue 5 March 2019				
<b>Wareneingangsdatum:</b> <i>Date of receipt:</i>	16.12.2019	Refer to photos			
<b>Prüfmuster-Nr.:</b> <i>Test sample No.:</i>	A001042789-001				
<b>Prüfzeitraum:</b> <i>Testing period:</i>	20.12.2019 - 20.12.2019				
<b>Ort der Prüfung:</b> <i>Place of testing:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.				
<b>Prüflaboratorium:</b> <i>Testing laboratory:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.				
<b>Prüfergebnis*:</b> <i>Test result*:</i>	Pass				
<b>geprüft von / tested by:</b> <i>Jackson Yang</i>		<b>kontrolliert von / reviewed by:</b> <i>Winnie Hou</i>			
07.01.2020	Jackson Yang / Project Engineer	07.01.2020	Winnie Hou / Technical Certifier		
<b>Datum</b> <i>Date</i>	<b>Name/Stellung</b> <i>Name/Position</i>	<b>Unterschrift</b> <i>Signature</i>	<b>Datum</b> <i>Date</i>	<b>Name/Stellung</b> <i>Name/Position</i>	<b>Unterschrift</b> <i>Signature</i>
<b>Sonstiges / Other:</b> FCC ID: 2AEUPRBDS001 IC: 20271-RBDS001 Note: The BLE Radiated Spurious Emission above 1GHz of this product are evaluated in this report which was additional tests as test report 50328926 001.					
<b>Zustand des Prüfgegenstandes bei Anlieferung:</b> <i>Condition of the test item at delivery:</i>			Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged:</i>		
* Legende: 1 = sehr gut      2 = gut      3 = befriedigend      4 = ausreichend      5 = mangelhalt P(ass) = entspricht o.g. Prüfgrundlage(n)      F(ail) = entspricht nicht o.g. Prüfgrundlage(n)      N/A = nicht anwendbar      N/T = nicht getestet Legend: 1 = very good      2 = good      3 = satisfactory      4 = sufficient      5 = poor P(ass) = passed a.m. test specifications(s)      F(ail) = failed a.m. test specifications(s)      N/A = not applicable      N/T = not tested					
<b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b> <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>					

V04

## Test Summary

### 5.1.1 RADIATED SPURIOUS EMISSIONS

*RESULT: Pass*

### *Table of Contents*

<b>1</b>	<b>GENERAL REMARKS .....</b>	<b>4</b>
<b>1.1</b>	<b>COMPLEMENTARY MATERIALS .....</b>	<b>4</b>
<b>2</b>	<b>TEST SITES .....</b>	<b>5</b>
<b>2.1</b>	<b>TEST FACILITIES .....</b>	<b>5</b>
<b>2.2</b>	<b>LIST OF TEST AND MEASUREMENT INSTRUMENTS.....</b>	<b>5</b>
<b>2.3</b>	<b>TRACEABILITY .....</b>	<b>6</b>
<b>2.4</b>	<b>CALIBRATION .....</b>	<b>6</b>
<b>2.5</b>	<b>MEASUREMENT UNCERTAINTY.....</b>	<b>6</b>
<b>2.6</b>	<b>LOCATION OF ORIGINAL DATA.....</b>	<b>6</b>
<b>2.7</b>	<b>STATUS OF FACILITY USED FOR TESTING.....</b>	<b>6</b>
<b>3</b>	<b>GENERAL PRODUCT INFORMATION .....</b>	<b>7</b>
<b>3.1</b>	<b>PRODUCT FUNCTION AND INTENDED USE.....</b>	<b>7</b>
<b>3.2</b>	<b>RATINGS AND SYSTEM DETAILS .....</b>	<b>7</b>
<b>3.3</b>	<b>INDEPENDENT OPERATION MODES .....</b>	<b>9</b>
<b>3.4</b>	<b>NOISE GENERATING AND NOISE SUPPRESSING PARTS.....</b>	<b>9</b>
<b>3.5</b>	<b>SUBMITTED DOCUMENTS.....</b>	<b>9</b>
<b>4</b>	<b>TEST SET-UP AND OPERATION MODES .....</b>	<b>10</b>
<b>4.1</b>	<b>PRINCIPLE OF CONFIGURATION SELECTION .....</b>	<b>10</b>
<b>4.2</b>	<b>TEST OPERATION AND TEST SOFTWARE.....</b>	<b>10</b>
<b>4.3</b>	<b>SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT .....</b>	<b>10</b>
<b>4.4</b>	<b>COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....</b>	<b>10</b>
<b>4.5</b>	<b>TEST SETUP DIAGRAM .....</b>	<b>10</b>
<b>5</b>	<b>TEST RESULTS .....</b>	<b>12</b>
<b>5.1</b>	<b>TRANSMITTER REQUIREMENT &amp; TEST SUITES .....</b>	<b>12</b>
5.1.1	<i>Radiated Spurious Emissions .....</i>	<i>12</i>
<b>6</b>	<b>PHOTOGRAPHS OF THE TEST SET-UP.....</b>	<b>21</b>
<b>7</b>	<b>LIST OF TABLES.....</b>	<b>22</b>
<b>8</b>	<b>LIST OF PHOTOGRAPHS .....</b>	<b>22</b>

## **1 General Remarks**

### **1.1 Complementary Materials**

N/A

## 2 Test Sites

### 2.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

1F East & 2-4F, Cybio Technology Building No.1, No.16 Kejibei 2nd Road, Nanshan District, Shenzhen, 518057, China

FCC Registration No.: 694916

IC Registration No.: 25069

### 2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Unwanted Emission Testing (TS9975)					
Equip. No.	Equipment	Manufacturer	Model	Serial No.	Cal. until
1826021	EMI Test Receiver	Rohde & Schwarz	ESR 7	102021	19.08.2020
1826023	Signal Analyzer	Rohde & Schwarz	FSV 40	101439	21.08.2020
1826024	System Controller Interface	Rohde & Schwarz	SCI-100	S10010038	N/A
1826025	Filterbank	Rohde & Schwarz	Wlan	100759	21.08.2020
1826026	OSP	Rohde & Schwarz	OSP 120	102040	N/A
1826028	Pre-amplifier	Rohde & Schwarz	SCU08F1	08320031	20.08.2020
1826029	Amplifier	Rohde & Schwarz	SCU-18F	180070	20.08.2020
1826030	Amplifier	Rohde & Schwarz	SCU40A	100475	20.09.2020
1826031	Trilog Broadband Antenna (30 MHz - 7 GHz)	Schwarzbeck	VULB 9162	193	02.09.2020
1826032	Double-Ridged Antenna (1 -18 GHz)	ETS-LINDGREN	3117	00218717	02.09.2020
1826033	Wideband Ridged Horn Antenna (18-40 GHz)	Steatite	QMS-00880	19067	02.09.2020
1826034	Active Loop Antenna	Schwarzbeck	FMZB 1513	302	01.09.2020
1826035	Wideband Ridged Horn Antenna (12-18 GHz)	Steatite	QMS-00208	18313	02.09.2020
1826036	Test software	Rohde & Schwarz	V10.40.10-EMC32	N/A	N/A
1826037	Control PC	Dell	OptiPlex 7050	36NV9P2	N/A
1826433	3m Semi-Anechoic Chamber	Albatross	SAC-3m	APC17151-SAC	06.07.2020

## 2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

## 2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

## 2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table:

Table 2: Measurement Uncertainty

Items	Extended Uncertainty
Radiated Spurious Emissions (up to 1GHz)	± 4.84 dB
Radiated Spurious Emissions (1GHz to 26.5GHz)	± 4.76 dB

## 2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached in this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. file for certification follow-up purposes.

## 2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at 1F East & 2-4F, Cybio Technology Building No.1, No.16 Kejibei 2nd Road, Nanshan District, Shenzhen, 518057, China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

### 3 General Product Information

#### 3.1 Product Function and Intended Use

The EUTs are Solar Steplight which support Bluetooth, LoRa DTSs, LoRa FHSs and FSK FHSs function operated at 2400-2483.5MHz and 902-928MHz respectively.

For details refer to the User Manual, Technical Description and Circuit Diagram.

#### 3.2 Ratings and System Details

Table 3: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment	Solar Steplight
Type Designation	5AT1S7
Operating Voltage	DC 5V@1A by USB port DC 3.7V@3200mAh via internal battery
Testing Voltage	Fully charged battery

Technical Specification of BLE

Technical Specification	BLE
Operating Frequency band	2402 – 2480 MHz
Bluetooth Core Version	Bluetooth Low Energy 4.2
Channel separation	2MHz
Extreme Temperature Range	-20°C ~ 50°C
Modulation	GFSK
Antenna Type	PCB layout Antenna
Antenna Gain(dBi)	3.26
Channel	0~39

Technical Specification of LoRa DTS

Technical Specification	LoRa DTS 500KHz 902.5-926.5MHz	LoRa DTS 500KHz 903-914.2MHz	LoRa DTS 500KHz 923.3-926.9MHz
Operating Frequency band	902 – 928 MHz		
Extreme Temperature Range	-20°C ~ 50°C		
Bandwidth(KHz)	500		
Modulation	LoRa DTS		
Antenna Type	Folded Stamped Metal Inverted-F Antenna		
Antenna Gain(dBi)	0.14		
Channel Separation (KHz)	800	1600	600
Channel Number	31	8	7
Channel (MHz)	902.5, 903.3, 904.1, 904.9, 905.7, 906.5, 907.3, 908.1, 908.9, 909.7, 910.5, 911.3, 912.1, 912.9, 913.7, 914.5, 915.3, 916.1, 916.9, 917.7, 918.5, 919.3, 920.1, 920.9, 921.7, 922.5, 923.3, 924.1, 924.9, 925.7, 926.5	903, 904.6, 906.2, 907.8, 909.4, 911, 912.6, 914.2	923.3, 923.9, 924.5, 925.1, 925.7, 926.3, 926.9

**Technical Specification of LoRa FHSS**

Technical Specification	LoRa 250KHz FHSS 902.3-926.7MHz	LoRa 125KHz FHSS 902.3-914.9MHz	LoRa 125KHz FHSS 902.2-927.8MHz
Operating Frequency band	902 – 928 MHz		
Extreme Temperature Range	-20°C ~ 50°C		
Modulation	LoRa FHSS		
Antenna Type	Folded Stamped Metal Inverted-F Antenna		
Antenna Gain(dBi)	0.14		
Channel Separation (KHz)	400	200	200
Channel Number	62	64	129
Bandwidth (KHz)	250	125	125
Hopping channel(MHz)	902.3~926.7	902.3~914.9	902.2-927.8

**Technical Specification of FSK FHSS**

Technical Specification	FSK150Kbps FHSS	FSK 50Kbps FHSS	FSK 5Kbps FHSS	FSK 250Kbps FHSS
Operating Frequency band	902 – 928 MHz			
Extreme Temperature Range	-20°C ~ 50°C			
Modulation	FSK FHSS			
Antenna Type	Folded Stamped Metal Inverted-F Antenna			
Antenna Gain(dBi)	0.14			
Channel Separation (KHz)	400	200	200	500
Channel Number	64	129	129	51
Data Rate (Kbps)	150	50	5	250
Hopping Channel(MHz)	902.4~927.6	902.2~927.8	902.2~927.8	902.5~927.5



### **3.3 Independent Operation Modes**

The basic operation modes are:

- A. On, BLE transmitting mode
  - 1. Low channel
  - 2. Middle channel
  - 3. High channel
- B. Off

### **3.4 Noise Generating and Noise Suppressing Parts**

Refer to Circuit Diagram for further details.

### **3.5 Submitted Documents**

N/A

## 4 Test Set-up and Operation Modes

### 4.1 Principle of Configuration Selection

**Emissions:** The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

According to the model differences description at section 3.1, all tests were performed on the model 5AT1S7.

### 4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.10: 2013.

### 4.3 Special Accessories and Auxiliary Equipment

Table 4: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	S/N	Rating
Laptop	Lenovo	T480	PF-16A6N8	N/A

### 4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

### 4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)





Diagram of Measurement Configuration for Radiation Test (Above 1GHz)



## 5 Test Results

### 5.1 Transmitter Requirement & Test Suites

#### 5.1.1 Radiated Spurious Emissions


**RESULT:****Pass****Test Specification**

Test standard	:	FCC Part 15.247 (d) & FCC Part 15.205 RSS-GEN Clause 8.9 & RSS-247 Clause 3.3
Basic standard	:	ANSI C63.10: 2013
Limits	:	Refer to 15.209(a) of FCC part 15.247(d) RSS-Gen Table 5
Kind of test site	:	3m Semi-anechoic Chamber


**Test Setup**

Date of testing	:	20.12.2019
Input voltage	:	Fully charged battery
Operation mode	:	A.1, A.2, A.3
Earthing	:	Not Connected
Ambient temperature	:	22 °C
Relative humidity	:	54 %
Atmospheric pressure	:	101 kPa


For details refer to following test result, only the worst case was shown.

**Mode A.1**  
**Horizontal**



Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4804.000000	---	46.66	54.00	7.34	100.0	H	191.0	13.6
4804.000000	52.72	---	74.00	21.28	100.0	H	191.0	13.6
7202.508333	---	34.53	54.00	19.47	100.0	H	313.0	8.8
7214.800000	44.42	---	74.00	29.58	100.0	H	358.0	8.7

**Vertical**



Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4804.000000	---	44.13	54.00	9.87	100.0	V	155.0	13.6
4804.500000	52.11	---	74.00	21.89	100.0	V	155.0	13.6
7205.950000	---	37.55	54.00	16.45	100.0	V	356.0	8.8
7206.441667	45.00	---	74.00	29.00	100.0	V	356.0	8.8

**Horizontal**



Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2337.747794	---	50.14	54.00	3.86	100.0	H	41.0	6.8
2389.753677	58.62	---	74.00	15.38	100.0	H	244.0	7.0

**Vertical**



Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2356.972059	---	44.06	54.00	9.94	100.0	V	188.0	6.9
2388.502941	53.42	---	74.00	20.58	100.0	V	146.0	7.0

**Horizontal**



Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
24117.562500	---	38.57	54.00	15.43	100.0	H	279.0	-10.1
24130.687500	46.02	---	74.00	27.98	100.0	H	251.0	-10.1

**Vertical**


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
22865.656250	47.36	---	74.00	26.64	100.0	V	165.0	-10.9
22867.625000	---	38.62	54.00	15.38	100.0	V	0.0	-10.9


**Mode A.2**  
**Horizontal**


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4879.500000	---	47.02	54.00	6.98	100.0	H	121.0	13.4
4880.000000	53.66	---	74.00	20.34	100.0	H	121.0	13.4
7315.591667	---	33.80	54.00	20.20	100.0	H	341.0	8.2
7322.475000	42.81	---	74.00	31.19	100.0	H	84.0	8.2


**Vertical**


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4880.000000	---	45.44	54.00	8.56	100.0	V	131.0	13.4
4880.000000	53.11	---	74.00	20.89	100.0	V	131.0	13.4
7320.508333	---	33.61	54.00	20.39	100.0	V	25.0	8.2
7327.391667	42.81	---	74.00	31.19	100.0	V	81.0	8.1




**Horizontal**



Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
23522.562500	46.98	---	74.00	27.02	100.0	H	268.0	-10.5
23572.437500	---	39.64	54.00	14.36	100.0	H	152.0	-10.4

**Vertical**



Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
23083.750000	---	38.84	54.00	15.16	100.0	V	328.0	-10.8
23185.250000	46.80	---	74.00	27.20	100.0	V	130.0	-10.6

**Mode A.3**  
**Horizontal**



Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4959.000000	---	45.55	54.00	8.45	100.0	H	60.0	13.2
4959.000000	52.91	---	74.00	21.09	100.0	H	60.0	13.2
7450.800000	43.91	---	74.00	30.09	100.0	H	67.0	8.5
7451.783333	---	33.97	54.00	20.03	100.0	H	344.0	8.5

**Vertical**



Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4959.000000	55.12	---	74.00	18.88	100.0	V	10.0	13.2
4959.500000	---	47.11	54.00	6.89	100.0	V	4.0	13.2
7439.000000	44.64	---	74.00	29.36	100.0	V	166.0	8.4
7439.000000	---	37.17	54.00	16.83	100.0	V	166.0	8.4

**Horizontal**



Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2483.577206	---	46.16	54.00	7.84	100.0	H	40.0	7.4
2483.863971	68.30	---	74.00	5.70	100.0	H	47.0	7.4

**Vertical**


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2483.566177	61.39	---	74.00	12.61	100.0	V	146.0	7.4
2483.584559	---	42.07	54.00	11.93	100.0	V	119.0	7.4

**Horizontal**


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
23222.000000	---	38.94	54.00	15.06	100.0	H	54.0	-10.5
23501.343750	47.15	---	74.00	26.85	100.0	H	258.0	-10.5

**Vertical**


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
23691.875000	---	38.88	54.00	15.12	100.0	V	89.0	-10.2
23740.218750	46.47	---	74.00	27.53	100.0	V	176.0	-10.1