




<b>Prüfbericht-Nr.:</b> <i>Test Report No.:</i>	<b>50176879 001</b>	<b>Auftrags-Nr.:</b> <i>Order No.:</i>	144194137	<b>Seite 1 von 13</b> <i>Page 1 of 13</i>	
<b>Kunden-Referenz-Nr.:</b> <i>Client Reference No.:</i>	N/A	<b>Auftragsdatum:</b> <i>Order date:</i>	23.08.2018		
<b>Auftraggeber:</b> <i>Client:</i>	<b>GUANGDONG ATTOP TECHNOLOGY CO.,LTD</b> Linghai Industry Zone, Laimei Road Chenghai District, Shantou, Guangdong, China				
<b>Prüfgegenstand:</b> <i>Test item:</i>	<b>Short Range Device - Radio Control Quadcopter</b>				
<b>Bezeichnung / Typ-Nr.:</b> <i>Identification / Type No.:</i>	<b>Please refer to "Models" on page 4</b>				
<b>Auftrags-Inhalt:</b> <i>Order content:</i>	FCC Cerification				
<b>Prüfgrundlage:</b> <i>Test specification:</i>	<b>FCC Part 15 Subpart C</b> <b>ANSI C63.10-2013</b>				
<b>Wareneingangsdatum:</b> <i>Date of receipt:</i>	01.03.2019				
<b>Prüfmuster-Nr.:</b> <i>Test sample No.:</i>	A000883278-002				
<b>Prüfzeitraum:</b> <i>Testing period:</i>	04.03.2019 - 18.03.2019				
<b>Ort der Prüfung:</b> <i>Place of testing:</i>	TÜV Rheinland Hong Kong Ltd				
<b>Prüflaboratorium:</b> <i>Testing laboratory:</i>	TÜV Rheinland Hong Kong Ltd				
<b>Prüfergebnis*:</b> <i>Test result*:</i>	Pass				
<b>geprüft von / tested by:</b>		<b>kontrolliert von / reviewed by:</b>			
 19.03.2019 Mika Chan / Project Manager		 19.03.2019 Sharon Li / Unit Senior Manager			
<b>Datum</b> <i>Date</i>	<b>Name / Stellung</b> <i>Name / Position</i>	<b>Unterschrift</b> <i>Signature</i>	<b>Datum</b> <i>Date</i>	<b>Name / Stellung</b> <i>Name / Position</i>	<b>Unterschrift</b> <i>Signature</i>
<b>Sonstiges / Other:</b>		<b>FCC ID: 2AEVN0754W8W</b>			
<b>Zustand des Prüfgegenstandes bei Anlieferung:</b> <i>Condition of the test item at delivery:</i>		<b>Prüfmuster vollständig und unbeschädigt</b> <i>Test item complete and undamaged</i>			
<p>* Legende: 1 = sehr gut    2 = gut    3 = befriedigend    4 = ausreichend    5 = mangelhaft          P(ass) = entspricht o.g. Prüfgrundlage(n)    F(ail) = entspricht nicht o.g. Prüfgrundlage(n)    N/A = nicht anwendbar    N/T = nicht getestet</p> <p>Legend: 1 = very good    2 = good    3 = satisfactory    4 = sufficient    5 = poor          P(ass) = passed a.m. test specification(s)    F(ail) = failed a.m. test specification(s)    N/A = not applicable    N/T = not tested</p>					
<p><b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b></p> <p><i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i></p>					

# Table of Content

	<b>Page</b>
<b>Cover Page</b> .....	<b>1</b>
<b>Table of Content</b> .....	<b>2</b>
<b>Product information</b> .....	<b>4</b>
<b>Manufacturers declarations</b> .....	<b>4</b>
<b>Product function and intended use</b> .....	<b>4</b>
<b>Submitted documents</b> .....	<b>4</b>
<b>Independent Operation Modes</b> .....	<b>4</b>
<b>Related Submittal(s) Grants</b> .....	<b>4</b>
<b>Remark</b> .....	<b>4</b>
<b>Test Set-up and Operation Mode</b> .....	<b>5</b>
<b>Principle of Configuration Selection</b> .....	<b>5</b>
<b>Test Operation and Test Software</b> .....	<b>5</b>
<b>Special Accessories and Auxiliary Equipment</b> .....	<b>5</b>
<b>Countermeasures to achieve EMC Compliance</b> .....	<b>5</b>
<b>Test Methodology</b> .....	<b>6</b>
<b>Radiated Emission</b> .....	<b>6</b>
<b>Field Strength Calculation</b> .....	<b>6</b>
<b>Test Setup Diagram</b> .....	<b>7</b>
<b>Test Facility</b> .....	<b>8</b>
<b>Test Laboratory Information</b> .....	<b>8</b>
<b>List of Test and Measurement Instruments</b> .....	<b>9</b>
<b>Measurement Uncertainty</b> .....	<b>10</b>
<b>Results FCC Part 15 – Subpart C</b> .....	<b>11</b>
<b>FCC 15.203 – Antenna Requirement 1</b> .....	<b>Pass</b> ..... <b>11</b>
<b>FCC 15.204 – Antenna Requirement 2</b> .....	<b>Pass</b> ..... <b>11</b>
<b>FCC 15.207 – Conducted Emission on AC Mains</b> .....	<b>N/A</b> ..... <b>11</b>
<b>Subclause 15.215 (c) – 20 dB Bandwidth</b> .....	<b>Pass</b> ..... <b>11</b>
<b>Subclause 15.249 (a) – Field Strength of Fundamental and Harmonics</b> .....	<b>Pass</b> ..... <b>12</b>
<b>Subclause 15.249 (d), 15.205 – Out Of Band Radiated Emission</b> .....	<b>Pass</b> ..... <b>13</b>
<b>Appendix 1 – Test protocols</b> .....	<b>2 pages</b>
<b>Appendix 2 – Test setup</b> .....	<b>2 pages</b>

**Appendix 3 – EUT External Photos ..... 6 pages**  
**Appendix 4 – EUT Internal Photos ..... 15 pages**  
**Appendix 5 – RF exposure information..... 2 pages**

## Product information

### Manufacturers declarations

	<b>Transmitter</b>
Operating frequency range	5745MHz
Type of modulation	802.11n-HT20: OFDM
Number of channels	1
Type of antenna	Integral wire Antenna
Number of TX chains	2
Power level	fix
Connection to public utility power line	No
Nominal voltage	V <sub>nor</sub> : 3.7 VDC (Rechargeable battery)

### Product function and intended use

The equipment under test (EUT) is radio controlled toy quadcopter embedded with WiFi camera and GPS. It is intended to use in following electromagnetic environment: residential and urban outdoors.

#### FCC ID: 2AEVN0754W8W

<b>Models</b>	<b>Product description</b>
W8, W, W Pro, W Fpv, W9, W18, W20, W28, W30, W38, W50, W58, W60, W68, W70, W78, W80, W88, W90, W98, X-PACK PLUS, X-PACK PRO, X-PACK GPS	Short Range Device - Radio Control Quadcopter

### Submitted documents

Circuit Diagram  
 Block Diagram  
 Technical Description  
 User manual  
 Label

### Independent Operation Modes

The basic operation modes are:

- Transmitting mode.
- Normal operation mode

For further information refer to User Manual

### Related Submittal(s) Grants

This is a single application for certification of the transmitter.

### Remark

The test results in this test report are only relevant to the tested sample and does not involve any assessment in the production.

## Test Set-up and Operation Mode

### Principle of Configuration Selection

**Emission:** The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

### Test Operation and Test Software

Test operation should refer to test methodology.

- Test mode samples with maximum RF output power and duty cycle provided by the applicant are used for testing.
- Test mode: ANT1+ANT2

### Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- None

### Countermeasures to achieve EMC Compliance

- None

## Test Methodology

### Radiated Emission

The radiated emission measurements of the transmitter part were performed according to the procedures in ANSI C63.10-2013.

For measurement below 1GHz - the equipment under test (EUT) was placed at the middle of the 80 cm height turntable. For measurement above 1GHz - the EUT was placed at the middle of the 1.5 m height turntable and RF absorbing material was placed on ground plane between turntable and measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

### Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:


$$FS = R + AF + CF + FA - PA$$

Where FS = Field Strength in dBuV/m at 3 meters.  
R = Reading of Spectrum Analyzer in dBuV.  
AF = Antenna Factor in dB.  
CF = Cable Attenuation Factor in dB.  
FA = Filter Attenuation Factor in dB.  
PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.


## Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1 GHz are done with a table height of 1.5m. In addition, there is RF absorbing material on the floor of the test site for above 1GHz measurement.

Diagram of Measurement Equipment Configuration for Mains Conduction Measurement (if applicable)



## Test Facility

### Test Laboratory Information

TÜV Rheinland Hong Kong Ltd.

Address: 3-4, 11/F., Fou Wah Industrial Building, 10-16 Pun Shan Street, Tsuen Wan, N.T., Hong Kong

Tel.: +852 2192 1000

Fax: +852 2192 1001

Email [service-gc@tuv.com](mailto:service-gc@tuv.com)

Web: [www.tuv.com](http://www.tuv.com)

The test facility is recognized or accredited by the following organizations:

#### **FCC**

Type	: Accredited Test Firm
Designation Number	: HK0013
Test Firm Registration Number	: 371735
Scope	: Intentional Radiators



## List of Test and Measurement Instruments

### TÜV Rheinland Hong Kong Ltd

#### Radiated Emission

Equipment	Manufacturer	Type	Cal. Date	Due Date
Semi-anechoic Chamber	Frankonia	Nil	23-Apr-18	23-Apr-19
Test Receiver	R & S	ESU40	12-Jun-18	12-Jun-19
Active Loop Antenna	EMCO	6502	25-Oct-18	25-Oct-19
Bi-conical Antenna	R & S	HK116	21-Mar-18	21-Mar-20
Log Periodic Antenna	R & S	HL223	22-Mar-18	22-Mar-20
Standard Gain Horn	ETS-Lindgren	3160-10	3-Oct-18	3-Oct-20
Double-Ridged Waveguide Horn	EMCO	3116	5-Oct-18	5-Oct-20
Double-Ridged Waveguide Horn	EMCO	3117	30-Aug-18	30-Aug-20
Coaxial cable	Huber+Suhner	CNM-NMCMILX800-473	11-Dec-17	11-Dec-19
High Frequency Cable	Pasternack	PE3VNA4001-3M	30-Jan-19	30-Jan-20
Microwave Preamplifier	COM-POWER Corporation	PAM-118A	25-Jun-18	25-Jun-19
Preamplifier 18GHz to 40GHz with cable	A.H. Systems, Inc.	PAM-1840VH	30-Jan-19	30-Jan-20
High Pass Filter (cutoff freq. =1000MHz)	Trilithic	23042	30-Oct-17	30-Oct-19

#### Radio Test

Equipment	Manufacturer	Type	Cal. Date	Due Date
Spectrum Analyzer	R & S	FSP30	03-May-18	02-May-19

## Measurement Uncertainty

The estimated combined standard uncertainty for power-line conducted emissions measurements is  $\pm 2.42$ dB.

The estimated combined standard uncertainty for radiated emissions measurements is  $\pm 4.81$ dB (9kHz to 30MHz) and  $\pm 4.62$ dB (30MHz to 200MHz) and  $\pm 5.67$ dB (200MHz to 1000MHz) and is  $\pm 5.07$ dB (1GHz to 8.2GHz) and  $\pm 4.58$ dB (8.2GHz to 12.4GHz) and  $\pm 4.78$ dB (12.4GHz to 18GHz)

The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of  $k=2$ , which for the level of confidence is approximately 95%.

## Results FCC Part 15 – Subpart C

<b>FCC 15.203 – Antenna Requirement 1</b>		<b>Pass</b>		
<b>FCC Requirement:</b> No antenna other than that furnished by the responsible party shall be used with the device				
<b>Results:</b>	a) Antenna type:	Integral wire Antenna		
	b) Manufacturer and model no:	N/A		
	c) Peak Gain:	2.5dBi		
<b>Verdict:</b>	Pass			
<b>FCC 15.204 – Antenna Requirement 2</b>		<b>Pass</b>		
<b>FCC Requirement:</b> An intentional radiator may be operated only with the antenna with which it is authorized. If an antenna is marketed with the intentional radiator, it shall be of a type which is authorized with the intentional radiator.				
<b>Results:</b>	Only one integral antenna can be used.			
<b>Verdict:</b>	N/A			
<b>FCC 15.207 – Conducted Emission on AC Mains</b>		<b>N/A</b>		
There is no AC power input or output ports on the EUT.				
<b>Subclause 15.215 (c) – 20 dB Bandwidth</b>		<b>Pass</b>		
Test Specification : ANSI C63.10 – 2013				
Test date : 16.03.2019				
Mode of operation : Tx mode				
Port of testing : Temporary antenna port				
Supply voltage : 3.7VDC				
Temperature : 23°C				
Humidity : 50%				
<b>Requirement:</b>	The intentional radiators must be designed to ensure that the 20dB bandwidth of the emission, is contained within the frequency band designated in the rule section under which the equipment is operated.			
<b>Results:</b>	Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.			
	For test protocols refer to Appendix 1.			
<b>Frequency (MHz)</b>	<b>20 dB left (MHz)</b>	<b>Limit (MHz)</b>	<b>20 dB right (MHz)</b>	<b>Limit (MHz)</b>
5745	5733.38	> 5725	5756.76	< 5875

<b>Subclause 15.249 (a) – Field Strength of Fundamental and Harmonics</b>		<b>Pass</b>
Test Specification : ANSI C63.10 – 2013 Test Specification : 15.03.2019 Mode of operation : Tx mode Port of testing : Enclosure Frequency range : 9kHz – 40GHz Supply voltage : 3.7VDC Temperature : 23°C Humidity : 50%		
Requirement: The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following limit.		
<b>Results:</b> PASS.		
Fundamental Frequency 5745MHz		Vertical Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
5740.750	94.3	114.0 / PK
5740.750	84.8	94.0 / AV
Fundamental Frequency 5745MHz		Horizontal Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
5744.567	85.1	114.0 / PK
5744.567	75.3	94.0 / AV
Harmonics 5745MHz		Vertical Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
11481.500	61.2	74.0 / PK
11481.500	45.0	54.0 / AV
17255.608	51.72	74.0 / PK
17255.608	37.03	54.0 / AV
23013.621	29.53	74.0 / PK
23013.621	15.91	54.0 / AV
Harmonics 5745MHz		Horizontal Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
11499.500	47.6	74.0 / PK
11499.500	34.1	54.0 / AV
17228.525	49.12	74.0 / PK
17228.525	36.19	54.0 / AV
23008.012	28.16	74.0 / PK
23008.012	15.88	54.0 / AV

<b>Subclause 15.249 (d), 15.205 – Out Of Band Radiated Emission</b>	<b>Pass</b>
---	-------------

Test Specification : ANSI C63.10 – 2013  
 Test Specification : 15.03.2019  
 Mode of operation : Tx mode  
 Port of testing : Enclosure  
 Frequency range : 9kHz – 25GHz  
 Supply voltage : 3.7VDC  
 Temperature : 23°C  
 Humidity : 50%

**Requirement:** Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

**Results:** All transmit frequency modes comply with the field strength limit of section 15.209. There is no spurious found below 30MHz.

Tx frequency 5745MHz		Vertical Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
144.390	32.2	43.5 / QP
709.109	36.2	46.0 / QP
5725.000	62.9	74.0 / PK
5725.000	41.1	54.0 / AV

Tx frequency 5745MHz		Horizontal Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
147.690	27.9	43.5 / QP
381.830	32.8	46.0 / QP
5725.000	61.4	74.0 / PK
5725.000	49.7	54.0 / AV