

Passive Test For BT2_4												
Freq (MHz)	Eff1 (%)	Eff1 (dBi)	Gain (dBi)	Gain (dB)	UHIS (%)	DHIS (%)	Max (dB)	Min (dB)	irectivity (dBi)	Beamwidth (3dB)	AttH (dB)	AttV (dB)
2400	31.41	-5.03	-0.05	-2.2	0	0	-0.05	-14.84	5.03	0	47.36	46.88
2410	29.14	-5.36	-0.34	-2.49	0	0	-0.34	-14.41	5.36	0	47.4	46.5
2420	25.66	-5.91	-0.89	-3.04	0	0	-0.89	-16.78	5.91	0	47.28	46.74
2430	28.02	-5.53	-0.57	-2.72	0	0	-0.57	-19.4	5.53	0	47.35	46.78
2440	23.53	-6.28	-1.35	-3.5	0	0	-1.35	-23.37	6.28	0	47.15	46.65
2450	25.01	-6.02	-1.09	-3.24	0	0	-1.09	-25.31	6.02	0	47.33	46.83
2460	26.28	-5.8	-0.89	-3.04	0	0	-0.89	-20.87	5.8	0	47.72	47.22
2470	18.57	-7.31	-2.25	-4.4	0	0	-2.25	-18.54	7.31	0	47.36	46.93
2480	21.2	-6.74	-1.49	-3.64	0	0	-1.49	-20.18	6.74	0	47.56	47.1
2490	17.74	-7.51	-2.17	-4.32	0	0	-2.17	-24.05	7.51	0	47.05	46.67
2500	17.73	-7.51	-2.15	-4.3	0	0	-2.15	-23.72	7.51	0	47.01	46.63

Application Information	
0Version	5.245.351
TotalTime	4m 18s 977ms
AdditionalInfor	NULL
model	645872

