


RF EXPOSURE REPORT

FOR

Applicant	:	Jovision Technology Co., Ltd.
Address	:	Floor 12, Building No.3, Aosheng Square, No. 1166 Xinluo Street, Jinan, Shandong, China
Equipment under Test	:	Network Camera
Model No.	:	JVS-H930E, JVS-H940E, JVS-H950E, JVS-H960E, JVS-H970E, JVS-H980E, JVS-H990E, JVS-N513-DS-Z5, JVS-N533-DS-Z5, JVS-N933-K1-PE, JVS-N933-K1, JVS-N933-KDL-PE, JVS-N916-KDL-PE, JVS-N916-KDL, JVS-N933-KDL, JVS-N513-K1-PE, JVS-N913-K1-PE, JVS-N913-K1, JVS-N933-YWC, JVS-N933-YWC-PE, JVS-N913-YWC, JVS-N913-YWC-PE, JVS-N913-YWS-PE, JVS-N96-X3, JVS-N97-X3, JVS-N98-X3, JVS-N99-X3, JVS-FPT-DL18, JVS-NL65-Z70, JVS-DL64-Z33, JVS-DL68-Z78, JVS-N5022, JVS-N510-YWS, JVS-N3122SL, JVS-N935SL-HY, JVS-N955-HY, JVS-N43-Z25, JVS-N917-SDL, JVS-N917-SDL-PE, JVS-N916-YWD, JVS-N9122SL, JVS-SD1, AS-DB01, AS-DB02, AS-DB03, AS-DB06, AS-DB08, JVS-516-YWD, JVS-936-HDL, JVS-536-HDL
Trade Mark	:	 JOVISION
FCC ID	:	2AEW9JVS-H930E
Manufacturer	:	Jovision Technology Co., Ltd.
Address	:	Floor 12, Building No.3, Aosheng Square, No. 1166 Xinluo Street, Jinan, Shandong, China

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808


Tel.: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

Table of Contents

	Test report declares.....	3
1.	General Information	5
1.1.	Description of equipment	5
1.2.	Assess laboratory.....	5
2.	RF Exposure Evaluation	6
2.1.	Requirement.....	6
2.2.	Calculation method	6
2.3.	Estimation result.....	7

Test Report Declare

Applicant	:	Jovision Technology Co., Ltd.
Address	:	P.O. Box 6264 General Post Office Hong Kong
Equipment under Test	:	Network Camera
Model No.	:	JVS-H930E, JVS-H940E, JVS-H950E, JVS-H960E, JVS-H970E, JVS-H980E, JVS-H990E, JVS-N513-DS-Z5, JVS-N533-DS-Z5, JVS-N933-K1-PE, JVS-N933-K1, JVS-N933-KDL-PE, JVS-N916-KDL-PE, JVS-N916-KDL, JVS-N933-KDL, JVS-N513-K1-PE, JVS-N913-K1-PE, JVS-N913-K1, JVS-N933-YWC, JVS-N933-YWC-PE, JVS-N913-YWC, JVS-N913-YWC-PE, JVS-N913-YWS-PE, JVS-N96-X3, JVS-N97-X3, JVS-N98-X3, JVS-N99-X3 JVS-FPT-DL18, JVS-NL65-Z70, JVS-DL64-Z33, JVS-DL68-Z78, JVS-N5022, JVS-N510-YWS, JVS-N3122SL, JVS-N935SL-HY, JVS-N955-HY, JVS-N43-Z25, JVS-N917-SDL, JVS-N917-SDL-PE, JVS-N916-YWD, JVS-N9122SL, JVS-SD1, AS-DB01, AS-DB02, AS-DB03, AS-DB06, AS-DB08, JVS-516-YWD, JVS-936-HDL, JVS-536-HDL
Trade mark	:	 JOVISION
Manufacturer	:	Jovision Technology Co., Ltd.
Address	:	8th floor, ZuoAn Building, NO.68 BeiSiHuanXiLu, Haidian District, Beijing 100080, CHINA

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No:	DDT-R22031014-2E04		
Date of Receipt:	May 25, 2022	Date of Test:	May 25, 2022 ~ Jun. 20, 2022

Prepared By:

Johnny Wang

Johnny Wang/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Jun. 20, 2022	

1. General Information

1.1. Description of equipment

EUT* Name	: Network Camera
Model Number	: JVS-H930E, JVS-H940E, JVS-H950E, JVS-H960E, JVS-H970E, JVS-H980E, JVS-H990E, JVS-N513-DS-Z5, JVS-N533-DS-Z5, JVS-N933-K1-PE, JVS-N933-K1, JVS-N933-KDL-PE, JVS-N916-KDL-PE, JVS-N916-KDL, JVS-N933-KDL, JVS-N513-K1-PE, JVS-N913-K1-PE, JVS-N913-K1, JVS-N933-YWC, JVS-N933-YWC-PE, JVS-N913-YWC, JVS-N913-YWC-PE, JVS-N913-YWS-PE, JVS-N96-X3, JVS-N97-X3, JVS-N98-X3, JVS-N99-X3 JVS-FPT-DL18, JVS-NL65-Z70, JVS-DL64-Z33, JVS-DL68-Z78, JVS-N5022, JVS-N510-YWS, JVS-N3122SL, JVS-N935SL-HY, JVS-N955-HY, JVS-N43-Z25, JVS-N917-SDL, JVS-N917-SDL-PE, JVS-N916-YWD, JVS-N9122SL, JVS-SD1, AS-DB01, AS-DB02, AS-DB03, AS-DB06, AS-DB08, JVS-516-YWD, JVS-936-HDL, JVS-536-HDL
Difference of models	: Above models are identical in schematic and structure, only the name is different for all the models, therefore the test performed on the model JVS-H930E.
EUT function description	: Please reference user manual of this device
Power supply	: DC 5V from adapter
Radio Technology	: IEEE 802.11b/g/n
FCC Operation frequency	: IEEE 802.11b: 2412MHz—2462MHz : IEEE 802.11g: 2412MHz—2462MHz : IEEE 802.11n HT20: 2412MHz—2462MHz
Modulation	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) : IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) : IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK, BPSK)
Transmitter rate	: IEEE 802.11b: 1, 2, 5.5, 11 Mbps : IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps : IEEE 802.11n HT20: up to 72.2 Mbps
Antenna Type	: FPC antenna, maximum PK gain: 2.5 dBi
Sample Number	: S22031014-04 for conductive : S22031014-05 for radiation

1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, G-20118

2. RF Exposure Evaluation

2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2. Calculation method

$$E(\text{V/m}) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(\text{mW/cm}^2) = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (mW)

G = EUT Antenna numeric gain (numeric)=

d = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, d= 0.2 m, as well as the gain of the used antenna, the RF power density can be obtained.

2.3. Estimation result

Mode	PK Output power (dBm)	Output power (mW)	tune up power (dBm)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm ²)	MPE Limit (mW/cm ²)
Bluetooth Max power	11.17	13.09	12.00	2.50	1.78	0.00561	1

Note: The estimation distance is 20 cm

Conclusion: The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

END OF REPORT