

Nanoleaf Skylight
Model: NL64K000
120V AC 60Hz 19.5W
RGB+2700K-6500K 1400lm
Made in China



FCC ID: 2AEWY-NL64 IC: 20489-NL64
Contains FCC ID: 2AEWY-NL04A
Contains IC: 20489-NL04A

Conforms to UL STD 1598 Certified to CSA STD C22.2 NO 250.0
SUITABLE FOR DAMP LOCATIONS. INHERENTLY PROTECTED. DO NOT
INSTALL INSULATION WITHIN 76 mm (3 in) OF ANY PART OF THE
LUMINAIRE. ACCESS ABOVE CEILING REQUIRED. FOR USE IN NON-
FIRE-RATED INSTALLATIONS ONLY MIN 90°C SUPPLY CONDUCTORS.
CONVIENT AUX EMPLACEMENTS HUMIDES. INHERENTLY PROTECTED.
PROTECTION INHERENTE. NE PAS METTRE L'ISOLANT À MOINS DE 76
mm (3 po) DE TOUTE PARTIE DU LUMINAIRE. ACCÈS REQUIS AU-
DESSUS DU PLAFOND. UTILISER SEULEMENT DANS DES INSTALLATIONS
D'UN DEGRÉ DE RÉSISTANCE AU FEU N'EST PAS ÉTABLI. LES FILS
D'ALIMENTATION 90 °C MIN.

