

# Appendix 5

## RF Exposure Information

**Maximum transmitter power:**

Frequency (MHz)	Maximum peak output power (dBuV/m)	Output power (mW)
2.405	85.81	0.1143
2.445	84.77	0.0900
2.475	84.52	0.0849

According to KDB 447498 D01:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and ≤7.5 for 10-g extremity SAR,24 where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

**Result:**

$$(0.1143/5) \cdot \sqrt{2.405} = 0.035 < 3.0$$

$$(0.0900/5) \cdot \sqrt{2.445} = 0.028 < 3.0$$

$$(0.0849/5) \cdot \sqrt{2.475} = 0.027 < 3.0$$

**Conclusion:**

No SAR is required.