



243 Jubug-Ri, Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 449-822  
 Tel: +82-31-323-6008 Fax: +82-31-323-6010  
<http://www.ltalab.com>

Dates of Tests: Jan 25 ~ April 30, 2018

Test Report S/N: LR500111805C

Test Site : LTA CO., LTD.

## CERTIFICATION OF COMPLIANCE

FCC ID

**2AEXZSHM912**

APPLICANT

**SEECODE CO.,LTD.**

<b>Equipment Class</b>	:	<b>Part 15 Spread Spectrum Transmitter (DSS)</b>
<b>Manufacturing Description</b>	:	<b>PTT Headset</b>
<b>Manufacturer</b>	:	<b>SEECODE CO.,LTD.</b>
<b>Model name</b>	:	<b>SHM912</b>
<b>Variant Model name</b>	:	<b>BCP912, NBT912, GWS912, BCP910, SHP912</b>
<b>Test Device Serial No.:</b>	:	<b>Identical prototype</b>
<b>Rule Part(s)</b>	:	<b>FCC Part 15.247</b>
		<b>Subpart C ; ANSI C-63.4-2014 / ANSI C-63.10-2013</b>
<b>Frequency Range</b>	:	<b>2402 ~ 2480 MHz</b>
<b>RF power</b>	:	<b>Max -10.70 dBm – Conducted (Basic)</b> <b>Max -15.79 dBm – Conducted (EDR)</b>
<b>Data of issue</b>	:	<b>April 04, 2018</b>

This test report is issued under the authority of:

Yong-Cheol Wang, Manager

The test was supervised by:

Eun-hwan, Jung / Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

**NVLAP**<sup>®</sup>

NVLAP LAB Code.: 200723-0

## **TABLE OF CONTENTS**

1. GENERAL INFORMATION -----	3
2. INFORMATION ABOUT TEST ITEM -----	4
3. TEST REPORT -----	5
3.1 SUMMARY OF TESTS -----	5
3.2 FREQUENCY HOPPING SYSTEM REQUIREMENTS-----	6
3.3 TECHNICAL CHARACTERISTICS TEST -----	8
3.3.1 CARRIER FREQUENCY SEPARATION -----	8
3.3.2 NUMBER OF HOPPING FREQUENCIES -----	10
3.3.3 20 dB BANDWIDTH -----	12
3.3.4 TIME OF OCCUPANCY (Dwell Time) -----	19
3.3.5 TRANSMITTER OUTPUT POWER -----	24
3.3.6 BAND EDGE -----	28
3.3.7 CONDUCTED SPURIOUS EMISSIONS -----	32
3.3.8 RADIATED SPURIOUS EMISSIONS -----	37
 <b>APPENDIX</b>	
APPENDIX TEST EQUIPMENT USED FOR TESTS -----	59

## 1. General information

### 1-1 Test Performed

Company name : LTA Co., Ltd.  
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822  
 Web site : <http://www.ltalab.com>  
 E-mail : [chahn@ltalab.com](mailto:chahn@ltalab.com)  
 Telephone : +82-31-323-6008  
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

### 1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2018-09-30	ECT accredited Lab.
RRA	KOREA	KR0049	-	EMC accredited Lab.
FCC	U.S.A	649054	2019-04-13	FCC CAB
VCCI	JAPAN	C-4948,	2020-09-10	VCCI registration
VCCI	JAPAN	T-2416,	2020-09-10	VCCI registration
VCCI	JAPAN	R-4483(10 m),	2020-10-15	VCCI registration
VCCI	JAPAN	G-847	2018-12-13	VCCI registration
IC	CANADA	5799A-1	2019-11-07	IC filing
KOLAS	KOREA	NO.551	2021-08-20	KOLAS accredited Lab.

## 2. Information about test item

## 2-1 Client & Manufacturer

Company name : SEE CODE CO., LTD.  
Address : A-1107, 60, Haan-ro, Gwangmyeong-si, Gyeonggi-do, Korea  
Tel / Fax : TEL No : +82-70-8855-8300 / FAX No : +82-02-2083-2272

## 2-2 Equipment Under Test (EUT)

Trade name	:	PTT Headset
Model name	:	SHM912
Serial number	:	Identical prototype
Date of receipt	:	Jan 25, 2018
EUT condition	:	Pre-production, not damaged
Antenna type	:	Chip Antenna (Max Gain : 1.99 dBi)
Frequency Range	:	2402 ~ 2480MHz
RF output power	:	Max -10.70 dBm – Conducted (Basic) Max -15.79 dBm – Conducted (EDR)
Number of channels	:	79
Duty cycle	:	77.8%(Basic) , 65.0 % (EDR)
Channel spacing	:	1 MHz
Channel Access Protocol	:	Frequency Hopping Spread Spectrum (FHSS)
Type of Modulation	:	Basic Mode(GFSK), EDR Mode(Pi/4 DQPSK, 8DPSK)
Power Source	:	DC 3.7 V by battery
Firmware Version	:	V0.1

## 2-3 Tested frequency

Bluetooth	LOW	MID	HIGH
<b>Frequency (MHz) – Basic &amp; EDR</b>	2402	2441	2480

## **2-4 Ancillary Equipment**

Equipment	Model No.	Serial No.	Manufacturer
Notebook	CR720	MS-1736	MSI

### 3. Test Report

#### 3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	Carrier Frequency Separation	$\geq 2/3$ of 20dB BW	Conducted	C
15.247(a)	Number of Hopping Frequencies	$\geq 15$ channels		C
15.247(a)	20 dB Bandwidth 99% Bandwidth	–		C
15.247(a)	Dwell Time	$\leq 0.4$ seconds		C
15.247(b)	Transmitter Output Power	$\leq 1$ W for 1Mbps $\leq 125$ mW for 2,3Mbps		C
15.247(d)	Conducted Spurious emission	$> 20$ dBc		C
15.247(d)	Band Edge	$> 20$ dBc		C
15.249 / 15.209	Field Strength of Harmonics	$< 54$ dBuV (at 3m)	Radiated	C
15.109	Field Strength	–		C
15.207 /15.107	AC Conducted Emissions	EN 55022	Line Conducted	N/A
15.203	Antenna requirement	–	–	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: This product operates only with battery and does not operate during charging.

#### Note 1: Antenna Requirement

→ The SEE CODE CO.,LTD. FCC ID: **2AEXZSHM912** unit complies with the requirement of §15.203.

The antenna type is Chip antenna.

The sample was tested according to the following specification:

\*FCC Parts 15.247; ANSI C-63.4-2014;ANSI C-63.10-2013

\*FCC KDB Publication No. 558074 D01 v03r05

\*FCC TCB Workshop 2012, April

## 3.2 Frequency Hopping System Requirements

### 3.2.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.


(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

### 3.2.2 EUT Pseudorandom Frequency Hopping Sequence


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage, and the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones. Number of shift register stages: 9

Length of pseudo-random sequence:  $2^9 - 1 = 511$  bits

Longest sequence of zeros: 8 (non-inverted signal)



*Linear Feedback Shift Register for Generation of the PRBS sequence*



Each frequency used equally on the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

### 3.2.3 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

\*Example for a Bluetooth device using channel numbers would be : Chan 44, 35, 78, 03, 15, 21, 76, 40, 56, 13, 02, 19, 67, 39, 78, 20, 21, 64, 75 etc.

### 3.3 TECHNICAL CHARACTERISTIC TEST

#### 3.3.1 Carrier Frequency Separation

##### Procedure:

The test follows DA00-705. The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

##### The spectrum analyzer is set to:

Span = 2~3 MHz (wide enough to capture the peaks of two adjacent channels)

RBW = 10 kHz (1% of the span or more)      Sweep = auto

VBW = 10 kHz      Detector function = peak

Trace = max hold

##### Measurement Data:

Test Results	
Carrier Frequency Separation (MHz)	Result
<b>1.003 (Basic)</b>	Complies
<b>1.169 (EDR)</b>	Complies

- See next pages for actual measured spectrum plots.

##### Minimum Standard:

The EUT shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or two-thirds of 20 dB bandwidth of the hopping channel, whichever is greater.

##### Measurement Setup






Figure 1: Measurement setup for the carrier frequency separation

Carrier Frequency SeparationBasic ModeEDR Mode

### 3.3.2 Number of Hopping Frequencies

#### Procedure:

The test follows DA00-705. The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

To get higher resolution, four frequency ranges within the 2400 ~ 2483.5 MHz FH band were examined.

The spectrum analyzer is set to (Bluetooth):

Frequency range      Start = 2400.0 MHz,   Stop = 2483.5 MHz

RBW = 100 kHz (1% of the span or more)      Sweep = auto

VBW = 100 kHz (VBW  $\geq$  RBW)      Detector function = peak

Trace = max hold      Span > 40 MHz

#### Measurement Data : **Complies**

<b>Total number of Hopping Channels</b>	79 (Basic, EDR)
---	-----------------



- See next pages for actual measured spectrum plots.

#### Minimum Standard:

At least 15 channels

#### Measurement Setup

Same as the Chapter 3.3.1 (Figure 1)

Number of Hopping Frequencies (Basic)Number of Hopping Frequencies (EDR)

### 3.3.3 20 dB Bandwidth

#### Procedure:

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is ( as close as possible to ) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

#### The spectrum analyzer is set to (Bluetooth):

Center frequency = the highest, middle and the lowest channels

Span = 3 MHz (approximately 2 or 3 times of the 20 dB bandwidth)

RBW = 30 kHz

Sweep = auto

VBW = 30 kHz (VBW  $\geq$  RBW)

Detector function = peak

Trace = max hold

#### Measurement Data: Basic Mode

Frequency (MHz)	Channel No.	Test Results(MHz)	
		20dB Bandwidth	99% Bandwidth
2402	0	0.838	0.968
2441	39	0.838	0.959
2480	78	0.838	0.951

- See next pages for actual measured spectrum plots.

#### Measurement Data: EDR Mode

Frequency (MHz)	Channel No.	Test Results(MHz)	
		20dB Bandwidth	99% Bandwidth
2402	0	1.255	1.159
2441	39	1.259	1.164
2480	78	1.259	1.164



- See next pages for actual measured spectrum plots.



#### Minimum Standard:



N/A



#### Measurement Setup



Same as the Chapter 3.3.1 (Figure 1)



Channel 1 of Basic mode20 dB Bandwidth99% Bandwidth

Channel 40 of Basic mode20 dB Bandwidth99% Bandwidth

Channel 79 of Basic mode20 dB Bandwidth99% Bandwidth

Channel 1 of EDR mode20 dB Bandwidth99% Bandwidth

**Channel 40 of EDR mode****20 dB Bandwidth****99% Bandwidth**

**Channel 79 of EDR mode****20 dB Bandwidth****99% Bandwidth**

### 3.3.4 Time of Occupancy (Dwell Time)

#### Procedure:

The test follows DA00-705. The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to :

Center frequency = 2441 MHz

Span = zero

RBW = 1 MHz

VBW = 1 MHz (VBW  $\geq$  RBW)

Trace = max hold

Detector function = peak

#### Measurement Data (Basic,EDR):

Mode	Number of transmission in a 31.6s ( 79Hopping*0.4)	Length of Transmission Time (msec)	Result (msec)	Limit (msec)
DH1	31(Times / 3sec) *10.533 = 326.523	0.449	146.61	400
DH3	15(Times / 3sec) *10.533 = 158.00	1.696	267.97	400
DH5	10(Times / 3sec) *10.533 = 105.33	2.978	313.67	400
3-DH5	10(Times / 3sec) *10.533 = 105.33	2.964	312.20	400



- See next pages for actual measured spectrum plots.
- dwell time = {(number of hopping per second / number of slot ) x duration time per channel} x 0.4 ms



#### Minimum Standard:



0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed



#### Measurement Setup

Same as the Chapter 3.3.1 (Figure 1)

**DH1 at Basic mode**

**DH3 at Basic mode**

DH5 at Basic mode

**3-DH5 at EDR mode**

### 3.3.5 Transmitter Output Power

### Procedure:

The test follows DA00-705. The peak output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

**The spectrum analyzer is set to :**

Center frequency = the highest, middle and the lowest channels

Span = 10 MHz (approximately 5 times of the 20 dB bandwidth)

RBW = 3 MHz (greater than the 20 dB bandwidth of the emission being measured)

VBW = 3 MHz (VBW  $\geq$  RBW)

Detector function = peak

## Measurement Data : Basic Mode

Frequency (MHz)	Ch.	Test Results		
		dBm	mW	Result
2402	1	<b>-10.70</b>	<b>0.085</b>	Complies
2441	40	<b>-12.09</b>	<b>0.062</b>	Complies
2480	79	<b>-14.20</b>	<b>0.038</b>	Complies

## Measurement Data : EDR Mode

Frequency (MHz)	Ch.	Test Results		
		dBm	mW	Result
2402	1	<b>-15.79</b>	<b>0.026</b>	Complies
2441	40	<b>-16.93</b>	<b>0.020</b>	Complies
2480	79	<b>-18.93</b>	<b>0.013</b>	Complies


- See next pages for actual measured spectrum plots.

<b>Minimum Standard:</b>	For frequency hopping systems with at least 75 non-overlapping hopping channels: 1 watt. For all other frequency hopping systems: 0.125 W.
--------------------------	--


## Measurement Setup

Same as the Chapter 3.3.1 (Figure 1)

**Channel 1**  
**Basic mode**




**Channel 40**  
**Basic mode**



## Channel 79

### Basic mode




## Channel 1

### EDR mode



### Channel 40 EDR mode



### Channel 79 EDR mode



### 3.3.6 Band Edge

### Procedure:

The bandwidth at 20 dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 10~30 MHz      Detector function = peak

Trace = max hold      Sweep = auto

### Measurement Data: **Complies**



- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.



---

<b>Minimum Standard:</b>	> 20 dBc
--------------------------	----------

## Measurement Setup

Same as the Chapter 3.3.1 (Figure 1)

**Band Edge (Basic)****Lower edge****Upper edge**

Band Edge (EDR)Lower edgeUpper edge

**Radiated Band edges in the restricted band 2310-2390 MHz measurement (Basic)**

Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction		Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]					
				Factor											
	AV	Peak		Antenna	Amp. Gain+CableLoss										
2324.5	33.91	43.12	V	28.08	22.9	54.0	74.0	39.09	48.3	14.91	25.7				
2316.7	32.58	42.05	V	28.09	22.9	54.0	74.0	37.77	47.24	16.23	26.76				
2322.4	32.18	41.93	V	28.09	22.9	54.0	74.0	37.37	47.12	16.63	26.88				

**Radiated Band edges in the restricted band 2483.5-2500 MHz measurement**

Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction		Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]			
				Factor									
	AV	Peak		Antenna	Amp. Gain+CableLoss					[MHz]			
2485.5	34.07	44.80	V	27.88	22.9	54.0	74.0	39.05	49.78	14.95	24.22		
2485.8	33.95	44.25	V	27.89	22.9	54.0	74.0	38.94	49.24	15.06	24.76		
2486.4	33.91	43.89	V	27.89	22.9	54.0	74.0	38.90	48.88	15.10	25.12		

**Radiated Band edges in the restricted band 2310-2390 MHz measurement (EDR)**

Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction		Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]					
				Factor											
	AV	Peak		Antenna	Amp. Gain+CableLoss										
2378.3	36.51	45.29	V	28.08	22.9	54.0	74.0	41.69	50.47	12.31	23.53				
2377.9	35.74	45.83	V	28.09	22.9	54.0	74.0	40.93	51.02	13.07	22.98				
2380.5	35.25	45.32	V	28.09	22.9	54.0	74.0	40.44	50.51	13.56	23.49				

**Radiated Band edges in the restricted band 2483.5-2500 MHz measurement**

Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction		Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]					
				Factor											
	AV	Peak		Antenna	Amp. Gain+CableLoss										
2485.5	37.05	46.28	V	27.88	22.9	54.0	74.0	42.03	51.26	11.97	22.74				
2485.8	36.73	46.98	V	27.89	22.9	54.0	74.0	41.72	51.97	12.28	22.03				
2486.4	36.81	46.25	V	27.89	22.9	54.0	74.0	41.80	51.24	12.20	22.76				

**Note : This EUT was tested in 3 orthogonal positions and the worst-case data was presented.**

### 3.3.7 Conducted Spurious Emissions

### **Procedure:**

The test follows DA00-705. The conducted spurious emissions were measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, set the marker on the peak of any spurious emission recorded.

The spectrum analyzer is set to:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions

RBW = 100 kHz Sweep = auto

VBW = 100 kHz      Detector function = peak

Trace = max hold

### Measurement Data: Complies



- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.

---


<b>Minimum Standard:</b>	> 20 dBc
--------------------------	----------



## Measurement Setup

Same as the Chapter 3.3.1 (Figure 1)


Unwanted Emission – Low channel (Basic)Frequency Range = 30 MHz ~ 26.5 GHzUnwanted Emission – Middle channelFrequency Range = 30 MHz ~ 26.5 GHz

Unwanted Emission – High channel  
Frequency Range = 30 MHz ~ 26.5 GHz



Unwanted Emission – Low channel (EDR)Frequency Range = 30 MHz ~ 26.5 GHzUnwanted Emission – Middle channelFrequency Range = 30 MHz ~ 26.5 GHz

**Unwanted Emission – High channel**  
**Frequency Range = 30 MHz ~ 26.5 GHz**



### 3.3.8 Radiated Spurious Emissions

#### Procedure:

Radiated emissions from the EUT were measured according to the dictates of DA00-705. The EUT was placed on a 0.8 m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

- (a) In the frequency range of 9 kHz to 30 MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 3 m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- (b) In the frequency range above 30 MHz, Bi-Log Test Antenna (30 MHz to 1 GHz) and Horn Test Antenna (above 1 GHz) are used. Test Antenna is 3 m away from the EUT. Test Antenna height is carried from 1 m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 9 kHz ~ 10<sup>th</sup> harmonic.

RBW = 120 kHz ( 30 MHz ~ 1 GHz)

VBW  $\geq$  RBW

= 1 MHz ( 1 GHz ~ 10<sup>th</sup> harmonic )


Span = 100 MHz



Detector function = peak

Trace = max hold

Sweep = auto

**below 30 MHz**



**below 1 GHz (30 MHz to 1 GHz)****above 1 GHz****Measurement Data: Complies**

- See next pages for actual measured data.
- No other emissions were detected at a level greater than 20 dB below limit include from 9 kHz to 30 MHz.

**Minimum Standard: FCC Part 15.209(a)**

Frequency (MHz)	Limit (uV/m) @ 3m
0.009 ~ 0.490	2400/F(kHz) (@ 300m)
0.490 ~ 1.705	24000/F(kHz) (@ 30m)
1.705 ~ 30	30(@ 30m)
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

\*\* Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

**Measurement Data : Basic Mode (BDR)**

Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor		D.C.F	Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
	AV / Peak			Antenna + (Cable-Amp.Gain)			AV/Peak		AV/Peak		AV / Peak	
10575.54	21.01	32.68	H		26.77	-30.16	54.0	74.0	17.62	29.29	36.38	44.71
7497.66	21.05	33.10	H		26.17	-30.16	54.0	74.0	17.06	29.11	36.96	44.89
10215.02	22.03	32.32	H		26.19	-30.16	54.0	74.0	18.06	28.35	35.94	45.65

- No other emissions were detected at a level greater than 20dB below limit.

- D.C.F ( Duty Cycle Correction Factor) =  $20\log(\text{The worst Case DWELL Time}/100\text{ms})$

$$= 20\log(3.101\text{ms}/100\text{ms}) = -30.16$$

**Measurement Data : EDR Mode**

Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor		D.C.F	Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
	AV / Peak			Antenna + (Cable-Amp.Gain)			AV/Peak		AV/Peak		AV / Peak	
10484.23	21.16	33.27	V		26.57	-30.60	54.0	74.0	17.13	29.24	36.87	44.76
10606.15	21.52	31.23	H		26.85	-30.60	54.0	74.0	17.77	27.48	36.23	46.52
18450.74	22.03	36.05	H		24.96	-30.60	54.0	74.0	16.39	30.41	37.61	43.59

- No other emissions were detected at a level greater than 20dB below limit.

- D.C.F ( Duty Cycle Correction Factor) =  $20\log(\text{The worst Case DWELL Time}/100\text{ms})$

$$= 20\log(2.949\text{ms}/100\text{ms}) = -30.60$$

Radiated Emissions – Basic mode (below 1GHz)


4, Songjuro 236Beon-gil, yanggi-myeon,  
Yongin-si, Gyeonggi-do, Korea  
Tel : +82-31-3236008,9  
Fax : +82-31-3236010  
www.ltalab.com

EUT/Model No.: SHM912

Temp/Humi: 25 / 49

Test Mode : BT BDR\_L

Tested by: JUNG E H



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	deg	
37.76	34.59	-14.43	20.16	40.00	19.84	135	238	HORIZONTAL
907.85	22.69	1.15	23.84	46.00	22.16	203	212	HORIZONTAL
945.68	21.20	2.36	23.56	46.00	22.44	211	197	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



4, Songiuro 236Beon-gil, yanggi-myeon,  
Yongin-si, Gyeonggi-do, Korea  
Tel : +82-31-3236008,9  
Fax : +82-31-3236010  
www.ltalab.com

EUT/Model No.: SHM912

Temp/Humi: 25 / 49


Test Mode : BT BDR\_L

Tested by: JUNG E H

Data: 669

File: C:\Program Files (x86)\e3\1706-1.EM6 (1422)

Date: 2018-04-16



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	deg	
37.76	45.19	-14.43	30.76	40.00	9.24	102	302	VERTICAL
41.64	35.70	-14.09	21.61	40.00	18.39	115	321	VERTICAL
500.45	33.47	-6.62	26.85	46.00	19.15	152	299	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



4, Songiuro 236Beon-gil, yanggi-myeon,  
Yongin-si, Gyeonggi-do, Korea  
Tel : +82-31-3236008,9  
Fax : +82-31-3236010  
www.ltalab.com

EUT/Model No.: SHM912

Temp/Humi: 25 / 49


Test Mode : BT BDR\_M

Tested by: JUNG E H

Data: 668

File: C:\Program Files (x86)\e3\1706-1.EM6 (1422)

Date: 2018-04-16



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	deg	
37.76	34.68	-14.43	20.25	40.00	19.75	130	240	HORIZONTAL
907.85	23.69	1.15	24.84	46.00	21.16	200	210	HORIZONTAL
945.68	23.30	2.36	25.66	46.00	20.34	210	200	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



4, Songiuro 236Beon-gil, yanggi-myeon,  
Yongin-si, Gyeonggi-do, Korea  
Tel : +82-31-3236008,9  
Fax : +82-31-3236010  
www.ltalab.com

EUT/Model No.: SHM912

Temp/Humi: 25 / 49


Test Mode : BT BDR\_M

Tested by: JUNG E H

Data: 669

File: C:\Program Files (x86)\e3\1706-1.EM6 (1422)

Date: 2018-04-16



Freq MHz	Reading dBuV	C.F dB	Result dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
								QP
37.76	45.69	-14.43	31.26	40.00	8.74	105	300	VERTICAL
41.64	35.70	-14.09	21.61	40.00	18.39	115	321	VERTICAL
500.45	33.87	-6.62	27.25	46.00	18.75	155	300	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



4, Songiuro 236Beon-gil, yanggi-myeon,  
Yongin-si, Gyeonggi-do, Korea  
Tel : +82-31-3236008,9  
Fax : +82-31-3236010  
www.ltalab.com

EUT/Model No.: SHM912

Temp/Humi: 25 / 49


Test Mode : BT BDR\_H

Tested by: JUNG E H

Data: 668

File: C:\Program Files (x86)\e3\1706-1.EM6 (1422)

Date: 2018-04-16



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	deg	
37.76	39.68	-14.43	25.25	40.00	14.75	137	240	HORIZONTAL
907.85	24.09	1.15	25.24	46.00	20.76	200	210	HORIZONTAL
945.68	28.30	2.36	30.66	46.00	15.34	215	207	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



4, Songiuro 236Beon-gil, yanggi-myeon,  
Yongin-si, Gyeonggi-do, Korea  
Tel : +82-31-3236008,9  
Fax : +82-31-3236010  
www.ltalab.com

EUT/Model No.: SHM912

Temp/Humi: 25 / 49


Test Mode : BT BDR\_H

Tested by: JUNG E H

Data: 669

File: C:\Program Files (x86)\e3\1706-1.EM6 (1422)

Date: 2018-04-16



Freq MHz	Reading dBuV	C.F dB	Result dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
								QP
37.76	41.69	-14.43	27.26	40.00	12.74	110	298	VERTICAL
41.64	39.40	-14.09	25.31	40.00	14.69	120	302	VERTICAL
500.45	33.87	-6.62	27.25	46.00	18.75	155	300	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions – Basic mode (Above 1GHz)

EMI I Chamber of LTA CO.,LTD.  
4, Songjuro236Beon-gil, Yangji-myeon,  
Yongin-si, Gyeonggi-do, Korea Autho. by NVLAP  
Tel:+82-31-3236008,9 www.ltalab.com  
Fax:+82-31-3236010


EUT/Model No.: SHM012

Test Mode: BT BDR\_L

Tested by : JUNG E H

Temp/Humi: 22 / 62

Data: 9 File: D:\LTA\_e3\le3\_backup\1GHz 미상\2018\CH1\_ABOVE 1GHz\_1803-1.EMI (20)  
Level (dBuV/m) Date: 2018-04-17



Freq MHz	Reading dBuV	C.F dB	Result PK dBuV/m	Limit dBuV/m	Margin dB	Polarity
						PK dBuV/m
1 1924.24	42.12	1.10	43.22	74.00	30.78	HORIZONTAL
2 1924.24	39.75	1.10	40.85	54.00	13.15	HORIZONTAL
3 2705.49	33.92	5.38	39.30	54.00	14.70	HORIZONTAL
4 2705.49	39.82	5.38	45.20	74.00	28.80	HORIZONTAL
5 2915.35	35.50	6.88	42.38	74.00	31.62	VERTICAL
6 2915.35	32.87	6.88	39.75	54.00	14.25	VERTICAL
7 4844.12	22.79	17.94	40.73	54.00	13.27	HORIZONTAL
8 4844.12	27.06	17.94	45.00	74.00	29.00	HORIZONTAL
9 5505.80	19.21	19.61	38.82	54.00	15.18	VERTICAL
10 5505.80	21.37	19.61	40.98	74.00	33.02	VERTICAL
11 5784.05	24.25	20.49	44.74	54.00	9.26	VERTICAL
12 5784.05	26.23	20.49	46.72	74.00	27.28	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain  
Blue : Vertical      Black : Horizontal



EMI I Chamber of LTA CO.,LTD.  
4, Songjuro236Beon-gil, Yangji-myeon,  
Yongin-si, Gyeonggi-do, Korea Autho. by NVLAP  
Tel :+82-31-3236008,9 www.ltalab.com  
Fax :+82-31-3236010


EUT/Model No.: SHM912

Test Mode: BT BDR\_M

Tested by : JUNG E H

Temp/Humi: 22 / 62

Data: 9 File: D:\LTA\_e3\Backup\1GHz 미상\2018\CH1\_ABOVE 1GHz\_1803-1.EMI (20)  
Level (dBuV/m) Date: 2018-04-17



Freq MHz	Reading dBuV	C.F dB	Result PK dBuV/m	Limit dBuV/m	Margin dB	Polarity
						Horizontal
1 1924.24	42.12	1.10	43.22	74.00	30.78	HORIZONTAL
2 1924.24	39.75	1.10	40.85	54.00	13.15	HORIZONTAL
3 3048.12	34.86	8.36	43.22	74.00	30.78	VERTICAL
4 3048.12	33.31	8.36	41.67	54.00	12.33	VERTICAL
5 4844.12	26.74	17.94	44.68	74.00	29.32	HORIZONTAL
6 4844.12	24.88	17.94	42.82	54.00	11.18	HORIZONTAL
7 5505.80	19.21	19.61	38.82	54.00	15.18	VERTICAL
8 5505.80	21.37	19.61	40.98	74.00	33.02	VERTICAL
9 5784.05	26.23	20.49	46.72	74.00	27.28	VERTICAL
10 5784.05	24.25	20.49	44.74	54.00	9.26	VERTICAL
11 7002.05	21.88	24.44	46.32	54.00	7.68	HORIZONTAL
12 7002.05	25.78	24.44	50.22	74.00	23.78	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain  
Blue : Vertical      Black : Horizontal



EMI I Chamber of LTA CO.,LTD.  
4, Songjuro236Beon-gil, Yangji-myeon,  
Yongin-si, Gyeonggi-do, Korea Autho. by NVLAP  
Tel :+82-31-3236008,9 www.ltalab.com  
Fax :+82-31-3236010


EUT/Model No.: SHM012

Test Mode: BT BDR\_H

Tested by : JUNG E H

Temp/Humi: 22 / 62

Data: 9 File: D:\LTA\_e3\Backup\1GHz 미상\2018\CH1\_ABOVE 1GHz\_1803-1.EMI (20)  
Level (dBuV/m) Date: 2018-04-17



Freq MHz	Reading dBuV	C.F dB	Result PK		Margin dB	Polarity
			dBuV/m	dBuV/m		
1 2004.08	38.44	1.58	40.02	74.00	33.98	HORIZONTAL
2 2004.08	36.35	1.58	37.93	54.00	16.07	HORIZONTAL
3 2705.49	27.42	5.38	32.80	54.00	21.20	HORIZONTAL
4 2705.49	30.82	5.38	36.20	74.00	37.80	HORIZONTAL
5 2915.35	35.50	6.88	42.38	74.00	31.62	VERTICAL
6 2915.35	32.87	6.88	39.75	54.00	14.25	VERTICAL
7 4844.12	22.79	17.94	40.73	54.00	13.27	HORIZONTAL
8 4844.12	27.06	17.94	45.00	74.00	29.00	HORIZONTAL
9 5505.80	19.21	19.61	38.82	54.00	15.18	VERTICAL
10 5505.80	21.37	19.61	40.98	74.00	33.02	VERTICAL
11 5784.05	21.15	20.49	41.64	54.00	12.36	VERTICAL
12 5784.05	23.23	20.49	43.72	74.00	30.28	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain  
Blue : Vertical      Black : Horizontal

Radiated Emissions – EDR mode (below 1GHz)


4, Songjuro 236Beon-gil, yanggi-myeon,  
Yongin-si, Gyeonggi-do, Korea  
Tel : +82-31-3236008,9  
Fax : +82-31-3236010  
www.ltalab.com

EUT/Model No.: SHM912

Temp/Humi: 25 / 49

Test Mode : BT EDR\_L

Tested by: JUNG E H



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	deg	
37.76	34.49	-14.43	20.06	40.00	19.94	205	79	HORIZONTAL
907.85	23.69	1.15	24.84	46.00	21.16	265	85	HORIZONTAL
945.68	22.25	2.36	24.61	46.00	21.39	201	68	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



4, Songjuro 236Beon-gil, yanggi-myeon,  
Yongin-si, Gyeonggi-do, Korea  
Tel : +82-31-3236008,9  
Fax : +82-31-3236010  
www.ltalab.com

EUT/Model No.: SHM912

Temp/Humi: 25 / 49


Test Mode : BT EDR\_L

Tested by: JUNG E H

Data: 671

File: C:\Program Files (x86)\e3\1706-1.EM6 (1422)

Date: 2018-04-19



Freq MHz	Reading dBuV	C.F dB	Result dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
								QP
37.76	45.19	-14.43	30.76	40.00	9.24	172	215	VERTICAL
41.64	35.75	-14.09	21.66	40.00	18.34	117	205	VERTICAL
500.45	33.92	-6.62	27.30	46.00	18.70	168	203	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



4, Songjuro 236Beon-gil, yanggi-myeon,  
Yongin-si, Gyeonggi-do, Korea  
Tel : +82-31-3236008,9  
Fax : +82-31-3236010  
www.ltalab.com

EUT/Model No.: SHM912

Temp/Humi: 25 / 49


Test Mode : BT EDR\_M

Tested by: JUNG E H

Data: 668

File: C:\Program Files (x86)\e3\1706-1.EM6 (1422)

Date: 2018-04-19



Freq MHz	Reading dBuV	C.F dB	Result dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
								QP
37.76	39.38	-14.43	24.95	40.00	15.05	137	240	HORIZONTAL
907.85	24.39	1.15	25.54	46.00	20.46	200	210	HORIZONTAL
945.68	28.30	2.36	30.66	46.00	15.34	215	207	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



4, Songjuro 236Beon-gil, yanggi-myeon,  
Yongin-si, Gyeonggi-do, Korea  
Tel : +82-31-3236008,9  
Fax : +82-31-3236010  
www.ltalab.com

EUT/Model No.: SHM912

Temp/Humi: 25 / 49


Test Mode : BT EDR\_M

Tested by: JUNG E H

Data: 670

File: C:\Program Files (x86)\e3\1706-1.EM6 (1422)

Date: 2018-04-19



Freq MHz	Reading dBuV	C.F dB	Result dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
								QP
37.76	46.25	-14.43	31.82	40.00	8.18	100	360	VERTICAL
41.64	38.75	-14.09	24.66	40.00	15.34	100	360	VERTICAL
500.45	36.93	-6.62	30.31	46.00	15.69	100	360	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



4, Songjuro 236Beon-gil, yanggi-myeon,  
Yongin-si, Gyeonggi-do, Korea  
Tel : +82-31-3236008,9  
Fax : +82-31-3236010  
www.ltalab.com

EUT/Model No.: SHM912

Temp/Humi: 20 / 41


Test Mode : BT EDR(H)

Tested by: E H JUNG

Data: 641

File: C:\Program Files (x86)\e3\1804-1.EM6 (1474)

Date: 2018-04-19



Freq MHz	Reading dBuV	C.F dB	Result dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
								QP
876.81	24.27	0.14	24.41	46.00	21.59	380	117	HORIZONTAL
879.72	25.40	0.19	25.59	46.00	20.41	390	270	HORIZONTAL
881.66	26.57	0.21	26.78	46.00	19.22	370	300	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



4, Songjuro 236Beon-gil, yanggi-myeon,  
Yongin-si, Gyeonggi-do, Korea  
Tel : +82-31-3236008,9  
Fax : +82-31-3236010  
www.ltalab.com

EUT/Model No.: SHM912

Temp/Humi: 20 / 41


Test Mode : BT EDR(H)

Tested by: E H JUNG

Data: 642

File: C:\Program Files (x86)\e3\1804-1.EM6 (1474)

Date: 2018-04-19



Freq MHz	Reading dBuV	C.F dB	Result dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
								QP
846.74	30.14	-0.27	29.87	46.00	16.13	105	130	VERTICAL
879.72	27.60	0.19	27.79	46.00	18.21	100	200	VERTICAL
888.45	27.34	0.32	27.66	46.00	18.34	100	260	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions – EDR mode (Above 1GHz)

EMI I Chamber of LTA CO.,LTD.  
4, Songjuro236Beon-gil, Yangji-myeon,  
Yongin-si, Gyeonggi-do, Korea Autho. by NVLAP  
Tel:+82-31-3236008,9 www.ltalab.com  
Fax:+82-31-3236010


EUT/Model No.: SHM012

Test Mode: BT EDR\_L

Tested by : JUNG E H

Temp/Humi: 22 / 62

Data: 10 File: D:\LTA\_e3\le3\_backup\1GHz 대상\2018\CH1\_ABOVE 1GHz\_1803-1.EMI (20)  
Level (dBuV/m) Date: 2018-04-17



Freq MHz	Reading dBuV	C.F dB	Result PK dBuV/m	Limit dBuV/m	Margin dB	Polarity
						Horizontal
1 2765.55	37.41	5.62	43.03	74.00	30.97	HORIZONTAL
2 2765.55	33.18	5.62	38.80	54.00	15.20	HORIZONTAL
3 3372.27	32.55	10.86	43.41	74.00	30.59	VERTICAL
4 3372.27	28.07	10.86	38.93	54.00	15.07	VERTICAL
5 4850.22	29.50	17.96	47.46	74.00	26.54	HORIZONTAL
6 4850.22	25.88	17.96	43.84	54.00	10.16	HORIZONTAL
7 5547.10	23.87	19.79	43.66	74.00	30.34	VERTICAL
8 5547.10	21.14	19.79	40.93	54.00	13.07	VERTICAL
9 5843.76	25.19	20.84	46.03	74.00	27.97	VERTICAL
10 5843.76	21.19	20.84	42.03	54.00	11.97	VERTICAL
11 6107.44	24.92	22.07	46.99	74.00	27.01	HORIZONTAL
12 6107.44	20.78	22.07	42.85	54.00	11.15	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain  
Blue : Vertical      Black : Horizontal



EMI I Chamber of LTA CO.,LTD.  
4, Songjuro236Beon-gil, Yangji-myeon,  
Yongin-si, Gyeonggi-do, Korea Autho. by NVLAP  
Tel :+82-31-3236008,9 www.ltalab.com  
Fax :+82-31-3236010


EUT/Model No.: SHM012

Test Mode: BT EDR\_M

Tested by : JUNG E H

Temp/Humi: 22 / 62

Data: 10 File: D:\LTA\_e3\Backup\1GHz 미상\2018\CH1\_ABOVE 1GHz\_1803-1.EMI (20)  
Level (dBuV/m) Date: 2018-04-17



Freq MHz	Reading dBuV	C.F dB	Result PK dBuV/m	Limit dBuV/m	Margin dB	Polarity
						Horizontal
1 2765.55	37.41	5.62	43.03	74.00	30.97	HORIZONTAL
2 2765.55	33.18	5.62	38.80	54.00	15.20	HORIZONTAL
3 3372.27	32.55	10.86	43.41	74.00	30.59	VERTICAL
4 3372.27	28.07	10.86	38.93	54.00	15.07	VERTICAL
5 4850.22	29.50	17.96	47.46	74.00	26.54	HORIZONTAL
6 4850.22	25.88	17.96	43.84	54.00	10.16	HORIZONTAL
7 5547.10	23.87	19.79	43.66	74.00	30.34	VERTICAL
8 5547.10	21.14	19.79	40.93	54.00	13.07	VERTICAL
9 5843.76	25.19	20.84	46.03	74.00	27.97	VERTICAL
10 5843.76	21.19	20.84	42.03	54.00	11.97	VERTICAL
11 6107.44	24.92	22.07	46.99	74.00	27.01	HORIZONTAL
12 6107.44	20.78	22.07	42.85	54.00	11.15	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain  
Blue : Vertical      Black : Horizontal



EMI I Chamber of LTA CO.,LTD.  
4, Songjuro236Beon-gil, Yangji-myeon,  
Yongin-si, Gyeonggi-do, Korea Autho. by NVLAP  
Tel :+82-31-3236008,9 www.ltalab.com  
Fax :+82-31-3236010


EUT/Model No.: SHM012

Test Mode: BT EDR\_H

Tested by : JUNG E H

Temp/Humi: 22 / 62

Data: 10 File: D:\LTA\_e3\Backup\1GHz 미상\2018\CH1\_ABOVE 1GHz\_1803-1.EMI (20)  
Level (dBuV/m) Date: 2018-04-17



Freq MHz	Reading dBuV	C.F dB	Result PK dBuV/m	Limit dBuV/m	Margin dB	Polarity
						Horizontal
1 2765.55	37.41	5.62	43.03	74.00	30.97	HORIZONTAL
2 2765.55	33.18	5.62	38.80	54.00	15.20	HORIZONTAL
3 3372.27	32.55	10.86	43.41	74.00	30.59	VERTICAL
4 3372.27	28.07	10.86	38.93	54.00	15.07	VERTICAL
5 4850.22	25.30	17.96	43.26	74.00	30.74	HORIZONTAL
6 4850.22	23.15	17.96	41.11	54.00	12.89	HORIZONTAL
7 5547.10	23.87	19.79	43.66	74.00	30.34	VERTICAL
8 5547.10	21.14	19.79	40.93	54.00	13.07	VERTICAL
9 5843.76	25.19	20.84	46.03	74.00	27.97	VERTICAL
10 5843.76	21.19	20.84	42.03	54.00	11.97	VERTICAL
11 5974.20	24.19	21.75	45.94	74.00	28.06	HORIZONTAL
12 5974.20	20.20	21.75	41.95	54.00	12.05	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain  
Blue : Vertical      Black : Horizontal

### 3.3.9 AC Conducted Emissions

#### Procedure:

AC power line conducted emissions from the EUT were measured according to the dictates of ANSI C63.4:2003.

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

#### Measurement Data: N/A

#### Minimum Standard: FCC Part 15.207(a)/EN 55022

Frequency Range	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

\* Note: This product operates only with battery and does not operate during charging.

## APPENDIX

## TEST EQUIPMENT USED FOR TESTS

Use	Description	Model No.	Serial No.	Manufacturer	Interval	Last Cal. Date
1	Signal Analyzer (9 kHz ~ 30 GHz)	FSV30	100757	R&S	1 year	2017-09-15
2	SYNTHESIZED CW GENERATOR	83711B	US34490456	HP	1 year	2018-03-19
3	Attenuator (3 dB)	8491A	37822	HP	1 year	2017-09-07
4	Attenuator (10 dB)	8491A	63196	HP	1 year	2017-09-07
5	EMI Test Receiver (~7 GHz)	ESCI7	100722	R&S	1 year	2017-09-07
6	RF Amplifier (~1.3 GHz)	8447D OPT 010	2944A07684	HP	1 year	2017-09-07
7	RF Amplifier (1~26.5 GHz)	8449B	3008A02126	HP	1 year	2018-03-21
8	■ Horn Antenna (1~18 GHz)	3115	00114105	ETS	2 year	2017-09-26
9	DRG Horn (Small)	3116B	81109	ETS-Lindgren	2 year	2016-05-03
10	DRG Horn (Small)	3116B	133350	ETS-Lindgren	2 year	2016-05-03
11	■ TRILOG Antenna	VULB 9160	9160-3237	SCHWARZBECK	2 year	2017-04-17
12	Temp.Humidity Data Logger	SK-L200TH II A	00801	SATO	1 year	2017-11-23
13	■ DC Power Supply	6674A	3637A01657	Agilent	-	-
14	AC Power Supply	HK-80	LR001	DAERIMTECH	-	-
15	■ Power Meter	EPM-441A	GB32481702	HP	1 year	2018-03-20
16	■ Power Sensor	8481A	3318A94972	HP	1 year	2017-12-26
17	Audio Analyzer	8903B	3729A18901	HP	1 year	2017-09-07
18	Modulation Analyzer	8901B	3749A05878	HP	1 year	2017-09-07
19	■ TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	JinYoung Tech	1 year	2017-09-07
20	Stop Watch	HS-3	812Q08R	CASIO	2 year	2018-03-21
21	LISN	KNW-407	8-1430-1	Kyoritsu	1 year	2017-09-07
22	Two-Lime V-Network	ESH3-Z5	893045/017	R&S	1 year	2018-03-20
23	Highpass Filter	WHKX1.5/15G-10SS	74	Wainwright Instruments	1 year	2018-03-19
24	Highpass Filter	WHKX3.0/18G-10SS	118	Wainwright Instruments	1 year	2018-03-19
25	OSP120 BASE UNIT	OSP120	101230	R&S	1 year	2018-03-21
26	■ Signal Generator(100 kHz ~ 40 GHz)	SMB100A	177621	R&S	1 year	2018-03-20
27	Vector Signal Generator(9kHz ~ 6 GHz)	SMBV100A	255081	R&S	1 year	2018-03-20
28	■ Signal Analyzer (10 Hz ~ 40 GHz)	FSV40	101367	R&S	1 year	2018-03-20