HB6233 英语说明书 (Hellobaby)

说明书为折叠式 尺寸: 540*120MM 材质: 100g双胶纸 (彩色)

版本: V1.0 类型: 环保

版本	修改内容	日期
Ver: 1.0	文件首发。	2022/02/21

设计	审核	审批
王勇		
2022/02/21		

- 540.00 mm

HelloBaby[®]

User Manual

2.4GHz Digital Wireless Video Baby Monitor



Model: HB6233

Thank you for purchasing the HB6233 Rahy Monitor. With our haby monitor, you could se

PLEASE MAKE SURE THE FOLLOWING INCLUDED IN YOUR PACKAGE

Parent unit x 1 Camera unit x 1
User manual x 1 Wall-mounting kit x 1

1. SAFETY INSTRUCTIOINS

CAUTION: Keep the device away from children. Strangulation Hazard: Children have STRANGLED in cords. Keep this cord out of the reach children (more than 3ft (0.9m) away). Never use extension cords with AC Adapters. Only us

assemble the product.

Read and keep to instructions: All the safety and operating in structions should be read
before the video baby monitor is operated. This product cannot replace responsible adu

DO NOT list in the appliance if the cord or pulse is damaged. If you tably monitor is not operating properly or has suffered any damage, constant "Videotitime" service center to operating properly or has suffered any damage, constant "Videotitime" service center to operating properly or has suffered any damage, constant "Videotitime" service center to the constant of the constant


S. GETTING STARTED

S 2 THEN ON THE PARENT HAIT-

5.3 INFRARED NIGHT VISION (AUTOMATIC)

The infrared night vision function allows the camera to pick up images in dark or low light conditions. In this mode, only black and white images will be displayed on the monitor, the optimum image lie in where abby unit is 6ft (2m) away from object. The camera is in night vision mode, the icon
will be displayed on the top of screen.





6. 3 BABY UNIT OVERVIEW: 0



short press the power ⊕ key to turn on / off the screen.
7.2 UP ▲ KEY

Press once to tilt the camera up by one step. Press and hold to tilt continuously.
7.3 DOWN ▼ KEY

7.5 RIGHT > KFY

7.6.CAMERA VIEW/SCAN
Press scan [®]Ex by to view/scan camera; during scan mode, the scan icon [®]Ex will be
displayed on the top of screen. Each camera video will be stay on the LCD around 10
sconds then change to next camera;
7.7.DIGITAL 200M
Press and 100M the [®]Ex key around 2 seconds to operate zoom in/ out;

△WARNING



Strangulation Hazard: Children have STRANGLED in cords. Keep this cord out of the reach of children (more than 3 ft (0.9 m) away). Do not remove this tag.

△ AVERTISSEMENT

DANGER D'ÉTRANGLEMENT: Des enfants se sont ÉTRANGLÉS avec des cordons électriques. Garde le cordonélectrique hors de la portée des enfants(à plus de 0.9m/3 pi du lit d'enfant). Ne pas enlever cette étiquette.



Note: Camera icon with """ means it is well registered. You should select and pair with the

- camer is non-without."* sign.

 1.1 Ano DCAMED.

 1.1 Press the MENUL® key then the menu will pop un;

 2. Press the "Akyo a"P key until the camer a load.

 1. Press the "key as "P key under dra camer;

 3. Press 10.® ley to select syour devired camers;

 3. Press 10.® ley to not ler into sub-menu;

 4. Press 1. Key of "keys colect. ADCAM (2011) then press 0.0° (20 key;

 5. When the lean (3. displayed on the LCD screen, press the ARII button on the back of
- camera;
 6. Once paired, "

 " appears on the LCD screen.
- 8. Uties pursu.

 1. 10Est Evolution steps.

 1. 10Est Evolution steps.

 1. 1ress the MRNII ②key and the menu will pop up:

 2. Press the MRNII ②key and the menu will pop up:

 1. ress the MRNII ②key and the menu will pop up:

 1. ress the MRNII ②key and the menu will pop up:

 1. ress the MRNII ②key and the menu will pop up:

 1. ress the MRNII ②key in the will pop up:

 1. ress the MRNII ②key in the will pop up:

 1. ress the MRNII ②key in the will pop up:

 1. ress the MRNII ③key in the WRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the will pop up:

 1. ress the MRNII ③key in the wi
- 4. Press ▲ key or ▼ key to select DEL CAM ☐ then press OK ③ key;
 5. Press ▼ key to select ▼ to delete the camera;

- e.a IEMPERATURE UNIT SETTING

 1. Press the (Ø) key and the menu will pop up:
 2. Press the Key vor → key until the temperature Icon
 3. Press & key or ▼ Key to select between F or ℂ;
 5. Press the ፩ key to Confirm;
 5. Press the ፩ key to Exit.

 Walter The deservations.

8.3.1 TEMPERATURE ALARM SETTING

- 8.3.1 TEMPERATURE ALAMM SETTING

 1. Press A | V * yes to lett [2] The heigh of lett setting.

 2. Press A | V * to select [2] Set hein followed by ⊚ for confirming alarm on of 22 then followed by ⊙ for switching of all and mucrion.

 8.3.2 SETTIMERATURE HI/O.AERT LIMITS

 2. Press A | V * keys to adjust the it fill limit then press ⊚ to confirm.

 3. Then the curron valid limps to to limit setting them.

- 4. Press ▲ / ▼ keys to adjust the Lo limit then press ② to confirm.
- To skip the setting edit, press p key to exit to last menu level.

 Note: The High temperature alarm range is 20-40 °C, and the Low temperature alarm range is 0-19 °C. The high temperature alarm default setting is 36 °C, and the low temperature alarm default setting is 8 °C. When the temperature goes above or below the settings, the temperature is one turns real. It will flash to a beet user by audio beeps. Press

- LA ULLARYSTING

 Our can souther the baby to sleep by playing a gentle fullaby from the Camera unit.

 1. Press the MENU® key and the menu will populy:

 2. Press the 4 | P. beg until the fullaby (one) \$\frac{1}{2}\$ by helpfulpted;

 3. Press A, 4 \times \ti

- E.S.ALARMSTING.

 You can use the Farent Unit to set an alarm as a reminder for you to take care of your baby. If an alarm time is selected, the Farent Unit will beep at the end of the selected hour perior from Johns to the size of the John Target Unit will be the selected of the John Target Unit of Target Unit of

- Press the (a) key and the menu bar will pop
 Press the ◀ / ▶ keys until (a) is highlighted.
- (The default brightness level setting is level 3.)

 3.7 VOX SETTING
- 8.7 VOX.SETTING
 This mode allows you to control the sound activation of your baby unit. If there is no around the baby unit within 30 seconds, It will stop audio transmission and turn off its excreen of the parent unit. When the baby unit detects any sounds louder than the se level, I will start transmitting the signal to the parent unit again and turn on the scre parent unit. On the stop and the signal to the parent unit. On the stop and the signal to the parent unit. On the stop and the stop are the stop and the stop

- Note: Sensitivity levels and indications:

 Hear everything from your baby. The speaker of the parent unit is continuously on.

 Hear all sounds from soft babbling. If your baby does not make any sound, the speak of the parent unit is off.

 The speaker of the parent unit only goes on if the baby makes loud sounds (e.g., crying).

9. TECHNICAL DATA

Frequency	2403.5MHz*2475.5MHz
Power Adaptor	Parent Unit: Input: 100-240YAC 50/60Hz Output: SV DC 1A Camera Unit: Input: 100-240VAC 50/60Hz Output: SV DC 1A
Operating Range	Up to 1000ft (300m) outdoor (line of sight) Up to 165ft (50m) indoor
Display	3.2" Diagonal TFT LCD
Battery (Parent Unit)	Li-ion 3.7V 950mAh (3.515Wh)
Battery Life	Up to 6 hours
Maximum power	< 19d8m
Operation	Operation Temperature: +32F~+104F (0°C-40°C) Battery Charging Temperature: +50F~+104F (10°C-40°C)
environment	Relative Humidity: 15%-85%

No reception on the monitor	The power adapters may not be properly connected; Confirm that the camera and monitor are DN; Camera may be fair away from the monitor; Camera may be fair away from the monitor; Camera and monitor may not be properly paired; follow PAIRING instructions,
Interference or poor reception	 Move the monitor close to the camera; The camera or monitor may be placed too close to many metal objects; Other electronic devices may be interfering with the signal; The battery power may be too low;
Audio feedback	* The camera and monitor may be placed too closed;
(high pitched noise)	* The volume on the monitor may be set too high;
Frozen Picture on	 Repower the baby unit (plug out the adapter, then plug it into the
Screen	socket again); Press the RESET key at the back of parent unit:

11. MAINTENANCE

Never use cleaning agents or solvents.
 DISPOSAL GUIDE FOR BATTERY AND PRODUCT
 Do not attempt to repair or adjust any of the elections.

Follow Menufacturer's instructions.

Opingoal foll batter in fife or a hot over, or mechanically crushing or cutting of a battery that can result in an explosion, that can result in an explosion. I have been a set termely half temperature surrounding environment that can result in an explosion or the leakage of flammable liquid or gas:

A battery subjected in certimely loval in grease that may sepast in an explosion or the leakage of flammable liquid or gas.

The battery subjected the expressed box and the surrounding environment of the leakage of flammable liquid or gas.

FICCS 1905 Statement
This could be supported to the FICC Bules and with Industry Canada licence-name, the supported coupling with Part 15 of the FICC Bules and with Industry Canada licence-name in case the fill bullet in the following two conditions: (1) bits device many the case the fill bullet ference, and (2) bits device must accept any innerference received, including interference chart may cause undesired operation. Cet apparall set conforms a lab part is 5 dec region de la FICC et aux moments \$\$C\$ exceptible of licence of industries for the fill of the fill

partie 15 des regles de 16 KC et aux nomes 155 exemptes de licence d'Industric Canela. I florationnement est soumis aux deuxondifishes insulates (116 Legis papirel in del sip a securité protein de l'extra personnement de l'extra personnement de l'extra personnement de l'extra de l'extra personnement

nitor with a slightly damp or anti-static cloth.

se personal injury or damage to property. Use only the types of the batteries

acouraged to try to correct the interference by one ormore of the following measures

device meets the exemption from the routine evaluation limits in section 2.5 of RSS compliance with RSS 102 RF exposure, users can obtain Canadian information on RF

Middlioth Capacity Statement for careful with minimum distance 20cm between the radiator Ry our body.

Cet dispipement district fair installed are utilised as medistance minimals de 20cm entre le Statement de la comment de la commentation de la commentation de 20cm entre le Statement de la commentation de la comm

assurer la sécurité de toutes les personnes, quel que soit leur âge ou leur état de santé. Information et déclaration d'ISDE sur l'exposition aux RF la limite DAS du Canada (ISDE) est

de 1,6 W / kg en moyenne sur un gramme de tissu. Types d'apparells: la Moniteur a également été testée par rapport à certe limite SAR. Cet appareil à crét exte pour des opportants prépaires de dans été sair le constitue de de da Mondreire paré à d'un mé ur opportant son Pour maintain la conformité avec les origences d'expessitions Ref d'EDE, quillises des services des la commandation de la Mondreire de la Mondreire de departain de d'un metrie le corps de l'un listate et l'arrière de la Mondreire. L'utilisation de clips de celeture, d'étusi et d'un listate de la Mondreire de la Mondreire de composants mediques dans son assemblage. L'utilisation d'accessionies qui me satisfort pas à ces exigences peut ne par être conforme aux exigences de departiere du l'arrivé de l'ar

Directive 2014/53/EU. The full text of the EU declaration of conformity is available on the website:

Risk Group 1 WARNING IR emitted from this product. Do not stare at operating lamp Product tested against EN62471