

FCC RF EXPOSURE REPORT

CERTIFICATION TEST REPORT

For

Square Register

MODEL NUMBER: SPS1-01

FCC ID: 2AF3K-SPS1

REPORT NUMBER: 4789598114.1-5

ISSUE DATE: October 15, 2020

Prepared for

Square, Inc. 1455 Market St, Suite 600, San Francisco, California, United States 94103

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

> Tel: +86 769 22038881 Fax: +86 769 33244054 Website: www.ul.com



REPORT NO.: 4789598114.1-2 Page 2 of 7

Revision History

| Rev. | Issue Date | Revisions | Revised By |
|------|------------|---------------|------------|
| V0 | 10/15/2020 | Initial Issue | |






TABLE OF CONTENTS

| 1. | ATTESTATION OF TEST RESULTS | . 4 |
|----|------------------------------|-----|
| 2. | TEST METHODOLOGY | . 5 |
| 3. | FACILITIES AND ACCREDITATION | . 5 |
| 4 | REQUIREMENT | 6 |



REPORT NO.: 4789598114.1-2 Page 4 of 7

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Square, Inc.

Address: 1455 Market St, Suite 600, San Francisco, California, United

States 94103

Manufacturer Information

Company Name: Square, Inc.

Address: 1455 Market St, Suite 600, San Francisco, California, United

States 94103

EUT Information

EUT Name: Square Register

Model: Square Register Model: SPS1-01

Brand: SQUARE

Sample Received Date: August 17, 2020

Sample Status: Normal Sample ID: 2809002

Date of Tested: August 17~ September 15, 2020

| APPLICABLE STANDARDS | | | |
|-----------------------|------|--|--|
| STANDARD TEST RESULTS | | | |
| FCC 47CFR§2.1091 | PASS | | |

Prepared By:

Checked By:

Shawn Wen
Laboratory Leader

Approved By:

Stephen Guo Laboratory Manager



REPORT NO.: 4789598114.1-2 Page 5 of 7

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091.

3. FACILITIES AND ACCREDITATION

| · | |
|---------------|---|
| | A2LA (Certificate No.: 4102.01) |
| | UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. |
| | has been assessed and proved to be in compliance with A2LA. |
| | FCC (FCC Designation No.: CN1187) |
| | UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. |
| | Has been recognized to perform compliance testing on equipment subject |
| | to the Commission's Declaration of Conformity (DoC) and Certification rules |
| | ISED (Company No.: 21320) |
| Accreditation | UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. |
| Certificate | has been registered and fully described in a report filed with |
| | Industry Canada. The Company Number is 21320. |
| | VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) |
| | UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. |
| | has been assessed and proved to be in compliance with VCCI, the |
| | Membership No. is 3793. |
| | Facility Name: |
| | Chamber D, the VCCI registration No. is G-20019 and R-20004 |
| | Shielding Room B, the VCCI registration No. is C-20012 and T-20011 |

Note: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China.



REPORT NO.: 4789598114.1-2

Page 6 of 7

4. REQUIREMENT

LIMIT AND CALCULATION METHOD

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with. Limits for General Population/Uncontrolled Exposure

RF EXPOSURE LIMIT

| Frequency Range (MHz) | E-field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm²) | Averaging Time E ², H ² or S (Minutes) |
|-----------------------------|----------------------------------|---|----------------------------------|--|
| 0.3 1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34 30 | 824/f | 2.19/f | (180/f ²)* | 30 |
| 30 300 | 27.5 | 0.073 | 0.2 | 30 |
| 300 1500 | | | f/1500 | 30 |
| 1500 100,000 | | | 1.0 | 30 |

CALCULATION METHOD

 $S=PG/4\pi R^2$

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna



REPORT NO.: 4789598114.1-2 Page 7 of 7

CALCULATED RESULTS

| BT Mode | | | | | | |
|-----------|--------------|--------------|--------------------|---------------------|----------------|--|
| Frequency | Output Power | Output Power | Power Density | Power Density Limit | Test Result | |
| MHz | dBm | mW | mW/cm ² | mW/cm ² | | |
| 2402-2480 | 10.0 | 10.0 | 0.00350 | 1.0 | Complies | |

| 2.4G Mode -SISO | | | | | | |
|-----------------|-----------------|-----------------|------------------|---------------------|----------------|--|
| Frequency | Output Power | Output Power | Power Density | Power Density Limit | Test Result | |
| MHz | dBm | mW | mW/cm2 | mW/cm2 | | |
| 2412-2462 | 21.0 | 125.9 | 0.0441 | 1.0 | Complies | |

| 2.4G Mode -MIMO | | | | | | |
|-----------------|-----------------|-----------------|------------------|---------------------|----------------|--|
| Frequency | Output Power | Output Power | Power Density | Power Density Limit | Test Result | |
| MHz | dBm | mW | mW/cm2 | mW/cm2 | 1 | |
| 2412-2462 | 18.0 | 63.1 | 0.0323 | 1.0 | Complies | |

| 5G Mode | | | | | | |
|--|-------|------------------|---------------------|----------------|----------|--|
| Frequency | | Power Density | Power Density Limit | Test Result | | |
| MHz | dBm | mW | mW/cm2 | mW/cm2 | | |
| 5180-5240, 5260-5320, 5500-5700, 5745-5825. | 21.00 | 125.89 | 0.104 | 1.0 | Complies | |

Note:

- 1. The Power comes from report operation description.
- 2. The EUT cannot support simultaneous emission.
- 3. The minimum separation distance of the device is greater than 20 cm.
- 4. Calculate by WORST-CASE mode

END OF REPORT