

Playbrush Ltd West Kensington Court 68 Edith Villas W14 9AB London, United Kingdom

RF Exposure Analysis

FCC ID: 2AF47PBR2

Analysis for FCC portable use

Standalone SAR test exclusion considerations are defined in KDB 447498 D01, Chapter 4.3.1 where the 1-g head or body and 10-g extremity SAR exclusion threshold is defined by the following formula:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] * $[\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

For the PBR2 the maximum conducted output power is +1.3dBm (1.35mW) at 2.4GHz

Applying the above data using the given KDB 447498 D01 formula, and minimum separation distance of 5mm, the following results:

 $(1.35 \text{mW} / 5 \text{mm}) \times \sqrt{2.4} \text{ GHz} = 0.42$

(i.e.: \leq 3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR)

Conclusion

This demonstrates the PBR2 meets the criteria for 1-g head / body and 10-g extremity SAR test exemption.

Signature:	Merigia.	Date: 7.11.2016	
	* 3 °		