

MPE Calculation / RF Exposure

Applicant : SAM JIN CO.,LTD
Product : Motion Sensor
Model : STS-IRM-250
FCC ID : 2AF4S-ST-IRM-250
IC ID : 20753-ST-SIRM250

The FCC requires that the calculated MPE be equal to or less than a given limit dependent on frequency at a distance of 20 cm from the device to the body of the user. According to §2.1091, §2.1093 and §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

$$S = \text{EIRP} / 4 \pi R^2$$

Where S = Power density
 EIRP = Effective Isotropically Radiated Power
 R = distance to the centre of radiation of the antenna

Values S = 1.0 mW/cm² for General population uncontrolled exposure (FCC Part 1.1310 Radiofrequency radiation exposure limits)
S = 1.0 mW/cm²
 PT = 7.09 dB m (5.1168 mW) : measured maximum output power
 G = Antenna gain = 1.05 dB i (1.2735 in linear terms)
 EIRP = PT x G
 R = 20 cm

Calculation EIRP = 5.1168 x 1.2735 = 6.5162 mW
 S = 6.5162 / (4 x π x (20)²)
 S = 6.5162 / 5024
S = 1.297 x 10⁻³ mW/cm²

Conclusion This confirms compliance to the required FCC Part 1.1310 Radiofrequency radiation exposure limit of 1.0 mW/cm² at 20 cm operation.