

Report Number: F690501/RF-RTL011980-1

TEST REPORT

of

FCC CFR 47 part 1, 1.1307(b), 1.1310 FCC ID: 2AF4XAPPBOT-RILEY

Equipment Under Test	:	HOME CAMERA
Model Name	:	APPBOT-RILEY
Applicant	:	VARRAM SYSTEM Co., Ltd.
Manufacturer	:	VARRAM SYSTEM Co., Ltd.
Date of Receipt	:	2017.09.27
Date of Test(s)	:	2017.10.31 ~ 2017.11.09
Date of Issue	:	2017.12.14

In the configuration tested, the EUT complied with the standards specified above.

Tested By:

Date: 2017.12.14 **Jinhyoung Cho Technical** Date: 2017.12.14 Manager: **Jungmin Yang**

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 http://www.sgsgroup.kr RTT5041-19(2017.07.10)(0) Tel. +82 31 428 5700 / Fax. +82 31 427 2370 A4(210 mm x 297 mm)



Report Number: F690501/RF-RTL011980-1

INDEX

Table of Contents	Page
1. General Information	3
2. RF Exposure Evaluation	5

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL011980-1

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- Wireless Div. 2FL, 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u>. Phone No. : +82 31 688 0901

Fax No. : +82 31 688 0921

1.2. Details of Applicant

Applicant:VARRAM SYSTEM Co., Ltd.Address:2 Floors, Dadong, 55-1, Techno 11-ro, Yuseong-gu, Daejeon, 34036, KoreaContact Person:Jung, Ju-YongPhone No.:+82 70 8797 8920

1.3. Details of manufacturer

Applicant	:	Same as applicant
Address	:	Same as applicant

1.4. Description of EUT

Kind of Product	HOME CAMERA	
Model Name	APPBOT-RELEY	
Power Supply	DC 3.6 V	
Frequency Range	2 412 № ~ 2 462 № (11b/g/n_HT20), 2 422 № ~ 2 452 № (11n_HT40)	
Modulation Technique	DSSS, OFDM	
Number of Channels	11 channels (11b/g/n_HT20), 7 channels (11n_HT40)	
Antenna Type	PCB Antenna	
Antenna Gain	0 dB i	
H/W version	ABR-HW_V1.1	
S/W version	ABR-SW_V1.0	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



1.5. Test report revision

Revision	Report number	Date of Issue	Description
0	F690501/RF-RTL011980	2017.11.09	Initial
1	F690501/RF-RTL011980-1	2017.12.14	Added Designation number

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



2. RF Exposure Evaluation

2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

Frequency Range (쌘)	Electric Field Strength(V/m)	Magnetic Field Strength (A/m)	Power Density (ﷺ/ﷺ)	Average Time		
(A) Limits for Occupational/Controlled Exposure						
0.3 - 3.0	614	1.63	*100	6		
3.0 - 30	1842/f	4.89/f	*900/f ²	6		
30 – 300	61.4	0.163	1.0	6		
300 – 1 500	-	-	f/300	6		
1 500 – 100 000	-	-	5	6		
(B) Limits for General Population/Uncontrolled Exposure						
0.3 – 1.34	614	1.63	*100	30		
1.34 – 30	824/f	2.19/f	*180/f ²	30		
30 – 300	27.5	0.073	0.2	30		
300 – 1 500	-	-	f/1500	30		
<u>1 500 – 100 000</u>	-	-	<u>1.0</u>	<u>30</u>		

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

2.1.1. Friis transmission formula: Pd = (Pout*G)/(4*pi*R²)

Where $Pd = power density in mW/cm^2$

- Pout = output power to antenna in mW
- G = gain of antenna in linear scale
- Pi = 3.1416

R = distance between observation point and center of the radiator in $\ {\rm cm}$

Pd the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data Test Mode : Normal Operation

2.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

WLAN (2.4G)

- Maximum tune up tolerance

Operating Frequency (暅)	Output Average Power to Antenna (ⓓB m)	Antenna Gain (dB i)	Power Density at 20 cm (ɪ\/cɪr)	Limits (nW/cm²)
2 412 ~ 2 462	10	0	0.001 989	1

Remark;

- The output average power is set as max. power from tune-up procedure.

Note:

- The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm².
- This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.
- This equipment should be installed and operated with minimum 20 $\,\,{\rm cm}\,$ between the radiator and your body.
- The antenna gain of this transmitter is less than 6 dB i and must not be collocated or operating in conjunction with any other antenna or transmitter unless authorized to do so by the FCC.

- End of the Test Report -

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.