



# RF EXPOSURE REPORT

Applicant	MTRLC LLC
Address	PO Box 121147 Boston, MA 02112-1147, United States.

Manufacturer or Supplier	MTRLC LLC
Address	PO Box 121147 Boston, MA 02112-1147, United States.
Product	16x4 DOCSIS 3.0 Cable Modem plus AC1900 Router
Brand Name	Motorola
Model	MG7550
Additional Model & Model Difference	MG7550XY(X can be A, B, C, D or blank, and Y can be A, B, C, D or blank)
Date of tests	Mar. 05, 2016 ~ Mar. 25, 2016

- ☒ FCC Part 2 (Section 2.1091)
- ☒ KDB 447498 D03
- ☒ IEEE C95.1

**CONCLUSION:** The submitted sample was found to COMPLY with the test requirement

Tested by Blue Zheng Project Engineer/ EMC Department	Approved by Chris Chen Manager / EMC Department
	  Date: Mar. 25, 2016

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



## Table of Contents

RELEASE CONTROL RECORD .....	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT .....	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION .....	5
5. ANTENNA GAIN .....	5
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



Test Report No.: FS160223N035

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FS160223N035	Original release	Mar. 25, 2016

**Bureau Veritas Shenzhen Co., Ltd.**  
**Dongguan Branch**

No. 34, Chenwulu Section, Guantai Rd., Houjie  
Town, Dongguan City,  
Guangdong 523942, China

Tel: +86 769 8593 5656  
Fax: +86 769 8593 1080  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)



Test Report No.: FS160223N035

## 1. CERTIFICATION

**PRODUCT:** 16x4 DOCSIS 3.0 Cable Modem plus AC1900 Router

**BRAND NAME:** Motorola

**MODEL NO.:** MG7550

**ADDITIONAL MODEL:** N/A

**FCC ID:** 2AF5PMG7550

**TEST SAMPLE:** ENGINEERING SAMPLE

**APPLICANT:** MTRLC LLC

**TESTED DATE:** Feb. 26, 2015

**STANDARDS:** FCC Part 2 (Section 2.1091)  
KDB 447498 D03  
IEEE C95.1

## 2. RF EXPOSURE LIMIT

### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm <sup>2</sup> )	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

## 3. MPE CALCULATION FORMULA

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

## 4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

## 5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	ANT Number	Total Gain (dBi)	Antenna Type
2.4G	3.1	3	7.87	Wire Antenna
5G	2.8	3	7.57	Wire Antenna

## 6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
WLAN 2.4GHz	461.318	7.87	20	0.5620	1.0
WLAN 5GHz Band 1	648.63443	7.57	20	0.7374	1.0
WLAN 5GHz Band 4	671.42885	7.57	20	0.7634	1.0

--- END ---