



CTK Co., Ltd.  
The First Leader of Global Regulatory Certification

## **CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea

Tel: +82-31-339-9970 Fax: +82-31-624-9501

www.e-ctk.com

---

# **RF EXPOSURE EVALUATION**

**Applicant** : BITFINDER, INC.

**Applicant Address** : 40 BOARDMAN PL # 2F, SAN FRANCISCO CA 94103

**Kind of Product** : AWAIR Omni Surface Mount

**Equipment  
model name** : AWAOMNSURF

**FCC ID** : 2AF65AWAIRBKT

**Antenna type** : Monopole Antenna

**Antenna Gain** : -1 dBi



## **\*\* MPE Calculations \*\***

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user. The MPE calculation for this exposure is shown below.

The peak radiated output power (EIRP) is calculated as follows:

$EIRP = P + G$	Where, P = Power input to the antenna (mW) G = Power gain of the antenna (dBi)
----------------	--

The numeric gain(G) of the antenna with a gain specified in dB is determined by:

$$G = \text{Log}^{-1} (\text{dB antenna gain} / 10)$$

### **Power density at the specific separation:**

$S = PG / (4R^2\pi)$	Where, S = Maximum power density (mW/cm <sup>2</sup> ) P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna (20cm = limit for MPE)
----------------------	---

The Maximum permissible exposure (MPE) for the general population is 1 mW/cm<sup>2</sup> .  
The power density at 20cm does not exceed the 1 mW/cm<sup>2</sup> limit.

### **Estimated safe separation:**

$R = \sqrt{(PG / 4\pi)}$	Where, P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna (20cm = limit for MPE)
--------------------------	--



CTK Co., Ltd.  
The Prime Leader of Global Regulatory Certification

# CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea  
Tel: +82-31-339-9970 Fax: +82-31-624-9501  
www.e-ctk.com

Mode	P (dBm)	P (mW)	G (dBi)	S (mW/cm <sup>2</sup> )	R (cm)
125 kHz bandwidth	18.73	74.64	-1	<b>0.0118</b>	<b>20</b>
500 kHz bandwidth	18.09	64.42		<b>0.0102</b>	