

# RF EXPOSURE EVALUATION REPORT

**Application No.:** SZCR2212004131AT  
**Applicant:** Shenzhen RAKwireless Technology Co.,Ltd.  
**Address of Applicant:** Room 506, Building B, New Compark, Pingshan First Road, Taoyuan Street, Nanshan District, Shenzhen, China  
**Manufacturer:** Shenzhen RAKwireless Technology Co.,Ltd.  
**Address of Manufacturer:** Room 506, Building B, New Compark, Pingshan First Road, Taoyuan Street, Nanshan District, Shenzhen, China  
**Equipment Under Test (EUT):**  
**EUT Name:** All-in-One. 5G  
**Model No.:** M320  
**Trade Mark:** RAK, MNTD  
**FCC ID:** 2AF6B-M320  
**Standard(s) :** FCC Rules 47 CFR §2.1091  
KDB 447498 D04 interim General RF Exposure Guidance v01  
**Date of Receipt:** 2022-12-08  
**Date of Evaluation:** 2023-03-14 to 2023-04-08  
**Date of Issue:** 2023-04-19

<b>Evaluation Result:</b>	<b>Pass*</b>
---------------------------	--------------

\* In the configuration evaluated, the EUT complied with the standards specified above.



Keny Xu  
EMC Laboratory Manager



Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2023-04-19		Original

<b>Authorized for issue by:</b>			
		<i>Benson Wang</i>	
		<b>Benson Wang/Project Engineer</b>	
		<i>Eric Fu</i>	
		<b>Eric Fu/Reviewer</b>	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN\_Doccheck@sgs.com

## 2 Contents

	Page
<b>1 Cover Page</b> .....	<b>1</b>
<b>2 Contents</b> .....	<b>3</b>
<b>3 General Information</b> .....	<b>4</b>
3.1 General Description of E.U.T. ....	4
3.2 Details of E.U.T. ....	4
3.3 Separation Distance .....	5
3.4 Test Location .....	6
3.5 Test Facility .....	6
3.6 Deviation from Standards .....	6
3.7 Abnormalities from Standard Conditions .....	6
<b>4 FCC Radiofrequency radiation exposure limits</b> .....	<b>7</b>
<b>5 Measurement and Calculation</b> .....	<b>8</b>
5.1 Maximum transmit power .....	8



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN\_Doccheck@sgs.com

### 3 General Information

#### 3.1 General Description of E.U.T.

Product Type:	<input type="checkbox"/> Portable device
	<input checked="" type="checkbox"/> Mobile device
	<input type="checkbox"/> Fixed device

#### 3.2 Details of E.U.T.

Power supply:	Powered by POE adapter: Adapter model: RP026-5601080YE Input: AC 100-240V 50/60Hz Output: DC 56.0V 1.08A
Cable:	Lan cable x 2: 302cm unshielded
EUT Type:	CBSD
Category of EUT:	Category A
LTE:	
Operation Frequency Band:	Band 48 (3550-3700MHz)
Test Mode:	E-TM1.1; E-TM3.2; E-TM3.1;
Modulation Type:	QPSK, 16QAM, 64QAM
Bandwidth:	10MHz; 20MHz
5G NR:	
Operation Frequency Band:	n48 (3550-3700MHz)
Test Mode:	NR-FR1-TM1.1; NR-FR1-TM3.1; NR-FR1-TM3.1a;
Modulation Type:	QPSK, 64QAM, 256QAM,
SCS:	30KHz
LTE & 5G NR:	
Transmission (TX) and Receiving (RX) Antenna Ports:	TX port: 2
MIMO supported	2*2 UL
Antenna Type:	Integral Antenna
Antenna Gain:	5.5dBi
Technical Specification of Lora DTS	
Operating Frequency:	904.6MHz (SF8) 923.3 - 927.5MHz (SF7 - SF12)
Type of Modulation:	LoRa
Data Rate:	SF7 - SF12, SF8 (904.6MHz)
Channel Number:	9 Channels
Channel Separation:	600KHz
Occupied Bandwidth:	500KHz



Technical Specification of Lora Hybrid	
Operating Frequency:	903.9 - 905.3MHz
Type of Modulation:	LoRa
Data Rate:	SF7 -SF9 - SF10
Channel Number:	8 Channels (DSS & DTS)
Channel Separation:	200KHz
Occupied Bandwidth:	125KHz
Antenna Gain:	Integral Antenna: 3dBi Fiberglass Antenna 1 (RAKARG14): 5.8dBi; Fiberglass Antenna 2 (RAKARG19): 5.1dBi;
<p>1. The EUT have a integral antenna and two different Fiberglass antennas. The Integral antenna and Fiberglass antenna cannot transmit simultaneously.</p> <p>2. The Fiberglass Antenna 1 and 2 have the same type and RF characteristics as equivalent antenna, so, only the Fiberglass Antenna 1(High antenna gain) was tested in the report.</p>	

**Note:**

(1)The antenna gain value is provided by the customer. The test lab will not be responsible for wrong test result due to incorrect information about antenna gain values.

**3.3 Separation Distance**

Minimum test separation distance:	20cm
<p>Remark: This minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander.</p>	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN\_Doccheck@sgs.com

### 3.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

### 3.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### • A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

#### • VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

#### • FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

#### • Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

### 3.6 Deviation from Standards

None

### 3.7 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN\_Doccheck@sgs.com

## 4 FCC Radiofrequency radiation exposure limits

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN\_Doccheck@sgs.com

## 5 Measurement and Calculation

### 5.1 Maximum transmit power

Lora:

The Power Data is based on the RF Test Report SZCR221200413102 and Tune up procedure.

Highest Antenna Gain: 5.8dBi

MPE Calculation

According to the formula  $S=P/4\pi R^2$ , we can calculate S which is MPE.

Note:

- 1) P (mW)
- 2) R = distance to the center of radiation of antenna (in centimeter)
- 3) MPE limit = 0.6mW/cm<sup>2</sup>

Test Mode	Frequency Band (MHz)	Max Conducted power (dBm)	Max E.I.R.P (dBm)	Operation Distance R(cm)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density S(mW/cm <sup>2</sup> )	Result
Lora	923.3	26	31.8	20	0.30	0.62	Pass

LTE & 5G NR:

The Power Data is based on the RF Test Report SZCR221200413103 and Tune up procedure.

Antenna Gain: 5.5dBi

MPE Calculation

According to the formula  $S=P/4\pi R^2$ , we can calculate S which is MPE.

Note:

- 4) P (mW)
- 5) R = distance to the center of radiation of antenna (in centimeter)
- 6) MPE limit = 1mW/cm<sup>2</sup>

Test Mode	Frequency Band (MHz)	Max Conducted power (dBm)	Max E.I.R.P (dBm)	Operation Distance R(cm)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density S(mW/cm <sup>2</sup> )	Result
LTE Band 48	3690	25	30.5	20	0.22	1.00	Pass

Test Mode	Frequency Band (MHz)	Max Conducted power (dBm)	Max E.I.R.P (dBm)	Operation Distance R(cm)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density S(mW/cm <sup>2</sup> )	Result
5G NR n48	3624.99	25	30.5	20	0.22	1.00	Pass





### exposure conditions for simultaneous transmission operations

The EUT has Four modules: Lora module, LTE module, 5GNR module and CM4 module:

- 1) For the module: CM4 (FCC ID: 2ABCB-RPICM4), it can't simultaneous transmission with Lora, LTE and 5GNR module.
- 2) The Lora module, LTE module and 5GNR module, they can simultaneous transmission at the same time. So, Simultaneous transmission SAR test is not required, because the Max. sum of the MPE ratios is  $0.48+0.22+0.22=0.92<1$ .

--End of the Report--

