

Prüfbericht-Nr.: <i>Test report no.:</i>	CN22TOCB 001	Auftrags-Nr.: <i>Order no.:</i>	168358593	Seite 1 von 31 <i>Page 1 of 31</i>	
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	2022-01-26		
Auftraggeber: <i>Client:</i>	Shenzhen RAKwireless Technology Co.,Ltd. Room 506, Building B, New Compark, Pingshan First Road, Taoyuan Street, Nanshan District, Shenzhen, Guangdong, China				
Prüfgegenstand: <i>Test item:</i>	WisBlock LPWAN Module				
Bezeichnung / Typ-Nr.: <i>Identification / Type no.:</i>	RAK13300 (Trademark: RAK)				
Auftrags-Inhalt: <i>Order content:</i>	FCC and IC approval				
Prüfgrundlage: <i>Test specification:</i>	CFR47 FCC Part 15: Subpart C Section 15.247 CFR47 FCC Part 15: Subpart C Section 15.207 CFR47 FCC Part 15: Subpart C Section 15.209 CFR47 FCC Part 2: Section 2.1093	RSS-247 Issue 2 February 2017 RSS-Gen Issue 5 February 2021 RSS-102 Issue 5 February 2021			
Wareneingangsdatum: <i>Date of sample receipt:</i>	2022-02-10	Please refer to photo documents			
Prüfmuster-Nr.: <i>Test sample no.:</i>	A003207708				
Prüfzeitraum: <i>Testing period:</i>	2022-02-11 - 2022-04-07				
Ort der Prüfung: <i>Place of testing:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.				
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.				
Prüfergebnis*: <i>Test result*:</i>	Pass				
geprüft von: <i>tested by:</i>	genehmigt von: <i>authorized by:</i>				
Datum: <i>Date:</i> 2022-04-18	 Signed by: Alex Lan		 Signed by: Winnie Hou		
Stellung / Position	Senior Project Engineer	Ausstellungsdatum: <i>Issue date:</i> 2022-04-19	Department Manager		
Sonstiges / Other:	FCC ID: 2AF6B-RAK13300 IC: 25908-RAK13300, HVIN: RAK13300				
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged:</i>				
Legend:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n) 1 = very good P(ass) = passed a.m. test specifications(s)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n) 2 = good F(ail) = failed a.m. test specifications(s)	3 = befriedigend 3 = satisfactory	4 = ausreichend 4 = sufficient	5 = mangelhalt N/T = nicht getestet 5 = poor N/T = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>					

Test Summary

5.1.1 ANTENNA REQUIREMENT*RESULT: Pass***5.1.2 MAXIMUM CONDUCTED OUTPUT POWER***RESULT: Pass***5.1.3 CONDUCTED POWER SPECTRAL DENSITY***RESULT: Pass***5.1.4 6dB BANDWIDTH***RESULT: Pass***5.1.5 20dB BANDWIDTH***RESULT: Pass***5.1.6 99% BANDWIDTH***RESULT: Pass***5.1.7 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHz BANDWIDTH***RESULT: Pass***5.1.8 RADIATED SPURIOUS EMISSION***RESULT: Pass***5.1.9 CARRIER FREQUENCY SEPARATION***RESULT: Pass***5.1.10 NUMBER OF HOPPING FREQUENCY***RESULT: Pass***5.1.11 TIME OF OCCUPANCY***RESULT: Pass***5.1.12 CONDUCTED EMISSION ON AC MAINS***RESULT: Pass***6.1.1 ELECTROMAGNETIC FIELDS***RESULT: Pass*

Contents

1	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS	5
2	TEST SITES.....	6
2.1	TEST FACILITIES.....	6
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS	6
2.3	TRACEABILITY.....	7
2.4	CALIBRATION.....	7
2.5	MEASUREMENT UNCERTAINTY	7
2.6	LOCATION OF ORIGINAL DATA	8
2.7	STATUS OF FACILITY USED FOR TESTING.....	8
3	GENERAL PRODUCT INFORMATION.....	9
3.1	PRODUCT FUNCTION AND INTENDED USE.....	9
3.2	RATINGS AND SYSTEM DETAILS	10
3.3	INDEPENDENT OPERATION MODES	12
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS.....	12
3.5	SUBMITTED DOCUMENTS.....	12
4	TEST SET-UP AND OPERATION MODES	13
4.1	PRINCIPLE OF CONFIGURATION SELECTION.....	13
4.2	TEST OPERATION AND TEST SOFTWARE.....	13
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT.....	13
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	13
4.5	TEST SETUP DIAGRAM	14
5	TEST RESULTS.....	16
5.1	TRANSMITTER REQUIREMENT & TEST SUITES.....	16
5.1.1	<i>Antenna Requirement.....</i>	<i>16</i>
5.1.2	<i>Maximum Conducted Output Power</i>	<i>17</i>
5.1.3	<i>Conducted Power Spectral Density.....</i>	<i>19</i>
5.1.4	<i>6dB Bandwidth.....</i>	<i>20</i>
5.1.5	<i>20dB Bandwidth</i>	<i>21</i>
5.1.6	<i>99% Bandwidth</i>	<i>22</i>
5.1.7	<i>Conducted Spurious Emissions Measured in 100 kHz Bandwidth</i>	<i>23</i>
5.1.8	<i>Radiated Spurious Emission.....</i>	<i>24</i>
5.1.9	<i>Carrier Frequency Separation.....</i>	<i>25</i>
5.1.10	<i>Number of Hopping Frequency.....</i>	<i>26</i>
5.1.11	<i>Time of Occupancy</i>	<i>27</i>
5.1.12	<i>Conducted Emission on AC Mains.....</i>	<i>28</i>
6	SAFETY HUMAN EXPOSURE	29
6.1	RADIO FREQUENCY EXPOSURE COMPLIANCE.....	29
6.1.1	<i>Electromagnetic Fields</i>	<i>29</i>

7	PHOTOGRAPHS OF THE TEST SET-UP	31
8	LIST OF TABLES	31

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Photographs of the Test Set-up

Appendix B: Test result.

2 Test Sites

2.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

362 Huanguan Road Middle Longhua District, Shenzhen 518110 People's Republic of China

FCC Registration No.: 694916

ISED wireless device testing laboratory: 25069, CAB identifier: CN0078

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

TÜV Rheinland (Shenzhen) Co., Ltd.

Radio Spectrum Testing				
Equipment	Manufacturer	Model	Serial No.	Cal. until
EXA Signal Analyzer, Multi-touch	Keysight	N9010B	MY60241175	2022-09-28
MXG X-Series RF Vector Signal Generator	Keysight	N5182B	MY61250137	2022-09-28
EXG X-Series Microwave Analog Signal Generator	Keysight	N5173B	MY61250141	2022-09-28
DC Power Supply	Keysight	E3642A	MY61276100	2022-09-28
Power Control Unit	Tonscend	JS0806-4ADC	N/A	2022-09-28
Automation Control Unit	Tonscend	JS0806-2	21C8060396	2022-09-28
Test Software	Tonscend	JS1120-3	N/A	N/A
Control PC	Lenovo	TianYi510S-071MB	YLX23JMF	N/A
Unwanted Emission Testing				
Equipment	Manufacturer	Model	Serial No.	Cal. until
EMI Test Receiver	R&S	ESR 7	102021	2022-08-10
Signal Analyzer	R&S	FSV 40	101439	2022-08-09
System Controller Interface	R&S	SCI-100	S10010038	N/A
Filterbank	R&S	Wlan	100759	2022-08-09
OSP	R&S	OSP 120	102040	N/A
Pre-amplifier	R&S	SCU08F1	08320031	2022-08-09
Amplifier	R&S	SCU-18F	180070	2022-08-09
Amplifier	R&S	SCU40A	100475	2022-08-09
Trilog Broadband Antenna (30 MHz - 7 GHz)	Schwarzbeck	VULB 9162	193	2022-08-08

Double-Ridged Antenna (1 -18 GHz)	ETS-LINDGREN	3117	00218717	2022-08-08
Wideband Ridged Horn Antenna (18-40 GHz)	Steatite	QMS-00880	19067	2022-08-08
Active Loop Antenna	Schwarzbeck	FMZB 1513	302	2022-09-13
Test software	R&S	EMC32 (V10.60.10)	N/A	N/A
Control PC	Dell	OptiPlex 7050	36NV9P2	N/A
3m Semi-Anechoic Chamber	Albatross	SAC-3m	APC17151-SAC	2024-06-22
Conducted Emission on AC Mains				
Equipment	Manufacturer	Model No.	Serial No.	Cali. until
EMI Test Receiver	R&S	ESR3	102680	2022-04-25
Artificial Mains Network	R&S	ENV216	101445	2022-04-25
EMC32 test software	R&S	EMC32(Ver.10.50.00)	N/A	N/A

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-7}$
RF Power (conducted)	± 2.5 dB
Radiated Emission of Transmitter, valid up to 26.5 GHz	± 6 dB
Radiated Emission of Receiver, valid up to 26.5 GHz	± 6 dB
Conducted Emission, (9kHz to 150kHz)/(150kHz to 30MHz)	± 3.70 dB / ± 3.30 dB
Radiated Emission (3m SAC), 30MHz to 1000MHz	± 4.52 dB
Radiated Emission (3m SAC), above 1000MHz	± 4.37 dB

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at 362 Huanguan Road Middle Longhua District, Shenzhen 518110 People's Republic of China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The EUT is a WisBlock LPWAN Module which supports Lora technology.

This module has three different antennas, the details specifications for these antennas as below:

Antenna #	Model	Antenna Gain	Antenna Type	Connector Type
1#	2701C02Q	0.8dBi	PCB Antenna	IPEX connector
2#	KRAKBJ2701C01A	2.3 dBi	Dipole Antenna	RPSMA connector
3#	KRAKBJ2701C01C	2.3 dBi	Dipole Antenna	RPSMA connector

1. When connecting to the module, all antennas listed above need to transfer to an **IPEX connector**.

2. Antennas 2# and 3# have the same type and similar in-band and out-of-band characteristics and only the color of enclosure different, they are considered as equivalent antennas. Thus, the antenna 3# with highest gain was selected to be tested.

Data Rate	Configuration	Indicative physical bit rate [bit/sec]
0	LoRa Modulation: SF10 / Bandwidth 125 kHz	980
1	LoRa Modulation: SF9 / Bandwidth 125 kHz	1760
2	LoRa Modulation: SF8 / Bandwidth 125 kHz	3125
3	LoRa Modulation: SF7 / Bandwidth 125 kHz	5470
4	LoRa Modulation: SF8 / Bandwidth 500 kHz	12500

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 2: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment	WisBlock LPWAN Module
Type Designation	RAK13300
Trademark	RAK
FCC ID	2AF6B-RAK13300
IC	25908-RAK13300
HVIN	RAK13300
Operating Voltage	DC 3.3V (Supplied by socket of PCB board)
Testing Voltage	DC 5V Via USB port
Technical Specification of Lora DTS	
Operating Frequency	903 – 914.2MHz
Type of Modulation	Lora
Data Rate	SF8 / DR4
Channel Number	8 channels (Upstream)
Channel Separation	1.6 MHz
Occupied Bandwidth	500 KHz
Technical Specification of Lora FHSS	
Frequency Range	902.3 – 914.9MHz
Type of Modulation	Lora
Data Rate	SF7 to SF10 / DR0 to DR3
Channel Number	64 channels (Upstream)
Channel Separation	200 KHz
Occupied Bandwidth	125 KHz

Table 3: RF Channel and Frequency of Lora FHSS

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
0	902.3	16	905.5	32	908.7	48	911.9
1	902.5	17	905.7	33	908.9	49	912.1
2	902.7	18	905.9	34	909.1	50	912.3
3	902.9	19	906.1	35	909.3	51	912.5
4	903.1	20	906.3	36	909.5	52	912.7
5	903.3	21	906.5	37	909.7	53	912.9
6	903.5	22	906.7	38	909.9	54	913.1
7	903.7	23	906.9	39	910.1	55	913.3
8	903.9	24	907.1	40	910.3	56	913.5
9	904.1	25	907.3	41	910.5	57	913.7
10	904.3	26	907.5	42	910.7	58	913.9
11	904.5	27	907.7	43	910.9	59	914.1
12	904.7	28	907.9	44	911.1	60	914.3
13	904.9	29	908.1	45	911.3	61	914.5
14	905.1	30	908.3	46	911.5	62	914.7
15	905.3	31	908.5	47	911.7	63	914.9

Table 4: RF Channel and Frequency of Lora DTS

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
64	903.0	66	906.2	68	909.4	70	912.6
65	904.6	67	907.8	69	911.0	71	914.2

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, Lora transmitting mode (FHSS)
 - 1) Low Channel
 - 2) Middle Channel
 - 3) High Channel
- B. On, Lora transmitting mode (DTS)
 - 1) Low Channel
 - 2) Middle Channel
 - 3) High Channel
- C. On, Transmitting on Hopping channel
- D. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- ID Label and Location Info

- User Manual

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All tests were performed according to the procedures in ANSI C63.10: 2013 and ANSI C63.4: 2014.

According to clause 3.1, all tests were performed on model RAK13300 with antenna #1, #3 in this report

4.3 Special Accessories and Auxiliary Equipment

Table 5: Auxiliary Equipment Used during Test

Description	Manufacturer	Model	S/N	Rating
PC	Lenovo	ThinkPad T480	N/A	PC
PC adapter	Lenovo	ADLX65YDC3A	01FR030	PC adapter

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 30MHz)




Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)




Diagram of Measurement Configuration for Mains Conduction Measurement





Diagram of Measurement Configuration for Conducted Transmitter Measurement



5 Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:**Pass****Test Specification**

Test standard : FCC Part 15.247(b)(4) and Part 15.203
RSS-Gen Clause 6.8

According to the manufacturer declared, the EUT has three IPEX Antenna, the directional gain of antenna are 2.3dBi & 0.8 dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

5.1.2 Maximum Conducted Output Power

RESULT:
Pass
Test Specification

Test standard	: FCC Part 15.247(b)(2)&(3) RSS-247 Clause 5.4(a)&(d)
Basic standard	: ANSI C63.10: 2013 Not more than 1Watt(30dBm) for DTS in the band 902-928MHz
Limits	: Not more than 1Watt(30dBm) for FHSS with at least 50 hopping channels in the band 902-928MHz
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2022-02-11 - 2022-03-30
Input voltage	: DC 5V Via USB port
Operation mode	: A, B
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101 kPa

For Antenna gain 0.8dBi

Table 6: Test Result of Maximum Conducted Average Output Power

Test Mode	Test Channel (MHz)	Maximum Conducted Average Power		Limit (W)
		(dBm)	(W)	
Lora DTS	903.0	10.43	0.0110	< 1.0
	907.8	10.31	0.0107	
	914.2	10.42	0.0110	
Lora FHSS SF7	902.3	10.52	0.0113	< 0.125
	908.5	10.45	0.0111	
	914.9	10.48	0.0112	
Lora FHSS SF10	902.3	10.60	0.0115	< 0.125
	908.5	10.43	0.0110	
	914.9	10.38	0.0109	
Max. Measured Value		10.60	0.0115	

Note:

- 1) The cable loss is taken into account in results.
- 2) The maximum Antenna gain(G) : 0.8 dBi,
e.i.r.p.=11.40dBm = 13.80mW, which is far below the 4 W

For Antenna gain 2.3dBi

Table 7: Test Result of Maximum Conducted Output Power, Lora FHSS

Test Mode	Test Channel (MHz)	Maximum Conducted Average Power		Limit (W)
		(dBm)	(W)	
Lora DTS	903.0	17.38	0.0547	< 1.0
	907.8	17.21	0.0526	
	914.2	18.07	0.0641	
Lora FHSS SF7	902.3	17.42	0.0552	< 0.125
	908.5	17.28	0.0535	
	914.9	18.18	0.0658	
Lora FHSS SF10	902.3	17.44	0.0555	< 0.125
	908.5	17.29	0.0536	
	914.9	18.18	0.0658	
Max. Measured Value		18.18	0.0658	

Note:

- 1) The cable loss is taken into account in results.
- 2) The maximum Antenna gain(G) : 2.3 dBi,
 e.i.r.p.=20.48dBm = 111.69mW, which is far below the 4 W

5.1.3 Conducted Power Spectral Density

RESULT:
Pass
Test Specification

Test standard : FCC Part 15.247(e)
 : RSS-247 Clause 5.2(b)
 Basic standard : ANSI C63.10: 2013
 Limits : < 8 dBm / 3kHz
 Kind of test site : Shielded Room

Test Setup

Date of testing : 2022-03-30
 Input voltage : DC 5V Via USB port
 Operation mode : B
 Test channel : Low / Middle / High
 Ambient temperature : 25 °C
 Relative humidity : 56 %
 Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix B.

Table 8: Test Result of Maximum Peak Power Spectral Density, Lora DTS

Antenna Gain	Test Mode	Test Channel (MHz)	Measured Peak Power Spectral Density (dBm/3KHz)
0.8 dBi	Lora DTS	903.0	-8.94
		907.8	-8.27
		914.2	-9.35
2.3 dBi	Lora DTS	903.0	-2.15
		907.8	-2.42
		914.2	-1.77
Maximum Measured Value			-1.77

5.1.4 6dB Bandwidth

RESULT:
Pass
Test Specification

Test standard : FCC Part 15.247(a)(2)
 : RSS-247 Clause 5.2(a)
 Basic standard : ANSI C63.10: 2013
 Limits : At least 500kHz for bandwidth(DTS)
 Kind of test site : Shielded Room

Test Setup

Date of testing : 2022-03-30
 Input voltage : DC 5V Via USB port
 Operation mode : B
 Test channel : Low / Middle / High
 Ambient temperature : 25 °C
 Relative humidity : 56 %
 Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix B.

Table 9: Test Result of 6dB Bandwidth

Test Mode	Test Channel (MHz)	6dB Bandwidth (KHz)	Limit (KHz)
Lora DTS	903.0	628.1	>500KHz
	907.8	628.1	
	914.2	636.8	
Minimum Measured Value		628.1	

5.1.5 20dB Bandwidth

RESULT:
Pass
Test Specification

Test standard	: FCC Part 15.247(a)(1) (i) RSS-247 Clause 5.1(a)
Basic standard	: ANSI C63.10: 2013 Not more than 500kHz and
Limits	: < 250KHz for at least 50 hopping frequencies >=250KHz for at least 25 hopping frequencies
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2022-03-30
Input voltage	: DC 5V Via USB port
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix B.

Table 10: Test Result of 20dB Bandwidth

Test Mode	Test Channel (MHz)	20dB Bandwidth (kHz)	Limit (KHz)	
Lora FHSS SF7	902.3	146.89	<500KHz	
	908.5	144.72		
	914.9	146.16		
Lora FHSS SF10	902.3	139.65		
	908.5	138.93		
	914.9	139.65		
Maximum Measured Value		146.89		

5.1.6 99% Bandwidth

RESULT:
Pass
Test Specification

Test standard : RSS-Gen Clause 6.7
 Basic standard : ANSI C63.10: 2013
 Kind of test site : Shielded Room

Test Setup

Date of testing : 2022-03-30
 Input voltage : DC 5V Via USB port
 Operation mode : A, B
 Test channel : Low / Middle / High
 Ambient temperature : 25 °C
 Relative humidity : 56 %
 Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix B.

Table 11: Test Result of 99% Bandwidth

Test Mode	Test Channel (MHz)	99% Bandwidth (KHz)	Limit (KHz)
Lora DTS	903.0	500.72	
	907.8	503.62	
	914.2	506.51	
Lora FHSS SF7	902.3	128.08	
	908.5	126.63	
	914.9	127.35	
Lora FHSS SF10	902.3	125.90	
	908.5	125.90	
	914.9	125.90	
Minimum Measured Value		125.90	

5.1.7 Conducted Spurious Emissions Measured in 100 kHz Bandwidth

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.247(d) RSS-247 Clause 5.5
Basic standard	: ANSI C63.10: 2013
Limits	: 20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power); In addition, radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified in 15.209(a)
Kind of test site	: Shielded Room

Test Setup

Date of testing	: Refer to test result
Input voltage	: DC 5V Via USB port
Operation mode	: A, B
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101 kPa

Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method refer to test plots, and compliance is achieved as well.

For the measurement records, refer to the appendix B.

5.1.8 Radiated Spurious Emission

RESULT:**Pass****Test Specification**

Test standard	:	FCC Part 15.247(d) & FCC Part 15.205 RSS-247 Clause 3.3
Basic standard	:	ANSI C63.10: 2013
Limits	:	Refer to 15.209(a) of FCC part 15.247(d)
Kind of test site	:	3m Semi-anechoic Chamber

Test Setup

Date of testing	:	2022-02-11 - 2022-03-30
Input voltage	:	DC 5V Via USB port
Operation mode	:	A, B
Test channel	:	Low / Middle / High
Ambient temperature	:	Refer to test result
Relative humidity	:	Refer to test result
Atmospheric pressure	:	101 kPa

Remark:

Testing was carried out within frequency range 9kHz to the tenth harmonics with all data rate and three channels (Lowest, middle and highest). Only the worst case spurious emissions configuration of the each mode were reported.

Radiated spurious emissions were performed on the EUT with antenna in three orthogonal orientations and only the worst (antenna horizontal) orientations was recorded.

For the measurement records, refer to the appendix B.

5.1.9 Carrier Frequency Separation

RESULT:
Pass
Test Specification

Test standard : FCC Part 15.247(a)(1)
 : RSS-247 Clause 5.1(b)
 Basic standard : ANSI C63.10: 2013
 Limits : $\geq 20\text{dB}$ bandwidth, whichever is greater
 Kind of test site : Shielded Room

Test Setup

Date of testing : 2022-03-30 to 2022-04-07
 Input voltage : DC 5V Via USB port
 Operation mode : C
 Test channel : Low / Middle / High
 Ambient temperature : 25 °C
 Relative humidity : 56 %
 Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix B.

Table 12: Test Result of Carrier Frequency Separation

Test Mode	Channel	Measured Channel Separation (KHz)	Limit (kHz)	Result
Lora FHSS SF7	Low Channel	221.418	$\geq 20\text{dB}$ bandwidth	Pass
	Adjacency Channel			
	Middle Channel	239.653		Pass
	Adjacency Channel			
	High Channel	269.175		Pass
	Adjacency Channel			
Lora FHSS SF10	Low Channel	230.970	$\geq 20\text{dB}$ bandwidth	Pass
	Adjacency Channel			
	Middle Channel	238.780		Pass
	Adjacency Channel			
	High Channel	235.31		Pass
	Adjacency Channel			

Note:

The limit is maximum 20 dB bandwidth: 136.7 KHz.

5.1.10 Number of Hopping Frequency

RESULT:**Pass****Test Specification**

Test standard : FCC part 15.247(a)(1)(iii)
RSS-247 Clause 5.1(d)

Basic standard : ANSI C63.10: 2013

Limits : ≥ 15 non-overlapping channels

Kind of test site : Shielded Room

Test Setup

Date of testing : 2022-03-30

Input voltage : DC 5V Via USB port

Operation mode : C

Ambient temperature : 25 °C

Relative humidity : 56 %

Atmospheric pressure : 101 kPa

Table 13: Test result of hopping channel number

Test Mode	20dB Bandwidth(kHz)	Hopping frequencies	Limit
Lora FHSS SF7	20dB Bandwidth < 250	64	≥ 50
Lora FHSS SF10	20dB Bandwidth < 250	64	≥ 50

5.1.11 Time of Occupancy**RESULT:****Pass****Test Specification**

Test standard : FCC part 15.247(a)(1)(iii)
RSS-247 Clause 5.1(d)
Basic standard : ANSI C63.10: 2013
Limits : < 0.4s
Kind of test site : Shielded Room

Test Setup

Date of testing : 2022-03-30
Input voltage : DC 5V Via USB port
Operation mode : C
Test channel : Low / Middle / High
Ambient temperature : 25 °C
Relative humidity : 56 %
Atmospheric pressure : 101 kPa

Table 14: Test result of Channel Occupancy

Test Mode	20dB Bandwidth(kHz)	Period (s)	Channel Occupancy Time (ms)	Limit (ms)
Lora FHSS SF7	20dB Bandwidth < 250	20	31.884	400
Lora FHSS SF10	20dB Bandwidth < 250	20	33.334	400

5.1.12 Conducted Emission on AC Mains**RESULT:****Pass****Test Specification**

Test standard	:	FCC Part 15.207(a) RSS-Gen Clause 8.8
Basic standard	:	ANSI C63.10: 2013
Frequency range	:	0.15 – 30MHz
Limits	:	FCC Part 15.207(a) RSS-Gen Table 3
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	2022-02-14
Input voltage	:	Powered by PC Adapter
Operation mode	:	A, B
Earthing	:	Not connected
Ambient temperature	:	22 °C
Relative humidity	:	64 %
Atmospheric pressure	:	101 kPa

For the measurement records, refer to the appendix B.

6 Safety Human Exposure

6.1 Radio Frequency Exposure Compliance

6.1.1 Electromagnetic Fields

RESULT:**Pass****Test Specification**

Test standard : CFR47 FCC Part 2: Section 2.1091
CFR47 FCC Part 1: Section 1.1310
FCC KDB Publication 447498 v06
FCC KDB Publication 865664 D02 v01r02
OET Bulletin 65 (Edition 97-01)
RSS-102 Issue 5 March 2019

This module has three different antennas, and the maximum e.r.i.p. configuration be evaluated as below:

FCC requirement: Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 20cm normally can be maintained between the user and the device.

MPE Calculation Method according to OET Bulletin 65

Power Density: $S_{(mW/cm^2)} = PG/4\pi R^2$ or $EIRP/4\pi R^2$

Where:

S = power density (mW/cm²)

P = power input to the antenna (mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (cm)

The worst-case mode (the configuration having highest EIRP) specified:

Lora FHSS SF7: 18.18 dBm with 2.3 dBi antenna gain

From the RF output power, the minimum mobile separation distance, d=20 cm, as well as the antenna gain, the RF power density can be calculated as below:

For Lora DTS: $S_{(mW/cm^2)} = PG/4\pi R^2 = 0.022$ mW/cm²

Limits for Maximum Permissible Exposure (MPE) according to FCC Part 1.1310: 1.0 mW/cm²

➤ **IC requirements:** The EUT shall comply with the requirement of RSS-102 section 2.5.2.

Exemption from Routine Evaluation Limits – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;

- RF exposure evaluation exempted power for Lora FHSS & DTS: 1.37 W

The worst-case mode (the configuration having highest EIRP) specified:

Lora FHSS SF7: 18.18 dBm

Antenna Gain: 2.3 dBi

The Max. e.i.r.p. for Lora DTS: 20.48dBm = 0.112 W

Both e.i.r.p. for the Lora FHSS and Lora DTS are less than the RF exposure evaluation exempted power. So RF exposure evaluation is not required.

“RF Radiation Exposure Statement Caution: This Transmitter must be installed to provide a separation distance of at least 20 cm from all persons.”

7 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix A.

8 List of Tables

Table 1: List of Test and Measurement Equipment.....	6
Table 2: Technical Specification of EUT	10
Table 3: RF Channel and Frequency of Lora FHSS.....	11
Table 4: RF Channel and Frequency of Lora DTS.....	11
Table 5: Auxiliary Equipment Used during Test.....	13
Table 6: Test Result of Maximum Conducted Average Output Power.....	17
Table 7: Test Result of Maximum Conducted Output Power, Lora FHSS	18
Table 8: Test Result of Maximum Peak Power Spectral Density, Lora DTS.....	19
Table 9: Test Result of 6dB Bandwidth.....	20
Table 10: Test Result of 20dB Bandwidth.....	21
Table 11: Test Result of 99% Bandwidth.....	22
Table 12: Test Result of Carrier Frequency Separation	25
Table 13: Test result of hopping channel number	26
Table 14: Test result of Channel Occupancy	27


Appendix B: Test Results

APPENDIX B: TEST RESULTS.....	1
APPENDIX B.1: CONDUCTED POWER SPECTRAL DENSITY	2
<i>Lora DTS, Antenna gain 0.8dBi</i>	2
<i>Lora DTS, Antenna Gain 2.3dBi</i>	3
APPENDIX B.2: 6dB BANDWIDTH	5
<i>Lora DTS</i>	5
APPENDIX B.3: 20dB BANDWIDTH	7
<i>Lora FHSS, Data rate SF7</i>	7
<i>Lora FHSS, Data rate SF10</i>	8
APPENDIX B.4: 99% BANDWIDTH	10
<i>Lora FHSS, Data rate SF7</i>	10
<i>Lora FHSS, Data rate SF10</i>	11
<i>Lora DTS</i>	13
APPENDIX B.5: CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHz BANDWIDTH	15
<i>Lora DTS</i>	15
<i>Lora FHSS, Data rate SF7, No hopping</i>	18
<i>Lora FHSS, Data rate SF10, No hopping</i>	21
<i>Lora FHSS, Data rate SF7, hopping</i>	24
<i>Lora FHSS, Data rate SF10, hopping</i>	25
<i>Lora DTS, Band Edge</i>	26
<i>Lora FHSS, Data rate SF7, No hopping, Band Edge</i>	27
<i>Lora FHSS, Data rate SF10, No hopping, Band Edge</i>	28
<i>Lora FHSS, Data rate SF7, hopping, Band Edge</i>	29
<i>Lora FHSS, Data rate SF10, hopping, Band Edge</i>	30
APPENDIX B.6: CARRIER FREQUENCY SEPARATION	31
<i>Lora FHSS, Data rate SF7</i>	31
<i>Lora FHSS, Data rate SF10</i>	32
APPENDIX B.7: TEST RESULTS OF RADIATED SPURIOUS EMISSIONS	34
<i>Lora FHSS SF7, Antenna Gain: 0.8dBi</i>	34
<i>Lora DTS, Antenna Gain: 0.8dBi</i>	52
<i>Lora FHSS SF7, Antenna Gain: 2.3dBi</i>	70
<i>Lora DTS, Antenna Gain: 2.3dBi</i>	88
APPENDIX B.8: TEST RESULTS OF CONDUCTED EMISSION ON AC MAINS	106

Appendix B.1: Conducted Power Spectral Density


Lora DTS, Antenna gain 0.8dBi

Low Channel




Date: 30.MAR.2022 07:20:07

Middle Channel



Date: 30.MAR.2022 07:17:27


High Channel



Date: 30.MAR.2022 03:46:25


Lora DTS, Antenna Gain 2.3dBi

Low Channel




Date: 30.MAR.2022 04:01:43

Middle Channel



Date: 30.MAR.2022 04:11:17


High Channel



Date: 30.MAR.2022 04:18:22


Appendix B.2: 6dB Bandwidth

Lora DTS
Low Channel




Date: 30.MAR.2022 04:12:35

Middle Channel



Date: 30.MAR.2022 04:05:49

High Channel




Date: 30.MAR.2022 04:24:43

Appendix B.3: 20dB Bandwidth


Lora FHSS, Data rate SF7

Low Channel




Date: 21.FEB.2022 07:09:43

Middle Channel



Date: 21.FEB.2022 07:16:51


High Channel



Date: 21.FEB.2022 07:18:20


Lora FHSS, Data rate SF10

Low Channel




Date: 21.FEB.2022 06:44:26

Middle Channel



Date: 21.FEB.2022 06:41:33

High Channel




Date: 21.FEB.2022 06:39:54

Appendix B.4: 99% Bandwidth


Lora FHSS, Data rate SF7

Low Channel




Date: 21.FEB.2022 07:10:02

Middle Channel



Date: 21.FEB.2022 07:16:33


High Channel



Date: 21.FEB.2022 07:18:36


Lora FHSS, Data rate SF10

Low Channel




Date: 21.FEB.2022 06:44:11

Middle Channel



Date: 21.FEB.2022 06:41:47


High Channel



Date: 21.FEB.2022 06:39:37


Lora DTS

Low Channel




Date: 30.MAR.2022 04:01:13

Middle Channel



Date: 30.MAR.2022 04:07:42

High Channel




Date: 30.MAR.2022 04:13:45


Appendix B.5: Conducted Spurious Emissions Measured in 100 kHz Bandwidth

Lora DTS

Low Channel




Date: 30.MAR.2022 04:02:29




Date: 1.APR.2022 10:47:39

Middle Channel



Date: 30.MAR.2022 04:05:26




Date: 1.APR.2022 10:48:17

High Channel




Date: 30.MAR.2022 04:24:33




Date: 1.APR.2022 10:49:13

Lora FHSS, Data rate SF7, No hopping
Low Channel




Date: 30.MAR.2022 04:47:27




Date: 1.APR.2022 10:53:39

Middle Channel




Date: 30.MAR.2022 04:44:04




Date: 1.APR.2022 10:54:28

High Channel




Date: 30.MAR.2022 04:42:10




Date: 1.APR.2022 10:55:15

Lora FHSS, Data rate SF10, No hopping

Low Channel




Date: 30.MAR.2022 07:08:44




Date: 1.APR.2022 11:01:21

Middle Channel




Date: 30.MAR.2022 07:09:48




Date: 1.APR.2022 11:01:55

High Channel




Date: 30.MAR.2022 07:11:40




Date: 1.APR.2022 11:02:39

Lora FHSS, Data rate SF7, hopping




Date: 21.FEB.2022 07:25:01




Date: 1.APR.2022 10:56:52

Lora FHSS, Data rate SF10, hopping




Date: 7.APR.2022 03:36:47



Date: 7.APR.2022 09:22:32


Lora DTS, Band Edge

Low Channel




Date: 30.MAR.2022 04:03:36

High Channel




Date: 30.MAR.2022 04:32:17

Lora FHSS, Data rate SF7, No hopping, Band Edge
Low Channel




Date: 30.MAR.2022 04:48:17

High Channel




Date: 30.MAR.2022 04:43:03

Lora FHSS, Data rate SF10, No hopping, Band Edge
Low Channel




Date: 30.MAR.2022 07:09:11

High Channel




Date: 30.MAR.2022 07:12:21

Lora FHSS, Data rate SF7, hopping, Band Edge




Date: 7.APR.2022 03:37:25




Date: 7.APR.2022 03:38:30

Lora FHSS, Data rate SF10, hopping, Band Edge



Date: 7.APR.2022 03:37:25




Date: 7.APR.2022 03:38:30

Appendix B.6: Carrier Frequency Separation


Lora FHSS, Data rate SF7

Low Channel




Date: 21.FEB.2022 06:55:42

Middle Channel



Date: 21.FEB.2022 06:54:19


High Channel



Date: 21.FEB.2022 06:53:13


Lora FHSS, Data rate SF10

Low Channel




Date: 7.APR.2022 03:44:53

Middle Channel



Date: 7.APR.2022 03:44:20

High Channel



Date: 7.APR.2022 03:43:18


Note 1: Testing was carried out within frequency range 9 kHz to the tenth harmonics. The measurement results below 30MHz and above 18GHz were greater than 20dB below the limit, so only the radiated spurious emissions from 30MHz to 18GHz were reported.

Appendix B.7: Test Results of Radiated Spurious Emissions

Lora FHSS SF7 , Antenna Gain: 0.8dBi

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK 125K_SF7_902.3MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
71.758500	28.41	40.00	11.59	100.0	H	298.0	-22.4
95.426500	35.78	43.50	7.72	100.0	H	150.0	-19.7
168.031000	29.93	43.50	13.57	100.0	H	269.0	-21.3
480.031500	33.15	46.00	12.85	100.0	H	117.0	-12.2

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK 125K_SF7_902.3MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
40.621500	25.17	40.00	14.83	100.0	V	325.0	-19.9
83.641000	29.52	40.00	10.48	100.0	V	256.0	-22.6
95.960000	36.11	43.50	7.39	100.0	V	243.0	-19.6
319.981500	25.38	46.00	20.62	100.0	V	263.0	-15.8
726.993500	30.98	46.00	15.02	100.0	V	15.0	-7.5

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK 125K_SF7_908.5MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
71.952500	28.66	40.00	11.34	100.0	H	316.0	-22.5
95.669000	36.23	43.50	7.27	100.0	H	158.0	-19.7
168.031000	29.60	43.50	13.90	100.0	H	276.0	-21.3
215.997500	30.32	43.50	13.18	100.0	H	198.0	-18.7
480.031500	34.32	46.00	11.68	100.0	H	25.0	-12.2

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK 125K_SF7_908.5MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
49.933500	25.06	40.00	14.94	100.0	V	0.0	-18.3
83.835000	32.06	40.00	7.94	100.0	V	232.0	-22.6
95.863000	35.96	43.50	7.54	100.0	V	258.0	-19.6
292.433500	24.45	46.00	21.55	100.0	V	258.0	-16.5
647.453500	30.26	46.00	15.74	100.0	V	62.0	-9.1

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK 125K_SF7_914.9MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
71.758500	28.84	40.00	11.16	100.0	H	272.0	-22.4
95.814500	36.19	43.50	7.31	100.0	H	316.0	-19.6
167.982500	29.77	43.50	13.73	100.0	H	300.0	-21.3
479.983000	32.33	46.00	13.67	100.0	H	122.0	-12.2

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK 125K_SF7_914.9MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
59.827500	26.47	40.00	13.53	100.0	V	210.0	-18.9
83.932000	29.36	40.00	10.64	100.0	V	256.0	-22.6
95.814500	36.69	43.50	6.81	100.0	V	218.0	-19.6
329.778500	25.95	46.00	20.05	100.0	V	245.0	-15.5
614.813000	30.35	46.00	15.65	100.0	V	210.0	-9.6

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK 125K_SF7_902.3MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1804.175000	54.61	---	74.00	19.39	100.0	H	235.0	4.7
1804.175000	---	52.35	54.00	1.65	100.0	H	235.0	4.7
2707.000000	55.11	---	74.00	18.89	100.0	H	46.0	7.6
2707.000000	---	51.93	54.00	2.07	100.0	H	46.0	7.6

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK 125K_SF7_902.3MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1804.175000	46.10	---	74.00	27.90	100.0	V	358.0	4.7
1804.175000	---	42.57	54.00	11.43	100.0	V	358.0	4.7
2706.162500	50.35	---	74.00	23.65	100.0	V	279.0	7.5
2707.000000	---	43.70	54.00	10.30	100.0	V	306.0	7.6

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK 125K_SF7_908.5MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1816.737500	51.28	---	74.00	22.72	100.0	H	0.0	4.8
1816.737500	---	48.10	54.00	5.90	100.0	H	0.0	4.8
2725.425000	54.98	---	74.00	19.02	100.0	H	36.0	7.7
2725.425000	---	52.06	54.00	1.94	100.0	H	36.0	7.7

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK 125K_SF7_908.5MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1816.737500	48.50	---	74.00	25.50	100.0	V	258.0	4.8
1816.737500	---	44.08	54.00	9.92	100.0	V	258.0	4.8
2725.425000	51.15	---	74.00	22.85	100.0	V	258.0	7.7
2725.425000	---	46.51	54.00	7.49	100.0	V	258.0	7.7

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK 125K_SF7_914.9MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1829.300000	---	47.72	54.00	6.28	100.0	H	0.0	4.9
1830.137500	50.30	---	74.00	23.70	100.0	H	152.0	4.9
2744.687500	54.96	---	74.00	19.04	100.0	H	47.0	7.8
2744.687500	---	52.41	54.00	1.59	100.0	H	47.0	7.8

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK 125K_SF7_914.9MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1829.300000	46.15	---	74.00	27.85	100.0	V	266.0	4.9
1829.300000	---	42.15	54.00	11.85	100.0	V	266.0	4.9
2744.687500	49.11	---	74.00	24.89	100.0	V	248.0	7.8
2744.687500	---	44.32	54.00	9.68	100.0	V	248.0	7.8

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK 125K_SF7_902.3MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9021.500000	42.69	---	74.00	31.31	100.0	H	70.0	8.9
9028.000000	---	31.71	54.00	22.29	100.0	H	28.0	8.9

EUT Information

EUT Name: WisBlock LPWAN Module
 Model: RAK13300
 Test Mode: FSK 125K_SF7_902.3MHz
 Order No/Sample No: 168358593/A003207710-009
 Test Voltage:: DC 5V From USB
 Remark: Temp 22 Humi:55%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
8120.500000	---	35.29	54.00	18.71	100.0	V	261.0	8.6
8121.500000	42.82	---	74.00	31.18	100.0	V	261.0	8.6

EUT Information

EUT Name: WisBlock LPWAN Module
 Model: RAK13300
 Test Mode: FSK 125K_SF7_908.5MHz
 Order No/Sample No: 168358593/A003207710-009
 Test Voltage:: DC 5V From USB
 Remark: Temp 22 Humi:55%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9085.000000	---	32.20	54.00	21.80	100.0	H	53.0	9.5
9089.000000	43.08	---	74.00	30.92	100.0	H	359.0	9.6

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK 125K_SF7_908.5MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
8176.500000	43.95	---	74.00	30.05	100.0	V	44.0	8.5
8176.500000	---	35.45	54.00	18.55	100.0	V	44.0	8.5

EUT Information

EUT Name: WisBlock LPWAN Module
 Model: RAK13300
 Test Mode: FSK 125K_SF7_914.9MHz
 Order No/Sample No: 168358593/A003207710-009
 Test Voltage:: DC 5V From USB
 Remark: Temp 22 Humi:55%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9147.000000	43.90	---	74.00	30.10	100.0	H	130.0	10.1
9148.000000	---	32.12	54.00	21.88	100.0	H	160.0	10.1

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK 125K_SF7_914.9MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
8234.000000	41.62	---	74.00	32.38	100.0	V	237.0	8.4
8234.000000	---	34.37	54.00	19.63	100.0	V	237.0	8.4

Lora DTS, Antenna Gain: 0.8dBi

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_903MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
71.661500	28.06	40.00	11.94	100.0	H	303.0	-22.4
95.717500	38.03	43.50	5.47	100.0	H	291.0	-19.7
168.031000	29.70	43.50	13.80	100.0	H	267.0	-21.3
263.915500	29.03	46.00	16.97	100.0	H	190.0	-17.0
479.983000	34.55	46.00	11.45	100.0	H	24.0	-12.2

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_903MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
50.030500	26.45	40.00	13.55	100.0	V	136.0	-18.3
83.883500	29.59	40.00	10.41	100.0	V	250.0	-22.6
95.766000	36.47	43.50	7.03	100.0	V	236.0	-19.7
318.866000	25.50	46.00	20.50	100.0	V	278.0	-15.8
730.970500	31.93	46.00	14.07	100.0	V	177.0	-7.5

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_907.8MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
71.710000	29.07	40.00	10.93	100.0	H	343.0	-22.4
95.669000	36.10	43.50	7.40	100.0	H	285.0	-19.7
167.982500	29.43	43.50	14.07	100.0	H	280.0	-21.3
252.033000	27.77	46.00	18.23	100.0	H	189.0	-17.3
480.031500	33.17	46.00	12.83	100.0	H	43.0	-12.2

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_907.8MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
37.469000	24.49	40.00	15.51	100.0	V	219.0	-21.0
83.786500	29.89	40.00	10.11	100.0	V	232.0	-22.6
95.669000	36.30	43.50	7.20	100.0	V	213.0	-19.7
168.031000	21.14	43.50	22.36	100.0	V	244.0	-21.3
378.909000	24.95	46.00	21.05	100.0	V	93.0	-14.3
628.587000	29.97	46.00	16.03	100.0	V	119.0	-9.4

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_914.2MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
72.001000	27.76	40.00	12.24	100.0	H	340.0	-22.5
84.077500	30.80	40.00	9.20	100.0	H	166.0	-22.5
95.717500	34.41	43.50	9.09	100.0	H	296.0	-19.7
168.031000	31.04	43.50	12.46	100.0	H	276.0	-21.3
275.458500	28.72	46.00	17.28	100.0	H	172.0	-16.8
480.031500	33.69	46.00	12.31	100.0	H	18.0	-12.2

EUT Information

EUT Name: WisBlock LPWAN Module
 Model: RAK13300
 Test Mode: Lora_DTS 500K_SF8_914.2MHz
 Order No/Sample No: 168358593/A003207710-009
 Test Voltage:: DC 5V From USB
 Remark: Temp 22 Humi:55%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
35.771500	36.95	40.00	3.05	100.0	V	25.0	-21.7
59.779000	30.79	40.00	9.21	100.0	V	164.0	-18.9
95.960000	34.89	43.50	8.61	100.0	V	31.0	-19.6
168.031000	23.91	43.50	19.59	100.0	V	228.0	-21.3
437.303000	28.63	46.00	17.37	100.0	V	271.0	-13.2

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_903MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1196.000000	---	38.54	54.00	15.46	100.0	H	175.0	1.1
1197.000000	52.41	---	74.00	21.59	100.0	H	175.0	1.1
1805.850000	52.79	---	74.00	21.21	100.0	H	0.0	4.8
1805.850000	---	50.62	54.00	3.38	100.0	H	0.0	4.8
2708.675000	---	52.08	54.00	1.92	100.0	H	46.0	7.6
2709.512500	55.33	---	74.00	18.67	100.0	H	46.0	7.6

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_903MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1805.850000	49.07	---	74.00	24.93	100.0	V	246.0	4.8
1805.850000	---	45.61	54.00	8.39	100.0	V	246.0	4.8
2708.675000	49.84	---	74.00	24.16	100.0	V	263.0	7.6
2709.512500	---	46.05	54.00	7.95	100.0	V	263.0	7.6

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_907.8MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1815.062500	51.84	---	74.00	22.16	100.0	H	1.0	4.8
1815.062500	---	49.07	54.00	4.93	100.0	H	1.0	4.8
2722.912500	56.42	---	74.00	17.58	100.0	H	43.0	7.7
2723.750000	---	52.01	54.00	1.99	100.0	H	52.0	7.7

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_907.8MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1815.062500	48.76	---	74.00	25.24	100.0	V	254.0	4.8
1815.062500	---	46.08	54.00	7.92	100.0	V	254.0	4.8
2722.912500	---	43.11	54.00	10.89	100.0	V	280.0	7.7
2723.750000	49.53	---	74.00	24.47	100.0	V	270.0	7.7

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_914.2MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1828.462500	---	49.47	54.00	4.53	100.0	H	167.0	4.9
1828.462500	51.77	---	74.00	22.23	100.0	H	167.0	4.9
2743.012500	54.93	---	74.00	19.07	100.0	H	49.0	7.8
2743.012500	---	52.21	54.00	1.79	100.0	H	49.0	7.8

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_914.2MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1827.625000	48.61	---	74.00	25.39	100.0	V	249.0	4.9
1828.462500	---	44.71	54.00	9.29	100.0	V	258.0	4.9
2743.012500	50.49	---	74.00	23.51	100.0	V	268.0	7.8
2743.012500	---	45.04	54.00	8.96	100.0	V	268.0	7.8

EUT Information

EUT Name: WisBlock LPWAN Module
 Model: RAK13300
 Test Mode: Lora_DTS 500K_SF8_903MHz
 Order No/Sample No: 168358593/A003207710-009
 Test Voltage:: DC 5V From USB
 Remark: Temp 22 Humi:55%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9031.000000	---	31.48	54.00	22.52	100.0	H	59.0	8.9
9031.500000	42.29	---	74.00	31.71	100.0	H	357.0	8.9

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_903MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
8125.000000	43.62	---	74.00	30.38	100.0	V	254.0	8.6
8125.000000	---	35.71	54.00	18.29	100.0	V	254.0	8.6

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_907.8MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9074.500000	41.80	---	74.00	32.20	100.0	H	230.0	9.4
9078.500000	---	31.47	54.00	22.53	100.0	H	5.0	9.4

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_907.8MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
8168.500000	---	37.00	54.00	17.00	100.0	V	247.0	8.5
8169.500000	43.08	---	74.00	30.92	100.0	V	247.0	8.5

EUT Information

EUT Name: WisBlock LPWAN Module
 Model: RAK13300
 Test Mode: Lora_DTS 500K_SF8_914.2MHz
 Order No/Sample No: 168358593/A003207710-009
 Test Voltage:: DC 5V From USB
 Remark: Temp 22 Humi:55%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9141.000000	---	32.27	54.00	21.73	100.0	H	213.0	10.0
9141.500000	43.17	---	74.00	30.83	100.0	H	325.0	10.0

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_914.2MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
8225.500000	42.29	---	74.00	31.71	100.0	V	348.0	8.4
8226.000000	---	33.92	54.00	20.08	100.0	V	348.0	8.4

Lora FHSS SF7, Antenna Gain: 2.3dBi

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK 125K_SF7_902.3MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
71.971154	33.96	40.00	6.04	100.0	H	306.0	-22.7
83.499231	38.06	40.00	1.94	100.0	H	341.0	-23.0
168.001154	27.79	43.50	15.71	100.0	H	291.0	-21.7
240.042308	34.06	46.00	11.94	100.0	H	208.0	-18.0
431.953077	31.21	46.00	14.79	100.0	H	119.0	-13.6
786.898462	32.88	46.00	13.12	100.0	H	306.0	-7.0

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK 125K_SF7_902.3MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
37.498846	25.12	40.00	14.88	100.0	V	45.0	-21.2
83.872308	35.78	40.00	4.22	100.0	V	229.0	-22.9
238.885769	25.71	46.00	20.29	100.0	V	275.0	-18.1
563.947692	28.96	46.00	17.04	100.0	V	287.0	-10.9
788.092308	32.31	46.00	13.69	100.0	V	76.0	-7.0

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK 125K_SF7_908.5MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
71.933846	36.08	40.00	3.92	100.0	H	340.0	-22.7
83.648462	37.57	40.00	2.43	100.0	H	0.0	-23.0
168.001154	26.10	43.50	17.40	100.0	H	0.0	-21.7
242.131539	31.63	46.00	14.37	100.0	H	206.0	-17.9
431.953077	35.33	46.00	10.67	100.0	H	267.0	-13.6
797.531154	34.89	46.00	11.11	100.0	H	298.0	-6.8

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK 125K_SF7_908.5MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
37.498846	20.99	40.00	19.01	100.0	V	132.0	-21.2
83.723077	35.89	40.00	4.11	100.0	V	242.0	-23.0
95.661539	29.87	43.50	13.63	100.0	V	271.0	-20.0
239.967692	27.46	46.00	18.54	100.0	V	290.0	-18.0
539.846923	27.92	46.00	18.08	100.0	V	26.0	-11.4
795.106154	35.22	46.00	10.78	100.0	V	90.0	-6.9

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK 125K_SF7_914.9MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
83.648462	35.73	40.00	4.27	100.0	H	144.0	-23.0
168.001154	26.98	43.50	16.52	100.0	H	293.0	-21.7
215.978846	33.93	43.50	9.57	100.0	H	194.0	-19.0
252.316539	33.52	46.00	12.48	100.0	H	194.0	-17.6
431.953077	31.08	46.00	14.92	100.0	H	202.0	-13.6
793.315385	33.43	46.00	12.57	100.0	H	310.0	-6.9

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK 125K_SF7_914.9MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
37.498846	22.71	40.00	17.29	100.0	V	139.0	-21.2
72.008462	30.59	40.00	9.41	100.0	V	233.0	-22.8
83.909615	36.24	40.00	3.76	100.0	V	250.0	-22.9
242.803077	26.05	46.00	19.95	100.0	V	267.0	-17.9
480.005385	25.80	46.00	20.20	100.0	V	139.0	-12.6
798.277308	33.11	46.00	12.89	100.0	V	198.0	-6.8

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK125K_SF7_902.3MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:52%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2707.000000	53.47	---	74.00	20.53	100.0	H	322.0	7.6
2707.000000	---	49.19	54.00	4.81	100.0	H	322.0	7.6

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK125K_SF7_902.3MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:52%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2707.000000	50.77	---	74.00	23.23	100.0	V	212.0	7.6
2707.000000	---	47.74	54.00	6.26	100.0	V	212.0	7.6

EUT Information

EUT Name: WisBlock LPWAN Module
 Model: RAK13300
 Test Mode: FSK125K_SF7_908.5MHz
 Order No/Sample No: 168358593/A003207710-009
 Test Voltage:: DC 5V From USB
 Remark: Temp 22 Humi:52%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2725.425000	53.73	---	74.00	20.27	100.0	H	331.0	7.7
2725.425000	---	49.89	54.00	4.11	100.0	H	331.0	7.7

EUT Information

EUT Name: WisBlock LPWAN Module
 Model: RAK13300
 Test Mode: FSK125K_SF7_908.5MHz
 Order No/Sample No: 168358593/A003207710-009
 Test Voltage:: DC 5V From USB
 Remark: Temp 22 Humi:52%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1816.737500	44.58	---	74.00	29.42	100.0	V	207.0	4.8
1816.737500	---	38.18	54.00	15.82	100.0	V	207.0	4.8
2725.425000	51.05	---	74.00	22.95	100.0	V	288.0	7.7
2725.425000	---	47.46	54.00	6.54	100.0	V	288.0	7.7

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK125K_SF7_914.9MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:52%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1829.300000	---	36.01	54.00	17.99	100.0	H	232.0	4.9
1830.137500	43.82	---	74.00	30.18	100.0	H	250.0	4.9
2744.687500	53.59	---	74.00	20.41	100.0	H	311.0	7.8
2744.687500	---	50.63	54.00	3.37	100.0	H	311.0	7.8

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK125K_SF7_914.9MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:52%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1829.300000	44.68	---	74.00	29.32	100.0	V	148.0	4.9
1829.300000	---	36.76	54.00	17.24	100.0	V	148.0	4.9
2744.687500	52.08	---	74.00	21.92	100.0	V	317.0	7.8
2744.687500	---	48.20	54.00	5.80	100.0	V	317.0	7.8

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK125K_SF7_902.3MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:52%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9023.000000	---	32.09	54.00	21.91	100.0	H	0.0	8.9
9025.500000	42.45	---	74.00	31.55	100.0	H	45.0	8.9

EUT Information

EUT Name: WisBlock LPWAN Module
 Model: RAK13300
 Test Mode: FSK125K_SF7_902.3MHz
 Order No/Sample No: 168358593/A003207710-009
 Test Voltage:: DC 5V From USB
 Remark: Temp 22 Humi:52%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9022.000000	---	32.23	54.00	21.77	100.0	V	262.0	8.9
9022.500000	42.24	---	74.00	31.76	100.0	V	320.0	8.9

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK125K_SF7_908.5MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:52%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9086.000000	43.43	---	74.00	30.57	100.0	H	325.0	9.5
9087.000000	---	31.92	54.00	22.08	100.0	H	345.0	9.5

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK125K_SF7_908.5MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:52%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
8172.500000	42.28	---	74.00	31.72	100.0	V	70.0	8.5
8176.000000	---	33.56	54.00	20.44	100.0	V	324.0	8.5

EUT Information

EUT Name: WisBlock LPWAN Module
 Model: RAK13300
 Test Mode: FSK125K_SF7_914.9MHz
 Order No/Sample No: 168358593/A003207710-009
 Test Voltage:: DC 5V From USB
 Remark: Temp 22 Humi:52%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9145.000000	---	32.53	54.00	21.47	100.0	H	14.0	10.1
9147.500000	43.17	---	74.00	30.83	100.0	H	288.0	10.1

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	FSK125K_SF7_914.9MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:52%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
8234.500000	---	31.75	54.00	22.25	100.0	V	321.0	8.4
8239.500000	41.80	---	74.00	32.20	100.0	V	262.0	8.4
9148.500000	---	32.58	54.00	21.42	100.0	V	84.0	10.1
9152.000000	43.88	---	74.00	30.12	100.0	V	321.0	10.1

Lora DTS, Antenna Gain: 2.3dBi

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_903MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
83.835000	37.39	40.00	2.61	100.0	H	315.0	-22.9
168.001154	27.11	43.50	16.39	100.0	H	298.0	-21.7
235.938462	33.07	46.00	12.93	100.0	H	202.0	-18.2
431.990385	29.83	46.00	16.17	100.0	H	118.0	-13.6
786.637308	35.73	46.00	10.27	100.0	H	298.0	-7.0

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_903MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
72.008462	30.45	40.00	9.55	100.0	V	240.0	-22.8
83.835000	36.39	40.00	3.61	100.0	V	235.0	-22.9
95.624231	28.53	43.50	14.97	100.0	V	249.0	-20.0
240.005000	25.99	46.00	20.01	100.0	V	249.0	-18.0
579.766154	27.65	46.00	18.35	100.0	V	7.0	-10.6

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_907.8MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
71.933846	34.54	40.00	5.46	100.0	H	146.0	-22.7
83.723077	36.53	40.00	3.47	100.0	H	298.0	-23.0
168.001154	26.72	43.50	16.78	100.0	H	298.0	-21.7
215.978846	33.00	43.50	10.50	100.0	H	193.0	-19.0
251.570385	32.54	46.00	13.46	100.0	H	185.0	-17.7
443.928846	32.76	46.00	13.24	100.0	H	258.0	-13.4
790.218846	35.67	46.00	10.33	100.0	H	306.0	-7.0

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_907.8MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
83.872308	36.29	40.00	3.71	100.0	V	258.0	-22.9
95.736154	30.88	43.50	12.62	100.0	V	215.0	-19.9
232.953846	24.98	46.00	21.02	100.0	V	278.0	-18.3
551.971923	27.17	46.00	18.83	100.0	V	28.0	-11.2
794.434615	33.52	46.00	12.48	100.0	V	69.0	-6.9

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_914.2MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
71.710000	33.53	40.00	6.47	100.0	H	304.0	-22.7
83.723077	37.13	40.00	2.87	100.0	H	312.0	-23.0
168.001154	26.90	43.50	16.60	100.0	H	295.0	-21.7
243.885000	33.20	46.00	12.80	100.0	H	189.0	-17.9
431.990385	32.83	46.00	13.17	100.0	H	287.0	-13.6
794.583846	35.96	46.00	10.04	100.0	H	295.0	-6.9

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_914.2MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:55%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
37.461539	24.21	40.00	15.79	100.0	V	32.0	-21.3
83.835000	38.29	40.00	1.71	100.0	V	228.0	-22.9
95.698846	28.89	43.50	14.61	100.0	V	221.0	-20.0
240.005000	28.93	46.00	17.07	100.0	V	277.0	-18.0
528.095000	28.61	46.00	17.39	100.0	V	301.0	-11.7
796.374615	37.38	46.00	8.62	100.0	V	70.0	-6.9

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_903MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:52%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2708.675000	54.05	---	74.00	19.95	100.0	H	322.0	7.6
2708.675000	---	50.87	54.00	3.13	100.0	H	322.0	7.6

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_903MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:52%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2708.675000	50.88	---	74.00	23.12	100.0	V	214.0	7.6
2708.675000	---	47.56	54.00	6.44	100.0	V	214.0	7.6

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_907.8MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:52%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2722.912500	54.75	---	74.00	19.25	100.0	H	332.0	7.7
2722.912500	---	49.54	54.00	4.46	100.0	H	332.0	7.7

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_907.8MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:52%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1815.062500	45.22	---	74.00	28.78	100.0	V	135.0	4.8
1815.062500	---	37.57	54.00	16.43	100.0	V	135.0	4.8
2723.750000	50.66	---	74.00	23.34	100.0	V	288.0	7.7
2723.750000	---	46.69	54.00	7.31	100.0	V	288.0	7.7

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_914.2MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:52%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2743.012500	54.37	---	74.00	19.63	100.0	H	331.0	7.8
2743.012500	---	51.54	54.00	2.46	100.0	H	331.0	7.8

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_914.2MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:52%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1827.625000	45.41	---	74.00	28.59	100.0	V	87.0	4.9
1828.462500	---	40.12	54.00	13.88	100.0	V	150.0	4.9
2742.175000	---	45.05	54.00	8.95	100.0	V	287.0	7.8
2743.012500	49.79	---	74.00	24.21	100.0	V	43.0	7.8

EUT Information

EUT Name: WisBlock LPWAN Module
 Model: RAK13300
 Test Mode: Lora_DTS 500K_SF8_903MHz
 Order No/Sample No: 168358593/A003207710-009
 Test Voltage:: DC 5V From USB
 Remark: Temp 22 Humi:52%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9031.000000	---	31.76	54.00	22.24	100.0	H	239.0	8.9
9034.000000	42.65	---	74.00	31.35	100.0	H	279.0	8.9

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_903MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:52%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
8126.500000	42.60	---	74.00	31.40	100.0	V	183.0	8.6
8128.000000	---	33.29	54.00	20.71	100.0	V	164.0	8.6
9030.500000	42.70	---	74.00	31.30	100.0	V	133.0	8.9
9031.000000	---	32.62	54.00	21.38	100.0	V	93.0	8.9

EUT Information

EUT Name: WisBlock LPWAN Module
 Model: RAK13300
 Test Mode: Lora_DTS 500K_SF8_907.8MHz
 Order No/Sample No: 168358593/A003207710-009
 Test Voltage:: DC 5V From USB
 Remark: Temp 22 Humi:52%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9072.500000	44.01	---	74.00	29.99	100.0	H	327.0	9.3
9075.500000	---	31.99	54.00	22.01	100.0	H	0.0	9.4

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_907.8MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:52%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
8168.000000	43.23	---	74.00	30.77	100.0	V	335.0	8.5
8170.500000	---	33.98	54.00	20.02	100.0	V	163.0	8.5
9076.000000	---	31.82	54.00	22.18	100.0	V	113.0	9.4
9079.000000	43.79	---	74.00	30.21	100.0	V	183.0	9.4

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_914.2MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:52%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9140.500000	43.14	---	74.00	30.86	100.0	H	221.0	10.0
9142.000000	---	32.28	54.00	21.72	100.0	H	0.0	10.0

EUT Information

EUT Name:	WisBlock LPWAN Module
Model:	RAK13300
Test Mode:	Lora_DTS 500K_SF8_914.2MHz
Order No/Sample No:	168358593/A003207710-009
Test Voltage::	DC 5V From USB
Remark:	Temp 22 Humi:52%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
8227.000000	42.58	---	74.00	31.42	100.0	V	160.0	8.4
8227.000000	---	34.06	54.00	19.94	100.0	V	160.0	8.4

Appendix B.8: Test Results of Conducted Emission on AC Mains

EUT Information

EUT Name: WisBlock LPWAN Module
 Order No: 168358593_P00577628
 Model: RAK13300
 Test Mode: Lora connect
 Test Voltage: AC 120V/60Hz
 Test By: Shower Dai
 Review By: Gary Chen
 Remark: SR1




Critical Freqs

Frequency (MHz)	MaxPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.162000	---	37.84	55.36	17.52	L1	9.6
0.162000	53.19	---	65.36	12.17	L1	9.6
0.580000	---	34.92	46.00	11.08	L1	9.7
0.580000	45.76	---	56.00	10.24	L1	9.7
0.936000	---	33.88	46.00	12.12	L1	9.7
0.936000	46.25	---	56.00	9.75	L1	9.7
1.320000	---	32.91	46.00	13.09	L1	9.7
1.320000	44.67	---	56.00	11.33	L1	9.7
4.880000	---	32.00	46.00	14.00	L1	10.0
4.936000	43.46	---	56.00	12.54	L1	10.0
14.556000	---	29.25	50.00	20.75	L1	10.2
14.556000	44.71	---	60.00	15.29	L1	10.2

EUT Information

EUT Name: WisBlock LPWAN Module
 Order No: 168358593_P00577628
 Model: RAK13300
 Test Mode: Lora connect
 Test Voltage: AC 120V/60Hz
 Test By: Shower Dai
 Review By: Gary Chen
 Remark: SR1



Critical_Freqs

Frequency (MHz)	MaxPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.158000	---	32.81	55.57	22.76	N	9.6
0.158000	52.04	---	65.57	13.53	N	9.6
0.520000	43.15	---	56.00	12.85	N	9.7
0.532000	---	35.75	46.00	10.25	N	9.7
1.004000	---	30.02	46.00	15.98	N	9.7
1.008000	42.65	---	56.00	13.35	N	9.7
4.308000	43.67	---	56.00	12.33	N	9.9
4.336000	---	32.51	46.00	13.49	N	9.9
4.904000	43.94	---	56.00	12.06	N	10.0
4.940000	---	32.38	46.00	13.62	N	10.0
14.704000	---	30.21	50.00	19.79	N	10.2
15.812000	43.92	---	60.00	16.08	N	10.2