FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure										
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)						
0.3-1.34	614	1.63	*(100)	30						
1.34-30	824/f	2.19/f	*(180/f ²)	30						
30-300	27.5	0.073	0.2	30						
300-1500	/	/	f/1500	30						
1500-100,000	/	/	1.0	30						

Limits for General Population/Uncontrolled Exposure

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$\mathbf{S} = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm2) P = power input to the antenna (in appropriate units, e.g., mW).

- G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.
- R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} \leq 1$$

FCC Part 15.247

Bay Area Compliance Laboratories Corp. (Shenzhen)

Report No.: RSZ200812005-00B

Mode	Frequency (MHz)	Antenna Gain		Tune up conducted power		Evaluation Distance	Power Density	MPE Limit
		(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm^2)	$(\mathrm{mW/cm}^2)$
BLE	2402-2480	1.75	1.5	3.5	2.24	20	0.001	1.0
Wi-Fi	2412-2462	1.75	1.5	18.5	70.79	20	0.021	1.0
Lora	923.3-927.5	2.3	1.7	13.0	19.95	20	0.007	0.6

Note: 1. The tune up conducted power was declared by the applicant
2. Lora, BLE and Wi-Fi can transmit simultaneously for this device..
3. Please refer to the MPE report of the FCC ID: 2AF6B-RAK2247 for the Lora output power.

So the worst simultaneous transmitting consideration:

The ratio=MPE_{BLE}/limit + MPE_{Wi-Fi}/limit + MPE_{Lora}/limit = $0.001/1.0 + 0.021/1.0 + 0.007/0.6 = 0.034 \le 1.0$

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliance