

---

# FCC Test Report

---

Report No.: AGC04499161101FE02


**FCC ID** : 2AF6M3396993M135  
**APPLICATION PURPOSE** : Original Equipment  
**PRODUCT DESIGNATION** : 2G Feature Phone  
**BRAND NAME** : Cellacom  
**MODEL NAME** : M135  
**CLIENT** : Mobile commodity corporation  
**DATE OF ISSUE** : Nov. 11, 2016  
**STANDARD(S)** : FCC Part 22H & 24E Rules  
**TEST PROCEDURE(S)**  
**REPORT VERSION** : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



**CAUTION:**

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



### Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Nov. 11, 2016	Valid	Original Report

## TABLE OF CONTENTS

<b>TABLE OF CONTENTS</b> .....	<b>3</b>
1. VERIFICATION OF COMPLIANCE.....	5
<b>2. GENERAL INFORMATION</b> .....	<b>6</b>
2.1 PRODUCT DESCRIPTION.....	6
2.2 RELATED SUBMITTAL(S) / GRANT (S) .....	7
2.3 TEST METHODOLOGY.....	7
2.4 TEST FACILITY .....	7
2.5 MEASUREMENT INSTRUMENTS.....	8
2.6 SPECIAL ACCESSORIES .....	9
2.7 EQUIPMENT MODIFICATIONS.....	9
<b>3. SYSTEM TEST CONFIGURATION</b> .....	<b>10</b>
3.1 EUT CONFIGURATION .....	10
3.2 EUT EXERCISE.....	10
3.3 GENERAL TECHNICAL REQUIREMENTS.....	10
3.4 CONFIGURATION OF EUT SYSTEM .....	11
<b>4. SUMMARY OF TEST RESULTS</b> .....	<b>12</b>
<b>5. DESCRIPTION OF TEST MODES</b> .....	<b>12</b>
<b>6. OUTPUT POWER</b> .....	<b>13</b>
6.1 CONDUCTED OUTPUT POWER .....	13
6.2 RADIATED OUTPUT POWER.....	16
<b>7. PEAK-TO-AVERAGE RATIO</b> .....	<b>20</b>
7.1 MEASUREMENT METHOD .....	20
7.2 PROVISIONS APPLICABLE .....	20
7.3 MEASUREMENT RESULT .....	21

<b>8. OCCUPIED BANDWIDTH .....</b>	<b>22</b>
8.1 TEST OVERVIEW .....	22
8.2 PROVISIONS APPLICABLE .....	22
8.3 MEASUREMENT RESULT .....	22
Appendix A: BandWidth.....	22
<b>9. BAND EDGE .....</b>	<b>29</b>
9.1 MEASUREMENT METHOD .....	29
9.2 PROVISIONS APPLICABLE .....	29
9.3 MEASUREMENT RESULT .....	29
APPENDIX B: BAND EDGES COMPLIANCE.....	29
<b>10. SPURIOUS EMISSION .....</b>	<b>34</b>
10.1 CONDUCTED SPURIOUS EMISSION.....	34
APPENDIX C: SPURIOUS EMISSION AT ANTENNA TERMINAL.....	35
10.2 RADIATED SPURIOUS EMISSION .....	53
<b>11. MAINS CONDUCTED EMISSION.....</b>	<b>57</b>
11.1 MEASUREMENT METHOD .....	57
11.2 PROVISIONS APPLICABLE .....	57
11.3 MEASUREMENT RESULT.....	58
<b>12. FREQUENCY STABILITY .....</b>	<b>60</b>
12.1 MEASUREMENT METHOD .....	60
12.2 PROVISIONS APPLICABLE .....	60
12.3 MEASUREMENT RESULT.....	61
Appendix D: Frequency Stability .....	61
<b>PHOTOGRAPHS OF TEST SETUP .....</b>	<b>65</b>
<b>APPENDIX B: PHOTOGRAPHS OF EUT .....</b>	<b>67</b>

## 1. VERIFICATION OF COMPLIANCE

<b>Applicant</b>	Mobile commodity corporation
<b>Address</b>	20955 Pathfinder Rroad, Suite 200,Diamond Bar,California 91765,United States
<b>Manufacturer</b>	Cellacom Incorporation
<b>Address</b>	20955 pathfinder road, Suite 100, Diamond bar, CA 91765,USA
<b>Product Designation</b>	2G Feature Phone
<b>Brand name</b>	Cellacom
<b>Test Model</b>	M135
<b>Date of Test</b>	Nov 2, 2016 to Nov 10, 2016
<b>Deviation</b>	None
<b>Condition of Test Sample</b>	Normal
<b>Report Template</b>	AGCRT-US-2.5G/RF

### WE HEREBY CERTIFY THAT:

The above equipment was tested by Dongguan Precise Testing Service Co., Ltd. The data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI/TIA- 603-D-2010. The sample tested as described in this report is in compliance with the FCC Rules Part 22H and 24E.

The test results of this report relate only to the tested sample identified in this report.

Tested By

*Dota Zhang*

Dota Zhang(Zhang Jianfeng)

Nov 10, 2016

Reviewed By

*Bart Xie*

Bart Xie(Xie Xiaobin)

Nov. 11, 2016

Approved By

*Solger Zhang*

Solger Zhang(Zhang Hongyi)

Authorized Officer

Nov. 11, 2016

## 2. GENERAL INFORMATION

### 2.1 PRODUCT DESCRIPTION

A major technical description of EUT is described as following:

Product Designation:	2G Feature Phone
Hardware Version:	HCC606_MAIN_PCB (V2.0)
Software Version:	CELLACOM_M135_V03
Frequency Bands:	<input checked="" type="checkbox"/> GSM 850 <input checked="" type="checkbox"/> PCS 1900 (U.S. Bands) <input checked="" type="checkbox"/> GSM 900 <input checked="" type="checkbox"/> DCS 1800 (Non-U.S. Bands)
Antenna:	PIFA Antenna
Antenna gain:	1.0dBi
Battery parameter:	DC3.7V/700mAh
Adapter Input:	AC100-240V, 50-60Hz
Adapter Output:	DC5.0V, 500mA
Output Power:	30.59dBm Maximum ERP measured for GSM 850 31.25dBm Maximum Average Burst Power for GSM 850 28.39dBm Maximum EIRP measured for PCS 1900 28.35dBm Maximum Average Burst Power for PCS 1900
Dual SIM Card:	The result for SIM1 is the worst case which was only recorded
GPRS Class:	12
Extreme Vol. Limits:	DC 3.4 V to DC4.2 V (Nominal DC 3.7 V)
Extreme Temp. Tolerance:	-10°C to +50°C
<p>** Note: 1.The High Voltage DC 4.2V and Low Voltage DC 3.4V were declared by manufacturer, The EUT could not operate normally with higher or lower voltage.</p> <p>2. Other functions have been performed according to verification procedure except for MS function.</p> <p>3. SIM1 and SIM2 can't transmit simultaneously.</p>	

## 2.2 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: 2AF6M3396993M135** filing to comply with the FCC Part 22H and 24E requirements.

## 2.3 TEST METHODOLOGY

The radiated emission testing was performed according to the procedures of ANSI/TIA-603-D-2010, and FCC CFR 47 Rules of 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057.

KDB 971168 D01 Power Meas License Digital Systems v02r02

## 2.4 TEST FACILITY

<b>Site</b>	Dongguan Precise Testing Service Co., Ltd.
<b>Location</b>	Building D, Baoding Technology Park, Guangming Road 2, Dongcheng District, Dongguan, Guangdong, China,
<b>FCC Registration No.</b>	371540
<b>Description</b>	The test site is constructed and calibrated to meet the FCC requirements in documents of ANSI/TIA-603-D-2010.

## 2.5 MEASUREMENT INSTRUMENTS

Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 3, 2016	July 2, 2017
Trilog Broadband Antenna (25M-1GHz)	SCHWARZBECK	VULB9168	D69250	Mar 1, 2016	Feb 28, 2017
Trilog Broadband Antenna(substituted antenna) (25M-1GHz)	SCHWARZBECK	VULB9160	9160-3355	July 3, 2016	July 2, 2017
Signal Amplifier	SCHWARZBECK	BBV 9475	9745-0013	July 3, 2016	July 2, 2017
RF Cable	SCHWARZBECK	AK9515E	96221	July 3, 2016	July 2, 2017
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 5, 2016	June 4, 2017
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A
Active loop antenna (9K-30MHz)	Schwarzbeck	FMZB1519	1519-038	June 5, 2016	June 4, 2017
Spectrum analyzer	Agilent	E4407B	MY46185649	June 5, 2016	June 4, 2017
Horn Antenna (1G-18GHz)	SCHWARZBECK	BBHA9120D	9120D-1246	July 10, 2016	July 9, 2017
Horn Antenna(substituted antenna) (1G-18GHz)	ETS LINDGREN	3117	00034609	Mar 1, 2016	Feb 28, 2017
Spectrum Analyzer	Agilent	E4411B	MY4511453	July 3, 2016	July 2, 2017
Signal Amplifier	SCHWARZBECK	BBV 9718	9718-269	July 6, 2016	July 5, 2017
RF Cable	SCHWARZBECK	AK9515H	96220	July 7, 2016	July 6, 2017
Horn Ant (18G-40GHz)	Schwarzbeck	BBHA 9170	9170-181	June 5, 2016	June 4, 2017
Artificial Mains Network	Narda	L2-16B	000WX31025	July 7, 2016	July 6, 2017
Artificial Mains Network (AUX)	Narda	L2-16B	000WX31026	July 7, 2016	July 6, 2017
RF Cable	SCHWARZBECK	AK9515E	96222	July 3, 2016	July 2, 2017
Shielded Room	CHENGYU	843	PTS-002	June 5, 2016	June 4, 2017
COMMUNICATION TESTER	AGILENT	8960	GB46490550	July 24,2016	July 23, 2017
RF attenuator	N/A	RFA20db	68	N/A	N/A
Signal Generator	AGILENT	N5182A	MY50140530	Oct 15,2016	Oct 14,2017
Signal Generator(substituted equipment)	AGILENT	E8257D	MY45141029	Oct 15,2016	Oct 14,2017



## **2.6 SPECIAL ACCESSORIES**

The battery and the charger supplied by the applicant were used as accessories and being tested with EUT intended for FCC grant together.

## **2.7 EQUIPMENT MODIFICATIONS**

Not available for this EUT intended for grant.

### 3. SYSTEM TEST CONFIGURATION

#### 3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

#### 3.2 EUT EXERCISE

The Transmitter was operated in the maximum output power mode through Communication Tester. The TX frequency was fixed which was for the purpose of the measurements.

#### 3.3 GENERAL TECHNICAL REQUIREMENTS

Item Number	Item Description		FCC Rules
1	Output Power	Conducted	22.913(a) / 24.232 (b)
		Radiated	
2	Peak-to-Average Ratio	Peak-to-Average Ratio	24.232(d)
3	Spurious Emission	Conducted Spurious Emission	2.1051 / 22.917 / 24.238
		Radiated Spurious Emission	
4	Mains Conducted Emission		15.107 / 15.207
5	Frequency Stability		2.1055 /24.235
6	Occupied Bandwidth		2.1049 (h)(i)
7	Emission Bandwidth		22.917(b) / 24.238 (b)
8	Band Edge		22.917(b) / 24.238 (b)

### 3.4 CONFIGURATION OF EUT SYSTEM

Fig. 2-1 Configuration of EUT System




Table 2-1 Equipment Used in EUT System

Item	Equipment	Model No.	ID or Specification	Note
1	2G Feature Phone	M135	FCC ID: 2AF6M3396993M135	EUT
2	Adapter	M135	DC5.0V / 500mA	Accessory
3	Battery	M135	DC3.7V/ 700mAh	Accessory

**Note:** All the accessories have been used during the test. The following “EUT” in setup diagram means EUT system.

#### 4. SUMMARY OF TEST RESULTS

Item Number	Item Description		FCC Rules	Result
1	Output Power	Conducted Output Power	22.913(a) / 24.232 (b)	Pass
		Radiated Output Power		
2	Peak-to-Average Ratio	Peak-to-Average Ratio	24.232(d)	Pass
3	Spurious Emission	Conducted Spurious Emission	2.1051/22.917/ 24.238	Pass
		Radiated Spurious Emission		
4	Mains Conducted Emission		15.107 / 15.207	Pass
5	Frequency Stability		2.1055 /24.235	Pass
6	Occupied Bandwidth		2.1049 (h)(i)	Pass
7	Emission Bandwidth		22.917(b) / 24.238 (b)	Pass
8	Band Edge		22.917(b) / 24.238 (b)	Pass

#### 5. DESCRIPTION OF TEST MODES

During the testing, the EUT (Quad-band GSM / GPRS Mobile Phone) was controlled via Rhode & Schwarz Digital Radio Communication Tester (CMU 200) to ensure max power transmission and proper modulation. Three channels (The top channel, the middle channel and the bottom channel) were chosen for testing on both GSM and PCS frequency band.

- Note:**
1. GSM and GPRS modes have been tested during the test. The worst condition (GSM) be recorded in the test report if no other modes test data.
  2. All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions
  3. All antenna port conducted emissions testing was performed on a test bench with the antenna Port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.

## 6. OUTPUT POWER

### 6.1 CONDUCTED OUTPUT POWER

#### 6.1.1 MEASUREMENT METHOD

The transmitter output port was connected to base station.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Measure the maximum burst average power and average power for other modulation signal.

The EUT was setup for the max output power with pseudo random data modulation. Power was measured with Spectrum Analyzer. The measurements were performed on all modes(GSM, GPRS,) at 3 typical channels(the Top Channel, the Middle Channel and the Bottom Channel) for both GSM band and PCS band.

#### 6.1.2 PROVISIONS APPLICABLE

Conducted Output Power Limits for GSM 850 MHz			
Mode	Power Step	Nominal Peak Power	Tolerance(dB)
GSM	5	33 dBm (2W)	-2
GPRS	3	33 dBm (2W)	-2

Conducted Output Power Limits for PCS 1900 MHz			
Mode	Power Step	Nominal Peak Power	Tolerance(dB)
GSM	0	30 dBm (1W)	-2
GPRS	3	30 dBm (1W)	-2

### 6.1.3 MEASUREMENT RESULT

#### Test Result of Conducted Output Power for GSM 850 MHZ (SIM1)

Mode	Frequency (MHz)	Reference Power	Peak Power	Tolerance	Avg.Burst Power	Duty cycle Factor(dB)	Frame Power(dBm)
GSM(SIM1)	824.2	33	<b>32.13</b>	-0.87	<b>31.25</b>	-9	22.25
	836.6	33	31.86	-1.14	31.16	-9	22.16
	848.8	33	31.92	-1.08	31.09	-9	22.09
GPRS850 (1 Slot)	824.2	33	31.41	-1.59	30.37	-9	21.37
	836.6	33	31.22	-1.78	30.52	-9	21.52
	848.8	33	31.17	-1.83	30.24	-9	21.24
GPRS850 (2 Slot)	824.2	30	29.56	-0.44	28.63	-6	22.63
	836.6	30	29.38	-0.62	28.19	-6	22.19
	848.8	30	29.27	-0.73	28.23	-6	22.23
GPRS850 (3 Slot)	824.2	28.23	27.45	-0.78	26.26	-4.26	22
	836.6	28.23	27.13	-1.1	26.38	-4.26	22.12
	848.8	28.23	27.26	-0.97	26.14	-4.26	21.88
GPRS850 (4 Slot)	824.2	27	26.54	-0.46	25.39	-3	22.39
	836.6	27	26.24	-0.76	25.86	-3	22.86
	848.8	27	26.39	-0.61	25.73	-3	22.73

**Test Result of Conducted Output Power for PCS 1900 MHZ (SIM1)**

Mode	Frequency (MHz)	Reference Power	Peak Power	Tolerance	Avg.Burst Power	Duty cycle Factor(dB)	Frame Power(dBm)
GSM(SIM1)	1850.2	30	<b>29.26</b>	-0.74	<b>28.35</b>	-9	19.35
	1880	30	28.79	-1.21	28.26	-9	19.26
	1909.8	30	28.89	-1.11	28.27	-9	19.27
GPRS1900 (1 Slot)	1850.2	30	28.43	-1.57	27.41	-9	18.41
	1880	30	28.28	-1.72	27.52	-9	18.52
	1909.8	30	28.31	-1.69	27.66	-9	18.66
GPRS1900 (2 Slot)	1850.2	27	26.19	-0.81	25.47	-6	19.47
	1880	27	26.26	-0.74	25.72	-6	19.72
	1909.8	27	26.57	-0.43	25.28	-6	19.28
GPRS1900 (3 Slot)	1850.2	25.23	24.23	-1	23.23	-4.26	18.97
	1880	25.23	24.46	-0.77	23.19	-4.26	18.93
	1909.8	25.23	24.27	-0.96	23.28	-4.26	19.02
GPRS1900 (4 Slot)	1850.2	24	23.18	-0.82	22.08	-3	19.08
	1880	24	23.36	-0.64	22.24	-3	19.24
	1909.8	24	23.29	-0.71	22.53	-3	19.53

**Test Result of Conducted Output Power for GSM 850 MHZ and PCS 1900 MHZ(SIM 2)**

Mode	Maximum Conducted Power(dBm)	Average Burst Power(dBm)	Duty cycle Factor (dB)	Frame Power (dBm)
GSM 850 MHZ for (SIM2)	31.82	31.21	-9	22.21
PCS 1900 MHZ for (SIM2)	28.55	28.32	-9	19.32

## 6.2 RADIATED OUTPUT POWER

### 6.2.1 MEASUREMENT METHOD

The measurements procedures specified in ANSI/TIA-603-D-2010 were applied.

1. Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-D-2010 with the EUT transmitting into an integral antenna. Measurements on signal operating below 1GHz are performed using dipole antennas. Measurements on signals operating above 1GHz are performed using broadband horn antennas. All measurements are performed as RMS average measurements while the EUT operating at its maximum duty cycle, at maximum power, and at the approximate frequencies.
2. In an anechoic antenna test chamber, a half-wave dipole antenna for the frequency band of interest is placed at the reference centre of the chamber. An RF Signal source for the frequency band of interest is connected to the dipole with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A known (measured) power ( $P_{in}$ ) is applied to the input of the dipole, and the power received ( $P_r$ ) at the chamber's probe antenna is recorded.
3. The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established as  $AR_{pl} = P_{in} + 2.15 - P_r$ . The  $AR_{pl}$  is the attenuation of "reference path loss", and including the gain of receive antenna, the cable loss and the air loss. The measurement results are obtained as described below:  $Power = P_{Mea} + AR_{pl}$
4. The EUT is substituted for the dipole at the reference centre of the chamber and a scan is performed to obtain the radiation pattern.
5. From the radiation pattern, the co-ordinates where the maximum antenna gain occurs are identified.
6. The EUT is then put into continuously transmitting mode at its maximum power level.
7. Power mode measurements are performed with the receiving antenna placed at the coordinates determined in Step 3 to determine the output power as defined in Rule 24.232 (b) and (c). The "reference path loss" from Step1 is added to this result.
8. This value is EIRP since the measurement is calibrated using a half-wave dipole antenna of known gain (2.15 dBi) and known input power ( $P_{in}$ ).
9. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15dBi$ .

### 6.2.2 PROVISIONS APPLICABLE

This is the test for the maximum radiated power from the EUT. Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 22.913(a) specifies "Maximum ERP. The effective radiated power (ERP) of base transmitters and cellular repeaters must not exceed 500 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."



<b>Radiated Power Limits for GSM 850 MHZ (ERP)</b>		
<b>Mode</b>	<b>Power Step</b>	<b>Nominal Peak Power</b>
GSM	5	$\leq 38.45$ dBm (7W)
GPRS	3	$\leq 38.45$ dBm (7W)

<b>Radiated Power Limits for PCS 1900 MHZ (E.I.R.P.)</b>		
<b>Mode</b>	<b>Power Step</b>	<b>Nominal Peak Power</b>
GSM	0	$\leq 33$ dBm (2W)
GPRS	3	$\leq 33$ dBm (2W)

**6.2.3 MEASUREMENT RESULT**

<b>Radiated Power (ERP) for GSM 850 MHZ</b>					
<b>Mode</b>	<b>Frequency</b>	<b>Power Step</b>	<b>Result</b>		<b>Conclusion</b>
			<b>Max. Peak ERP (dBm)</b>	<b>Polarization Of Max. ERP</b>	
GSM	824.2	5	<b>30.59</b>	Horizontal	Pass
	836.6	5	30.33	Horizontal	Pass
	848.8	5	30.45	Horizontal	Pass
GPRS 1 slot	824.2	3	30.18	Horizontal	Pass
	836.6	3	30.26	Horizontal	Pass
	848.8	3	30.15	Horizontal	Pass
GPRS 2 slots	824.2	3	Less than 27 dBm	Horizontal	Pass
	836.6	3		Horizontal	Pass
	848.8	3		Horizontal	Pass
GPRS 3 slots	824.2	2		Horizontal	Pass
	836.6	2		Horizontal	Pass
	848.8	2		Horizontal	Pass
GPRS 4 slots	824.2	2		Horizontal	Pass
	836.6	2		Horizontal	Pass
	848.8	2		Horizontal	Pass

Radiated Power (E.I.R.P) for PCS 1900 MHZ					
Mode	Frequency	Power Step	Result		Conclusion
			Max. Peak E.I.R.P.(dBm)	Polarization Of Max. E.I.R.P.	
GSM	1850.2	0	28.39	Horizontal	Pass
	1880.0	0	28.25	Horizontal	Pass
	1909.8	0	28.20	Horizontal	Pass
GPRS 1slot	1850.2	3	28.17	Horizontal	Pass
	1880.0	3	28.28	Horizontal	Pass
	1909.8	3	28.11	Horizontal	Pass
GPRS 2 slots	1850.2	3	Less than 27 dBm	Horizontal	Pass
	1880.0	3		Horizontal	Pass
	1909.8	3		Horizontal	Pass
GPRS 3 slots	1850.2	2		Horizontal	Pass
	1880.0	2		Horizontal	Pass
	1909.8	2		Horizontal	Pass
GPRS 4 slots	1850.2	2		Horizontal	Pass
	1880.0	2		Horizontal	Pass
	1909.8	2		Horizontal	Pass

## 7. PEAK-TO-AVERAGE RATIO

### 7.1 MEASUREMENT METHOD

Use one of the procedures presented in 4.1 to measure the total peak power and record as PPk. Use one of the applicable procedures presented 4.2 to measure the total average power and record as PAvg. Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$\text{PAPR (dB)} = \text{PPk (dBm)} - \text{PAvg (dBm)}.$$

### 7.2 PROVISIONS APPLICABLE

This is the test for the Peak-to-Average Ratio from the EUT.

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

**7.3 MEASUREMENT RESULT**

<b>Modes</b>	<b>GSM850(GSM)</b>		
<b>Channel</b>	<b>128</b>	<b>190</b>	<b>251</b>
	<b>(Low)</b>	<b>(Mid)</b>	<b>(High)</b>
<b>Frequency (MHz)</b>	<b>824.2</b>	<b>836.6</b>	<b>848.8</b>
<b>Peak-To-Average Ratio (dB)/GSM</b>	0.88	0.70	0.83

<b>Modes</b>	<b>PCS 1900 (GSM)</b>		
<b>Channel</b>	<b>512</b>	<b>661</b>	<b>810</b>
	<b>(Low)</b>	<b>(Mid)</b>	<b>(High)</b>
<b>Frequency (MHz)</b>	<b>1850.2</b>	<b>1880</b>	<b>1909.8</b>
<b>Peak-To-Average Ratio (dB)/GSM</b>	0.91	0.53	0.62

## 8. OCCUPIED BANDWIDTH

### 8.1 TEST OVERVIEW

1. The Occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper Frequency limits, the mean power radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured.
2. RBW=1~5% of the expected OBW, VBW>=3 x RBW, Detector=Peak, Trace mode=max hold, Sweep=auto couple, and the trace was allowed to stabilize.

### 8.2 PROVISIONS APPLICABLE

The occupied bandwidth (99%) shall not exceed 300 KHz.

### 8.3 MEASUREMENT RESULT

#### Appendix A: BandWidth

##### Test Results

Test Band	Test Mode	Test Channel	Occupied Bandwidth (kHz)	Emission Bandwidth (kHz)	Verdict
GSM850	GSM	LCH	243.049	312.321	PASS
		MCH	245.250	318.321	PASS
		HCH	243.671	317.483	PASS


Test Band	Test Mode	Test Channel	Occupied Bandwidth (kHz)	Emission Bandwidth (kHz)	Verdict
GSM1900	GSM	LCH	241.446	313.530	PASS
		MCH	243.742	315.803	PASS
		HCH	239.707	316.640	PASS

For GSM



Test Band=GSM850

Test Mode=GSM

Test Channel=LCH




Test Channel=MCH

 <b>Agilent</b>		R	T	<b>Meas Setup</b>	
<b>Ch Freq</b> 836.6 MHz		<b>Trig</b> Free		<b>Avg Number</b> 10 On <u>Off</u>	
Occupied Bandwidth				<b>Avg Mode</b> Exp Repeat	
Ref 30 dBm      Atten 40 dB				<b>Max Hold</b> On Off	
#Peak Log 10 dB/				<b>Occ BW % Pwr</b> 99.00 %	
Center 836.600 MHz		Span 1 MHz		<b>OBW Span</b> 1.00000000 MHz	
#Res BW 10 kHz		#VBW 30 kHz      Sweep 9.56 ms (601 pts)		<b>x dB</b> -26.00 dB	
<b>Occupied Bandwidth</b> 245.2501 kHz		<b>Occ BW % Pwr</b> 99.00 % <b>x dB</b> -26.00 dB		<b>Optimize</b> Ref Level	
<b>Transmit Freq Error</b> -865.769 Hz		<b>x dB Bandwidth</b> 318.321 kHz			
<b>Copyright 2000-2002 Agilent Technologies</b>					




Test Channel=HCH





Test Band=GSM1900

Test Mode=GSM


Test Channel=LCH



Test Channel=MCH

 <b>Agilent</b>		R	T	<b>Freq/Channel</b>	
<b>Ch Freq</b> 1.88 GHz		<b>Trig</b> Free		<b>Center Freq</b> 1.88000000 GHz	
Occupied Bandwidth				<b>Start Freq</b> 1.87950000 GHz	
Ref 30 dBm      Atten 40 dB				<b>Stop Freq</b> 1.88050000 GHz	
#Peak Log 10 dB/				<b>CF Step</b> 100.000000 kHz Auto      Man	
Center 1.880 000 GHz		Span 1 MHz		<b>Freq Offset</b> 0.00000000 Hz	
#Res BW 10 kHz		#VBW 30 kHz		Sweep 9.56 ms (601 pts)	
<b>Occupied Bandwidth</b>		<b>Occ BW % Pwr</b> 99.00 %		<b>Signal Track</b> On      Off	
243.7417 kHz		x dB -26.00 dB			
<b>Transmit Freq Error</b> -648.613 Hz					
<b>x dB Bandwidth</b> 315.803 kHz					
<b>Copyright 2000-2002 Agilent Technologies</b>					

Test Channel=HCH

 <b>Agilent</b>		R	T	<b>Meas Setup</b>	
<b>Ch Freq</b> 1.9098 GHz		<b>Trig</b> Free		<b>Avg Number</b> 10 On <u>Off</u>	
Occupied Bandwidth				<b>Avg Mode</b> Exp Repeat	
Ref 30 dBm      Atten 40 dB				<b>Max Hold</b> On Off	
#Peak Log 10 dB/				<b>Occ BW % Pwr</b> 99.00 %	
Center 1.909 800 GHz		Span 1 MHz		<b>OBW Span</b> 1.00000000 MHz	
#Res BW 10 kHz		#VBW 30 kHz		<b>x dB</b> -26.00 dB	
		Sweep 9.56 ms (601 pts)		<b>Optimize</b> Ref Level	
<b>Occupied Bandwidth</b> 239.7065 kHz		<b>Occ BW % Pwr</b> 99.00 % <b>x dB</b> -26.00 dB			
<b>Transmit Freq Error</b> 1.076 kHz					
<b>x dB Bandwidth</b> 316.640 kHz					
<b>Copyright 2000-2002 Agilent Technologies</b>					

## **9. BAND EDGE**

### **9.1 MEASUREMENT METHOD**

1. All out of band emissions are measured with an analyzer spectrum connected to the antenna terminal of the EUT while the EUT at its maximum duty cycle, at maximum power, and at the approximate frequencies. All data rates were investigated to determine the worst case configuration
2. The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.
3. Start and stop frequency were set such that the band edge would be placed in the center of the plot.
4. Span was set large enough so as to capture all out of band emissions near the band edge.
5. RBW>1% of the emission bandwidth, VBW  $\geq 3 \times$  RBW, Detector=RMS, Number of points $\geq 2 \times$  Span/RBW, Trace mode=max hold, Sweep time=auto couple, and the trace was allowed to stabilize

### **9.2 PROVISIONS APPLICABLE**

As Specified in FCC rules of 22.917(b) and 24.238(b) and KDB 971168 V02r02

### **9.3 MEASUREMENT RESULT**

## **APPENDIX B: BAND EDGES COMPLIANCE**


### **Test Results**

### **For GSM**


**Test Band=GSM850**

Test Mode=GSM

Test Channel=LCH




Test Channel=HCH



Test Band=GSM1900


Test Mode=GSM

Test Channel=LCH





Test Channel=HCH



## 10. SPURIOUS EMISSION

### 10.1 CONDUCTED SPURIOUS EMISSION

#### 10.1.1 MEASUREMENT METHOD

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. The level of the carrier and the various conducted spurious and harmonic frequency is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the approximate frequencies. All data rates were investigated to determine the worst case configuration.
2. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM 850, data taken from 30 MHz to 9 GHz.
3. Determine EUT transmit frequencies: the following typical channels were chosen to conducted emissions testing.

Typical Channels for testing of GSM 850 MHz	
Channel	Frequency (MHz)
128	824.2
190	836.6
251	848.8

Typical Channels for testing of PCS 1900 MHz	
Channel	Frequency (MHz)
512	1850.2
661	1880.0
810	1909.8

#### 10.1.2 PROVISIONS APPLICABLE

On any frequency outside frequency band of the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least  $43+10\log(P)$  dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.

### 10.1.3 MEASUREMENT RESULT


#### APPENDIX C: SPURIOUS EMISSION AT ANTENNA TERMINAL


##### Test Results

Test Band=GSM850


Test Mode=GSM


Test Channel=LCH







Test Channel=MCH





Test Channel=HCH










Test Band=GSM1900


Test Mode=GSM

Test Channel=LCH













Test Channel=MCH















Test Channel=HCH










## 10.2 RADIATED SPURIOUS EMISSION

### 10.2.1 MEASUREMENT METHOD


The measurements procedures specified in TIA-603-D-2010 were used for testing. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set 1MHz as outlined in Part 24.238. The measurements were performed on all modes(GSM, GPRS) at 3 typical channels(the Top Channel, the Middle Channel and the Bottom Channel) for both GSM band and PCS band.

The procedure of radiated spurious emissions is as follows:

a) Pre-calibration With pre-calibration method, the Radiated Spurious Emissions(RSE) is calculated as,  $RSE = R_x (\text{dBuV}) + CL (\text{dB}) + SA (\text{dB}) + \text{Gain} (\text{dBi}) - 107 (\text{dBuV to dBm})$  The SA is calibrated using following setup.



b) EUT was placed on a 0.8 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the test item for emission measurements. The height of receiving antenna is 0.8m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the test item and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector and 1MHz bandwidth.



Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS band (1850.2 MHz, 1880 MHz and 1909.8 MHz), GSM850 band (824.2MHz, 836.6MHz, 848.8MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the PCS1900, GSM850 into any of the other blocks.

The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established and the  $A_{Rpl}$  is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss and the air loss. The measurement results are obtained as described below:  $Power = P_{Mea} + A_{Rpl}$

### 10.2.2 PROVISIONS APPLICABLE

(a) On any frequency outside a IMOBOnsee's frequency block (e.g. A, D, B, etc.) within the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least  $43 + 10 \log(P)$  dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

**10.2.3 MEASUREMENT RESULT**

<b>The Worst Test Results for Channel 128 / 824.2 MHz</b>					
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity
1648.00	-43.11	-5.01	-48.12	-13.00	Horizontal
1752.00	-42.59	-2.18	-44.77	-13.00	Vertical
2472.00	-47.42	3.46	-43.96	-13.00	Horizontal
9086.00	-45.26	2.79	-42.47	-13.00	Horizontal

<b>The Worst Test Results for Channel 190/836.6 MHz</b>					
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity
1673.00	-43.54	-3.22	-46.76	-13.00	Horizontal
1903.00	-42.69	-0.24	-42.93	-13.00	Vertical
9089.00	-44.16	3.98	-40.18	-13.00	Vertical

<b>The Worst Test Results for Channel 251/848.8 MHz</b>					
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity
1698.00	-41.58	-2.26	-43.84	-13.00	Horizontal
1888.50	-44.38	-3.12	-47.50	-13.00	Vertical
2131.00	-42.73	-1.74	-44.47	-13.00	Vertical
9089.00	-42.64	8.46	-34.18	-13.00	Horizontal

<b>The Worst Test Results for Channel 512/1850.2 MHz</b>					
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity
1999.00	-43.96	9.5	-34.46	-13.00	Horizontal
3700.00	-41.27	8.74	-32.53	-13.00	Horizontal
12950.40	-43.05	11.56	-31.49	-13.00	Vertical
17919.60	-42.46	17.89	-24.57	-13.00	Vertical

<b>The Worst Test Results for Channel 661/1880.0 MHz</b>					
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity
2000.50	-42.61	9.7	-32.91	-13.00	Vertical
9399.00	-43.48	11.6	-31.88	-13.00	Vertical
13160.40	-42.53	14.89	-27.64	-13.00	Horizontal
15039.60	-48.23	13.87	-34.36	-13.00	Vertical
17941.20	-41.29	19.76	-21.53	-13.00	Horizontal
<b>The Worst Test Results for Channel 810/1909.8 MHz</b>					
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity
2000.00	-45.36	10.02	-35.34	-13.00	Vertical
9548.50	-42.17	11.3	-30.87	-13.00	Horizontal
13367.40	-41.64	12.4	-29.24	-13.00	Horizontal
15277.80	-55.28	18.03	-37.25	-13.00	Vertical
17931.60	-43.53	19	-24.53	-13.00	Horizontal

**Note:** ARpl= Factor=Antenna Factor+ Cable loss-Amplifier gain.

The “Factor” value can be calculated automatically by software of measurement system.

Below 30MHZ no Spurious found and The GSM modes is the worst condition.



## 11. MAINS CONDUCTED EMISSION

### 11.1 MEASUREMENT METHOD

The measurement procedure specified in ANSI/TIA-603-D-2010 was used for testing. Conducted Emission was measured with travel charger.


### 11.2 PROVISIONS APPLICABLE

Frequency of Emission (MHz)	Conducted Limit(dBuV)	
	Quasi-Peak	Average
0.15 – 0.5	66 to 56 *	56 to 46 *
0.5 – 5	56	46
5 – 30	60	50

1.\*Decreases with the logarithm of the frequency.  
2.\*The lower limit shall apply at the transition frequency.

11.3 MEASUREMENT RESULT

LINE CONDUCTED EMISSION – L1



MEASUREMENT RESULT: "AGC\_fin"

2016/11/3 10:13


Frequency	Level	Transd	Limit	Margin	Detector	Line	PE	AUX
MHz	dBuV	dB	dBuV	dB				STATE
0.172500	45.40	10.3	65	19.4	QP	L1	FLO	ON
0.375000	35.90	10.3	58	22.5	QP	L1	FLO	ON
0.843000	28.60	10.4	56	27.4	QP	L1	FLO	ON
2.125500	29.50	10.5	56	26.5	QP	L1	FLO	ON
6.418500	21.10	10.6	60	38.9	QP	L1	FLO	ON
24.243000	14.70	11.9	60	45.3	QP	L1	FLO	ON

MEASUREMENT RESULT: "AGC\_fin2"

2016/11/3 10:13

Frequency	Level	Transd	Limit	Margin	Detector	Line	PE	AUX
MHz	dBuV	dB	dBuV	dB				STATE
0.172500	29.80	10.3	55	25.0	AV	L1	FLO	ON
0.375000	24.90	10.3	48	23.5	AV	L1	FLO	ON
0.843000	18.30	10.4	46	27.7	AV	L1	FLO	ON
2.179500	19.10	10.5	46	26.9	AV	L1	FLO	ON
6.418500	10.40	10.6	50	39.6	AV	L1	FLO	ON
24.243000	8.90	11.9	50	41.1	AV	L1	FLO	ON

LINE CONDUCTED EMISSION - N



**MEASUREMENT RESULT: "AGC\_fin"**

2016/11/3 10:20

Frequency	Level	Transd	Limit	Margin	Detector	Line	PE	AUX STATE
MHz	dBuV	dB	dBuV	dB				
0.217500	40.90	10.3	63	22.0	QP	N	FLO	ON
0.375000	39.20	10.3	58	19.2	QP	N	FLO	ON
1.194000	36.20	10.4	56	19.8	QP	N	FLO	ON
3.646500	32.10	10.5	56	23.9	QP	N	FLO	ON
8.970000	21.00	10.7	60	39.0	QP	N	FLO	ON
25.863000	16.30	11.9	60	43.7	QP	N	FLO	ON

**MEASUREMENT RESULT: "AGC\_fin2"**

2016/11/3 10:20

Frequency	Level	Transd	Limit	Margin	Detector	Line	PE	AUX STATE
MHz	dBuV	dB	dBuV	dB				
0.217500	28.20	10.3	53	24.7	AV	N	FLO	ON
0.375000	28.90	10.3	48	19.5	AV	N	FLO	ON
1.194000	24.70	10.4	46	21.3	AV	N	FLO	ON
3.727500	19.90	10.5	46	26.1	AV	N	FLO	ON
8.970000	11.00	10.7	50	39.0	AV	N	FLO	ON
25.201500	9.20	11.9	50	40.8	AV	N	FLO	ON

**Note:** The GSM850 mode is the worst condition.

## 12. FREQUENCY STABILITY

### 12.1 MEASUREMENT METHOD

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -10°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 661 for PCS 1900 , channel 190 for GSM850 measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -10°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10°C increments from +50°C to -10°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

### 12.2 PROVISIONS APPLICABLE

#### 12.2.1 For Hand carried battery powered equipment

According to the ANSI/TIA-603-D-2010, the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.4VDC and 4.2VDC, with a nominal voltage of 3.7VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

**12.2.2 For equipment powered by primary supply voltage**

According to the ANSI/TIA-603-D-2010, the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

**12.3 MEASUREMENT RESULT**

**Appendix D: Frequency Stability**

**Test Results**

**Frequency Error vs. Voltage:**

Test Band	Test Mode	Test Channel	Test Temp.	Test Volt. (V)	Freq.Error (Hz)	Freq.vs.rated (ppm)	Limit (ppm)	Verdict
GSM 850	GSM	LCH	TN	3.4	21.05	0.03	±2.5	PASS
			TN	3.7	-18.79	-0.02	±2.5	PASS
			TN	4.2	13.04	0.02	±2.5	PASS
		MCH	TN	3.4	24.09	0.03	±2.5	PASS
			TN	3.7	-13.82	-0.02	±2.5	PASS
			TN	4.2	-23.50	-0.03	±2.5	PASS
		HCH	TN	3.4	19.05	0.02	±2.5	PASS
			TN	3.7	26.35	0.03	±2.5	PASS
			TN	4.2	25.25	0.03	±2.5	PASS

Test Band	Test Mode	Test Channel	Test Temp.	Test Volt. (V)	Freq.Error (Hz)	Freq.vs.rated (ppm)	Limit (ppm)	Verdict
GSM 1900	GSM	LCH	TN	3.4	-27.83	-0.02	±2.5	PASS
			TN	3.7	-24.21	-0.01	±2.5	PASS
			TN	4.2	-34.09	-0.02	±2.5	PASS
		MCH	TN	3.4	-23.05	-0.01	±2.5	PASS
			TN	3.7	-25.96	-0.01	±2.5	PASS
			TN	4.2	-19.57	-0.01	±2.5	PASS
		HCH	TN	3.4	-46.56	-0.02	±2.5	PASS
			TN	3.7	-48.30	-0.03	±2.5	PASS
			TN	4.2	-57.21	-0.03	±2.5	PASS

**Frequency Error vs. Temperature:**

Test Band	Test Mode	Test Channel	Test Volt.	Test Temp	Freq.Error (Hz)	Freq.vs.rated (ppm)	Limit (ppm)	Verdict
GSM850	GSM	LCH	VN	-10	18.60	0.02	±2.5	PASS
			VN	0	15.76	0.02	±2.5	PASS
			VN	10	19.76	0.02	±2.5	PASS
			VN	20	18.21	0.02	±2.5	PASS
			VN	30	-20.60	-0.02	±2.5	PASS
			VN	40	-25.31	-0.03	±2.5	PASS
			VN	50	-16.79	-0.02	±2.5	PASS
GSM850	GSM	MCH	VN	-10	21.83	0.03	±2.5	PASS
			VN	0	-31.64	-0.04	±2.5	PASS
			VN	10	17.37	0.02	±2.5	PASS
			VN	20	-17.63	-0.02	±2.5	PASS
			VN	30	18.60	0.02	±2.5	PASS
			VN	40	-18.27	-0.02	±2.5	PASS
			VN	50	21.24	0.03	±2.5	PASS
GSM850	GSM	HCH	VN	-10	28.99	0.03	±2.5	PASS
			VN	0	27.77	0.03	±2.5	PASS
			VN	10	24.34	0.03	±2.5	PASS
			VN	20	23.25	0.03	±2.5	PASS
			VN	30	-21.11	-0.02	±2.5	PASS
			VN	40	23.18	0.03	±2.5	PASS
			VN	50	21.50	0.03	±2.5	PASS


Test Band	Test Mode	Test Channel	Test Volt.	Test Temp	Freq.Error (Hz)	Freq.vs.rated (ppm)	Limit (ppm)	Verdict
GSM 1900	GSM	LCH	VN	-10	-27.83	-0.02	±2.5	PASS
			VN	0	-22.73	-0.01	±2.5	PASS
			VN	10	-27.38	-0.01	±2.5	PASS
			VN	20	-25.25	-0.01	±2.5	PASS
			VN	30	-37.39	-0.02	±2.5	PASS
			VN	40	-22.34	-0.01	±2.5	PASS
			VN	50	-26.86	-0.01	±2.5	PASS
GSM 1900	GSM	MCH	VN	-10	-25.18	-0.01	±2.5	PASS
			VN	0	-22.28	-0.01	±2.5	PASS
			VN	10	-19.89	-0.01	±2.5	PASS
			VN	20	-32.54	-0.02	±2.5	PASS
			VN	30	-35.32	-0.02	±2.5	PASS
			VN	40	-39.52	-0.02	±2.5	PASS
			VN	50	-34.09	-0.02	±2.5	PASS
GSM 1900	GSM	HCH	VN	-10	-44.68	-0.02	±2.5	PASS
			VN	0	-45.46	-0.02	±2.5	PASS
			VN	10	-31.12	-0.02	±2.5	PASS
			VN	20	-40.94	-0.02	±2.5	PASS
			VN	30	-43.65	-0.02	±2.5	PASS
			VN	40	-42.68	-0.02	±2.5	PASS
			VN	50	-49.78	-0.03	±2.5	PASS




### PHOTOGRAPHS OF TEST SETUP CONDUCTED EMISSION



### RADIATED SPURIOUS EMISSION





CONDUCTED MEASUREMENTS





## APPENDIX B: PHOTOGRAPHS OF EUT TOTAL VIEW OF EUT



### THE LABEL OF BATTERY



THE LABEL OF ADAPTER



TOP VIEW OF EUT





BOTTOM VIEW OF EUT



FRONT VIEW OF EUT



BACK VIEW OF EUT



LEFT VIEW OF EUT





RIGHT VIEW OF EUT




OPEN VIEW OF EUT-1



OPEN VIEW OF EUT-2



OPEN VIEW OF EUT-3






INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



----END OF REPORT----