



RF EXPOSURE EVALUATION REPORT

FCC ID : 2AF77-H2221540
Equipment : Communication Device
Brand Name : blink
Model Name : BSM00500U
Applicant : Immedia Semiconductor LLC.
100 Riverpark Drive Suite 125, North
Reading, MA, United States 01864
Manufacturer : Immedia Semiconductor LLC.
100 Riverpark Drive Suite 125, North
Reading, MA, United States 01864
Standard : 47 CFR Part 2.1091

We, SPORTON INTERNATIONAL INC has been evaluated this product in accordance with 47 CFR Part2.1091 and it complies with applicable limit.

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC evaluation.

The results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Laboratory, the test report shall not be reproduced except in full

Approved by: Cona Huang / Deputy Manager



SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	4
2. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS	4
3. RF EXPOSURE LIMIT INTRODUCTION	5
4. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	6
4.1. Standalone Power Density Calculation	6



1. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	Communication Device
Brand Name	blink
Model Name	BSM00500U
FCC ID	2AF77-H2221540
Wireless Technology and Frequency Range	WLAN 2.4 GHz Band: 2400 MHz ~ 2483.5 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz SRD: 902.4 MHz ~ 927.6MHz 802.11ah: 902.5 MHz ~ 927.5 MHz
Mode	WLAN: 802.11b/g/n HT20 Bluetooth LE SRD:GFSK 802.11ah: OFDM
EUT Stage	Identical Prototype

Reviewed by: Jason Wang

Report Producer: Paula Chen

2. Maximum RF average output power among production units

Mode	Maximum Average power(dBm)
WLAN 2.4GHz	15.5
Bluetooth	9
SRD	15
802.11ah	25



3. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Table with 5 columns: Frequency range (MHz), Electric field strength (V/m), Magnetic field strength (A/m), Power density (mW/cm²), Averaging time (minutes). It is divided into two sections: (A) Limits for Occupational/Controlled Exposures and (B) Limits for General Population/Uncontrolled Exposure.

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

S = PG / (4πR²)

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



4. Radio Frequency Radiation Exposure Evaluation

4.1. Standalone Power Density Calculation

Band	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)
WLAN 2.4GHz	4.20	15.50	19.7	0.09	93.33	0.019	1.000
Bluetooth	4.20	9.00	13.2	0.02	20.89	0.004	1.000
SRD	0.78	15.00	15.8	0.04	37.84	0.008	0.602
802.11ah	1.58	25.00	26.6	0.45	454.99	0.091	0.602

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.