

# FCC Part 15C Measurement and Test Report

For

**Shenzhen Mercury Innovations Science and Technology Ltd**

**FCC ID: 2AF7A-A60**

<b>FCC Rule(s):</b>	<u>FCC Part 15.247</u>
<b>Product Description:</b>	<u>Bluetooth Speaker</u>
<b>Tested Model:</b>	<u>A60</u>
<b>Report No.:</b>	<u>BSL18051060040001Y-ER-4</u>
<b>Tested Date:</b>	<u>2018-05-04 to 2018-05-17</u>
<b>Issued Date:</b>	<u>2018-05-18</u>
<b>Tested By:</b>	<u>Lisa. Li / Engineer</u>
<b>Reviewed By:</b>	<u>arno. Liu / EMC Manager</u>
<b>Approved &amp; Authorized By:</b>	<u>Mike mo / PSQ Manager</u>
<b>Prepared By:</b>	

*Lisa. Li*  
*arno. Liu*  
*Mike mo*

**BSL Testing Co.,LTD.**

NO. 24, ZH Park, Nantou, Shenzhen, 518000 China

Tel: 86- 755-26508703

Fax: 86- 755-26508703

**TABLE OF CONTENTS**

**1. GENERAL INFORMATION.....3**

1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....3

1.2 TEST STANDARDS.....4

1.3 TEST METHODOLOGY.....4

1.4 TEST FACILITY.....4

1.5 EUT SETUP AND TEST MODE.....5

1.6 MEASUREMENT UNCERTAINTY.....5

1.7 TEST EQUIPMENT LIST AND DETAILS.....6

**2. SUMMARY OF TEST RESULTS.....7**

**3. RF EXPOSURE.....8**

3.1 STANDARD APPLICABLE.....8

3.2 TEST RESULT.....8

**4. ANTENNA REQUIREMENT.....9**

4.1 STANDARD APPLICABLE.....9

4.2 EVALUATION INFORMATION.....9

**5. POWER SPECTRAL DENSITY.....10**

5.1 STANDARD APPLICABLE.....10

5.2 TEST PROCEDURE.....10

5.3 ENVIRONMENTAL CONDITIONS.....10

5.4 SUMMARY OF TEST RESULTS/PLOTS.....10

**6. 6DB BANDWIDTH.....13**

6.1 STANDARD APPLICABLE.....13

6.2 TEST PROCEDURE.....13

6.3 ENVIRONMENTAL CONDITIONS.....13

6.4 SUMMARY OF TEST RESULTS/PLOTS.....13

**7. RF OUTPUT POWER.....16**

7.1 STANDARD APPLICABLE.....16

7.2 TEST PROCEDURE.....16

7.3 ENVIRONMENTAL CONDITIONS.....16

7.4 SUMMARY OF TEST RESULTS/PLOTS.....16

**8. FIELD STRENGTH OF SPURIOUS EMISSIONS.....19**

8.1 STANDARD APPLICABLE.....19

8.2 TEST PROCEDURE.....19

8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....20

8.4 ENVIRONMENTAL CONDITIONS.....20

8.5 SUMMARY OF TEST RESULTS/PLOTS.....21

**9. OUT OF BAND EMISSIONS.....26**

9.1 STANDARD APPLICABLE.....26

9.2 TEST PROCEDURE.....26

9.3 ENVIRONMENTAL CONDITIONS.....27

9.4 SUMMARY OF TEST RESULTS/PLOTS.....27

**10. CONDUCTED EMISSIONS.....29**

10.1 TEST PROCEDURE.....29

10.2 BASIC TEST SETUP BLOCK DIAGRAM.....29

10.3 ENVIRONMENTAL CONDITIONS.....29

10.4 TEST RECEIVER SETUP.....30

10.5 SUMMARY OF TEST RESULTS/PLOTS.....30

10.6 CONDUCTED EMISSIONS TEST DATA.....30

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: Shenzhen Mercury Innovations Science and Technology Ltd  
 Address of applicant: 3rd & 5th Floor, Building A1, Xixiang TongFuYu Industrial Park, Bao'an District, Shenzhen, China

Manufacturer: Shenzhen Mercury Innovations Science and Technology Ltd  
 Address of manufacturer: 3rd & 5th Floor, Building A1, Xixiang TongFuYu Industrial Park, Bao'an District, Shenzhen, China

General Description of EUT	
Product Name:	Bluetooth Speaker
Trade Name:	Mifa
Model No.:	A60
Adding Model(s):	N/A
Rated Voltage:	5V/1A from USB Cable 3.7V by 2200mAh Li-ion Battery
Power Adapter Model:	N/A

Technical Characteristics of EUT	
Bluetooth Version:	V4.2(BLE)
Frequency Range:	2402-2480MHz
RF Output Power:	0.86dBm (Conducted)
Data Rate:	1Mbps
Modulation:	GFSK
Quantity of Channels:	40
Channel Separation:	2MHz
Type of Antenna:	PCB
Antenna Gain:	0dBi
Lowest Internal Frequency of EUT:	26MHz

## 1.2 Test Standards

The following report is prepared on behalf of the Shenzhen Mercury Innovations Science and Technology Ltd in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The measurement guide KDB 558074 D01 v04 for digital transmission systems shall be performed also.

## 1.4 Test Facility

BSL Testing Co.,LTD.

NO. 24, ZH Park, Nantou, Shenzhen, 518000 China

Designation Number : CN1217

Test Firm Registration Number: 866035

Tel: 86- 755-26508703

Fax: 86- 755-26508703

## 1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	GFSK(BLE)	2402MHz, 2442MHz, 2480MHz

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
USB Cable	0.5	Unshielded	Without Ferrite

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Adapter	ANDI	5V/2A USB	/

## 1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	$\pm 2.88\text{dB}$
Transmitter Spurious Emissions	Radiated	$\pm 5.1\text{dB}$

## 1.7 Test Equipment List and Details

Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
Communication Tester	Rohde & Schwarz	CMW500	100358	2017-10-21	2018-10-20
Spectrum Analyzer	R&S	FSP40	100550	2017-10-21	2018-10-20
Test Receiver	R&S	ESCI7	US47140102	2017-10-21	2018-10-20
Signal Generator	HP	83630B	3844A01028	2017-10-22	2018-10-21
Test Receiver	R&S	ESPI-3	100180	2017-10-21	2018-10-20
Amplifier	Agilent	8449B	4035A00116	2017-10-22	2018-10-21
Amplifier	HP	8447E	2945A02770	2017-10-22	2018-10-21
Signal Generator	IFR	2023A	202307/242	2017-10-22	2018-10-21
Broadband Antenna	SCHAFFNER	2774	2774	2017-10-17	2018-10-16
Biconical and log periodic antennas	ELECTRO-METRICS	EM-6917B-1	171	2017-10-17	2018-10-16
Horn Antenna	R&S	HF906	100253	2017-10-17	2018-10-16
Horn Antenna	EM	EM-6961	6462	2017-10-17	2018-10-16
LISN	R&S	ESH3-Z5	100196	2017-10-17	2018-10-16
LISN	COM-POWER	LI-115	02027	2017-10-17	2018-10-16
3m Semi-Anechoic Chamber	Chengyu Electron	9 (L)*6 (W)* 6 (H)	BSL086	2017-10-21	2018-10-20
Horn Antenna	A-INFOMW	LB-180400KF	BSL088	2017-10-21	2018-10-20

## 2. SUMMARY OF TEST RESULTS

<b>FCC Rules</b>	<b>Description of Test Item</b>	<b>Result</b>
§ 2.1093	RF Exposure	PASS
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	PASS
§15.205	Restricted Band of Operation	PASS
§ 15.207(a)	Conducted Emission	PASS
§ 15.247(e)	Power Spectral Density	PASS
§ 15.247(a)(2)	6 dB Bandwidth	PASS
§ 15.247(b)(3)	RF Output Power	PASS
§ 15.209(a)	Radiated Emission	PASS
§ 15.247(d)	Band Edge (Out of Band Emissions)	PASS

Note: PASS: applicable, N/A: not applicable.

### **3. RF Exposure**

---

#### **3.1 Standard Applicable**

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

#### **3.2 Test Result**

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.



## **4. Antenna Requirement**

---

### **4.1 Standard Applicable**

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **4.2 Evaluation Information**

This product has a RP-SMA antenna, fulfill the requirement of this section.

## 5. Power Spectral Density

### 5.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 5.2 Test Procedure

According to the KDB 558074 D01 v04, the test method of power spectral density as below:

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set the VBW  $\geq 3 \times \text{RBW}$ .
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### 5.3 Environmental Conditions


Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

### 5.4 Summary of Test Results/Plots

Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
GFSK(BLE)	2402	-17.62	8
	2442	-18.53	8
	2480	-19.54	8


Please refer to the following test plots:

Low Channel




Date: 16.MAY.2018 16:05:28

Middle Channel



Date: 16.MAY.2018 16:04:55

High Channel



Date: 16.MAY.2018 16:04:25

## 6. 6dB Bandwidth

### 6.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 6.2 Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 6.3 Environmental Conditions

Temperature:	25° C
Relative Humidity:	53%
ATM Pressure:	1018 mbar


### 6.4 Summary of Test Results/Plots

Test Mode	Test Channel MHz	6 dB Bandwidth kHz	99% Bandwidth kHz	Limit kHz
GFSK(BLE)	2402	678	1110	$\geq 500$
	2442	570	1110	$\geq 500$
	2480	672	1092	$\geq 500$

Please refer to the following test plots:


For BLE

Low Channel:




Date: 16.MAY.2018 16:13:02

Middle Channel:



Date: 16.MAY.2018 16:11:48

High Channel:



Date: 16.MAY.2018 16:10:20

## 7. RF Output Power

### 7.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

### 7.2 Test Procedure

According to section KDB-558074 D01 v04 section 9.1.1, this procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- a) Set the RBW  $\geq$  DTS bandwidth.
- b) Set VBW  $\geq 3 \times$  RBW.
- c) Set span  $\geq 3 \times$  RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

### 7.3 Environmental Conditions

Temperature:	26° C
Relative Humidity:	57%
ATM Pressure:	1011 mbar

### 7.4 Summary of Test Results/Plots


Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
GFSK(BLE)	2402	0.86	1.22	1000
	2442	0.38	1.09	1000
	2480	-0.82	0.83	1000

*Note: the antenna gain of 1.31dBi less than 6dBi maximum permission antenna gain value based on 1 watt peak output power limit.*




For BLE:

Low Channel:




Date: 16.MAY.2018 16:03:00

Middle Channel:



Date: 16.MAY.2018 16:03:34

High Channel:



Date: 16.MAY.2018 16:03:58

## 8. Field Strength of Spurious Emissions

### 8.1 Standard Applicable


According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

### 8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz  
 RBW=10KHz,  
 VBW =30KHz  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak

Frequency :30MHz-1GHz  
 RBW=120KHz,  
 VBW=300KHz  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak, QP

Frequency :Above 1GHz  
 RBW=1MHz,  
 VBW=3MHz(Peak), 10Hz(AV)  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak, AV

### 8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

### 8.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

### 8.5 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst cases:


Note:

1. Worst-case radiated emission below 1GHz is GFSK (CH Middle) mode.
2. Worst-case radiated emission above 1GHz is GFSK (CH Low, Middle, High) mode.

The Worst Test Data Below 1GHz GFSK (CH Middle) mode:


#### Plot of Radiated Emissions

Test Specification:           Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dBuV/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		38.4809	20.36	0.26	20.62	40.00	-19.38	QP
2		59.4405	22.22	-1.54	20.68	40.00	-19.32	QP
3		117.3603	14.67	5.97	20.64	43.50	-22.86	QP
4		298.2681	13.15	11.70	24.85	46.00	-21.15	QP
5		449.5558	14.41	12.61	27.02	46.00	-18.98	QP
6	*	699.3046	13.58	17.28	30.86	46.00	-15.14	QP

Test Specification: Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dBuV/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		123.6985	14.58	7.45	22.03	43.50	-21.47	QP
2		208.5803	16.64	5.93	22.57	43.50	-20.93	QP
3		321.0608	10.28	13.82	24.10	46.00	-21.90	QP
4		482.2156	13.74	14.25	27.99	46.00	-18.01	QP
5	*	687.1507	14.52	17.30	31.82	46.00	-14.18	QP
6		979.1804	13.57	18.56	32.13	54.00	-21.87	QP

*The Worst Spurious Emissions Above 1GHz**Transmitting: BLE mode:*

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2402MHz							
4804	55.29	-3.59	51.7	74	-22.3	H	PK
4804	46.26	-3.59	42.67	54	-11.33	H	AV
7206	54.27	-0.52	53.75	74	-20.25	H	PK
7206	45.69	-0.52	45.17	54	-8.83	H	AV
4804	52.78	-3.59	49.19	74	-24.81	V	PK
4804	43.71	-3.59	40.12	54	-13.88	V	AV
7206	50.86	-0.52	50.34	74	-23.66	V	PK
7206	41.52	-0.52	41.00	54	-13.00	V	AV
Middle Channel-2442MHz							
4884	56.24	-3.49	52.75	74	-21.25	H	PK
4884	47.15	-3.49	43.66	54	-10.34	H	AV
7326	55.62	-0.47	55.15	74	-18.85	H	PK
7326	45.16	-0.47	44.69	54	-9.31	H	AV
4884	52.41	-3.49	48.92	74	-25.08	V	PK
4884	42.86	-3.49	39.37	54	-14.63	V	AV
7326	51.46	-0.47	50.99	74	-23.01	V	PK
7326	40.86	-0.47	40.39	54	-13.61	V	AV
High Channel-2480MHz							
4960	54.26	-3.41	50.85	74	-23.15	H	PK
4960	47.15	-3.41	43.74	54	-10.26	H	AV
7440	53.26	-0.42	52.84	74	-21.16	H	PK
7440	46.48	-0.42	46.06	54	-7.94	H	AV
4960	51.42	-3.41	48.01	74	-25.99	V	PK
4960	44.18	-3.41	40.77	54	-13.23	V	AV
7440	50.53	-0.42	50.11	74	-23.89	V	PK
7440	42.45	-0.42	42.03	54	-11.97	V	AV


## Note:

1. Calculation of result is: Result (dBm) = Reading (dBm) + Correction Factor (dB).
2. Correction Factor (dB)=Ant. Factor + Cable Loss – Ampl. Gain.
3. Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Spurious Emission(Conducted)


For BLE

Low channel:



Date: 17.MAY.2018 09:51:50


Middle channel:



Date: 17.MAY.2018 09:55:16



High channel:



Date: 17.MAY.2018 09:58:35

---

## 9. Out of Band Emissions

---

### 9.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

### 9.2 Test Procedure

According to the KDB 558074 D01 v04, the band-edge radiated test method as follows:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

According to the KDB 558074 D01 v04, the conducted spurious emissions test method as follows:

1. Set start frequency to DTS channel edge frequency.
2. Set stop frequency so as to encompass the spectrum to be examined.
3. Set RBW = 100 kHz.
4. Set VBW  $\geq$  300 kHz.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.
8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
9. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

### 9.3 Environmental Conditions

Temperature:	23°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar


### 9.4 Summary of Test Results/Plots

Bandedge (Radiated)

No.	Frequency (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2400	44.62	54	-9.38	Average Detector
	2400	58.12	74	-15.88	Peak Detector
2	2483.5	45.32	54	-8.68	Average Detector
	2483.5	57.16	74	-16.84	Peak Detector


Bandedge (Conducted)

Lowest



Date: 16.MAY.2018 16:06:57

High Channel:



Date: 16.MAY.2018 16:08:13

## 10. Conducted Emissions


### 10.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

### 10.2 Basic Test Setup Block Diagram



### 10.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

## 10.4 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency ..... 150 kHz  
Stop Frequency..... 30 MHz  
Sweep Speed ..... Auto  
IF Bandwidth..... 10 kHz  
Quasi-Peak Adapter Bandwidth ..... 9 kHz  
Quasi-Peak Adapter Mode ..... Normal

## 10.5 Summary of Test Results/Plots


According to the data in section 10.6, the EUT complied with the FCC Part 15.207 Conducted margin for this device

## 10.6 Conducted Emissions Test Data

Note: we are pre-scan all modes, the worst data is BLE (Low Channel) mode.


**Plot of Conducted Emissions Test Data: TX(Low Channel)**

Test Specification: Neutral



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
		MHz	Level	Factor	ment			Detector
			dBuV	dB	dBuV	dBuV	dB	
1		0.1650	49.36	0.00	49.36	65.21	-15.85	QP
2		0.1650	27.10	0.00	27.10	55.21	-28.11	AVG
3	*	0.4350	51.42	0.00	51.42	57.16	-5.74	QP
4		0.4350	38.56	0.00	38.56	47.16	-8.60	AVG
5		0.6900	44.19	0.00	44.19	56.00	-11.81	QP
6		0.6900	31.80	0.00	31.80	46.00	-14.20	AVG
7		1.1750	42.76	0.00	42.76	56.00	-13.24	QP
8		1.1750	29.39	0.00	29.39	46.00	-16.61	AVG
9		5.5000	41.15	0.00	41.15	60.00	-18.85	QP
10		5.5000	29.48	0.00	29.48	50.00	-20.52	AVG
11		22.8500	36.17	0.00	36.17	60.00	-23.83	QP
12		22.8500	25.66	0.00	25.66	50.00	-24.34	AVG

Test Specification: Live



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.2100	47.08	0.00	47.08	63.21	-16.13	QP
2		0.2100	28.50	0.00	28.50	53.21	-24.71	AVG
3	*	0.4450	50.62	0.00	50.62	56.97	-6.35	QP
4		0.4450	39.33	0.00	39.33	46.97	-7.64	AVG
5		0.7800	44.31	0.00	44.31	56.00	-11.69	QP
6		0.7800	32.85	0.00	32.85	46.00	-13.15	AVG
7		1.2350	43.37	0.00	43.37	56.00	-12.63	QP
8		1.2350	32.57	0.00	32.57	46.00	-13.43	AVG
9		2.2800	43.07	0.00	43.07	56.00	-12.93	QP
10		2.2800	30.92	0.00	30.92	46.00	-15.08	AVG
11		22.8250	36.41	0.00	36.41	60.00	-23.59	QP
12		22.8250	24.96	0.00	24.96	50.00	-25.04	AVG

\*\*\*\*\* END OF REPORT \*\*\*\*\*