

# FCC TEST REPORT

## FCC ID: 2AF7JINNOBAND-O

Product Name : Wristband Activity Tracker with BLE

Model Name : innoBand-O

Brand : innoBand

Report No. : PT800872160603E-FC02

### Prepared for

3 N Half, Ltd.  
#605, 6/F, China Insurance Group Building  
141 Des Voeux Road, Central, Hong Kong

### Prepared by

DongGuan Precise Testing Service Co.,Ltd.  
Building D, Baoding Technology Park, Guangming Road 2, Guangming Community  
Dongcheng District, Dongguan, Guangdong, China



**TEST RESULT CERTIFICATION**

Applicant's name : 3 N Half, Ltd.  
Address : #605, 6/F, China Insurance Group Building, 141 Des Voeux Road, Central, Hong Kong.  
Manufacture's name : ZYI Limited  
Address : 5F, Building#2-5 TongFuYu Industrial Park ShiYan, BaoAn District, ShenZhen, China  
Product name : Wristband Activity Tracker with BLE  
Model name : innoBand-O  
Standards : FCC CFR47 Part 1.1307(b)(1)  
Test procedure : KDB 447498 D01 General RF Exposure Guidance v05  
Test Date : Jun. 4, 2016 ~ Jun. 15, 2016  
Date of Issue : Jun. 16, 2016  
Test Result : Pass

This device described above has been tested by PTS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTS, this document may be altered or revised by PTS, personal only, and shall be noted in the revision of the document.

Testing Engineer

August Qiu

Technical Manager

Hack Ye

Authorized Signatory

Chris Du



## Contents

	<b>Page</b>
<b>2 TEST SUMMARY</b> .....	<b>4</b>
<b>3 GENERAL INFORMATION</b> .....	<b>5</b>
3.1 GENERAL DESCRIPTION OF EUT .....	5
<b>4 RF EXPOSURE</b> .....	<b>6</b>
4.1 REQUIREMENTS .....	6
4.2 THE PROCEDURES / LIMIT .....	6



## 2 Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS
Remark:		
N/A: Not Applicable		



### 3 General Information

#### 3.1 General Description of EUT

Product Name : Wristband Activity Tracker with BLE  
Model Name : innoBand-O  
Model Description : N/A  
Bluetooth Version: : V4.0( BLE)  
Frequency Range: : 2402-2480MHz, 40 channels  
Antenna installation: : Integrated Antenna  
Antenna Gain: : 0.5dBi  
Type of Modulation : GFSK  
The lowest oscillator: : 32.768kHz  
Power supply : DC 3V power by battery

## 4 RF Exposure

Test Requirement : FCC Part 1.1307

Evaluation Method : KDB 447498 D01 General RF Exposure Guidance v05

### 4.1 Requirements

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR where

$f(\text{GHz}) \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR where

1.  $f(\text{GHz})$  is the RF channel transmit frequency in GHz
2. Power and distance are rounded to the nearest mW and mm before calculation
3. The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

### 4.2 The procedures / limit

Conducted Peak power(dBm)	Conducted Peak power(mW)	Source-based time-averaged maximum conducted output power(mW)	Minimum test separation distance required for the exposure conditions (mm)	SAR Test Exclusion Thresholds(mW)
-0.60	0.871	0.871	5	9.525

\*\*\*\*\*THE END REPORT\*\*\*\*\*