

Label drafts

The labels are printed/lasered directly on the housing of the devices.

NivoRadar 4100

UWT LEVEL CONTROL		UWT GmbH D-87488 Betzigau		CE 0158	
NivoRadar® NR 4100 s/n 12345678		    			
NR 4100...					
Supply	12...30V ~	T _a	-40 °C...+80 °C	 345678	
Output	4...20mA HART	Process	1NPT		
Enclosure	IP66/68 (3bar), Type 6P	connection			
FCC-ID: 2AF8D-NR4000, IC: 20874-NR4000 IECEx KIWA 22...X, KIWA 22ATEX...X II 1G, 1/2G Ex ia IIC T4 Ga, Ga/Gb; II 1D, 1/2D Ex ia IIC T134°C Da, Da/Db; FM22CA...X, CSA 22CA...X - Intrinsic Safe for CI I, Div 1, Gp ABCD, CI II, Div 1, Gp EFG, CI III T4; CI I, Zn 0,0/1 AEx/Ex ia IIC T4 Ga, Ga/Gb; Zn 20,20/21 AEx/Ex ia IIC T134°C Da, Da/Db; Install per Document WARNING - POTENTIAL ELECTROSTATIC CHARGING HAZARD - SEE INSTRUCTIONS AVERTISSEMENT - DANGER POTENTIEL DE CHARGES ELECTROSTATIQUES - VOIR INSTRUCTIONS					
Made in Germany					

Location
for
FCC/IC