



FCC / ISED Test Report

FOR:

iRhythm Technologies

Model Name:

A102A5001

Product Description:

Zio AT Gateway

FCC ID: 2AFBP-AT18G

IC ID: -----

Applied Rules and Standards:
47 CFR Part 15.247 (DTS)

REPORT #: EMC_IRHYT_011_15.247_DTS

DATE: 2018-04-17



A2LA Accredited

IC recognized #
3462B-1

CETECOM Inc.

411 Dixon Landing Road • Milpitas, CA 95035 • U.S.A.

Phone: + 1 (408) 586 6200 • Fax: + 1 (408) 586 6299 • E-mail: info@cetecom.com • <http://www.cetecom.com>
CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571

TABLE OF CONTENTS

1	ASSESSMENT.....	3
2	ADMINISTRATIVE DATA.....	4
2.1	IDENTIFICATION OF THE TESTING LABORATORY ISSUING THE EMC TEST REPORT	4
2.2	IDENTIFICATION OF THE CLIENT	4
2.3	IDENTIFICATION OF THE MANUFACTURER.....	4
3	EQUIPMENT UNDER TEST (EUT).....	5
3.1	EUT SPECIFICATIONS	5
3.2	EUT SAMPLE DETAILS.....	6
3.3	ACCESSORY EQUIPMENT (AE) DETAILS.....	6
3.4	TEST SAMPLE CONFIGURATION	6
3.5	JUSTIFICATION FOR WORST CASE MODE OF OPERATION.....	6
4	SUBJECT OF INVESTIGATION	7
5	MEASUREMENT RESULTS SUMMARY	7
6	MEASUREMENT UNCERTAINTY.....	8
6.1	ENVIRONMENTAL CONDITIONS DURING TESTING:.....	8
6.2	DATES OF TESTING:.....	8
7	MEASUREMENT PROCEDURES.....	9
7.1	RADIATED MEASUREMENT.....	9
7.2	POWER LINE CONDUCTED MEASUREMENT PROCEDURE	11
7.3	RF CONDUCTED MEASUREMENT PROCEDURE	11
8	TEST RESULT DATA	12
8.1	MAXIMUM PEAK CONDUCTED OUTPUT POWER.....	12
8.2	POWER SPECTRAL DENSITY	20
8.3	BAND EDGE COMPLIANCE	24
8.4	EMISSION BANDWIDTH 6dB AND 99% OCCUPIED BANDWIDTH.....	29
8.5	RADIATED TRANSMITTER SPURIOUS EMISSIONS AND RESTRICTED BANDS	36
9	TEST SETUP PHOTOS.....	43
10	TEST EQUIPMENT AND ANCILLARIES USED FOR TESTING	43
11	HISTORY	44

1 Assessment

The following device was evaluated against the applicable criteria specified in FCC rules Parts 15.247 of Title 47 of the Code of Federal Regulations and the relevant ISED Canada standard RSS-247.

No deviations were ascertained.

Company	Description	Model #
iRhythm Technologies	Zio AT Gateway	A102A5001

Responsible for Testing Laboratory:

2018-04-17	Compliance	James Donnellan (Lab Manager - EMC)
Date	Section	Name

Responsible for the Report:

2018-04-17	Compliance	Kevin Wang (Senior EMC Engineer)
Date	Section	Name

The test results of this test report relate exclusively to the test item specified in Section3. CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.

2 Administrative Data

2.1 Identification of the Testing Laboratory Issuing the EMC Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Street Address:	411 Dixon Landing Road
City/Zip Code	Milpitas, CA 95035
Country	USA
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
Lab Manager-EMC:	James Donnellan
Responsible Project Leader:	Kevin Wang

2.2 Identification of the Client

Applicant's Name:	iRhythm Technologies
Street Address:	650 Townsend St. #500
City/Zip Code	San Francisco, CA 94103
Country	United States
Contact Person:	Chase Hathaway
Phone No.	415-757-3086
e-mail:	chathaway@irhythmtech.com

2.3 Identification of the Manufacturer

Manufacturer's Name:	iRhythm Technologies
Manufacturers Address:	11085 Knott Ave B
City/Zip Code	Cypress, CA 90630
Country	United States

3 Equipment Under Test (EUT)

3.1 EUT Specifications

Model No:	A102A5001
HW Version :	Hardware PCBA PN: A102A6002 Gateway Assembly PN: A102A5001
SW Version :	Application Processor Firmware Version: 180321 Gateway CC2640R2F Production 2.1.2.3 Bluetooth Processor Firmware Version: 180321 Gateway EFM32GG290 Manufacturing 2.1.1.3 Release
FCC-ID :	2AFBP-AT18G
IC-ID:	-----
FWIN:	-----
HVIN:	-----
PMN:	-----
Product Description:	Zio AT Gateway, The Gateway device transfers cardiac monitoring data to/from a Bluetooth radio to/from a LTE Cat M1 radio, powered by a single LiPo battery for up to 14 days.
Frequency Range / number of channels:	Nominal band: 2400 MHz – 2483.5 MHz; Center to center: 2402 MHz (ch 0) – 2480 MHz (ch 39), 40 channels
Type(s) of Modulation:	Bluetooth version 4.0 and 5.0, Low Energy, using Dynamic Sequence Spread Spectrum with GFSK modulation.
Modes of Operation:	Bluetooth LE in both advertising and connected mode of operation
Antenna Information as declared:	Peak 1 dBi typ.
Max. Peak Output Power:	Conducted Power 7.04 dBm for Bluetooth LE 4.0 Conducted Power 8.11 dBm for Bluetooth LE 5.0 with 2Mbps
Power Supply/ Rated Operating Voltage Range:	Dedicated Battery Pack Vmin: 2.75 VDC/ Vnom: 3.6 VDC / Vmax: 4.2 VDC
Operating Temperature Range	0 °C to 40 °C
Other Radios included in the device:	LTE Band 13: QPSK
Sample Revision	<input type="checkbox"/> Prototype Unit; <input type="checkbox"/> Production Unit; <input checked="" type="checkbox"/> Pre-Production

3.2 EUT Sample details

EUT #	Serial Number	HW Version	SW Version	Notes/Comments
1	KETA RPS 180053	Hardware PCBA PN: A102A6002 Gateway Assembly PN: A102A5001	Application Processor Firmware Version: 180321 Gateway CC2640R2F Production 2.1.2.3 Bluetooth Processor Firmware Version: 180321 Gateway EFM32GG290 Manufacturing 2.1.1.3 Release	Conducted Testing
2	KETA RPS 180058	Hardware PCBA PN: A102A6002 Gateway Assembly PN: A102A5001	Application Processor Firmware Version: 180321 Gateway CC2640R2F Production 2.1.2.3 Bluetooth Processor Firmware Version: 180321 Gateway EFM32GG290 Manufacturing 2.1.1.3 Release	Radiated Testing

3.3 Accessory Equipment (AE) details

AE #	Type	Model	Manufacturer	Serial Number
1	3.6V Battery	NCA103450-PC-1 Rev. C	House of Batteries	B622190812

3.4 Test Sample Configuration

EUT Set-up #	Combination of AE used for test set up	Comments
1	EUT#1	The radio of the EUT was configured to a fixed channel transmission with highest possible duty cycle using software that is not available to the end user. The measurement equipment was connected to the 50 ohm RF port of the EUT.
2	EUT#2	The radio of the EUT was configured to a fixed channel transmission with highest possible duty cycle using software that is not available to the end user. The internal antenna was connected.

3.5 Justification for Worst Case Mode of Operation

During the testing process, the EUT was tested with transmitter sets on low, mid and high channels, and highest possible duty cycle of 35%. Based on the maximum peak output power measurement result, the worst mode is Bluetooth 5.0 with 2Mbps. Then all of the testing, only the worst case was measured. For radiated measurements, all

data in this report shows the worst case between horizontal and vertical antenna polarizations and for all orientations of the EUT.

4 Subject of Investigation

The objective of the measurements done by CETECOM Inc. was to assess the performance of the EUT according to the relevant requirements specified in FCC rules Part 15.247 of Title 47 of the Code of Federal Regulations and Radio Standard Specification RSS-247 of ISED Canada.

This test report is to support a request for new equipment authorization under the FCC ID: 2AFBP-AT18G IC ID: ---

Testing procedures are based on 558074 D01 DTS Meas Guidance v04 – “GUIDANCE FOR PERFORMING COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEMS (DTS) OPERATING UNDER SECTION 15.247” - April 5, 2017, by the Federal Communications Commission, Office of Engineering and Technology, Laboratory Division.

5 Measurement Results Summary

Test Specification	Test Case	Temperature and Voltage Conditions	Mode	Pass	NA	NP	Result
§15.247(a)(1) RSS-247 5.2(1)	Emission Bandwidth	Nominal	BTLE	■	□	□	Complies
§15.247(e) RSS-247 5.2(2)	Power Spectral Density	Nominal	BTLE	■	□	□	Complies
§15.247(b)(1) RSS-247 5.4(4)	Maximum Conducted Output Power and EIRP	Nominal	BTLE	■	□	□	Complies
§15.247(d) RSS-247 5.5	Band edge compliance Unrestricted Band Edges	Nominal	BTLE	■	□	□	Complies
§15.247; 15.209; 15.205 RSS-Gen 8.9; 8.10	Band edge compliance Restricted Band Edges	Nominal	BTLE	■	□	□	Complies
§15.247(d); §15.209 RSS-Gen 6.13	TX Spurious emissions- Radiated	Nominal	BTLE	■	□	□	Complies
§15.207(a) RSS Gen 8.8	AC Conducted Emissions	Nominal	BTLE	□	■	□	Note2

Note: NA= Not Applicable; NP= Not Performed.

Note2: EUT is battery powered.

6 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus, with 95% confidence interval (in dB delta to result), based on a coverage factor k=1.

Radiated measurement

9 kHz to 30 MHz	±2.5 dB (Magnetic Loop Antenna)
30 MHz to 1000 MHz	±2.0 dB (Biconilog Antenna)
1 GHz to 40 GHz	±2.3 dB (Horn Antenna)

Conducted measurement

150 kHz to 30 MHz	±0.7 dB (LISN)
RF conducted measurement	±0.5 dB

According to TR 102 273 a multiplicative propagation of error is assumed for RF measurement systems. For this reason the RMS method is applied to dB values and not to linear values as appropriate for additive propagation of error. Also used: <http://physics.nist.gov/cuu/Uncertainty/typeb.html>. The above calculated uncertainties apply to direct application of the Substitution method. The Substitution method is always used when the EUT comes closer than 3 dB to the limit.

6.1 Environmental Conditions During Testing:

The following environmental conditions were maintained during the course of testing:

- Ambient Temperature: 20-25° C
- Relative humidity: 40-60%

6.2 Dates of Testing:


03/26/2018 - 03/30/2018



7 Measurement Procedures

7.1 Radiated Measurement

The radiated measurement is performed according to ANSI C63.10 (2013)

- The exploratory measurement is accomplished by running a matrix of 16 sweeps over the required frequency range with R&S Test-SW EMC32 for 4 positions of the turntable, two orthogonal positions of the EUT and both antenna polarizations. This procedure exceeds the requirement of the above standards to cover the 3 orthogonal axis of the EUT. A max peak detector is utilized during the exploratory measurement. The Test-SW creates an overall maximum trace for all 12 sweeps and saves the settings for each point of this trace. The maximum trace is part of the test report.
- The 10 highest emissions are selected with an automatic algorithm of EMC32 searching for peaks in the noise floor and ensuring that broadband signals are not selected multiple times.
- The maxima are then put through the final measurement and again maximized in a 90deg range of the turntable, fine search in frequency domain and height scan between 1m and 4m.
- The above procedure is repeated for all possible ways of power supply to EUT and for all supported modulations.
- In case there are no emissions above noise floor level only the maximum trace is reported as described above.
- The results are split up into up to 4 frequency ranges due to antenna bandwidth restrictions. A magnetic loop is used from 9 kHz to 30 MHz, a Biconilog antenna is used from 30 MHz to 1 GHz, and two different horn antennas are used to cover frequencies up to 40 GHz.



Radiated Emissions Test Setup 30MHz-1GHz Measurements**Radiated Emissions Test Setup above 1GHz Measurements**

7.1.1 Sample Calculations for Field Strength Measurements

Field Strength is calculated from the Spectrum Analyzer/ Receiver readings, taking into account the following parameters:

1. Measured reading in dB μ V
2. Cable Loss between the receiving antenna and SA in dB and
3. Antenna Factor in dB/m

All radiated measurement plots in this report are taken from a test SW that calculates the Field Strength based on the following equation:

$$FS \text{ (dB}\mu\text{V/m)} = \text{Measured Value on SA (dB}\mu\text{V)} - \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$$

Example:

Frequency (MHz)	Measured SA (dB μ V)	Cable Loss (dB)	Antenna Factor Correction (dB)	Field Strength Result (dB μ V/m)
1000	80.5	3.5	14	98.0

7.2 Power Line Conducted Measurement Procedure

AC Power Line conducted emissions measurements performed according to: ANSI C63.4 (2014)

7.3 RF Conducted Measurement Procedure

Testing procedures are based on 558074 D01 DTS Meas Guidance v04 – “GUIDANCE FOR PERFORMING COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEMS (DTS) OPERATING UNDER SECTION 15.247” - April 5, 2017, by the Federal Communications Commission, Office of Engineering and Technology, Laboratory Division.



- Connect the equipment as shown in the above diagram.
- Adjust the settings of the SA (Rohde-Schwarz Spectrum Analyzer) to connect the EUT at the required mode of test.
- Measurements are to be performed with the EUT set to the low, middle and high channels and for worst case modulation schemes.

8 Test Result Data

8.1 Maximum Peak Conducted Output Power

8.1.1 Measurement according to FCC 558074 D01 DTS Meas Guidance v04

Spectrum Analyzer settings:

- RBW \geq DTS bandwidth
- VBW $\geq 3 \times$ RBW
- Span $\geq 3 \times$ RBW
- Sweep = Auto couple
- Detector function = Peak
- Trace = Max hold
- Use peak marker function to determine the peak amplitude level

8.1.2 Limits:

Maximum Peak Output Power:

- FCC §15.247 (b)(1): 1 W
- IC RSS-247: 1 W

8.1.3 Test conditions and setup:

Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input	Antenna Gain
22° C	1	GFSK continuous fixed channel	Battery, 3.6VDC nominal	1 dBi


8.1.4 Measurement result:**BTLE 4.0**


Plot #	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)	EIRP (dBm)	Limit (dBm)	Result
1	2402	5.04	7.04	30 (Pk) / 36 (EIRP)	Pass
2	2440	4.51	6.51	30 (Pk) / 36 (EIRP)	Pass
3	2480	4.44	6.44	30 (Pk) / 36 (EIRP)	Pass


BTLE 5.0 with 2Mbps


Plot #	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)	EIRP (dBm)	Limit (dBm)	Result
4	2402	6.11	8.11	30 (Pk) / 36 (EIRP)	Pass
5	2440	5.94	7.94	30 (Pk) / 36 (EIRP)	Pass
6	2480	5.94	7.94	30 (Pk) / 36 (EIRP)	Pass


8.1.5 Measurement Plots:














8.2 Power Spectral Density

8.2.1 Measurement according to FCC 558074 D01 DTS Meas Guidance v04

Spectrum Analyzer settings for Peak PSD method:

- Set analyzer center frequency to DTS channel center frequency
- Set the span to 1.5 x DTS bandwidth
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
- Set the VBW $\geq 3 \times \text{RBW}$
- Detector = Peak
- Sweep time = Auto couple
- Trace mode = Max hold
- Allow trace to fully stabilize
- Use the peak marker function to determine the maximum amplitude level within the RBW
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat

8.2.2 Limits:

FCC§15.247(e) & RSS-247 5.2(2)

- For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


8.2.3 Test conditions and setup:


Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input	Antenna Gain
22° C	1	BTLE 5.0 with 2Mbps GFSK continuous fixed channel	3.6 VDC	1 dBi


8.2.4 Measurement result:

Plot #	Frequency (MHz)	Maximum Power Spectral Density (dBm/3 kHz)	PSD Adjusted for Antenna Gain (dBm/3 kHz)	Limit (dBm / 3 kHz)	Result
1	2402	-11.71	-9.71	8	Pass
2	2441	-12.19	-10.19	8	Pass
3	2480	-11.98	-9.98	8	Pass

8.2.5 Measurement Plots:







8.3 Band Edge Compliance

8.3.1 Measurement according to FCC 558074 D01 DTS Meas Guidance v04

Spectrum Analyzer settings for band edge:

- Set the center frequency and span to encompass frequency range to be measured
- RBW = 100 kHz
- VBW \geq 3 x RBW
- Sweep Time: Auto couple
- Detector = Peak
- Trace = Max hold
- Allow trace to fully stabilize
- Use the peak marker function to determine the maximum amplitude level
- Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge

8.3.2 Limits non restricted band:

FCC§15.247 (d)

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

RSS-247 5/5

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB.

Spectrum Analyzer settings for restricted band:

- Peak measurements are made using a peak detector and RBW=1 MHz

8.3.3 Limits restricted band §15.247/15.209/15.205 and RSS-Gen 8.9/8.10

- *PEAK LIMIT= 74 dB μ V/m @3m =-21.23 dBm
- *AVG. LIMIT= 54 dB μ V/m @3m =-41.23 dBm
- Start frequency & stop frequency according to frequency range specified in the restricted band table in FCC section 15.205 & RSS-Gen 8.10
- Measurements with a peak detector were used to show compliance to average limits, thus showing compliance to both peak and average limits.

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

8.3.4 Test conditions and setup:


Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input	Antenna Gain
22° C	1	BTLE 5.0 with 2Mbps GFSK continuous fixed channel	3.6 VDC	1 dBi


8.3.5 Measurement result:


Plot #	EUT operating mode	Band Edge	Band Edge Delta (dBc)	Limit (dBc)	Result
1	GFSK continuous fixed channel	Lower, Non-restricted	31.83	20	Pass

Plot #	EUT operating mode	Band Edge	Measured Peak Value (dBm)	Corrected by duty cycle	Corrected by Antenna Gain (dBm)	Limit (dBm)	Result
2	GFSK continuous fixed channel	Upper Restricted Peak	-23.35	NA due to peak detector, and trace max hold	-21.35	-21.23 Peak	Pass
3	GFSK continuous fixed channel	Upper Restricted AVG	-51.06	-46.5	-44.5	-41.23 AVG	Pass

8.3.6 Measurement Plots:







8.4 Emission Bandwidth 6dB and 99% Occupied Bandwidth

8.4.1 Measurement according to FCC 558074 D01 DTS Meas Guidance v04

Spectrum Analyzer settings:

- Set RBW = 100 kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW
- Detector = Peak
- Trace mode = Max hold
- Sweep = Auto couple
- Allow the trace to stabilize
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

8.4.2 Limits:

FCC §15.247(a)(1) and RSS-247 5.2(1)

- Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

8.4.3 Test conditions and setup:


Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input
22° C	1	BTLE 5.0 with 2Mbps GFSK continuous fixed channel	3.6 VDC


8.4.4 Measurement result:


Plot #	Frequency (MHz)	6dB Emissions Bandwidth (MHz)	Limit (MHz)	Result
1	2402	1.159	> 0.5	Pass
2	2441	1.187	> 0.5	Pass
3	2480	1.201	> 0.5	Pass


Plot #	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Limit (MHz)	Result
4	2402	2.057	> 0.5	Pass
5	2441	2.057	> 0.5	Pass
6	2480	2.072	> 0.5	Pass


8.4.5 Measurement Plots:














8.5 Radiated Transmitter Spurious Emissions and Restricted Bands

8.5.1 Measurement according to ANSI C63.10 (2013)

Spectrum Analyzer Settings:

- Frequency = 9 KHz – 30 MHz
- RBW = 9 KHz
- Detector: Peak
- Frequency = 30 MHz – 1 GHz
- Detector = Peak / Quasi-Peak
- RBW= 120 KHz (<1GHz)
- Frequency > 1 GHz
- Detector = Peak / Average
- RBW = 1 MHz
- Radiated spurious emissions shall be measured for the transmit frequencies, transmit power, and data rate for the lowest, middle and highest channel in each frequency band of operation and for the highest gain antenna for each antenna type, and using the appropriate parameters and test requirements.
- The highest (or worst-case) data rate shall be recorded for each measurement.
- For testing at distance other than the specified in the standard, the limit conversion is calculated by using 40 dB/decade extrapolation factor as follow: Conversion factor (CF) = $40 \log(D/d) = 40 \log(300m / 3m) = 80dB$

8.5.2 Limits:

FCC §15.247

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

FCC §15.209 & RSS-Gen 8.9

- Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency of emission (MHz)	Field strength (μ V/m)	Measurement Distance (m)	Field strength @ 3m (dB μ V/m)
0.009–0.490	2400/F(kHz) / -----	300	-
0.490–1.705	24000/F(kHz) / -----	30	-
1.705–30.0	30 / (29.5)	30	-
30–88	100	3	40 dB μ V/m
88–216	150	3	43.5 dB μ V/m
216–960	200	3	46 dB μ V/m
Above 960	500	3	54 dB μ V/m

FCC §15.205 & RSS-Gen 8.10

- Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

- Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

*PEAK LIMIT= 74 dB μ V/m

*AVG. LIMIT= 54 dB μ V/m


8.5.3 Test conditions and setup:




Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input
22° C	2	BTLE 5.0 with 2Mbps GFSK continuous fixed channel	Battery 3.6 VDC




8.5.4 Measurement result:




Plot #	Channel #	Scan Frequency	Limit	Result
1-3	Low	30 MHz – 18 GHz	See section 8.5.2	Pass
4-8	Mid	9 kHz – 26 GHz	See section 8.5.2	Pass
9-11	High	30 MHz – 18 GHz	See section 8.5.2	Pass


8.5.5 Measurement Plots:











9 Test setup photos

Setup photos are included in supporting file name: "EMC_IRHYT_011_15.247_DTS_Setup_Photos.pdf"

10 Test Equipment And Ancillaries Used For Testing

Item Name	Equipment Type	Manufacturer	Model	Serial #	Calibration Cycle	Last Calibration Date
Antenna Loop Passive	Loop Antenna	ETS Lindgren	6507	161344	3 Year	10/26/2017
Antenna Biconilog 3142E	Biconlog Antenna	EMCO	3142E	166067	3 Year	06/27/2017
Antenna Horn 3115 SN 35111	Horn Antenna	EMCO	3115	35111	3 Year	07/24/2015
Antenna Horn 3116	Horn Antenna	ETS Lindgren	3116	70497	3 Year	10/31/2017
Horn Antenna 3117-PA	Horn Antenna	ETS Lindgren	3117-PA	215984	3 Year	01/26/2018
ESU40	EMI Test Receiver	Rohde & Schwarz	ESU40	100251	3 Year	01/31/2018
Thermometer Humidity TM320	Thermometer Humidity	Dickson	TM320	5280063	1 Year	11/02/2017
CMW500	Base Station Simulator	R&S	CMW500	127068	2 Year	07/01/2017
FSU	Spectrum Analyzer	R&S	FSU	200256	2 Year	07/04/2017

Note:

1. Equipment used meets the measurement uncertainty requirements as required per applicable standards for 95% confidence levels.

Calibration due dates, unless defined specifically, falls on the last day of the month. Items indicated "N/A" for cal status either do not specifically require calibration or is internally characterized before use.

Test Report #: EMC_IRHYT_011_15.247_DTS

FCC ID: 2AFBP-AT18G

Date of Report 2018-04-17

Page 44 of 44

IC ID: -----

11 History

Date	Report Name	Changes to report	Report prepared by
2018-04-17	EMC_IRHYT_011_15.247_DTS	Initial Version	Kevin Wang