

RF Exposure Evaluation Report

FCC ID : 2AFD2-IO6
Equipment : Bluetooth Headphone
Brand Name : DALI
Model Name : DALI iO-6, DALI iO-4
Applicant : DALI A/S
Dali Alle 1, 9610 Noerager, Denmark
Manufacturer : DALI A/S
Dali Alle 1, 9610 Noerager, Denmark
Standard : 47 CFR FCC Part 2 Subpart J, section 2.1093

The product was received on Jun. 28, 2019, and testing was started from Jul. 04, 2019 and completed on Jul. 04, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in KDB447498 D01 General RF Exposure Guidance v06 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Allen Lin

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of This Test Report	3
1. General Description	4
1.1. EUT General Information	4
1.2. Testing Location Information	4
1.3. Table for Multiple Listing	4
2. RF Exposure Evaluation	5
2.1. Applicable Standard	5
2.2. SAR evaluation	5
Photographs of EUT V01	



HISTORY OF THIS TEST REPORT

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA962606	01	Initial issue of report	Aug. 14, 2019

Reviewed by: Sam Tsai

Report Producer: Michelle Tsai

1. GENERAL DESCRIPTION

1.1. EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
Bluetooth	2400-2483.5	2402-2480	BR / EDR: FHSS (GFSK / $\pi/4$ -DQPSK / 8DPSK) LE: DSSS (GFSK)

1.2. Testing Location Information

Testing Location		
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL : 886-3-327-3456 FAX : 886-3-327-0973
Test site Designation No. TW1190 with FCC.		
<input type="checkbox"/>	JHUBEI	ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.) TEL : 886-3-656-9065 FAX : 886-3-656-9085
Test site Designation No. TW0006 with FCC.		

1.3. Table for Multiple Listing

The model names in the following table are all refer to the identical product.

Model Name	Description
DALI iO-6	Model iO-6 is full function, iO-4 removed a function ANC noise reduction and button, compared to iO-6. There are two appearance colors.
DALI iO-4	

2. RF EXPOSURE EVALUATION

2.1. Applicable Standard

In accordance with FCC 47 CFR part 2 (2.1093) this device has been defined as a portable device which is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

Portable devices must be evaluated using the specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

2.2. SAR evaluation

- Per FCC KDB 447498 D01 v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$$

$$[\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

- ♦ $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- ♦ Power and distance are rounded to the nearest mW and mm before calculation
- ♦ The result is rounded to one decimal place for comparison

Max. Power (dBm)	Gain (dBi)	Tolerance (dB)	Tune-up Max. Power (dBm)	Max. Power (mW)	Test Distance (mm)	Frequency (GHz)	Exclusion Thresholds
1.95	1.94	0.00	3.89	2.45	5	2.402	0.76

- Per FCC KDB 447498 D01 v06 exclusion thresholds is $2.45 < 3$, RF exposure evaluation is not required.

—————THE END—————