

溧阳金利宝胶粘制品有限公司

KINGLABEL ADHESIVE PRODUCTS CO.,LTD (LIYANG)

SPECIFICATION

编号: B-013-007

品名 ARTICLE NAME	50 番白色特 多龙标纸自 动贴标用	代 号 CODE	HTLW50	英文名 称 ENGLISH NAME	50μ POLYESTER WHITE FOR AUTO-STICKER
产品结构 PRODUCTION CONSTRUCTION				 SURFACE MATERIAL  SYNTHETIC RESIN  LINER	
面 材 SURFACE MATERIAL	T174		底 纸 LINER		SP-FCRPW80
材料名称 ARTICLE NAME	聚酯膜 POLYESTER FILM		材料名称 ARTICLE NAME		格拉辛离型纸 GLASSINE RELEASE PAPER
厚度 (mm) THICKNESS	0.050±0.005		厚度 (mm) THICKNESS		0.066±0.008
基重(g/m ²) BASIC WEIGHT	70±5		基重(g/m ²) BASIC WEIGHT		80±5
颜色 COLOR	白色 WHITE		颜色 COLOR		白色 WHITE
平滑度 SMOOTHNESS	GOOD		平滑度 SMOOTHNESS		GOOD
印刷性 PRINT ABILITY	GOOD		斩性 DIE CUTTING		GOOD
粘 胶 PRESSURE SENSITIVE ADHESIVE			F06		
胶系 ADHESIVE	压克力系 ACRYLIC		剥离力(gf/inch) RELEASE FORCE		10±6
上胶厚度 (mm) THICKNESS	0.026±0.003		保持力 (hr/kg × inch) HOLDING POWER		8 ↑
上胶量 (g/m ²) DRY COATING WEIGHT	26±3		耐候性 WEATHER RESISTANCE		GOOD
加热减量(WT%) SOVLANT RETENTION	1.0 ↓		适用温度(°C) TEMPERATURE RANGE		5~125
初期力(NO/BALL) INITIAL TACK	4~10		耐溶剂 SOLVENT RESISTANCE		GOOD
粘着力(kgf/inch) 180° PEEL ADHESIVE	0.6~1.8				
备注: REMARK:	以上诸项技术资料乃本公司采用公认可靠之检验方法,经多次检验所得平均数据,为确保正确选择与使用本公司之产品,请您基于欲使用之对象,先行对使用目的与条件作详细了解与试用,或通知本公司,以便为您更进一步说明与服务。 THE TECHNIAL DATA ARE BASED ON THE RELIABLE EXPERIMENT CARRIED BY THE COMPANY.WHICH HOWEVER ARE NOT TO GAURANTEE THOSE PROPERTIES AND CHARACTERISTICS COMPLETELY AS SPECIFIED THEREIN,KINDLY STUDY YOUR PURPOSE AND CONDITION TO USE THIS PRODUCT PREVIOUSLY IN DETAIL UPON YOUR OWN RESPONSIBILITY.				
版本号	第 1 版	修订日期	8/5/2010	修订次数	第 0 次