

# FCC Radio Test Report

## FCC ID: 2AFFY-FT02

### Original Grant


**Report No.** : TB-FCC161390  
**Applicant** : Viatek Consumer Products Group, Inc.  
**Equipment Under Test (EUT)**  
**EUT Name** : Bluetooth FM Transmitter  
**Model No.** : FT-02  
**Series Model No.** : N/A  
**Brand Name** : N/A  
**Receipt Date** : 2018-08-08  
**Test Date** : 2018-08-09 to 2018-08-19  
**Issue Date** : 2018-08-25  
**Standards** : FCC Part 15: 2017, Subpart C(15.247)  
**Test Method** : ANSI C63.10: 2013  
**Conclusions** : **PASS**

In the configuration tested, the EUT complied with the standards specified above,  
The EUT technically complies with the FCC requirements

**Test/Witness Engineer** : Jason Xu

**Engineer Supervisor** : Ivan Su

**Engineer Manager** : Ray Lai



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.



---

---

## Contents

<b>CONTENTS.....</b>	<b>2</b>
<b>1. GENERAL INFORMATION ABOUT EUT .....</b>	<b>5</b>
1.1 Client Information.....	5
1.2 General Description of EUT (Equipment Under Test) .....	5
1.3 Block Diagram Showing the Configuration of System Tested.....	6
1.4 Description of Support Units .....	7
1.5 Description of Test Mode.....	7
1.6 Description of Test Software Setting .....	8
1.7 Measurement Uncertainty .....	8
1.8 Test Facility.....	9
<b>2. TEST SUMMARY.....</b>	<b>10</b>
<b>3. TEST EQUIPMENT.....</b>	<b>11</b>
<b>4. CONDUCTED EMISSION TEST .....</b>	<b>12</b>
4.1 Test Standard and Limit.....	12
4.2 Test Setup.....	12
4.3 Test Procedure.....	12
4.4 EUT Operating Mode .....	13
4.5 Test Data.....	13
<b>5. RADIATED EMISSION TEST .....</b>	<b>14</b>
5.1 Test Standard and Limit.....	14
5.2 Test Setup.....	15
5.3 Test Procedure.....	16
5.4 EUT Operating Condition .....	16
5.5 Test Data.....	16
<b>6. RESTRICTED BANDS REQUIREMENT .....</b>	<b>17</b>
6.1 Test Standard and Limit.....	17
6.2 Test Setup.....	17
6.3 Test Procedure.....	17
6.4 EUT Operating Condition .....	18
6.5 Test Data.....	18
<b>7. NUMBER OF HOPPING CHANNEL .....</b>	<b>19</b>
7.1 Test Standard and Limit.....	19
7.2 Test Setup.....	19
7.3 Test Procedure.....	19
7.4 EUT Operating Condition .....	19
7.5 Test Data.....	19
<b>8. AVERAGE TIME OF OCCUPANCY.....</b>	<b>20</b>
8.1 Test Standard and Limit.....	20
8.2 Test Setup.....	20



---

8.3 Test Procedure.....	20
8.4 EUT Operating Condition .....	20
8.5 Test Data.....	20
<b>9. CHANNEL SEPARATION AND BANDWIDTH TEST .....</b>	<b>21</b>
9.1 Test Standard and Limit.....	21
9.2 Test Setup.....	21
9.3 Test Procedure.....	21
9.4 EUT Operating Condition .....	21
9.5 Test Data.....	21
<b>10. PEAK OUTPUT POWER TEST.....</b>	<b>22</b>
10.1 Test Standard and Limit .....	22
10.2 Test Setup.....	22
10.3 Test Procedure.....	22
10.4 EUT Operating Condition .....	22
10.5 Test Data.....	22
<b>11. ANTENNA REQUIREMENT.....</b>	<b>23</b>
11.1 Standard Requirement.....	23
11.2 Antenna Connected Construction .....	23
11.3 Result.....	23
<b>ATTACHMENT A-- CONDUCTED EMISSION TEST DATA .....</b>	<b>24</b>
<b>ATTACHMENT B-- RADIATED EMISSION TEST DATA .....</b>	<b>28</b>
<b>ATTACHMENT C-- RESTRICTED BANDS REQUIREMENT TEST DATA.....</b>	<b>42</b>
<b>ATTACHMENT D-- NUMBER OF HOPPING CHANNEL TEST DATA .....</b>	<b>54</b>
<b>ATTACHMENT E-- AVERAGE TIME OF OCCUPANCY TEST DATA.....</b>	<b>56</b>
<b>ATTACHMENT F-- CHANNEL SEPARATION AND BANDWIDTH TEST DATA.....</b>	<b>60</b>
<b>ATTACHMENT G-- PEAK OUTPUT POWER TEST DATA .....</b>	<b>68</b>

---

---

## Revision History

Report No.	Version	Description	Issued Date
TB-FCC161390	Rev.01	Initial issue of report	2018-08-25



## 1. General Information about EUT

### 1.1 Client Information

<b>Applicant</b>	:	Viatak Consumer Products Group, Inc.
<b>Address</b>	:	6011 Century Oaks Drive Chattanooga, TN 37416 USA.
<b>Manufacturer</b>	:	New Tech Development Co., Ltd.
<b>Address</b>	:	3 Flr. Bldg A, JinKe Industrial Park, No.310 Wuhe Road, ShangJing Community, GuanLan Street, LongHua District, Shenzhen, China.

### 1.2 General Description of EUT (Equipment Under Test)

<b>EUT Name</b>	:	Bluetooth FM Transmitter	
<b>Models No.</b>	:	FT-02	
<b>Model Difference</b>	:	N/A	
<b>Product Description</b>	:	Operation Frequency:	Bluetooth V3.0: 2402~2480 MHz
	:	Number of Channel:	Bluetooth: 79 Channels See Note 2
	:	Max Peak Output Power:	Bluetooth: -3.296dBm( $\pi$ /4-DQPSK)
	:	Antenna Gain:	0dBi PCB Antenna
	:	Modulation Type:	GFSK (1 Mbps) $\pi$ /4-DQPSK (2 Mbps)
<b>Power Rating</b>	:	Input: DC 12V-24V.	
<b>Software Version</b>	:	Output:5V/2.1A (Max)	
<b>Hardware Version</b>	:	N/A	
<b>Connecting I/O Port(S)</b>	:	Please refer to the User's Manual	

**Note:**

- (1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.


(2) Channel List:

Bluetooth Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

(3) The Antenna information about the equipment is provided by the applicant.

### 1.3 Block Diagram Showing the Configuration of System Tested

#### Mode 1





## 1.4 Description of Support Units

The EUT has been tested as an independent unit.

## 1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	Description
Mode 1	Normal Working+ TX Mode

For Radiated Test	
Final Test Mode	Description
Mode 1	TX GFSK Mode
Mode 2	TX Mode(GFSK) Channel 00/39/78
Mode 3	TX Mode( $\pi/4$ -DQPSK) Channel 00/39/78
Mode 4	Hopping Mode(GFSK)
Mode 5	Hopping Mode( $\pi/4$ -DQPSK)

### Note:

- (1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate. We have pretested all the test modes above.  
According to ANSI C63.10 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:  
TX Mode: GFSK (1 Mbps)  
TX Mode:  $\pi/4$ -DQPSK (2 Mbps)
- (2) The EUT is considered a portable unit; it was pre-tested on the positioned of each 3 axis, X-plane, Y-plane and Z-plane. The worst case was found positioned on X-plane as the normal use. Therefore only the test data of this X-plane was used for radiated emission measurement test.



## 1.6 Description of Test Software Setting

During testing channel power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of Bluetooth mode.

Test Software Version	FCCAssist_2.4.exe		
Frequency	2402 MHz	2441MHz	2480 MHz
GFSK	DEF	DEF	DEF
$\pi/4$ -DQPSK	DEF	DEF	DEF

## 1.7 Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty ( $U_{Lab}$ )
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	$\pm 3.42$ dB $\pm 3.42$ dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	$\pm 4.60$ dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	$\pm 4.40$ dB
Radiated Emission	Level Accuracy: Above 1000MHz	$\pm 4.20$ dB



---

## 1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

### **CNAS (L5813)**

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

### **A2LA Certificate No.: 4750.01**

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01.

### **IC Registration No.: (11950A-1)**

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.



## 2. Test Summary

FCC Part 15 Subpart C(15.247)/ RSS 247 Issue 2				
Standard Section		Test Item	Judgment	Remark
FCC	IC			
15.203		Antenna Requirement	PASS	N/A
15.207	RSS-GEN 7.2.2	Conducted Emission	PASS	N/A
15.205	RSS-Gen 7.2.3	Restricted Bands	PASS	N/A
15.247(a)(1)	RSS 247 5.1 (2)	Hopping Channel Separation	PASS	N/A
15.247(a)(1)	RSS 247 5.1 (4)	Dwell Time	PASS	N/A
15.247(b)(1)	RSS 247 5.4 (2)	Peak Output Power	PASS	N/A
15.247(b)(1)	RSS 247 5.1 (4)	Number of Hopping Frequency	PASS	N/A
15.247(d)	RSS 247 5.5	Band Edge	PASS	N/A
15.247(c)& 15.209	RSS 247 5.5	Radiated Spurious Emission	PASS	N/A
15.247(a)	RSS 247 5.1 (1)	99% Occupied Bandwidth & 20dB Bandwidth	PASS	99%OBW: GFSK: 838.57kHz $\pi$ /4-DQPSK: 1153.8kHz
<b>Note:</b> N/A is an abbreviation for Not Applicable.				



### 3. Test Equipment

Conducted Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jul. 18, 2018	Jul. 17, 2019
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul. 18, 2018	Jul. 17, 2019
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul. 18, 2018	Jul. 17, 2019
LISN	Rohde & Schwarz	ENV216	101131	Jul. 18, 2018	Jul. 17, 2019
Radiation Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 18, 2018	Jul. 17, 2019
EMI Test Receiver	Rohde & Schwarz	ESPI	100010/007	Jul. 18, 2018	Jul. 17, 2019
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar.16, 2018	Mar. 15, 2019
Bilog Antenna	ETS-LINDGREN	3142E	00117542	Mar.16, 2018	Mar. 15, 2019
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar.16, 2018	Mar. 15, 2019
Horn Antenna	ETS-LINDGREN	3117	00143209	Mar.16, 2018	Mar. 15, 2019
Loop Antenna	Laplace instrument	RF300	0701	Mar.16, 2018	Mar. 15, 2019
Pre-amplifier	Sonoma	310N	185903	Mar.16, 2018	Mar. 15, 2019
Pre-amplifier	HP	8449B	3008A00849	Mar.16, 2018	Mar. 15, 2019
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar.16, 2018	Mar. 15, 2019
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
Antenna Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 18, 2018	Jul. 17, 2019
Spectrum Analyzer	Rohde & Schwarz	ESCI	100010/007	Jul. 18, 2018	Jul. 17, 2019
MXA Signal Analyzer	Agilent	N9020A	MY49100060	Oct. 26, 2017	Oct. 25, 2018
Vector Signal Generator	Agilent	N5182A	MY50141294	Oct. 26, 2017	Oct. 25, 2018
Analog Signal Generator	Agilent	N5181A	MY50141953	Oct. 26, 2017	Oct. 25, 2018
RF Power Sensor	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO26	Oct. 26, 2017	Oct. 25, 2018
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO29	Oct. 26, 2017	Oct. 25, 2018
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO31	Oct. 26, 2017	Oct. 25, 2018
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO33	Oct. 26, 2017	Oct. 25, 2018



## 4. Conducted Emission Test

### 4.1 Test Standard and Limit

4.1.1 Test Standard  
FCC Part 15.207

4.1.2 Test Limit


**Conducted Emission Test Limit**

Frequency	Maximum RF Line Voltage (dB $\mu$ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:

- (1) \*Decreasing linearly with logarithm of the frequency.
- (2) The lower limit shall apply at the transition frequencies.
- (3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2 Test Setup



### 4.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.

#### 4.4 EUT Operating Mode

Please refer to the description of test mode.

#### 4.5 Test Data

Please refer to the Attachment A.



## 5. Radiated Emission Test

### 5.1 Test Standard and Limit

#### 5.1.1 Test Standard

FCC Part 15.209

#### 5.1.2 Test Limit

#### Radiated Emission Limit (9 kHz~1000MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


#### Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Distance Meters(at 3m)	
	Peak	Average
Above 1000	74	54


**Note:**

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBuV/m)=20log Emission Level (uV/m)

## 5.2 Test Setup




**Below 30MHz Test Setup**



**Below 1000MHz Test Setup**





**Above 1GHz Test Setup**

### 5.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

### 5.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power in TX mode.

### 5.5 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Please refer to the Attachment B.



## 6. Restricted Bands Requirement

### 6.1 Test Standard and Limit

#### 6.1.1 Test Standard

FCC Part 15.209


FCC Part 15.205

#### 6.1.2 Test Limit

Restricted Frequency Band (MHz)	Distance Meters(at 3m)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54

**Note: All restriction bands have been tested, only the worst case is reported.**

### 6.2 Test Setup



### 6.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.



- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with AVG Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

#### 6.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

#### 6.5 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

All restriction bands have been tested, only the worst case is reported.

Please refer to the Attachment C.

## 7. Number of Hopping Channel

### 7.1 Test Standard and Limit


#### 6.1.1 Test Standard

FCC Part 15.247 (a)(1)

#### 6.1.2 Test Limit

Section	Test Item	Limit
15.247	Number of Hopping Channel	>15

### 7.2 Test Setup



### 7.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=100 KHz, VBW=100 KHz, Sweep time= Auto.

### 7.4 EUT Operating Condition

The EUT was set to the Hopping Mode by the Customer.

### 7.5 Test Data

Please refer to the Attachment D.



## 8. Average Time of Occupancy

### 8.1 Test Standard and Limit


#### 8.1.1 Test Standard

FCC Part 15.247 (a)(1)

#### 8.1.2 Test Limit

Section	Test Item	Limit
15.247(a)(1)	Average Time of Occupancy	0.4 sec

### 8.2 Test Setup



### 8.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=1MHz, VBW=1MHz.
- (3) Use video trigger with the trigger level set to enable triggering only on full pulses.
- (4) Sweep Time is more than once pulse time.
- (5) Set the center frequency on any frequency would be measure and set the frequency span to zero.
- (6) Measure the maximum time duration of one single pulse.
- (7) Set the EUT for packet transmitting.
- (8) Measure the maximum time duration of one single pulse.

### 8.4 EUT Operating Condition

The average time of occupancy on any channel within the Period can be calculated with formulas:

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / X) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$
$$\{\text{Period}\} = 0.4s * \{\text{Number of Hopping Frequency}\}$$

Note: X=2 or 4 or 6 (1DH1=2, 1DH3=4, 1DH5=6. 2DH1=2, 2DH3=4, 2DH5=6. 3DH1=2, 3DH3=4, 3DH5=6)

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

The EUT was set to the Hopping Mode by the Customer.

### 8.5 Test Data

Please refer to the Attachment E.



## 9. Channel Separation and Bandwidth Test


### 9.1 Test Standard and Limit

9.1.1 Test Standard  
FCC Part 15.247

9.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Bandwidth	$\leq 1$ MHz (20dB bandwidth)	2400~2483.5
Channel Separation	$>25$ KHz or $>$ two-thirds of the 20 dB bandwidth Which is greater	2400~2483.5

### 9.2 Test Setup



### 9.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:  
Channel Separation: RBW=100 kHz, VBW=100 kHz.  
Bandwidth: RBW=30 kHz, VBW=100 kHz.
- (3) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst –case (i.e the widest) bandwidth.
- (4) Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:30 kHz, and Video Bandwidth:100 kHz. Sweep Time set auto.

### 9.4 EUT Operating Condition

The EUT was set to the Hopping Mode for Channel Separation Test and continuously transmitting for the Bandwidth Test.

### 9.5 Test Data

Please refer to the Attachment F.



## 10. Peak Output Power Test

### 10.1 Test Standard and Limit


#### 10.1.1 Test Standard

FCC Part 15.247 (b) (1)

#### 10.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Peak Output Power	Hopping Channels>75 Power<1W(30dBm) Other <125 mW(21dBm)	2400~2483.5

### 10.2 Test Setup



### 10.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:  
Peak Detector: RBW=1 MHz, VBW=3 MHz for bandwidth less than 1MHz.  
RBW=3 MHz, VBW=3 MHz for bandwidth more than 1MHz.

### 10.4 EUT Operating Condition

The EUT was set to continuously transmitting in the max power during the test.

### 10.5 Test Data

Please refer to the Attachment G.

## 11. Antenna Requirement

### 11.1 Standard Requirement

#### 11.1.1 Standard

FCC Part 15.203

#### 11.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 11.2 Antenna Connected Construction

The gains of the antenna used for transmitting is 0dBi, and the antenna connector is de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

### 11.3 Result


The EUT antenna is a PCB Antenna. It complies with the standard requirement.

Antenna Type	
<input checked="" type="checkbox"/>	Permanent attached antenna
<input type="checkbox"/>	Unique connector antenna
<input type="checkbox"/>	Professional installation antenna



## Attachment A-- Conducted Emission Test Data


Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 12V		
Terminal:	Line		
Test Mode:	Normal Mode		
Remark:	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.2139	33.45	0.08	33.53	63.05	-29.52	QP
2		0.2139	32.83	0.08	32.91	53.05	-20.14	AVG
3		0.3180	40.44	0.07	40.51	59.76	-19.25	QP
4	*	0.3180	40.10	0.07	40.17	49.76	-9.59	AVG
5		0.4259	29.91	0.06	29.97	57.33	-27.36	QP
6		0.4259	28.85	0.06	28.91	47.33	-18.42	AVG
7		0.5299	35.29	0.06	35.35	56.00	-20.65	QP
8		0.5299	34.74	0.06	34.80	46.00	-11.20	AVG
9		0.7419	32.51	0.05	32.56	56.00	-23.44	QP
10		0.7419	31.90	0.05	31.95	46.00	-14.05	AVG
11		0.9578	29.79	0.05	29.84	56.00	-26.16	QP
12		0.9578	28.68	0.05	28.73	46.00	-17.27	AVG

Emission Level= Read Level+ Correct Factor


Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 12V		
Terminal:	Neutral		
Test Mode:	Normal Mode		
Remark:	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.2139	32.18	0.04	32.22	63.05	-30.83	QP
2		0.2139	31.35	0.04	31.39	53.05	-21.66	AVG
3		0.3180	41.11	0.03	41.14	59.76	-18.62	QP
4	*	0.3180	40.74	0.03	40.77	49.76	-8.99	AVG
5		0.5299	34.78	0.02	34.80	56.00	-21.20	QP
6		0.5299	34.25	0.02	34.27	46.00	-11.73	AVG
7		0.7419	30.47	0.01	30.48	56.00	-25.52	QP
8		0.7419	29.99	0.01	30.00	46.00	-16.00	AVG
9		5.9378	33.75	0.02	33.77	60.00	-26.23	QP
10		5.9378	31.10	0.02	31.12	50.00	-18.88	AVG
11		18.2577	38.83	0.16	38.99	60.00	-21.01	QP
12		18.2577	30.36	0.16	30.52	50.00	-19.48	AVG

Emission Level= Read Level+ Correct Factor





Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 24V		
Terminal:	Neutral		
Test Mode:	Normal Mode		
Remark:	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.2139	38.34	0.04	38.38	63.05	-24.67	QP
2		0.2139	37.77	0.04	37.81	53.05	-15.24	AVG
3		0.3180	39.06	0.03	39.09	59.76	-20.67	QP
4	*	0.3180	38.26	0.03	38.29	49.76	-11.47	AVG
5		0.5299	34.97	0.02	34.99	56.00	-21.01	QP
6		0.5299	34.07	0.02	34.09	46.00	-11.91	AVG
7		0.7419	33.29	0.01	33.30	56.00	-22.70	QP
8		0.7419	32.49	0.01	32.50	46.00	-13.50	AVG
9		0.9577	30.90	0.01	30.91	56.00	-25.09	QP
10		0.9577	29.83	0.01	29.84	46.00	-16.16	AVG
11		6.2698	34.57	0.03	34.60	60.00	-25.40	QP
12		6.2698	32.48	0.03	32.51	50.00	-17.49	AVG

Emission Level= Read Level+ Correct Factor



## Attachment B-- Radiated Emission Test Data


### 9KHz~30MHz

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

### 30MHz~1GHz

Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 12V		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		57.5938	42.79	-24.10	18.69	40.00	-21.31	QP
2		62.2128	46.03	-24.17	21.86	40.00	-18.14	QP
3	*	87.7248	45.67	-22.10	23.57	40.00	-16.43	QP
4		301.4223	36.10	-16.16	19.94	46.00	-26.06	QP
5		385.2805	39.15	-12.95	26.20	46.00	-19.80	QP
6		482.2155	40.31	-11.10	29.21	46.00	-16.79	QP

\*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 12V		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		59.6492	47.43	-24.32	23.11	40.00	-16.89	QP
2	*	87.7248	55.07	-22.10	32.97	40.00	-7.03	QP
3		170.7923	43.49	-20.49	23.00	43.50	-20.50	QP
4		192.4182	49.87	-19.85	30.02	43.50	-13.48	QP
5		289.0020	48.75	-16.42	32.33	46.00	-13.67	QP
6		385.2805	42.98	-12.95	30.03	46.00	-15.97	QP


\*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor



**Above 1GHz (Only worse case is reported)**


Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 12V		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4803.340	43.04	14.42	57.46	74.00	-16.54	peak
2	*	4803.340	29.25	14.42	43.67	54.00	-10.33	AVG

**Emission Level= Read Level+ Correct Factor**

Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 12V		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4835.200	29.81	14.62	44.43	54.00	-9.57	AVG
2		4838.400	42.51	14.64	57.15	74.00	-16.85	peak

Emission Level= Read Level+ Correct Factor




Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 12V		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2441MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4880.554	29.93	14.90	44.83	54.00	-9.17	AVG
2		4882.150	43.96	14.91	58.87	74.00	-15.13	peak

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 12V		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2441MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4880.500	29.80	14.89	44.69	54.00	-9.31	AVG
2		4883.398	43.60	14.91	58.51	74.00	-15.49	peak

Emission Level= Read Level+ Correct Factor




Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 12V		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2480MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4959.928	43.47	15.39	58.86	74.00	-15.14	peak
2	*	4959.928	29.64	15.39	45.03	54.00	-8.97	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 12V		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2480MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4959.580	43.40	15.39	58.79	74.00	-15.21	peak
2	*	4959.580	29.90	15.39	45.29	54.00	-8.71	AVG

Emission Level= Read Level+ Correct Factor




Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 12V		
Ant. Pol.	Horizontal		
Test Mode:	TX $\pi$ /4-DQPSK Mode 2402MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4804.474	29.68	14.44	44.12	54.00	-9.88	AVG
2		4804.888	43.22	14.44	57.66	74.00	-16.34	peak

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 12V		
Ant. Pol.	Vertical		
Test Mode:	TX $\pi$ /4-DQPSK Mode 2402MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4805.242	42.73	14.44	57.17	74.00	-16.83	peak
2	*	4805.500	29.33	14.44	43.77	54.00	-10.23	AVG

Emission Level= Read Level+ Correct Factor




Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 12V		
Ant. Pol.	Horizontal		
Test Mode:	TX $\pi$ /4-DQPSK Mode 2441MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4883.086	43.56	14.91	58.47	74.00	-15.53	peak
2	*	4883.086	29.66	14.91	44.57	54.00	-9.43	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 12V		
Ant. Pol.	Vertical		
Test Mode:	TX $\pi$ /4-DQPSK Mode 2441MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4881.040	43.04	14.91	57.95	74.00	-16.05	peak
2	*	4883.266	29.95	14.91	44.86	54.00	-9.14	AVG

Emission Level= Read Level+ Correct Factor




Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 12V		
Ant. Pol.	Horizontal		
Test Mode:	TX $\pi$ /4-DQPSK Mode 2480MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4960.378	43.06	15.40	58.46	74.00	-15.54	peak
2	*	4961.500	30.09	15.41	45.50	54.00	-8.50	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 12V		
Ant. Pol.	Vertical		
Test Mode:	TX $\pi$ /4-DQPSK Mode 2480MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4958.560	30.01	15.39	45.40	54.00	-8.60	AVG
2		4960.450	43.10	15.40	58.50	74.00	-15.50	peak

Emission Level= Read Level+ Correct Factor



## Attachment C-- Restricted Bands Requirement Test Data

### (1) Radiation Test

Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 12V		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	Only worse case is reported		

100.0 dBuV/m

50

0.0

2306.00 2316.00 2326.00 2336.00 2346.00 2356.00 2366.00 2376.00 2386.00 2406.00 MHz

(RF) FCC PART 15C (PEAK) 3 X

(RF) FCC PART 15C (AVG) 4 X

1 X

2 X


  

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	41.64	2.82	44.46	74.00	-29.54	peak
2		2390.000	30.16	2.82	32.98	54.00	-21.02	AVG
3	X	2402.000	71.38	2.87	74.25	Fundamental Frequency		peak
4	*	2402.000	61.36	2.87	64.23	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor


Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 12V		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	41.11	2.82	43.93	74.00	-30.07	peak
2		2390.000	30.20	2.82	33.02	54.00	-20.98	AVG
3		2402.000	67.58	2.87	70.45	Fundamental Frequency		peak
4	*	2402.200	56.12	2.87	58.99	Fundamental Frequency		AVG


Emission Level= Read Level+ Correct Factor




























## (2) Conducted Test

Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 12V		
Test Mode:	TX GFSK Mode 2402MHz/2480 MHz		
Remark:	Only worse case is reported		





Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 12V		
Test Mode:	GFSK Hopping Mode		
Remark:	Only worse case is reported		







Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 12V		
Test Mode:	TX $\pi$ /4-DQPSK Mode 2402MHz/2480 MHz		
Remark:	Only worse case is reported		



Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 12V		
Test Mode:	$\pi$ /4-DQPSK Hopping Mode		
Remark:	Only worse case is reported		






## Attachment D-- Number of Hopping Channel Test Data

Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 12V		
Test Mode:	Hopping Mode		
Frequency Range	Test Mode	Quantity of Hopping Channel	Limit
2402MHz~2480MHz	GFSK	79	>15
	$\pi$ /4-DQPSK	79	

GFSK Mode



Keysight Spectrum Analyzer - Swept SA

Center Freq 2.441750000 GHz

Ref Offset 3.59 dB  
Ref 23.59 dBm


Mkr1 2.402 087 5 GHz  
-4.818 dBm

Start 2.40000 GHz  
#Res BW 100 kHz

Stop 2.48350 GHz  
Sweep 8.000 ms (1001 pts)

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.402 087 5 GHz	-4.818 dBm			
2	N	1	f	2.480 160 0 GHz	-5.127 dBm			
3								
4								
5								
6								
7								
8								
9								
10								
11								

$\pi$  /4-DQPSK Mode






## Attachment E-- Average Time of Occupancy Test Data

Temperature:		25℃		Relative Humidity:		55%	
Test Voltage:		DC 12V					
Test Mode:		Hopping Mode (GFSK)					
Test Mode	Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result	
1DH1	2441	0.367	117.44	31.60	400	PASS	
1DH3	2441	1.623	259.68	31.60	400	PASS	
1DH5	2441	2.871	306.24	31.60	400	PASS	
1DH1 Total of Dwell= Pulse Time*(1600/2)*31.6/79							
1DH3 Total of Dwell= Pulse Time*(1600/4)*31.6/79							
1DH5 Total of Dwell= Pulse Time*(1600/6)*31.6/79							


### GFSK Hopping Mode 1DH1

2441 MHz




### GFSK Hopping Mode 1DH3

2441 MHz




### GFSK Hopping Mode 1DH5

2441 MHz






Temperature:		25°C		Relative Humidity:		55%
Test Voltage:		DC 12V				
Test Mode:		Hopping Mode ( $\pi$ /4-DQPSK)				
Test Mode	Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2DH1	2441	0.377	120.64	31.60	400	PASS
2DH3	2441	1.628	260.48	31.60	400	PASS
2DH5	2441	2.877	306.88	31.60	400	PASS
2DH1 Total of Dwell= Pulse Time*(1600/2)*31.6/79						
2DH3 Total of Dwell= Pulse Time*(1600/4)*31.6/79						
2DH5 Total of Dwell= Pulse Time*(1600/6)*31.6/79						
$\pi$ /4-DQPSK Hopping Mode 2DH1						
2441 MHz						




$\pi/4$ -DQPSK Hopping Mode 2DH3

2441 MHz




$\pi/4$ -DQPSK Hopping Mode 2DH5

2441 MHz






# Attachment F-- Channel Separation and Bandwidth Test Data

Temperature:	25°C	Relative Humidity:	55%																																
Test Voltage:	DC 12V																																		
Test Mode:	TX Mode (GFSK)																																		
Channel frequency (MHz)	99% OBW (kHz)	20dB Bandwidth (kHz)	20dB Bandwidth *2/3 (kHz)																																
2402	838.57	890.8																																	
2441	831.85	890.4																																	
2480	823.57	881.1																																	
GFSK TX Mode																																			
2402 MHz																																			
 <table border="1"> <thead> <tr> <th colspan="4">Keysight Spectrum Analyzer - Occupied BW</th> </tr> </thead> <tbody> <tr> <td>Center Freq: 2.402000000 GHz</td> <td>Trig: Free Run</td> <td>Avg/Hold: &gt;10/10</td> <td>Radio Std: None</td> </tr> <tr> <td>#FGain: Low</td> <td>#Atten: 10 dB</td> <td colspan="2">Radio Device: BTS</td> </tr> <tr> <td colspan="4"> <p>15 dB/div Ref 20.00 dBm</p> <p>Center 2.402 GHz #Res BW 30 kHz #VBW 100 kHz Span 2 MHz Sweep 2.667 ms</p> </td> </tr> <tr> <td>Occupied Bandwidth</td> <td>Total Power</td> <td colspan="2">-1.58 dBm</td> </tr> <tr> <td>838.57 kHz</td> <td>% of OBW Power</td> <td colspan="2">99.00 %</td> </tr> <tr> <td>Transmit Freq Error</td> <td>91.633 kHz</td> <td>x dB Bandwidth</td> <td>890.8 kHz</td> </tr> <tr> <td>x dB Bandwidth</td> <td>890.8 kHz</td> <td>x dB</td> <td>-20.00 dB</td> </tr> </tbody> </table>				Keysight Spectrum Analyzer - Occupied BW				Center Freq: 2.402000000 GHz	Trig: Free Run	Avg/Hold: >10/10	Radio Std: None	#FGain: Low	#Atten: 10 dB	Radio Device: BTS		<p>15 dB/div Ref 20.00 dBm</p> <p>Center 2.402 GHz #Res BW 30 kHz #VBW 100 kHz Span 2 MHz Sweep 2.667 ms</p>				Occupied Bandwidth	Total Power	-1.58 dBm		838.57 kHz	% of OBW Power	99.00 %		Transmit Freq Error	91.633 kHz	x dB Bandwidth	890.8 kHz	x dB Bandwidth	890.8 kHz	x dB	-20.00 dB
Keysight Spectrum Analyzer - Occupied BW																																			
Center Freq: 2.402000000 GHz	Trig: Free Run	Avg/Hold: >10/10	Radio Std: None																																
#FGain: Low	#Atten: 10 dB	Radio Device: BTS																																	
<p>15 dB/div Ref 20.00 dBm</p> <p>Center 2.402 GHz #Res BW 30 kHz #VBW 100 kHz Span 2 MHz Sweep 2.667 ms</p>																																			
Occupied Bandwidth	Total Power	-1.58 dBm																																	
838.57 kHz	% of OBW Power	99.00 %																																	
Transmit Freq Error	91.633 kHz	x dB Bandwidth	890.8 kHz																																
x dB Bandwidth	890.8 kHz	x dB	-20.00 dB																																


### GFSK TX Mode

2441 MHz



### GFSK TX Mode

2480 MHz






Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 12V		
Test Mode:	TX Mode ( $\pi$ /4-DQPSK)		
Channel frequency (MHz)	99% OBW (kHz)	20dB Bandwidth (kHz)	20dB Bandwidth *2/3 (kHz)
2402	1152.2	1254	836.00
2441	1149.8	1252	834.67
2480	1153.8	1255	836.67
$\pi$ /4-DQPSK TX Mode			
2402 MHz			
<div> <div> <div>Keysight Spectrum Analyzer - Occupied BW</div> <div> <div> <div>Center Freq 2.402000000 GHz</div> <div> <div>Trig: Free Run</div> <div>#Atten: 10 dB</div> </div> </div> <div> <div>Align: AUTO</div> <div>Avg Hold:&gt;10/10</div> </div> <div> <div>Radio Std: None</div> <div>Radio Device: BTS</div> </div> </div> <div> <div>15 dB/div</div> <div>Ref 20.00 dBm</div> <div> <div>Log</div> <div> <div>6.00</div> <div>-10.0</div> <div>-25.0</div> <div>-40.0</div> <div>-55.0</div> <div>-70.0</div> <div>-85.0</div> <div>-100</div> <div>-115</div> </div> </div> <div> <div>Center 2.402 GHz</div> <div>#Res BW 30 kHz</div> <div>#VBW 100 kHz</div> <div>Span 2 MHz</div> <div>Sweep 2.667 ms</div> </div> <div> <div>Occupied Bandwidth</div> <div>1.1522 MHz</div> <div>Total Power</div> <div>-1.22 dBm</div> </div> <div> <div>Transmit Freq Error</div> <div>87.741 kHz</div> <div>% of OBW Power</div> <div>99.00 %</div> </div> <div> <div>x dB Bandwidth</div> <div>1.254 MHz</div> <div>x dB</div> <div>-20.00 dB</div> </div> </div> <div>MSG</div> <div>STATUS</div> </div> </div>			


$\pi$  /4-DQPSK TX Mode

2441 MHz




$\pi$  /4-DQPSK TX Mode

2480 MHz







## GFSK Hopping Mode

2441 MHz



## GFSK Hopping Mode

2480 MHz







$\pi$  /4-DQPSK Hopping Mode

2441 MHz

 $\pi$  /4-DQPSK Hopping Mode


2480 MHz






## Attachment G-- Peak Output Power Test Data

Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 12V		
Test Mode:	TX Mode (GFSK)		
Channel frequency (MHz)	Test Result (dBm)	Limit (dBm)	
2402	-4.428	30	
2441	-4.613		
2480	-4.556		
GFSK TX Mode			
2402 MHz			




# GFSK TX Mode

2441 MHz




# GFSK TX Mode

2480 MHz









$\pi/4$ -DQPSK TX Mode

2441 MHz



$\pi/4$ -DQPSK TX Mode

2480 MHz



-----END OF REPORT-----