



**CFR 47 FCC PART 15 SUBPART C**

**CERTIFICATION TEST REPORT**

*For*

**Speakerphone**

**MODEL NUMBER: UC BM35, BM31, UC BMXXX(X:0~9, A~Z OR BLANK)**

**FCC ID: 2AFG6-BM31**

**REPORT NUMBER: 4790311613-9**

**ISSUE DATE: May 9, 2022**

*Prepared for*

**Guangzhou Shirui Electronics Co., Ltd.  
192 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology  
Development District, Guangzhou, Guangdong, China**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch**

**Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China**

**Tel: +86 769 22038881**

**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V0	05/09/2022	Initial Issue	



Summary of Test Results			
Clause	Test Items	FCC/ISED Rules	Test Results
1	6dB Bandwidth and 99% Occupied Bandwidth	FCC Part 15.247 (a) (2)	Pass
2	Peak Conducted Output Power	FCC Part 15.247 (b) (3)	Pass
3	Power Spectral Density	FCC Part 15.247 (e)	Pass
4	Conducted Bandedge and Spurious Emission	FCC Part 15.247 (d)	Pass
5	Radiated Bandedge and Spurious Emission	FCC Part 15.247 (d) FCC Part 15.209 FCC Part 15.205	Pass
6	Conducted Emission Test for AC Power Port	FCC Part 15.207	Pass
7	Antenna Requirement	FCC Part 15.203	Pass
<b>Note:</b> 1. This test report is only published to and used by the applicant, and it is not for evidence purpose in China. 2. The measurement result for the sample received is <Pass> according to < CFR 47 FCC PART 15 SUBPART C > when <Accuracy Method> decision rule is applied. 3. The EUT has two independent RF Modules, each RF module supports one antenna. All the modules and antennas are identical. When we test one module, another module will be disabled.			



## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS</b> .....	<b>6</b>
<b>2. TEST METHODOLOGY</b> .....	<b>7</b>
<b>3. FACILITIES AND ACCREDITATION</b> .....	<b>7</b>
<b>4. CALIBRATION AND UNCERTAINTY</b> .....	<b>8</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i> .....	8
4.2. <i>MEASUREMENT UNCERTAINTY</i> .....	8
<b>5. EQUIPMENT UNDER TEST</b> .....	<b>9</b>
5.1. <i>DESCRIPTION OF EUT</i> .....	9
5.2. <i>CHANNEL LIST</i> .....	9
5.3. <i>MAXIMUM PEAK OUTPUT POWER</i> .....	9
5.4. <i>TEST CHANNEL CONFIGURATION</i> .....	10
<i>THE WORSE CASE POWER SETTING PARAMETER</i> .....	10
5.5. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i> .....	10
5.6. <i>WORST-CASE CONFIGURATIONS</i> .....	11
5.7. <i>DESCRIPTION OF TEST SETUP</i> .....	12
<b>6. MEASURING INSTRUMENT AND SOFTWARE USED</b> .....	<b>13</b>
<b>7. ANTENNA PORT TEST RESULTS</b> .....	<b>15</b>
7.1. <i>ON TIME AND DUTY CYCLE</i> .....	15
7.2. <i>6 dB DTS BANDWIDTH AND 99 % OCCUPIED BANDWIDTH</i> .....	16
7.3. <i>CONDUCTED OUTPUT POWER</i> .....	18
7.4. <i>POWER SPECTRAL DENSITY</i> .....	19
7.5. <i>CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS</i> .....	21
<b>8. RADIATED TEST RESULTS</b> .....	<b>23</b>
8.1. <i>RESTRICTED BANDEDGE</i> .....	29
8.1.1. <i>LE 1M MODE</i> .....	29
8.1.2. <i>LE 2M MODE</i> .....	33
8.2. <i>SPURIOUS EMISSIONS (1 GHz ~ 3 GHz)</i> .....	36
8.2.1. <i>LE 1M MODE</i> .....	36
8.3. <i>SPURIOUS EMISSIONS (3 GHz ~ 18 GHz)</i> .....	42
8.3.1. <i>LE 1M MODE</i> .....	42
8.3.2. <i>LE 2M MODE</i> .....	48
8.4. <i>SPURIOUS EMISSIONS (18 GHz ~ 26 GHz)</i> .....	54
8.4.1. <i>LE 1M MODE</i> .....	54
8.5. <i>SPURIOUS EMISSIONS (30 MHz ~ 1 GHz)</i> .....	56



8.5.1.	LE 1M MODE .....	56
8.6.	SPURIOUS EMISSIONS BELOW 30 MHz .....	58
8.6.1.	LE 1M MODE .....	58
<b>9.</b>	<b>AC POWER LINE CONDUCTED EMISSIONS .....</b>	<b>61</b>
9.1.	LE 1M MODE .....	62
<b>10.</b>	<b>ANTENNA REQUIREMENTS.....</b>	<b>64</b>
<b>11.</b>	<b>Photo.....</b>	<b>65</b>
11.1.	External Photo .....	65
11.2.	Internal Photo.....	67
11.3.	Setup Photo .....	73
<b>12.</b>	<b>Appendix.....</b>	<b>77</b>
12.1.	Appendix A: DTS Bandwidth.....	77
12.1.1.	Test Result.....	77
12.1.2.	Test Graphs .....	78
12.2.	Appendix B: Occupied Channel Bandwidth .....	80
12.2.1.	Test Result.....	80
12.2.2.	Test Graphs .....	81
12.3.	Appendix C: Maximum conducted output power .....	83
12.3.1.	Test Result.....	83
12.4.	Appendix D: Maximum power spectral density .....	84
12.4.1.	Test Result.....	84
12.4.2.	Test Graphs .....	85
12.5.	Appendix E: Band edge measurements .....	87
12.5.1.	Test Result.....	87
12.5.2.	Test Graphs .....	88
12.6.	Appendix F: Conducted Spurious Emission.....	90
12.6.1.	Test Result.....	90
12.6.2.	Test Graphs .....	91
12.7.	Appendix G: Duty Cycle.....	97
12.7.1.	Test Result.....	97
12.7.2.	Test Graphs .....	98



# 1. ATTESTATION OF TEST RESULTS

## Applicant Information

Company Name: Guangzhou Shirui Electronics Co., Ltd.  
 Address: 192 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District, Guangzhou, Guangdong, China

## Manufacturer Information

Company Name: Guangzhou Shirui Electronics Co., Ltd.  
 Address: 192 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District, Guangzhou, Guangdong, China

## EUT Information

EUT Name: Speakerphone  
 Model: UC BM35, BM31, UC BMXXX(X:0~9, A~Z OR BLANK)  
 Brand: MAXHUB  
 Sample Received Date: March 11, 2022  
 Sample Status: Normal  
 Sample ID: 4819782  
 Date of Tested: March 11, 2022~ May 9, 2022

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	PASS

Prepared By:

Dean Hua  
Project Engineer

Checked By:

Shawn Wen  
Laboratory Leader

Approved By:

Stephen Guo  
Laboratory Manager



## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 15.247 Meas Guidance v05r02, 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, CFR 47 FCC Part 15, ANSI C63.10-2013.

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4102.01)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p><b>ISED (Company No.: 21320)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p><b>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B, the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	--

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.



## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognize national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95 % confidence level using a coverage factor of k=2.	





## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

EUT Name:	Speakerphone		
Model Name:	UC BM35, BM31, UC BMXXX (X:0~9, A~Z OR BLANK)		
Model difference:	There are no difference except the model name.		
Product Description	Operation Frequency	2402 MHz ~ 2480 MHz	
	Modulation Type	Data Rate	
	GFSK	1Mbps	
	GFSK	2Mbps	
Ratings	DC 7.4 V		
Note:			
1.The EUT has two independent RF Modules, each RF module supports one antenna. All the modules and antennas are identical. When we test one module, another module will be disabled.			

### 5.2. CHANNEL LIST

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	11	2424	22	2446	33	2468
1	2404	12	2426	23	2448	34	2470
2	2406	13	2428	24	2450	35	2472
3	2408	14	2430	25	2452	36	2474
4	2410	15	2432	26	2454	37	2476
5	2412	16	2434	27	2456	38	2478
6	2414	17	2436	28	2458	39	2480
7	2416	18	2438	29	2460	/	/
8	2418	19	2440	30	2462	/	/
9	2420	20	2442	31	2464	/	/
10	2422	21	2444	32	2468	/	/

### 5.3. MAXIMUM PEAK OUTPUT POWER

Test Mode	Frequency (MHz)	Channel Number	Maximum Peak Output Power (dBm)	Maximum EIRP (dBm)
LE 1M	2402 ~ 2480	0-39[40]	1.72	4.72
LE 2M	2402 ~ 2480	0-39[40]	1.29	4.29



### 5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
LE 1M	CH 0(Low Channel), CH 19(MID Channel), CH 39(High Channel)	2402 MHz, 2440 MHz, 2480 MHz
LE 2M	CH 0(Low Channel), CH 19(MID Channel), CH 39(High Channel)	2402 MHz, 2440 MHz, 2480 MHz

### THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band				
Test Software Version		FCC_assist 1.0.2.2		
Modulation Type	Transmit Antenna Number	Test Software setting value		
		CH 0	CH 19	CH 39
GFSK(1Mbps)	1	default	default	default
GFSK(2Mbps)	1	default	default	default

### 5.5. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2402-2480	PCB	3

Note:

1.The EUT has two independent RF Modules, each RF module supports one antenna. All the modules and antennas are identical. When we test one module, another module will be disabled.

Test Mode	Transmit and Receive Mode	Description
GFSK(1Mbps)	1TX, 1RX	Chain 1 can be used as transmitting/receiving antenna.
GFSK(2Mbps)	1TX, 1RX	Chain 1 can be used as transmitting/receiving antenna.

Note:

1.The value of the antenna gain was declared by customer.  
2. The EUT has two independent RF Modules, each RF module supports one antenna. All the modules and antennas are identical. When we test one module, another module will be disabled.



## 5.6. WORST-CASE CONFIGURATIONS

Test Mode	Modulation Type	Data Rate (Mbps)
LE 1M	GFSK	1Mbit/s
LE 2M	GFSK	2Mbit/s

**Note:**

The EUT has two independent RF Modules, each RF module supports one antenna. All the modules and antennas are identical. When we test one module, another module will be disabled.

## 5.7. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remarks
1	Laptop	Lenovo	E42	/
2	Laptop	Lenovo	E42	/

### I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	/	Type-C Cable	1.0	/


### ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
/	Adapter	FEIYING	PS05L050K1000CU	Input: 100-240~, 50/60Hz, 0.25A Max Output: 5Vdc, 1A, 5W

### TEST SETUP

The EUT can work in engineering mode with a software through a Laptop.

### SETUP DIAGRAM FOR TESTS



Note: AC adapter only use for AC POWER LINE CONDUCTED EMISSIONS testing.

**6. MEASURING INSTRUMENT AND SOFTWARE USED**

<b>R&amp;S TS 8997 Test System</b>					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Power sensor, Power Meter	R&S	OSP120	100921	Mar.23,2021	Mar.22,2022
Vector Signal Generator	R&S	SMBV100A	261637	Oct.30, 2021	Oct.29, 2022
Signal Generator	R&S	SMB100A	178553	Oct.30, 2021	Oct.29, 2022
Signal Analyzer	R&S	FSV40	101118	Oct.30, 2021	Oct.29, 2022
<b>Software</b>					
Description	Manufacturer	Name		Version	
For R&S TS 8997 Test System	Rohde & Schwarz	EMC 32		10.60.10	
<b>Tonsend RF Test System</b>					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Wideband Radio Communication Tester	R&S	CMW500	155523	Oct.30, 2021	Oct.29, 2022
Wireless Connectivity Tester	R&S	CMW270	1201.0002N75-102	Sep.29, 2021	Sep.28, 2022
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Oct.30, 2021	Oct.29, 2022
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Oct.30, 2021	Oct.29, 2022
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Oct.30, 2021	Oct.29, 2022
DC power supply	Keysight	E3642A	MY55159130	Oct.30, 2021	Oct.29, 2022
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Nov.20,2020	Nov.19,2022
<b>Software</b>					
Description	Manufacturer	Name		Version	
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System		2.6.77.0518	



Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Oct.30, 2021	Oct.29, 2022
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130959	Aug.02, 2021	Aug.01, 2024
Preamplifier	HP	8447D	2944A09099	Oct.30, 2021	Oct.29, 2022
EMI Measurement Receiver	R&S	ESR26	101377	Oct.30, 2021	Oct.29, 2022
Horn Antenna	TDK	HRN-0118	130940	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Oct.30, 2021	Oct.29, 2022
Horn Antenna	Schwarzbeck	BBHA9170	697	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-2	TRS-307-00003	Oct.31, 2021	Oct.30, 2022
Preamplifier	TDK	PA-02-3	TRS-308-00002	Oct.31, 2021	Oct.30, 2022
Loop antenna	Schwarzbeck	1519B	00008	Dec.14, 2021	Dec.14, 2024
Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Oct.31, 2021	Oct.30, 2022
Preamplifier	Mini-Circuits	ZX60-83LN-S+	SUP01201941	Oct.31, 2021	Oct.30, 2022
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Oct.31, 2021	Oct.30, 2022
Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Oct.31, 2021	Oct.30, 2022
Software					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1

## 7. ANTENNA PORT TEST RESULTS

### 7.1. ON TIME AND DUTY CYCLE


#### LIMITS

None; for reporting purposes only.

#### PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	23.8 °C	Relative Humidity	54.9 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 7.4 V

#### RESULTS

Please refer to appendix G.

## 7.2. 6 dB DTS BANDWIDTH AND 99 % OCCUPIED BANDWIDTH

### LIMITS

CFR 47FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.


Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW
Detector	Peak
RBW	For 6 dB Bandwidth: 100 kHz For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 6 dB Bandwidth: ≥3 × RBW For 99 % Occupied Bandwidth: ≥3 × RBW
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### TEST SETUP





**TEST ENVIRONMENT**

Temperature	23.8 °C	Relative Humidity	54.9 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 7.4 V

**RESULTS**

Please refer to appendix A & B.

### 7.3. CONDUCTED OUTPUT POWER


#### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3)	Peak Conducted Output Power	1 watt or 30 dBm	2400-2483.5

#### TEST PROCEDURE

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth). Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	23.8 °C	Relative Humidity	54.9 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 7.4 V

#### RESULTS

Please refer to appendix C.

## 7.4. POWER SPECTRAL DENSITY

### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.10.


Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### TEST SETUP



### TEST ENVIRONMENT

Temperature	23.8 °C	Relative Humidity	54.9 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 7.4 V



**RESULTS**

Please refer to appendix D.



## 7.5. CONDUCTED BANDEGE AND SPURIOUS EMISSIONS

### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d)	Conducted Bandedge and Spurious Emissions	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyser and use the following settings for reference level measurement:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.


Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

### TEST SETUP



### **TEST ENVIRONMENT**

Temperature	23.8 °C	Relative Humidity	54.9 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 7.4 V

### **RESULTS**

Please refer to appendix E & F.



## 8. RADIATED TEST RESULTS

### LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz-1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30



FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
<sup>1</sup> 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			


Note: <sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup>Above 38.6c



**TEST SETUP AND PROCEDURE**

Below 30 MHz




The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of  $377\Omega$ . For example, the measurement frequency X KHz resulted in a level of Y dBuV/m, which is equivalent to  $Y-51.5 = Z$  dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz




The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1GHz




The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1.ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

### **TEST ENVIRONMENT**

Temperature	24.3 °C	Relative Humidity	61 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 7.4 V


### **RESULTS**

## 8.1. RESTRICTED BANDEDGE

### 8.1.1. LE 1M MODE

#### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

#### PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2383.605	18.28	32.61	50.89	74.00	-23.11	peak
2	2390.000	17.24	32.66	49.90	74.00	-24.10	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**

**PEAK**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2381.820	17.10	32.59	49.69	74.00	-24.31	peak
2	2390.000	15.43	32.66	48.09	74.00	-25.91	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)**


**PEAK**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	21.09	33.10	54.19	74.00	-19.81	peak
2	2485.850	23.78	33.10	56.88	74.00	-17.12	peak
3	2496.075	18.52	33.14	51.66	74.00	-22.34	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	4.49	33.10	37.59	54.00	-16.41	AVG
2	2485.850	4.14	33.10	37.24	54.00	-16.76	AVG
3	2496.075	7.46	33.14	40.60	54.00	-13.40	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Note: All the polarities (Vertical & Horizontal) had been tested, only the worst data was recorded in the report.



8.1.2. LE 2M MODE

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2380.840	17.50	32.59	50.09	74.00	-23.91	peak
2	2390.000	16.09	32.66	48.75	74.00	-25.25	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)**

**PEAK**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	22.00	33.10	55.10	74.00	-18.90	peak
2	2485.570	27.90	33.10	61.00	74.00	-13.00	peak
3	2499.700	18.39	33.16	51.55	74.00	-22.45	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: All the polarities (Vertical & Horizontal) had been tested, only the worst data was recorded in the report.

**AVG**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	8.00	33.10	41.10	54.00	-12.90	AVG
2	2485.570	4.84	33.10	37.94	54.00	-16.06	AVG
3	2499.700	8.02	33.16	41.18	54.00	-12.82	AVG


Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: All the polarities (Vertical & Horizontal) had been tested, only the worst data was recorded in the report.

## 8.2. SPURIOUS EMISSIONS (1 GHz ~ 3 GHz)

### 8.2.1. LE 1M MODE

#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1163.000	49.49	-13.96	35.53	74.00	-38.47	peak
2	1599.000	48.18	-11.85	36.33	74.00	-37.67	peak
3	1660.000	48.49	-11.47	37.02	74.00	-36.98	peak
4	1920.000	47.64	-10.81	36.83	74.00	-37.17	peak
5	2130.000	47.39	-10.15	37.24	74.00	-36.76	peak
6	2402.000	49.30	-8.94	40.36	74.00	-33.64	peak

Note:

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1164.000	58.30	-13.95	44.35	74.00	-29.65	peak
2	1593.000	54.06	-11.89	42.17	74.00	-31.83	peak
3	1659.000	54.69	-11.48	43.21	74.00	-30.79	peak
4	2325.000	47.18	-9.24	37.94	74.00	-36.06	peak
5	2402.000	46.52	-8.94	37.58	74.00	-36.42	peak
6	2661.000	49.34	-8.30	41.04	74.00	-32.96	peak

Note:

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1162.000	50.78	-13.97	36.81	74.00	-37.19	peak
2	1407.000	46.04	-13.02	33.02	74.00	-40.98	peak
3	1875.000	45.59	-10.72	34.87	74.00	-39.13	peak
4	2126.000	47.55	-10.17	37.38	74.00	-36.62	peak
5	2327.000	46.31	-9.23	37.08	74.00	-36.92	peak
6	2440.000	49.46	-8.86	40.60	74.00	-33.40	peak

Note:

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1161.000	60.54	-13.97	46.57	74.00	-27.43	peak
2	1592.000	52.08	-11.90	40.18	74.00	-33.82	peak
3	1660.000	54.11	-11.47	42.64	74.00	-31.36	peak
4	2128.000	49.16	-10.16	39.00	74.00	-35.00	peak
5	2440.000	48.80	-8.86	39.94	74.00	-34.06	peak
6	2662.000	49.39	-8.30	41.09	74.00	-32.91	peak

**Note:**

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1140.000	47.19	-14.11	33.08	74.00	-40.92	peak
2	1585.000	45.38	-11.94	33.44	74.00	-40.56	peak
3	1920.000	47.22	-10.81	36.41	74.00	-37.59	peak
4	2266.000	43.94	-9.46	34.48	74.00	-39.52	peak
5	2480.000	46.63	-8.76	37.87	74.00	-36.13	peak
6	2559.000	55.94	-8.63	47.31	74.00	-26.69	peak

Note:

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1166.000	54.19	-13.94	40.25	74.00	-33.75	peak
2	1666.000	50.58	-11.43	39.15	74.00	-34.85	peak
3	1995.000	49.25	-10.95	38.30	74.00	-35.70	peak
4	2348.000	46.28	-9.16	37.12	74.00	-36.88	peak
5	2480.000	48.92	-8.76	40.16	74.00	-33.84	peak
6	2559.000	50.88	-8.63	42.25	74.00	-31.75	peak

Note:


1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

Note: All the modes and channels had been tested, but only the worst data was recorded in the report.

### 8.3. SPURIOUS EMISSIONS (3 GHz ~ 18 GHz)

#### 8.3.1. LE 1M MODE

##### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4860.000	41.51	-0.49	41.02	74.00	-32.98	peak
2	7882.500	39.11	6.72	45.83	74.00	-28.17	peak
3	9607.500	41.90	10.67	52.57	74.00	-21.43	peak
4	12360.000	34.68	17.55	52.23	74.00	-21.77	peak
5	14287.500	32.68	20.66	53.34	74.00	-20.66	peak
6	17595.000	30.11	22.62	52.73	74.00	-21.27	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	43.14	-0.33	42.81	74.00	-31.19	peak
2	8107.500	37.63	7.94	45.57	74.00	-28.43	peak
3	9607.500	39.86	10.67	50.53	74.00	-23.47	peak
4	11760.000	36.02	16.86	52.88	74.00	-21.12	peak
5	13612.500	32.54	20.47	53.01	74.00	-20.99	peak
6	17430.000	31.37	21.46	52.83	74.00	-21.17	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	41.53	-0.52	41.01	74.00	-32.99	peak
2	7845.000	38.79	6.94	45.73	74.00	-28.27	peak
3	9757.500	40.54	10.21	50.75	74.00	-23.25	peak
4	11955.000	35.37	17.28	52.65	74.00	-21.35	peak
5	13950.000	31.01	21.33	52.34	74.00	-21.66	peak
6	17295.000	29.88	21.86	51.74	74.00	-22.26	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3187.500	53.90	-5.23	48.67	74.00	-25.33	peak
2	3982.500	50.61	-3.61	47.00	74.00	-27.00	peak
3	9757.500	40.60	10.21	50.81	74.00	-23.19	peak
4	11872.500	35.40	17.11	52.51	74.00	-21.49	peak
5	13912.500	31.43	21.22	52.65	74.00	-21.35	peak
6	17692.500	28.23	23.61	51.84	74.00	-22.16	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7762.500	38.86	6.87	45.73	74.00	-28.27	peak
2	8992.500	38.05	10.01	48.06	74.00	-25.94	peak
3	9922.500	42.07	11.30	53.37	74.00	-20.63	peak
4	11812.500	35.76	16.89	52.65	74.00	-21.35	peak
5	14445.000	33.66	19.23	52.89	74.00	-21.11	peak
6	18000.000	27.20	25.28	52.48	74.00	-21.52	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3195.000	54.20	-5.28	48.92	74.00	-25.08	peak
2	3990.000	50.24	-3.57	46.67	74.00	-27.33	peak
3	9922.500	42.96	11.30	54.26	74.00	-19.74	peak
4	9922.500	39.23	11.30	50.53	54.00	-3.47	AVG
5	11865.000	35.57	17.08	52.65	74.00	-21.35	peak
6	14002.500	31.17	21.45	52.62	74.00	-21.38	peak
7	18000.000	27.27	25.28	52.55	74.00	-21.45	peak

- Note:
1. Peak Result = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. Peak: Peak detector.
  4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
  5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

### 8.3.2. LE 2M MODE

#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5917.500	37.79	2.52	40.31	74.00	-33.69	peak
2	8047.500	38.56	7.10	45.66	74.00	-28.34	peak
3	9607.500	41.80	10.67	52.47	74.00	-21.53	peak
4	11707.500	35.60	16.87	52.47	74.00	-21.53	peak
5	14055.000	31.73	21.11	52.84	74.00	-21.16	peak
6	17407.500	30.66	21.38	52.04	74.00	-21.96	peak

- Note:
1. Peak Result = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. Peak: Peak detector.
  4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
  5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4642.500	41.52	-1.24	40.28	74.00	-33.72	peak
2	7897.500	38.96	6.64	45.60	74.00	-28.40	peak
3	9607.500	39.21	10.67	49.88	74.00	-24.12	peak
4	12547.500	35.60	17.22	52.82	74.00	-21.18	peak
5	14385.000	33.54	19.66	53.20	74.00	-20.80	peak
6	17962.500	27.34	25.03	52.37	74.00	-21.63	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7807.500	38.34	7.13	45.47	74.00	-28.53	peak
2	9022.500	37.09	9.94	47.03	74.00	-26.97	peak
3	9757.500	38.62	10.21	48.83	74.00	-25.17	peak
4	11842.500	35.28	17.00	52.28	74.00	-21.72	peak
5	14812.500	33.96	18.37	52.33	74.00	-21.67	peak
6	17895.000	26.96	24.62	51.58	74.00	-22.42	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	42.49	-0.52	41.97	74.00	-32.03	peak
2	8130.000	38.05	7.87	45.92	74.00	-28.08	peak
3	9757.500	40.34	10.21	50.55	74.00	-23.45	peak
4	11685.000	35.79	16.76	52.55	74.00	-21.45	peak
5	13980.000	31.31	21.41	52.72	74.00	-21.28	peak
6	17295.000	29.94	21.86	51.80	74.00	-22.20	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5655.000	39.33	1.26	40.59	74.00	-33.41	peak
2	8085.000	37.79	7.71	45.50	74.00	-28.50	peak
3	9922.500	40.73	11.30	52.03	74.00	-21.97	peak
4	11737.500	35.05	16.86	51.91	74.00	-22.09	peak
5	14062.500	32.00	21.07	53.07	74.00	-20.93	peak
6	17985.000	27.59	25.18	52.77	74.00	-21.23	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4957.500	43.89	-0.18	43.71	74.00	-30.29	peak
2	8962.500	37.52	9.40	46.92	74.00	-27.08	peak
3	9922.500	38.65	11.30	49.95	74.00	-24.05	peak
4	12555.000	34.89	17.23	52.12	74.00	-21.88	peak
5	13507.500	32.11	20.40	52.51	74.00	-21.49	peak
6	17602.500	29.35	22.70	52.05	74.00	-21.95	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

### 8.4. SPURIOUS EMISSIONS (18 GHz ~ 26 GHz)

#### 8.4.1. LE 1M MODE

#### SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18144.000	49.77	-5.48	44.29	74.00	-29.71	peak
2	20016.000	50.06	-5.47	44.59	74.00	-29.41	peak
3	20504.000	49.71	-5.35	44.36	74.00	-29.64	peak
4	22784.000	47.98	-3.65	44.33	74.00	-29.67	peak
5	23744.000	48.15	-3.20	44.95	74.00	-29.05	peak
6	25616.000	46.18	-1.24	44.94	74.00	-29.06	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.



**SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18536.000	50.10	-5.27	44.83	74.00	-29.17	peak
2	19784.000	49.57	-5.28	44.29	74.00	-29.71	peak
3	21432.000	48.74	-4.71	44.03	74.00	-29.97	peak
4	21928.000	48.05	-4.43	43.62	74.00	-30.38	peak
5	24256.000	46.62	-2.82	43.80	74.00	-30.20	peak
6	24968.000	46.76	-2.14	44.62	74.00	-29.38	peak


- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.

Note: All the modes and antenna have been tested, only the worst data was recorded in the report.

## 8.5. SPURIOUS EMISSIONS (30 MHz ~ 1 GHz)

### 8.5.1. LE 1M MODE

#### SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	107.6000	56.11	-20.58	35.53	43.50	-7.97	QP
2	167.7400	56.33	-17.41	38.92	43.50	-4.58	QP
3	372.4100	51.71	-13.87	37.84	46.00	-8.16	QP
4	480.0800	54.30	-11.79	42.51	46.00	-3.49	QP
5	888.4500	46.63	-5.29	41.34	46.00	-4.66	QP
6	935.9800	46.77	-4.61	42.16	46.00	-3.84	QP

Note: 1. Result Level = Read Level + Correct Factor.  
 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.



**SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	167.7400	54.21	-17.41	36.80	43.50	-6.70	QP
2	191.9900	55.63	-16.56	39.07	43.50	-4.43	QP
3	468.4400	51.90	-12.04	39.86	46.00	-6.14	QP
4	527.6100	52.48	-10.88	41.60	46.00	-4.40	QP
5	576.1100	49.31	-10.02	39.29	46.00	-6.71	QP
6	839.9500	40.46	-6.47	33.99	46.00	-12.01	QP

Note: 1. Result Level = Read Level + Correct Factor.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto


Note: All the modes and antenna have been tested, only the worst data was recorded in the report.

## 8.6. SPURIOUS EMISSIONS BELOW 30 MHz

### 8.6.1. LE 1M MODE

#### SPURIOUS EMISSIONS (HIGH CHANNEL, LOOP ANTENNA FACE ON TO THE EUT, WORST-CASE CONFIGURATION)

9 kHz~ 150 kHz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0102	74.55	-101.40	-26.85	47.43	-74.28	peak
2	0.0131	71.95	-101.38	-29.43	45.25	-74.68	peak
3	0.0221	69.13	-101.35	-32.22	40.71	-72.93	peak
4	0.0320	64.34	-101.40	-37.06	37.5	-74.56	peak
5	0.0636	61.31	-101.54	-40.23	31.53	-71.76	peak
6	0.0981	58.77	-101.78	-43.01	27.77	-70.78	peak

Note:

1. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
2. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

**150 kHz ~ 490 kHz**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1554	75.27	-101.65	-26.38	23.77	-50.15	peak
2	0.1917	69.54	-101.70	-32.16	21.95	-54.11	peak
3	0.2190	68.27	-101.75	-33.48	20.79	-54.27	peak
4	0.2605	64.64	-101.81	-37.17	19.28	-56.45	peak
5	0.3163	62.70	-101.87	-39.17	17.6	-56.77	peak
6	0.4062	59.14	-101.96	-42.82	15.43	-58.25	peak

Note:

1. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
2. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

**490 kHz ~ 30 MHz**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.5039	62.93	-62.07	0.86	33.56	-32.70	peak
2	0.6965	62.55	-62.11	0.44	30.74	-30.30	peak
3	1.6491	56.05	-61.98	-5.93	23.26	-29.19	peak
4	6.2445	54.63	-61.32	-6.69	29.54	-36.23	peak
5	11.8513	52.56	-60.88	-8.32	29.54	-37.86	peak
6	25.8978	52.76	-60.36	-7.6	29.54	-37.14	peak

Note:

1. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
2. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

Note: All the modes and antenna have been tested, only the worst data was recorded in the report.

## 9. AC POWER LINE CONDUCTED EMISSIONS


### LIMITS

Please refer to CFR 47 FCC §15.207 (a)

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

### TEST SETUP AND PROCEDURE

Refer to ANSI C63.10-2013 clause 6.2.



The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.


### TEST ENVIRONMENT

Temperature	21.7 °C	Relative Humidity	52.4 %
Atmosphere Pressure	101 kPa	Test Voltage	AC 120 V, 60 Hz

**RESULTS**


**9.1. LE 1M MODE**

**LINE L RESULTS (HIGH CHANNEL, WORST-CASE CONFIGURATION)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1576	41.05	9.51	50.56	65.59	-15.03	QP
2	0.1576	17.76	9.51	27.27	55.59	-28.32	AVG
3	0.1652	35.03	9.52	44.55	65.20	-20.65	QP
4	0.1652	14.44	9.52	23.96	55.20	-31.24	AVG
5	0.5068	31.92	9.50	41.42	56.00	-14.58	QP
6	0.5068	26.65	9.50	36.15	46.00	-9.85	AVG
7	0.5558	29.85	9.50	39.35	56.00	-16.65	QP
8	0.5558	22.22	9.50	31.72	46.00	-14.28	AVG
9	1.1776	27.53	9.53	37.06	56.00	-18.94	QP
10	1.1776	18.25	9.53	27.78	46.00	-18.22	AVG
11	14.7172	19.95	9.66	29.61	60.00	-30.39	QP
12	14.7172	11.25	9.66	20.91	50.00	-29.09	AVG

- Note: 1. Result = Reading + Correct Factor.  
 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).  
 4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

**LINE N RESULTS (HIGH CHANNEL, WORST-CASE CONFIGURATION)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1538	40.88	9.50	50.38	65.79	-15.41	QP
2	0.1538	17.65	9.50	27.15	55.79	-28.64	AVG
3	0.1578	41.05	9.51	50.56	65.58	-15.02	QP
4	0.1578	18.92	9.51	28.43	55.58	-27.15	AVG
5	0.1696	33.16	9.53	42.69	64.98	-22.29	QP
6	0.1696	13.99	9.53	23.52	54.98	-31.46	AVG
7	0.1992	36.84	9.59	46.43	63.64	-17.21	QP
8	0.1992	16.76	9.59	26.35	53.64	-27.29	AVG
9	0.5588	35.49	9.50	44.99	56.00	-11.01	QP
10	0.5588	27.26	9.50	36.76	46.00	-9.24	AVG
11	1.1803	34.41	9.53	43.94	56.00	-12.06	QP
12	1.1803	23.72	9.53	33.25	46.00	-12.75	AVG

Note: 1. Result = Reading + Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).

4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes and antenna have been tested, only the worst data was recorded in the report.



## 10. ANTENNA REQUIREMENTS

### APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### RESULTS

Complies



## 11. Photo

### 11.1. External Photo

View of EUT-1



View of EUT-2



View of EUT-3




View of EUT-4






## 11.2. Internal Photo

### Internal View of EUT-1




### Internal View of EUT-2









### Internal View of EUT-5




### Internal View of EUT-6




### Internal View of EUT-7




### Internal View of EUT-8



### Internal View of EUT-9



### Internal View of EUT-10






### Internal View of EUT-11




### Internal View of EUT-12






### Internal View of EUT-13




### 11.3. Setup Photo


Radiated Disturbance below 1 GHz and above 30 MHz



Radiated Disturbance below 30 MHz




Radiated Disturbance Setup (Above 1 GHz – X axis)





Radiated Disturbance Setup (Above 1 GHz – Y axis)




Radiated Disturbance Setup (Above 1 GHz – Z axis)



## Radiated Disturbance Setup (Above 1 GHz – Worst Case)



## AC Power Line Conducted Emissions setup





## 12. Appendix

### 12.1. Appendix A: DTS Bandwidth

#### 12.1.1. Test Result

Test Mode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.660	2401.664	2402.324	0.5	PASS
		2440	0.690	2439.646	2440.336	0.5	PASS
		2480	0.666	2479.661	2480.327	0.5	PASS
BLE_2M	Ant1	2402	0.832	2401.420	2402.252	0.5	PASS
		2440	0.844	2439.420	2440.264	0.5	PASS
		2480	0.840	2479.420	2480.260	0.5	PASS

Note:

The EUT has two independent RF Modules, each RF module supports one antenna. All the modules and antennas are identical. When we test one module, another module will be disabled.



### 12.1.2. Test Graphs




BLE 1M Ant1 2402



BLE 1M Ant1 2440



BLE 1M Ant1 2480



BLE 2M Ant1 2402



BLE 2M Ant1 2440



BLE 2M Ant1 2480



## 12.2. Appendix B: Occupied Channel Bandwidth

### 12.2.1. Test Result

Test Mode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Verdict
BLE_1M	Ant1	2402	1.0299	2401.479	2402.509	PASS
		2440	1.0318	2439.478	2440.510	PASS
		2480	1.0362	2479.478	2480.515	PASS
BLE_2M	Ant1	2402	2.0371	2401.001	2403.038	PASS
		2440	2.0322	2439.002	2441.034	PASS
		2480	2.0179	2479.007	2481.025	PASS

Note:


The EUT has two independent RF Modules, each RF module supports one antenna. All the modules and antennas are identical. When we test one module, another module will be disabled.






### 12.2.2. Test Graphs






BLE 2M Ant1 2402



BLE 2M Ant1 2440



BLE 2M Ant1 2480



## 12.3. Appendix C: Maximum conducted output power

### 12.3.1. Test Result

Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	1.72	≤30	PASS
		2440	-0.03	≤30	PASS
		2480	1.69	≤30	PASS
BLE_2M	Ant1	2402	0.02	≤30	PASS
		2440	0.98	≤30	PASS
		2480	1.29	≤30	PASS

Note:

The EUT has two independent RF Modules, each RF module supports one antenna. All the modules and antennas are identical. When we test one module, another module will be disabled.



## 12.4. Appendix D: Maximum power spectral density


### 12.4.1. Test Result

Test Mode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-17.17	≤8.00	PASS
		2440	-18.96	≤8.00	PASS
		2480	-17.32	≤8.00	PASS
BLE_2M	Ant1	2402	-20.85	≤8.00	PASS
		2440	-20.04	≤8.00	PASS
		2480	-20.03	≤8.00	PASS


Note:

The EUT has two independent RF Modules, each RF module supports one antenna. All the modules and antennas are identical. When we test one module, another module will be disabled.


### 12.4.2. Test Graphs



BLE 1M Ant1 2402




BLE 1M Ant1 2440




BLE 1M Ant1 2480






BLE 2M Ant1 2402



BLE 2M Ant1 2440



BLE 2M Ant1 2480



## 12.5. Appendix E: Band edge measurements

### 12.5.1. Test Result

Test Mode	Antenna	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	0.63	-41.74	≤-19.37	PASS
		High	2480	0.66	-41.77	≤-19.34	PASS
BLE_2M	Ant1	Low	2402	-0.31	-33.42	≤-20.31	PASS
		High	2480	0.80	-45.96	≤-19.2	PASS


Note:

The EUT has two independent RF Modules, each RF module supports one antenna. All the modules and antennas are identical. When we test one module, another module will be disabled.

### 12.5.2. Test Graphs







## 12.6. Appendix F: Conducted Spurious Emission


### 12.6.1. Test Result


Test Mode	Antenna	Channel	FreqRange [MHz]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	Reference	0.59	---	PASS
			30~1000	-45.17	≤-19.41	PASS
			1000~26500	-45.66	≤-19.41	PASS
		2440	Reference	-1.10	---	PASS
			30~1000	-53.91	≤-21.1	PASS
			1000~26500	-44.77	≤-21.1	PASS
		2480	Reference	0.61	---	PASS
			30~1000	-53.09	≤-19.39	PASS
			1000~26500	-45.32	≤-19.39	PASS
BLE_2M	Ant1	2402	Reference	-0.38	---	PASS
			30~1000	-58.98	≤-20.38	PASS
			1000~26500	-51.87	≤-20.38	PASS
		2440	Reference	0.64	---	PASS
			30~1000	-59.19	≤-19.36	PASS
			1000~26500	-51.96	≤-19.36	PASS
		2480	Reference	0.84	---	PASS
			30~1000	-60.32	≤-19.16	PASS
			1000~26500	-51.64	≤-19.16	PASS

**Note:**


The EUT has two independent RF Modules, each RF module supports one antenna. All the modules and antennas are identical. When we test one module, another module will be disabled.

### 12.6.2. Test Graphs






BLE 1M Ant1 2440 0~Reference




BLE 1M Ant1 2440 30~1000




BLE 1M Ant1 2440 1000~26500



BLE 1M Ant1 2480 0~Reference



BLE 1M Ant1 2480 30~1000




BLE 1M Ant1 2480 1000~26500






BLE 2M Ant1 2402 0~Reference




BLE 2M Ant1 2402 30~1000




BLE 2M Ant1 2402 1000~26500



BLE 2M Ant1 2440 0~Reference




BLE 2M Ant1 2440 30~1000




BLE 2M Ant1 2440 1000~26500



BLE 2M Ant1 2480 0~Reference



BLE 2M Ant1 2480 30~1000



BLE 2M Ant1 2480 1000~26500



## 12.7. Appendix G: Duty Cycle

### 12.7.1. Test Result

Test Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
BLE_1M	0.096	0.625	0.1536	15.36	8.14	10.42	11
BLE_2M	0.063	0.625	0.1008	10.08	9.97	15.87	16

Note:

Duty Cycle Correction Factor= $10\log(1/x)$ .

Where: x is Duty Cycle (Linear)

Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.

The EUT has two independent RF Modules, each RF module supports one antenna. All the modules and antennas are identical. When we test one module, another module will be disabled.

### 12.7.2. Test Graphs

