



FCC RF EXPOSURE REPORT CERTIFICATION TEST REPORT

For

Wifi Module

MODEL NUMBER: SI01B

FCC ID: 2AR82-SI01B

IC: 24728-SI01B

REPORT NUMBER: 4790081441-2

ISSUE DATE: October 25, 2021

Prepared for

Guangzhou Shirui Electronics Co., Ltd.

192 Kezhu Road, Scientech Park, Guangzhou Economic & Technology

Development District, Guangzhou, Guangdong, China

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

> Tel: +86 769 22038881 Fax: +86 769 33244054 Website: www.ul.com



REPORT NO.: 4790089699.2-5 Page 2 of 7

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	11/04/2021	Initial Issue	






TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	. 4
2.	TEST METHODOLOGY	. 5
3.	FACILITIES AND ACCREDITATION	. 5
1	REQUIREMENT	G



REPORT NO.: 4790089699.2-5 Page 4 of 7

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Guangzhou Shirui Electronics Co., Ltd.

Address: 192 Kezhu Road, Scientech Park, Guangzhou Economic &

Technology Development District, Guangzhou, Guangdong, China

Manufacturer Information

Company Name: Guangzhou Shirui Electronics Co., Ltd.

Address: 192 Kezhu Road, Scientech Park, Guangzhou Economic &

Technology Development District, Guangzhou, Guangdong, China

EUT Information

EUT Name: Wifi Module Model: SI01B

Sample Received Date: August 31, 2021

Sample Status: Normal Sample ID: 4175727

Date of Tested: September 1, 2021 ~ November 3, 2021

APPLICABLE STANDARDS			
STANDARD	TEST RESULTS		
FCC 47CFR§2.1091	PASS		

Prepared By:

Denny Grany

Denny Huang
Project Engineer

Checked By:

Shawn Wen
Laboratory Leader

Approved By:

Stephen Guo Laboratory Manager

REPORT NO.: 4790089699.2-5 Page 5 of 7

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091.

3. FACILITIES AND ACCREDITATION

	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.
Accreditation Certificate	FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Delcaration of Conformity (DoC) and Certification rules ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046. VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B, the VCCI registration No. is C-20012 and T-20011

Note: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China.



REPORT NO.: 4790089699.2-5 Page 6 of 7

4. REQUIREMENT

LIMIT AND CALCULATION METHOD

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with. Limits for General Population/Uncontrolled Exposure

RF EXPOSURE LIMIT

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time E ² , H ² or S (Minutes)
0.3 1.34	614	1.63	(100)*	30
1.34 30	824/f	2.19/f	(180/f ²)*	30
30 300	27.5	0.073	0.2	30
300 1500			f/1500	30
1500 100,000			1.0	30

CALCULATION METHOD

 $S=PG/4\pi R^2$

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna



REPORT NO.: 4790089699.2-5 Page 7 of 7

CALCULATED RESULTS

Mode	Output Power	Antenna Gain	Power Density	Power Density Limit	Test Result
	dBm	dBi	mW/cm ²	mW/cm ²	
BLE	4	3.18	0.00104	1.0	Complies

Mode	Output Power	Antenna Gain	Power Density	Power Density Limit	Test Result
	dBm	dBi	mW/cm ²	mW/cm ²	
ВТ	4	3.18	0.00104	1.0	Complies

Mode	Output Power	Directional Gain	Power Density	Power Density Limit	Test Result
	dBm	dBi	mW/cm ²	mW/cm ²	
WIFI 2.4G	19	3.18	0.03287	1.0	Complies

Mode	Output Power	Directional Gain	Power Density	Power Density Limit	Test Result
	dBm	dBi	mW/cm ²	mW/cm²	
WIFI 5G	15	4.36	0.01717	1.0	Complies

Note:

- 1. The Power comes from report operation description.
- 2. The minimum separation distance of the device is greater than 20 cm.
- 3. BT + 2.4GHz=0.00104 + 0.03287= $0.03391 (mW/cm^2)$, BT + 5GHz = 0.00104 + 0.01717= $0.01821 (mW/cm^2)$
- 4. Therefor the maximum calculations of above situations are less than the "1" limit.
- 5. Calculate by WORST-CASE mode.

END OF REPORT