



**CFR 47 FCC PART 15 SUBPART E
ISED RSS-247 ISSUE 2**

CERTIFICATION TEST REPORT

For

WiFi Module

MODEL NUMBER: SI07

FCC ID: 2AFG6-SI07

IC: 22166-SI07

REPORT NUMBER: 4789708215-7

ISSUE DATE: November 30, 2020

Prepared for

**Guangzhou Shirui Electronics Co Ltd
192 Kezhu Road, Scientech Park, Guangzhou Economic Technology Development
District Guangzhou China**

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

**Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-
Tech Development Zone Dongguan, 523808, People's Republic of China**

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V0	11/30/2020	Initial Issue	



Summary of Test Results			
Clause	Test Items	FCC/IC Rules	Test Results
1	6dB/26dB Bandwidth	FCC 15.407 (a)&(e) RSS-247 Clause 6.2	PASS
2	99% Occupied Bandwidth	RSS-Gen Clause 6.6	PASS
3	Conducted Output Power	FCC 15.407 (a) RSS-247 Clause 6.2	PASS
4	Power Spectral Density	FCC 15.407 (a) RSS-247 Clause 6.2	PASS
5	Radiated Bandedge and Spurious Emission	FCC 15.407 (b) FCC 15.209 FCC 15.205 RSS-247 Clause 6.2 RSS-GEN Clause 8.9	PASS
6	Conducted Emission Test for AC Power Port	FCC 15.207 RSS-GEN Clause 8.8	PASS
7	Frequency Stability	FCC 15.407 (g)	PASS
8	Dynamic Frequency Selection	FCC 15.407 (h) RSS-247 Clause 6.3	PASS
9	Antenna Requirement	FCC 15.203 RSS-GEN Clause 6.8	PASS
Note: 1.This test report is only published to and used by the applicant, and it is not for evidence purpose in China. 2. The measurement result for the sample received is <Pass> according to < CFR 47 FCC PART 15 SUBPART C >< ISED RSS-247 > when <Accuracy Method> decision rule is applied.			



TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	7
2. TEST METHODOLOGY	8
3. FACILITIES AND ACCREDITATION	8
4. CALIBRATION AND UNCERTAINTY	9
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	9
4.2. <i>MEASUREMENT UNCERTAINTY</i>	9
5. EQUIPMENT UNDER TEST	10
5.1. <i>DESCRIPTION OF EUT</i>	10
5.2. <i>MAXIMUM OUTPUT POWER</i>	11
5.3. <i>CHANNEL LIST</i>	12
5.4. <i>TEST CHANNEL CONFIGURATION</i>	13
5.5. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	14
5.6. <i>THE WORSE CASE POWER SETTING PARAMETER</i>	15
5.7. <i>THE WORSE CASE CONFIGURATIONS</i>	17
5.8. <i>DESCRIPTION OF TEST SETUP</i>	18
6. MEASURING INSTRUMENT AND SOFTWARE USED	19
7. ANTENNA PORT TEST RESULTS	21
7.1. <i>ON TIME AND DUTY CYCLE</i>	21
7.2. <i>6/26 dB EMISSION BANDWIDTH AND 99 % OCCUPIED BANDWIDTH</i>	22
7.3. <i>CONDUCTED OUTPUT POWER</i>	24
7.4. <i>POWER SPECTRAL DENSITY</i>	27
8. RADIATED TEST RESULTS	29
8.1. <i>RESTRICTED BANDEDGE</i>	36
8.1.1. 802.11a SISO MODE	36
UNII-1 BAND	36
UNII-2A BAND	38
UNII-2C BAND	40
UNII-3 BAND	43
8.1.2. 802.11n HT20 MIMO MODE	45
UNII-1 BAND	45
UNII-2A BAND	47
UNII-2C BAND	49
UNII-3 BAND	52
8.1.3. 802.11n HT40 MIMO MODE	54
UNII-1 BAND	54
UNII-2A BAND	56



UNII-2C BAND.....	58
UNII-3 BAND	61
8.1.4. 802.11ac VHT80 MIMO MODE.....	63
UNII-1 BAND	63
UNII-2A BAND.....	65
UNII-2C BAND.....	67
UNII-3 BAND	70
8.2. SPURIOUS EMISSIONS (1 GHz ~ 7 GHz).....	71
8.2.1. 802.11a SISO MODE	71
UNII-3 BAND	71
8.3. SPURIOUS EMISSIONS (7 GHz ~ 18 GHz).....	77
8.3.1. 802.11a SISO MODE	77
UNII-1 BAND	77
UNII-2A BAND.....	83
UNII-2C BAND.....	89
STRADDLE CHANNEL 144	95
UNII-3 BAND	97
8.3.2. 802.11n HT20 MIMO MODE	103
UNII-1 BAND	103
UNII-2A BAND.....	109
UNII-2C BAND.....	115
STRADDLE CHANNEL 144	121
UNII-3 BAND	123
8.3.3. 802.11n HT40 MIMO MODE	129
UNII-1 BAND	129
UNII-2A BAND.....	133
UNII-2C BAND.....	137
STRADDLE CHANNEL 142	143
UNII-3 BAND	145
8.3.4. 802.11ac VHT80 MIMO MODE.....	149
UNII-1 BAND	149
UNII-2A BAND.....	151
UNII-2C BAND.....	153
STRADDLE CHANNEL 138	157
UNII-3 BAND	159
8.4. SPURIOUS EMISSIONS (18 GHz ~ 26 GHz).....	161
8.4.1. 802.11n HT40 MODE.....	161
8.5. SPURIOUS EMISSIONS (26 GHz ~ 40 GHz).....	163
8.5.1. 802.11n HT40 MODE.....	163
8.6. SPURIOUS EMISSIONS (30 MHz ~ 1 GHz).....	165
8.6.1. 802.11n HT40 MODE.....	165
8.7. SPURIOUS EMISSIONS BELOW 30 MHz	167
8.7.1. 802.11n HT40 MODE.....	167
9. AC POWER LINE CONDUCTED EMISSIONS	170
9.1. 802.11a MODE.....	171
10. FREQUENCY STABILITY	173



11. DYNAMIC FREQUENCY SELECTION 175

12. ANTENNA REQUIREMENTS..... 179

Appendix..... 180

 Appendix A1: Emission Bandwidth..... 180

 Test Result..... 180

 Test Graphs 182

 Appendix A2: Occupied channel bandwidth.....226

 Test Result.....226

 Test Graphs229

 Appendix A3: Min emission bandwidth.....273

 Test Result.....273

 Test Graphs274

 Appendix B: Maximum conducted output power288

 Test Result.....288

 Appendix C: Maximum power spectral density292

 Test Result.....292

 Test Graphs295

 Appendix D: Duty Cycle 321

 Test Result.....321

 Test Graphs322

 Appendix E FREQUENCY STABILITY 324

 Test Result.....324

 Appendix F DYNAMIC FREQUENCY SELECTION..... 325



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Guangzhou Shirui Electronics Co Ltd
Address: 192 Kezhu Road, Sciencetech Park, guangzhou Economic Technology Development District Guangzhou China

Manufacturer Information

Company Name: Guangzhou Shirui Electronics Co Ltd
Address: 192 Kezhu Road, Sciencetech Park, guangzhou Economic Technology Development District Guangzhou China

EUT Information

EUT Name: WiFi Module
Model: SI07
Sample Received Date: October 29, 2020
Sample Status: Normal
Sample ID: 3437335
Date of Tested: October 29, 2020~ November 28, 2020

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART E	PASS
ISED RSS-247 Issue 2	PASS
ISED RSS-GEN Issue 5	PASS

Prepared By:

Mick Zhang
Project Engineer

Checked By:

Shawn Wen
Laboratory Leader

Approved By:

Stephen Guo
Laboratory Manager



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2013, CFR 47 FCC Part 2, CFR 47 FCC Part 15, KDB 789033 D02 v02r01, RSS-GEN Issue 5, RSS-247 Issue 2, KDB414788 D01 Radiated Test Site v01, KDB 662911 D01 Multiple Transmitter Output v02r01, KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02, KDB 905462 D03 UNII clients without radar detection New Rules v01r02 and KDB 905462 D04 Operational Modes for DFS Testing New Rules v01.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p>A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p>FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p>ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320.</p> <p>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B, the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	---

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognize national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 40 GHz)	5.78 dB (1 GHz-18 GHz)
	5.23dB (18 GHz-26 GHz)
	5.64 dB (26 GHz-40 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95 % confidence level using a coverage factor of k=2.	



5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	WiFi Module		
Model	SI07		
Radio Technology	WLAN (IEEE 802.11a/n HT20/n HT40/ac VHT20/VHT 40/VHT 80)		
Operation frequency	UNII-1: 5150 ~ 5250 MHz UNII-2A: 5250 ~ 5350 MHz UNII-2C: 5470 ~ 5725 MHz UNII-3: 5725 ~ 5850 MHz		
Modulation	IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac VHT20: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac VHT40: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac VHT80: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)		
Power Supply	DC State	Rate Input:	DC 5 V
Wireless Module	SKI.WB8822CU.1		



5.2. MAXIMUM OUTPUT POWER

UNII-1 BAND

IEEE Std. 802.11	Frequency (MHz)	Maximum Average Conducted Power (dBm)	Max Average EIRP (dBm)
a	5150 ~ 5250	15.27	20.15
n HT20		13.52	20.53
n HT40		15.02	22.03
ac VHT20		13.41	20.42
ac VHT40		15.02	22.03
ac VHT80		14.91	21.92

UNII-2A BAND

IEEE Std. 802.11	Frequency (MHz)	Maximum Average Conducted Power (dBm)
a	5250 ~ 5350	15.26
n HT20		18.13
n HT40		17.96
ac VHT20		17.31
ac VHT40		17.06
ac VHT80		17.01

UNII-2C BAND

IEEE Std. 802.11	Frequency (MHz)	Max Power (dBm)
a	5470 ~ 5725	15.57
n HT20		18.44
n HT40		18.47
ac VHT20		17.36
ac VHT40		17.54
ac VHT80		17.46

UNII-3 BAND

IEEE Std. 802.11	Frequency (MHz)	Max Power (dBm)
a	5725 ~ 5850	15.77
n HT20		18.12
n HT40		18.19
ac VHT20		17.25
ac VHT40		17.36
ac VHT80		17.00

**5.3. CHANNEL LIST**

UNII-1 (For Bandwidth = 20 MHz)		UNII-1 (For Bandwidth = 40 MHz)		UNII-1 (For Bandwidth = 80 MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190	42	5210
40	5200	46	5230		
44	5220				
48	5240				

UNII-2A (For Bandwidth = 20 MHz)		UNII-2A (For Bandwidth = 40 MHz)		UNII-2A (For Bandwidth = 80 MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	54	5270	58	5290
56	5280	62	5310		
60	5300				
64	5320				

UNII-2C (For Bandwidth = 20 MHz)		UNII-2C (For Bandwidth = 40 MHz)		UNII-2C (For Bandwidth = 80 MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	102	5510	106	5530
104	5520	110	5550	122	5610
108	5540	118	5590	138	5690
112	5560	126	5630		
116	5580	134	5670		
120	5600	142	5710		
124	5620				
128	5640				
132	5660				
136	5680				
140	5700				
144	5720				

UNII-3 (For Bandwidth = 20 MHz)		UNII-3 (For Bandwidth = 40 MHz)		UNII-3 (For Bandwidth = 80 MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	151	5755	155	5775
153	5765	159	5795		
157	5785				
161	5805				
165	5825				

Note: All channels in the 5600-5650MHz band was not operational in Canada.

**5.4. TEST CHANNEL CONFIGURATION**

UNII-1 Test Channel Configuration		
IEEE Std.	Test Channel Number	Frequency
802.11a	CH 36(Low Channel), CH 40(MID Channel), CH 48(High Channel)	5180 MHz, 5200 MHz, 5240 MHz
802.11n HT20	CH 36(Low Channel), CH 40(MID Channel), CH 48(High Channel)	5180 MHz, 5200 MHz, 5240 MHz
802.11n HT40	CH 38(Low Channel), CH 46(High Channel)	5190 MHz, 5230 MHz
802.11ac VHT20	CH 36(Low Channel), CH 40(MID Channel), CH 48(High Channel)	5180 MHz, 5200 MHz, 5240 MHz
802.11ac VHT40	CH 38(Low Channel), CH 46(High Channel)	5190 MHz, 5230 MHz
802.11ac VHT80	CH 42(Low Channel)	5210 MHz

UNII-2A Test Channel Configuration		
IEEE Std.	Test Channel Number	Frequency
802.11a	CH 52(Low Channel), CH 56(MID Channel), CH 64(High Channel)	5260 MHz, 5280 MHz, 5320 MHz
802.11n HT20	CH 52(Low Channel), CH 56(MID Channel), CH 64(High Channel)	5260 MHz, 5280 MHz, 5320 MHz
802.11n HT40	CH 54(Low Channel), CH 62(High Channel)	5270 MHz, 5310 MHz
802.11ac VHT20	CH 52(Low Channel), CH 56(MID Channel), CH 64(High Channel)	5260 MHz, 5280 MHz, 5320 MHz
802.11ac VHT40	CH 54(Low Channel), CH 62(High Channel)	5270 MHz, 5310 MHz
802.11ac VHT80	CH 58(Low Channel)	5290 MHz

UNII-2C Test Channel Configuration		
IEEE Std.	Test Channel Number	Frequency
802.11a	CH 100(Low Channel), CH 120(MID Channel), CH 140(High Channel)	5500 MHz, 5600 MHz, 5700 MHz
802.11n VHT20	CH 100(Low Channel), CH 120(MID Channel), CH 140(High Channel)	5500 MHz, 5600 MHz, 5700 MHz
802.11n VHT40	CH 102(Low Channel), CH 118(MID Channel), CH 134(High Channel)	5510 MHz, 5590 MHz, 5670 MHz
802.11ac VHT20	CH 100(Low Channel), CH 120(MID Channel), CH 140(High Channel)	5500MHz, 5600 MHz, 5700MHz
802.11ac VHT40	CH 102(Low Channel), CH 118(MID Channel), CH 134(High Channel)	5510 MHz, 5590 MHz, 5670 MHz
802.11ac VHT80	CH 102(Low Channel), CH 122(High Channel)	5530 MHz, 5610 MHz



UNII-3 Test Channel Configuration		
IEEE Std.	Test Channel Number	Frequency
802.11a	CH 149(Low Channel), CH 157(MID Channel), CH 165(High Channel)	5745 MHz, 5785 MHz, 5825 MHz
802.11n HT20	CH 149(Low Channel), CH 157(MID Channel), CH 165(High Channel)	5745 MHz, 5785 MHz, 5825 MHz
802.11n HT40	CH 151(Low Channel), CH 159(High Channel)	5755MHz, 5795MHz
802.11ac VHT20	CH 149(Low Channel), CH 157(MID Channel), CH 165(High Channel)	5745 MHz, 5785 MHz, 5825 MHz
802.11ac VHT40	CH 151(Low Channel), CH 159(High Channel)	5755 MHz, 5795 MHz
802.11ac VHT80	CH 155(Low Channel)	5775 MHz

5.5. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna No.	Frequency (MHz)	Antenna Type	Max Antenna Gain (dBi)
1	5150-5850	FPC antenna	3.01
2	5150-5850	FPC antenna	4.88

Note: Directional gain= $10 \log [(10^{G1/20} + 10^{G2/20})^2 / N_{ANT}] = 7.01 \text{ dBi}$

G_{ANT} : Average of the Antenna Gain

N_{ANT} : Antenna numbers

Note: The value of the antenna gain was declared by customer.

IEE Std. 802.11	Transmit and Receive Mode	Description
802.11a	<input checked="" type="checkbox"/> 2TX, 2RX	ANT 1,2 can be used as transmitting/receiving antenna.
802.11n HT20	<input checked="" type="checkbox"/> 2TX, 2RX	ANT 1,2 can be used as transmitting/receiving antenna.
802.11n HT40	<input checked="" type="checkbox"/> 2TX, 2RX	ANT 1,2 can be used as transmitting/receiving antenna.
802.11ac VHT20	<input checked="" type="checkbox"/> 2TX, 2RX	ANT 1,2 can be used as transmitting/receiving antenna.
802.11ac VHT40	<input checked="" type="checkbox"/> 2TX, 2RX	ANT 1,2 can be used as transmitting/receiving antenna.
802.11ac VHT80	<input checked="" type="checkbox"/> 2TX, 2RX	ANT 1,2 can be used as transmitting/receiving antenna.
Note: 1.WLAN 2.4G & WLAN 5G can't transmit simultaneously. (declared by client)		

**5.6. THE WORSE CASE POWER SETTING PARAMETER**

The Worse Case Power Setting Parameter			
Test Software	MPTool		
Frequency Band	mode	channel	setting

UNII-1

IEEE Std. 802.11	Rate	Channel	Test Software Setting Value	
			ANT 1	ANT 2
a	6M	36	75	81
		40	75	80
		48	75	80
n HT20	MCS0	36	65	70
		40	65	70
		48	65	70
n HT40	MCS0	38	73	73
		46	78	78
ac VHT20	MCS0	36	65	70
		40	65	70
		48	65	70
ac VHT40	MCS0	38	73	78
		46	73	78
ac VHT80	MCS0	42	73	78

UNII-2A

IEEE Std. 802.11	Rate	Channel	Soft set value	
			ANT 1	ANT 2
a	6M	52	79	80
		60	82	82
		64	84	84
n HT20	MCS0	52	91	91
		60	95	95
		64	97	97
n HT40	MCS0	54	94	94
		62	97	97
ac VHT20	MCS0	52	88	88
		60	90	90
		64	91	91
ac VHT40	MCS0	54	89	89
		62	92	92
ac VHT80	MCS0	58	92	92

UNII-2C

IEEE Std. 802.11	Rate	Channel	Soft set value	
			ANT 1	ANT 2
a	6M	100	77	73
		120	68	65
		140	72	68
		144	76	76



n HT20	MCS0	100	85	58
		120	78	78
		140	85	85
		144	85	85
n HT40	MCS0	102	83	83
		118	80	80
		134	85	85
		142	85	85
ac VHT20	MCS0	100	80	80
		120	73	73
		140	80	80
		144	80	80
ac VHT40	MCS0	102	83	83
		118	75	75
		134	80	80
		142	80	80
ac VHT80	MCS0	106	82	82
		122	78	78
		138	78	78

UNII-3

IEEE Std. 802.11	Rate	Channel	Soft set value	
			ANT 1	ANT 2
a	6M	144	76	76
		149	75	75
		157	77	77
		165	78	78
n HT20	MCS0	144	85	85
		149	87	87
		157	90	90
		165	92	92
n HT40	MCS0	142	85	85
		151	88	88
		159	91	91
ac VHT20	MCS0	144	80	80
		149	84	84
		157	85	85
		165	87	87
ac VHT40	MCS0	142	80	80
		151	83	83
		159	86	86
ac VHT80	MCS0	138	78	78
		155	85	85

5.7. THE WORSE CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.6.

Worst case Data Rates declared by the customer:

IEEE 802.11a / SISO – BPSK / 6 Mbps
 IEEE 802.11n HT20 / MIMO – BPSK / MCS0
 IEEE 802.11n HT40 / MIMO – BPSK / MCS0
 IEEE 802.11ac VHT20 / MIMO – BPSK / MCS0
 IEEE 802.11ac VHT40 / MIMO – BPSK / MCS0
 IEEE 802.11ac VHT80 / MIMO – BPSK / MCS0

Since 802.11ac VHT20/VHT40 mode are different from 802.11n HT20/HT40 only in control messages, so all the tests (except conducted output power and power spectral density) were performed on the worst case (802.11n HT20/802.11n HT40) mode between these 4 modes and only the worst data was recorded in this report.

Note: The EUT have two wireless modules, one is called module SKI.WB7668CU.1 and the other one called module SKI.WB8822CU.1.

Simultaneously transmission condition.

Condition	Technology				Support (YES/NO)
1 (Module SKI.WB7668CU.1)	WLAN(2.4G)		WLAN(5G)		NO
2 (Module SKI.WB8822CU.1)	BT	BLE	WLAN(2.4G)	WLAN(5G)	NO

Co-Location condition.

Condition	Technology (Module SKI.WB7668CU.1)	Technology (Module SKI.WB8822CU.1)	Support (YES/NO)
1	WLAN(2.4G)	BT	YES
2	WLAN(2.4G)	BLE	YES
3	WLAN(2.4G)	WLAN (2.4G)	YES
4	WLAN(2.4G)	WLAN (5G)	YES
5	WLAN (5G)	BT	YES
6	WLAN (5G)	BLE	YES
7	WLAN (5G)	WLAN (2.4G)	YES
8	WLAN (5G)	WLAN (5G)	YES

Note: For the Co-Location test result please refer to test report 4789708215-10.

5.8. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	P/N
1	PC	Dell	Vostro 3902	8KNDDDB2

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	Ribbon cable	/	/	1.0	/

ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
/	/	/	/	/

TEST SETUP


The EUT can work in engineering mode with a software through a Laptop.

SETUP DIAGRAM FOR TESTS

For DFS Test:



For the other RF Test:



**6. MEASURING INSTRUMENT AND SOFTWARE USED**

Conducted Emissions						
Instrument						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	EMI Test Receiver	R&S	ESR3	101961	Dec.05,2019	Dec.05,2020
<input checked="" type="checkbox"/>	Two-Line V-Network	R&S	ENV216	101983	Dec.05,2019	Dec.05,2020
Software						
Used	Description	Manufacturer	Name	Version		
<input checked="" type="checkbox"/>	Test Software for Conducted disturbance	Farad	EZ-EMC	Ver. UL-3A1		
Radiated Emissions						
Instrument						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Dec.06,2019	Dec.06,2020
<input checked="" type="checkbox"/>	Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	Sep.17, 2018	Sep.17, 2021
<input checked="" type="checkbox"/>	Preamplifier	HP	8447D	2944A09099	Dec.05,2019	Dec.05,2020
<input checked="" type="checkbox"/>	EMI Measurement Receiver	R&S	ESR26	101377	Dec.05,2019	Dec.05,2020
<input checked="" type="checkbox"/>	Horn Antenna	TDK	HRN-0118	130939	Sep.17, 2018	Sep.17, 2021
<input checked="" type="checkbox"/>	High Gain Horn Antenna	Schwarzbeck	BBHA-9170	691	Aug.11, 2018	Aug.11, 2021
<input checked="" type="checkbox"/>	Preamplifier	TDK	PA-02-0118	TRS-305-00066	Dec.05,2019	Dec.05,2020
<input checked="" type="checkbox"/>	Preamplifier	TDK	PA-02-2	TRS-307-00003	Dec.05,2019	Dec.05,2020
<input checked="" type="checkbox"/>	Preamplifier	TDK	PA-02-3	TRS-308-00002	Dec.05,2019	Dec.05,2020
<input checked="" type="checkbox"/>	Loop antenna	Schwarzbeck	1519B	00008	Jan.07, 2019	Jan.07, 2022
<input checked="" type="checkbox"/>	Band Reject Filter	Wainwright	WRCJV12-5695-5725-5850-5880-40SS	4	Dec.05,2019	Dec.05,2020
<input checked="" type="checkbox"/>	Band Reject Filter	Wainwright	WRCJV20-5120-5150-5350-5380-60SS	2	Dec.05,2019	Dec.05,2020
<input checked="" type="checkbox"/>	Band Reject Filter	Wainwright	WRCJV20-5440-5470-5725-5755-60SS	1	Dec.05,2019	Dec.05,2020
<input checked="" type="checkbox"/>	Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Dec.05,2019	Dec.05,2020



<input checked="" type="checkbox"/>	High Pass Filter	Wainwright	WHKX10-5850-6500-1800-40SS	4	Dec.05,2019	Dec.05,2020
Software						
Used	Description	Manufacturer		Name	Version	
<input checked="" type="checkbox"/>	Test Software for Radiated disturbance	Farad		EZ-EMC	Ver. UL-3A1	
Other instruments						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	Spectrum Analyzer	Keysight	N9030A	MY55410512	Dec.06,2019	Dec.06,2020
<input checked="" type="checkbox"/>	Power sensor, Power Meter	R&S	OSP120	100921	Dec.06,2019	Dec.06,2020
<input checked="" type="checkbox"/>	Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Dec.06,2019	Dec.06,2020
<input checked="" type="checkbox"/>	DC power supply	Array	3662A	A1512015	Dec.05,2019	Dec.05,2020
<input checked="" type="checkbox"/>	Power sensor, Power Meter	R&S	OSP120	100921	Mar.13,2020	Mar.13,2021
<input checked="" type="checkbox"/>	Vector Signal Generator	R&S	SMBV100A	261637	Dec.06,2019	Dec.06,2020
<input checked="" type="checkbox"/>	Signal Generator	R&S	SMB100A	178553	Dec.06,2019	Dec.06,2020
<input checked="" type="checkbox"/>	Signal Analyzer	R&S	FSV40	A1512015	Dec.06,2019	Dec.06,2020
<input checked="" type="checkbox"/>	Attenuator	Weinschel	3M-10	T9692	Dec.06,2019	Dec.06,2020
Software						
Used	Description	Manufacturer		Name	Version	
<input checked="" type="checkbox"/>	Test Software for RF Conducted Test	Tonscend		JS1120-3 RF Test System	2.6.77.0518	
<input checked="" type="checkbox"/>	Test Software for DFS Test	R&S		EMC 32	10.60.10	

7. ANTENNA PORT TEST RESULTS

7.1. ON TIME AND DUTY CYCLE

LIMITS


None; for reporting purposes only.

PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.B.

The zero-span mode on a spectrum analyzer or EMI receiver, if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set $RBW \geq EBW$ if possible; otherwise, set RBW to the largest available value. Set $VBW \geq RBW$. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$, where T is defined in II.B.1.a), and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

TEST SETUP



TEST ENVIRONMENT

Temperature	27.3 °C	Relative Humidity	47.8 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V

RESULTS

Please refer to appendix D.

7.2. 6/26 dB EMISSION BANDWIDTH AND 99 % OCCUPIED BANDWIDTH

LIMITS

CFR 47 FCC Part15, Subpart E ISED RSS-247 ISSUE 2		
Test Item	Limit	Frequency Range (MHz)
26 dB Emission Bandwidth	For reporting purposes only.	5150 ~ 5250
26 dB Emission Bandwidth	For reporting purposes only.	5250 ~ 5350
26 dB Emission Bandwidth	For reporting purposes only.	5470 ~ 5725 (For FCC) 5470 ~ 5600 (For ISED) 5650 ~ 5725 (For ISED)
6 dB Emission Bandwidth	The minimum 6 dB emission bandwidth shall be 500 kHz.	5725 ~ 5850
99 % Occupied Bandwidth	For reporting purposes only.	5150 ~ 5825 (For ISED)

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.C1. for 26 dB Emission Bandwidth; section II.C2. for 6 dB Emission Bandwidth; section II.D. for 99 % Occupied Bandwidth.

Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	For 6 dB Emission Bandwidth: RBW=100 kHz For 26 dB Emission bandwidth: approximately 1 % of the EBW. For 99 % Occupied Bandwidth: approximately 1 % ~ 5 % of the OBW.
VBW	For 6 dB Bandwidth: $\geq 3 \times \text{RBW}$ For 26 dB Bandwidth: $>3 \times \text{RBW}$ For 99 % Bandwidth: $>3 \times \text{RBW}$
Trace	Max hold
Sweep	Auto couple

- a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.
- b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6/26 dB relative to the maximum level measured in the fundamental emission.

Calculation for 99 % Bandwidth of UNII-2C and UNII-3 Straddle Channel:

For Example: Fundamental Frequency: 5720 MHz

99 % OBW: 21.00 MHz

Turning Frequency: 5725 MHz

99 % Bandwidth of UNII-2C Band Portion = $(5725-(5720-(21.00/2))) = 15.50$ MHz

99 % Bandwidth of UNII-3 Band Portion = $(5720+(21.00/2)-5725) = 5.50$ MHz

Calculation for 26 dB Bandwidth of UNII-2C Straddle Channel:

For Example: Fundamental frequency: 5720 MHz

26 dB BW: 20.00 MHz

FL: 5710.16 MHz

FH: 5730.16 MHz

Turning Frequency: 5725 MHz

26 dB Bandwidth of UNII-2C Band Portion = $5725-5710.16=14.84$ MHz

Calculation for 6dB Bandwidth of UNII-3 Straddle Channel:

For Example: Fundamental frequency: 5720 MHz

6 dB BW: 16.44 MHz


FL: 5711.76 MHz

FH: 5728.2 MHz

Turning Frequency: 5725 MHz

6 dB Bandwidth of UNII-3 band Portion = $5728.2-5725=3.2$ MHz

TEST SETUP



TEST ENVIRONMENT

Temperature	27.3 °C	Relative Humidity	47.8 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V

RESULTS

Please refer to Appendix A1&A2&A3.



7.3. CONDUCTED OUTPUT POWER

LIMITS

CFR 47 FCC Part15, Subpart E		
Test Item	Limit	Frequency Range (MHz)
Conducted Output Power	<input type="checkbox"/> Outdoor Access Point: 1 W (30 dBm) <input type="checkbox"/> Indoor Access Point: 1 W (30 dBm) <input type="checkbox"/> Fixed Point-To-Point Access Points: 1 W (30 dBm) <input checked="" type="checkbox"/> Client Devices: 250 mW (24 dBm)	5150 ~ 5250
	Shall not exceed the lesser of 250 mW (24dBm) or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz.	5250 ~ 5350 5470 ~ 5725
	Shall not exceed 1 Watt (30 dBm).	5725 ~ 5850

ISED RSS-247 ISSUE 2		
Test Item	Limit	Frequency Range (MHz)
Conducted Output Power or e.i.r.p.	The maximum e.i.r.p. shall not exceed 200 mW (23 dBm) or 10 + 10 log ₁₀ B, dBm, whichever power is less. B is the 99 % emission bandwidth in megahertz.	5150 ~ 5250
	a. The maximum conducted output power shall not exceed 250 mW (24 dBm) or 11 + 10 log ₁₀ B dBm, whichever is less. b. The maximum e.i.r.p. shall not exceed 1.0 W (30 dBm) or 17 + 10 log ₁₀ B dBm, whichever is less. B is the 99 % emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.	5250 ~ 5350 5470 ~ 5600 5650 ~ 5725
	Shall not exceed 1 Watt (30 dBm). The e.i.r.p. shall not exceed 4 W	5725 ~ 5850

Note:

The above limits are based upon the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.E.

Method SA-1 (trace averaging with the EUT transmitting at full power throughout each sweep):

- (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- (ii) Set RBW = 1 MHz.
- (iii) Set VBW \geq 3 MHz.
- (iv) Number of points in sweep $\geq 2 \times$ span / RBW. (This ensures that bin-to-bin spacing is \leq RBW/2, so that narrowband signals are not lost between frequency bins.)
- (v) Sweep time = auto.
- (vi) Detector = power averaging (rms), if available. Otherwise, use sample detector mode.
- (vii) If transmit duty cycle $<$ 98 %, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle \geq 98 %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run.”
- (viii) Trace average at least 100 traces in power averaging (rms) mode.
- (ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument’s band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

Method PM (Measurement using an RF average power meter):

- (i) Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the following conditions are satisfied:
 - a. The EUT is configured to transmit continuously or to transmit with a constant duty cycle.
 - b. At all times when the EUT is transmitting, it must be transmitting at its maximum power control level.
 - c. The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- (ii) If the transmitter does not transmit continuously, measure the duty cycle, x , of the transmitter output signal as described in II.B.
- (iii) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
- (iv) Adjust the measurement in dBm by adding $10 \log (1/x)$ where x is the duty cycle (e.g., $10 \log (1/0.25)$ if the duty cycle is 25 %).


Method PM-G (Measurement using a gated RF average power meter):

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

Straddle channel power was measured using spectrum analyzer.



TEST SETUP



TEST ENVIRONMENT

Temperature	27.3 °C	Relative Humidity	47.8 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V

RESULTS

Please refer to Appendix B.



7.4. POWER SPECTRAL DENSITY

LIMITS

CFR 47 FCC Part15, Subpart E		
Test Item	Limit	Frequency Range (MHz)
Power Spectral Density	<input type="checkbox"/> Outdoor Access Point: 17 dBm/MHz <input type="checkbox"/> Indoor Access Point: 17 dBm/MHz <input type="checkbox"/> Fixed Point-To-Point Access Points: 17 dBm/MHz <input checked="" type="checkbox"/> Client Devices: 11 dBm/MHz	5150 ~ 5250
	11 dBm/MHz	5250 ~ 5350 5470 ~ 5725
	30 dBm/500kHz	5725 ~ 5850

ISED RSS-247 ISSUE 2		
Test Item	Limit	Frequency Range (MHz)
Power Spectral Density	The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.	5150 ~ 5250
	The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.	5250 ~ 5350 5470 ~ 5600 5650 ~ 5725
	30 dBm / 500 kHz	5725 ~ 5850

Note:

The above limits are based upon the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.F.

Connect the EUT to the spectrum analyser and use the following settings:

For U-NII-1, U-NII-2A and U-NII-2C band:

Center Frequency	The center frequency of the channel under test
Detector	RMS
RBW	1 MHz
VBW	$\geq 3 \times \text{RBW}$
Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Max hold
Sweep time	Auto


For U-NII-3:

Center Frequency	The center frequency of the channel under test
Detector	RMS
RBW	500 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Max hold
Sweep time	Auto

Allow trace to fully stabilize and Use the peak search function on the instrument to find the peak of the spectrum and record its value.

Add $10 \log(1/x)$, where x is the duty cycle, to the peak of the spectrum, the result is the Maximum PSD over 1 MHz / 500 kHz reference bandwidth.

TEST SETUP



TEST ENVIRONMENT

Temperature	27.3 °C	Relative Humidity	47.8 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V

RESULTS

Please refer to Appendix C.

8. RADIATED TEST RESULTS

LIMITS

Refer to CFR 47 FCC §15.205, §15.209 and §15.407 (b).

Refer to ISED RSS-GEN Clause 8.9, Clause 8.10 and ISED RSS-247 6.2.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) (µA/m)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

ISED Restricted bands refer to ISED RSS-GEN Clause 8.10

Table 7 – Restricted frequency bands^{Note 1}

MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.89475 - 16.89525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5480	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c




Limits of unwanted/undesirable emission out of the restricted bands refer to CFR 47 FCC §15.407 (b) and ISED RSS-247 6.2.

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1GHz)		
Frequency Range (MHz)	EIRP Limit	Field Strength Limit (dBuV/m) at 3 m
5150~5250 MHz	PK: -27 (dBm/MHz)	PK:68.2(dBμV/m)
5250~5350 MHz		
5470~5725 MHz		
5725~5850 MHz	PK: -27 (dBm/MHz) *1 PK: 10 (dBm/MHz) *2 PK: 15.6 (dBm/MHz) *3 PK: 27 (dBm/MHz) *4	PK: 68.2(dBμV/m) *1 PK: 105.2 (dBμV/m) *2 PK: 110.8(dBμV/m) *3 PK: 122.2 (dBμV/m) *4
<p>Note:</p> <p>*1 beyond 75 MHz or more above of the band edge.</p> <p>*2 below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above.</p> <p>*3 below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above.</p> <p>*4 from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.</p>		

TEST SETUP AND PROCEDURE

Below 30 MHz




The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 11.11.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

Below 1 GHz and above 30 MHz




The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 11.11.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1 GHz




The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.G.3 ~ II.G.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (1.5 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1.ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

Note 2: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

TEST ENVIRONMENT

Temperature	24.9 °C	Relative Humidity	57 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V

RESULTS




8.1. RESTRICTED BANDEDGE

8.1.1. 802.11a SISO MODE

UNII-1 BAND

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)


PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4842.370	17.79	39.42	57.21	74.00	-16.79	peak
2	5150.000	15.08	40.46	55.54	74.00	-18.46	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4842.370	2.40	39.42	41.82	54.00	-12.18	AVG
2	5150.000	2.64	40.46	43.10	54.00	-10.90	AVG


- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. AVG: $VBW=1/T_{on}$, where: T_{on} is the transmitting duration.
 4. For the transmitting duration, please refer to clause 7.1.
 5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



UNII-2A BAND

RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)


PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	23.95	40.64	64.59	74.00	-9.41	peak
2	5350.880	24.30	40.64	64.94	74.00	-9.06	peak

- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	5.04	40.64	45.68	54.00	-8.32	AVG
2	5350.880	4.62	40.64	45.26	54.00	-8.74	AVG


- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
 4. For the transmitting duration, please refer to clause 7.1.
 5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



UNII-2C BAND

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)


PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5447.740	17.38	41.13	58.51	74.00	-15.49	peak
2	5460.000	15.86	41.28	57.14	68.20	-11.06	peak
3	5466.820	17.40	41.37	58.77	68.20	-9.43	peak
4	5470.000	16.58	41.41	57.99	68.20	-10.21	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5447.740	2.52	41.13	43.65	54.00	-10.35	AVG
2	5460.000	2.44	41.28	43.72	54.00	-10.28	AVG
3	5466.820	2.94	41.37	44.31	68.20	-23.89	AVG
4	5470.000	3.31	41.41	44.72	68.20	-23.48	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
 4. For the transmitting duration, please refer to clause 7.1.
 5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	16.09	41.61	57.70	68.20	-10.50	peak
2	5869.000	18.06	43.25	61.31	68.20	-6.89	peak

- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

UNII-3 BAND

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5639.360	17.73	41.48	59.21	68.20	-8.99	peak
2	5725.000	21.84	41.61	63.45	122.20	-58.75	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	16.58	42.89	59.47	122.20	-62.73	peak
2	5946.680	18.56	43.06	61.62	68.20	-6.58	peak


- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

8.1.2. 802.11n HT20 MIMO MODE

UNII-1 BAND

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)


PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.950	17.83	39.44	57.27	74.00	-16.73	peak
2	5150.000	15.57	40.46	56.03	74.00	-17.97	peak

- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.950	2.64	39.44	42.08	54.00	-11.92	AVG
2	5150.000	2.33	40.46	42.79	54.00	-11.21	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. AVG: $VBW=1/T_{on}$, where: T_{on} is the transmitting duration.
 4. For the transmitting duration, please refer to clause 7.1.
 5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

UNII-2A BAND

RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)


PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	26.39	40.64	67.03	74.00	-6.97	peak
2	5354.240	27.90	40.63	68.53	74.00	-5.47	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	8.82	40.64	49.46	54.00	-4.54	AVG
2	5354.240	7.79	40.63	48.42	54.00	-5.58	AVG


- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. AVG: $VBW=1/T_{on}$, where: T_{on} is the transmitting duration.
 4. For the transmitting duration, please refer to clause 7.1.
 5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



UNII-2C BAND

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)


PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5450.980	17.07	41.17	58.24	74.00	-15.76	peak
2	5460.000	15.50	41.28	56.78	68.20	-11.42	peak
3	5465.380	20.32	41.35	61.67	68.20	-6.53	peak
4	5470.000	19.17	41.41	60.58	68.20	-7.62	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5450.980	2.54	41.17	43.71	54.00	-10.29	AVG
2	5460.000	2.50	41.28	43.78	54.00	-10.22	AVG
3	5465.380	2.97	41.35	44.32	68.20	-23.88	AVG
4	5470.000	3.73	41.41	45.14	68.20	-23.06	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. AVG: $VBW=1/T_{on}$, where: T_{on} is the transmitting duration.
 4. For the transmitting duration, please refer to clause 7.1.
 5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	20.91	41.61	62.52	68.20	-5.68	peak
2	5877.600	18.36	43.42	61.78	68.20	-6.42	peak


- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



UNII-3 BAND

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5636.640	17.50	41.47	58.97	68.20	-9.23	peak
2	5725.000	28.29	41.61	69.90	122.20	-52.30	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	20.50	42.89	63.39	122.20	-58.81	peak
2	5952.270	18.33	42.95	61.28	68.20	-6.92	peak


- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

8.1.3. 802.11n HT40 MIMO MODE

UNII-1 BAND

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)


PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	21.94	40.46	62.40	74.00	-11.60	peak

- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	5.35	40.46	45.81	54.00	-8.19	AVG


- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. AVG: $VBW=1/T_{on}$, where: T_{on} is the transmitting duration.
 4. For the transmitting duration, please refer to clause 7.1.
 5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



UNII-2A BAND

RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)


PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	30.46	40.64	71.10	74.00	-2.90	peak
2	5351.280	31.75	40.64	72.39	74.00	-1.61	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	12.00	40.64	52.64	54.00	-1.36	AVG
2	5351.280	11.64	40.64	52.28	54.00	-1.72	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
 4. For the transmitting duration, please refer to clause 7.1.
 5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

UNII-2C BAND

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	37.98	22.15	60.13	68.20	-8.07	peak
2	5462.480	42.38	22.16	64.54	68.20	-3.66	peak
3	5470.000	42.84	22.21	65.05	68.20	-3.15	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	24.79	22.15	46.94	54.00	-7.06	AVG
2	5462.480	25.33	22.16	47.49	68.20	-20.71	AVG
3	5470.000	28.77	22.21	50.98	68.20	-17.22	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
 4. For the transmitting duration, please refer to clause 7.1.
 5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	15.93	41.61	57.54	68.20	-10.66	peak
2	5759.280	18.21	41.75	59.96	68.20	-8.24	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

UNII-3 BAND

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5604.320	17.44	41.47	58.91	68.20	-9.29	peak
2	5725.000	28.33	41.61	69.94	122.20	-52.26	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	16.71	42.89	59.60	122.20	-62.60	peak
2	5948.480	18.12	43.02	61.14	68.20	-7.06	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




8.1.4. 802.11ac VHT80 MIMO MODE

UNII-1 BAND

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)


PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	18.73	40.46	59.19	74.00	-14.81	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	5.40	40.46	45.86	54.00	-8.14	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
 4. For the transmitting duration, please refer to clause 7.1.
 5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

UNII-2A BAND

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	23.95	40.64	64.59	74.00	-9.41	peak

- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	9.50	40.64	50.14	54.00	-3.86	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
 4. For the transmitting duration, please refer to clause 7.1.
 5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

UNII-2C BAND

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	41.22	22.15	63.37	68.20	-4.83	peak
2	5468.220	42.69	22.20	64.89	68.20	-3.31	peak
3	5470.000	42.01	22.21	64.22	68.20	-3.98	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	28.26	22.15	50.41	54.00	-3.59	AVG
2	5468.220	29.86	22.20	52.06	68.20	-16.14	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
 4. For the transmitting duration, please refer to clause 7.1.
 5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	15.94	41.61	57.55	68.20	-10.65	peak
2	5829.700	18.33	42.50	60.83	68.20	-7.37	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



UNII-3 BAND

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBUV)	Correct (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	5611.200	17.50	41.46	58.96	68.20	-9.24	peak
2	5725.000	24.91	41.61	66.52	122.20	-55.68	peak
3	5850.000	19.55	42.89	62.44	122.20	-59.76	peak
4	5936.400	18.27	43.22	61.49	68.20	-6.71	peak


Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

8.2. SPURIOUS EMISSIONS (1 GHz ~ 7 GHz)

8.2.1. 802.11a SISO MODE

UNII-3 BAND


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2008.000	55.42	-10.21	45.21	74.00	-28.79	peak
2	2674.000	54.32	-7.71	46.61	74.00	-27.39	peak
3	3988.000	41.67	-3.72	37.95	74.00	-36.05	peak
4	4756.000	40.73	0.26	40.99	74.00	-33.01	peak
5	5745.000	47.27	1.96	49.23	74.00	-24.77	peak
6	6754.000	35.64	4.45	40.09	74.00	-33.91	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1066.000	55.93	-13.73	42.20	74.00	-31.80	peak
2	1996.000	51.36	-10.24	41.12	74.00	-32.88	peak
3	2134.000	53.13	-9.53	43.60	74.00	-30.40	peak
4	2998.000	46.29	-6.08	40.21	74.00	-33.79	peak
5	4012.000	45.56	-3.62	41.94	74.00	-32.06	peak
6	5745.000	44.77	1.96	46.73	74.00	-27.27	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2008.000	55.12	-10.21	44.91	74.00	-29.09	peak
2	2140.000	50.30	-9.51	40.79	74.00	-33.21	peak
3	2680.000	54.02	-7.68	46.34	74.00	-27.66	peak
4	4666.000	40.46	-0.25	40.21	74.00	-33.79	peak
5	5785.000	42.60	1.95	44.55	74.00	-29.45	peak
6	6376.000	37.12	3.34	40.46	74.00	-33.54	peak


Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1066.000	55.97	-13.73	42.24	74.00	-31.76	peak
2	2008.000	51.90	-10.21	41.69	74.00	-32.31	peak
3	2128.000	52.27	-9.56	42.71	74.00	-31.29	peak
4	2998.000	46.81	-6.08	40.73	74.00	-33.27	peak
5	4012.000	45.84	-3.62	42.22	74.00	-31.78	peak
6	5785.000	43.00	1.95	44.95	74.00	-29.05	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1060.000	50.38	-13.76	36.62	74.00	-37.38	peak
2	2008.000	54.77	-10.21	44.56	74.00	-29.44	peak
3	2140.000	50.26	-9.51	40.75	74.00	-33.25	peak
4	2680.000	54.30	-7.68	46.62	74.00	-27.38	peak
5	5825.000	46.36	2.03	48.39	74.00	-25.61	peak
6	6814.000	35.79	4.48	40.27	74.00	-33.73	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1066.000	56.10	-13.73	42.37	74.00	-31.63	peak
2	1996.000	51.28	-10.24	41.04	74.00	-32.96	peak
3	2122.000	51.80	-9.60	42.20	74.00	-31.80	peak
4	2998.000	46.93	-6.08	40.85	74.00	-33.15	peak
5	4012.000	45.81	-3.62	42.19	74.00	-31.81	peak
6	5825.000	46.17	2.03	48.20	74.00	-25.80	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


Note: All the modes, bands and antennas had been tested, but only the worst data was recorded in the report.

8.3. SPURIOUS EMISSIONS (7 GHz ~ 18 GHz)

8.3.1. 802.11a SISO MODE

UNII-1 BAND


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9376.000	37.44	9.79	47.23	74.00	-26.77	peak
2	10608.000	36.04	12.39	48.43	74.00	-25.57	peak
3	11631.000	36.25	13.38	49.63	74.00	-24.37	peak
4	13809.000	32.36	16.99	49.35	74.00	-24.65	peak
5	15998.000	31.94	17.80	49.74	74.00	-24.26	peak
6	17615.000	29.55	21.96	51.51	74.00	-22.49	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7836.000	38.24	7.96	46.20	74.00	-27.80	peak
2	10355.000	38.02	11.23	49.25	74.00	-24.75	peak
3	11598.000	35.52	13.54	49.06	74.00	-24.94	peak
4	13809.000	32.59	16.99	49.58	74.00	-24.42	peak
5	15536.000	33.62	16.75	50.37	74.00	-23.63	peak
6	17076.000	30.59	20.82	51.41	74.00	-22.59	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8111.000	37.14	8.21	45.35	74.00	-28.65	peak
2	10102.000	36.38	10.78	47.16	74.00	-26.84	peak
3	11400.000	35.93	12.74	48.67	74.00	-25.33	peak
4	13776.000	32.55	16.84	49.39	74.00	-24.61	peak
5	14788.000	33.59	16.08	49.67	74.00	-24.33	peak
6	16691.000	31.39	20.02	51.41	74.00	-22.59	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8936.000	38.37	8.95	47.32	74.00	-26.68	peak
2	10399.000	38.86	11.17	50.03	74.00	-23.97	peak
3	11499.000	35.45	13.35	48.80	74.00	-25.20	peak
4	13886.000	33.33	16.30	49.63	74.00	-24.37	peak
5	15591.000	33.43	17.07	50.50	74.00	-23.50	peak
6	17032.000	30.59	20.72	51.31	74.00	-22.69	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9376.000	37.38	9.79	47.17	74.00	-26.83	peak
2	10608.000	36.03	12.39	48.42	74.00	-25.58	peak
3	11499.000	35.14	13.35	48.49	74.00	-25.51	peak
4	13864.000	33.57	16.48	50.05	74.00	-23.95	peak
5	15987.000	31.46	17.79	49.25	74.00	-24.75	peak
6	17076.000	30.90	20.82	51.72	74.00	-22.28	peak


Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9343.000	37.30	9.57	46.87	74.00	-27.13	peak
2	10476.000	39.87	11.31	51.18	74.00	-22.82	peak
3	12588.000	36.23	14.27	50.50	74.00	-23.50	peak
4	13908.000	33.90	16.16	50.06	74.00	-23.94	peak
5	15063.000	33.44	16.01	49.45	74.00	-24.55	peak
6	16427.000	32.20	19.37	51.57	74.00	-22.43	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

UNII-2A BAND
HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9574.000	37.29	9.66	46.95	74.00	-27.05	peak
2	10619.000	36.19	12.32	48.51	74.00	-25.49	peak
3	12566.000	34.35	14.42	48.77	74.00	-25.23	peak
4	13798.000	32.95	17.05	50.00	74.00	-24.00	peak
5	14810.000	33.56	16.07	49.63	74.00	-24.37	peak
6	17065.000	30.61	20.79	51.40	74.00	-22.60	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10520.000	37.72	11.57	49.29	74.00	-24.71	peak
2	11499.000	35.96	13.35	49.31	74.00	-24.69	peak
3	12687.000	34.84	14.40	49.24	74.00	-24.76	peak
4	13809.000	32.98	16.99	49.97	74.00	-24.03	peak
5	15602.000	32.61	17.11	49.72	74.00	-24.28	peak
6	17065.000	30.48	20.79	51.27	74.00	-22.73	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9354.000	36.61	9.64	46.25	74.00	-27.75	peak
2	10564.000	39.31	12.06	51.37	74.00	-22.63	peak
3	12533.000	34.36	14.65	49.01	74.00	-24.99	peak
4	13831.000	33.34	16.79	50.13	74.00	-23.87	peak
5	14755.000	33.56	16.13	49.69	74.00	-24.31	peak
6	16460.000	31.48	19.49	50.97	74.00	-23.03	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9277.000	37.56	9.21	46.77	74.00	-27.23	peak
2	10553.000	38.10	11.93	50.03	74.00	-23.97	peak
3	12599.000	35.26	14.19	49.45	74.00	-24.55	peak
4	13798.000	33.41	17.05	50.46	74.00	-23.54	peak
5	16438.000	31.89	19.41	51.30	74.00	-22.70	peak
6	16988.000	30.73	20.57	51.30	74.00	-22.70	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7880.000	38.25	7.72	45.97	74.00	-28.03	peak
2	10586.000	36.00	12.30	48.30	74.00	-25.70	peak
3	11521.000	35.55	13.40	48.95	74.00	-25.05	peak
4	14392.000	33.32	16.65	49.97	74.00	-24.03	peak
5	15987.000	31.98	17.79	49.77	74.00	-24.23	peak
6	17098.000	30.51	20.88	51.39	74.00	-22.61	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9365.000	36.35	9.72	46.07	74.00	-27.93	peak
2	10641.000	37.50	12.16	49.66	74.00	-24.34	peak
3	12599.000	34.47	14.19	48.66	74.00	-25.34	peak
4	13864.000	33.43	16.48	49.91	74.00	-24.09	peak
5	15954.000	33.49	17.75	51.24	74.00	-22.76	peak
6	17054.000	30.89	20.76	51.65	74.00	-22.35	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

UNII-2C BAND


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8936.000	37.37	8.95	46.32	74.00	-27.68	peak
2	10366.000	36.34	11.22	47.56	74.00	-26.44	peak
3	11642.000	35.00	13.33	48.33	74.00	-25.67	peak
4	12555.000	34.69	14.49	49.18	74.00	-24.82	peak
5	14821.000	33.59	16.09	49.68	74.00	-24.32	peak
6	16647.000	31.64	19.80	51.44	74.00	-22.56	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9640.000	36.79	9.71	46.50	74.00	-27.50	peak
2	10608.000	35.97	12.39	48.36	74.00	-25.64	peak
3	11356.000	36.24	12.51	48.75	74.00	-25.25	peak
4	13402.000	33.16	16.17	49.33	74.00	-24.67	peak
5	14821.000	33.54	16.09	49.63	74.00	-24.37	peak
6	16493.000	32.29	19.59	51.88	74.00	-22.12	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10102.000	36.45	10.78	47.23	74.00	-26.77	peak
2	11367.000	36.08	12.58	48.66	74.00	-25.34	peak
3	12533.000	34.87	14.65	49.52	74.00	-24.48	peak
4	14777.000	33.93	16.10	50.03	74.00	-23.97	peak
5	15987.000	32.52	17.79	50.31	74.00	-23.69	peak
6	16922.000	31.22	20.22	51.44	74.00	-22.56	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9068.000	37.75	9.45	47.20	74.00	-26.80	peak
2	11367.000	36.03	12.58	48.61	74.00	-25.39	peak
3	13545.000	33.58	15.98	49.56	74.00	-24.44	peak
4	14216.000	34.08	16.49	50.57	74.00	-23.43	peak
5	16449.000	31.91	19.45	51.36	74.00	-22.64	peak
6	16801.000	31.77	20.19	51.96	74.00	-22.04	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.




HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10333.000	36.60	11.25	47.85	74.00	-26.15	peak
2	11499.000	36.15	13.35	49.50	74.00	-24.50	peak
3	13083.000	33.67	15.32	48.99	74.00	-25.01	peak
4	14645.000	34.04	16.11	50.15	74.00	-23.85	peak
5	15987.000	32.00	17.79	49.79	74.00	-24.21	peak
6	17263.000	29.94	21.64	51.58	74.00	-22.42	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9750.000	36.54	9.91	46.45	74.00	-27.55	peak
2	10597.000	35.27	12.43	47.70	74.00	-26.30	peak
3	12533.000	34.77	14.65	49.42	74.00	-24.58	peak
4	13611.000	33.76	16.10	49.86	74.00	-24.14	peak
5	14766.000	34.13	16.11	50.24	74.00	-23.76	peak
6	16801.000	31.66	20.19	51.85	74.00	-22.15	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

STRADDLE CHANNEL 144

ANTENNA 1 TEST RESULTS (WORST CASE)


HARMONICS AND SPURIOUS EMISSIONS (HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8837.000	37.62	8.43	46.05	74.00	-27.95	peak
2	9398.000	37.98	9.93	47.91	74.00	-26.09	peak
3	11510.000	35.87	13.39	49.26	74.00	-24.74	peak
4	13853.000	33.73	16.59	50.32	74.00	-23.68	peak
5	16438.000	31.25	19.41	50.66	74.00	-23.34	peak
6	17604.000	29.58	21.89	51.47	74.00	-22.53	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

HARMONICS AND SPURIOUS EMISSIONS (VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9464.000	36.88	9.82	46.70	74.00	-27.30	peak
2	10586.000	35.99	12.30	48.29	74.00	-25.71	peak
3	11367.000	36.14	12.58	48.72	74.00	-25.28	peak
4	13798.000	32.97	17.05	50.02	74.00	-23.98	peak
5	14854.000	33.86	16.13	49.99	74.00	-24.01	peak
6	16977.000	30.99	20.51	51.50	74.00	-22.50	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

UNII-3 BAND

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8958.000	36.65	9.10	45.75	74.00	-28.25	peak
2	10443.000	36.31	11.25	47.56	74.00	-26.44	peak
3	11499.000	35.15	13.35	48.50	74.00	-25.50	peak
4	13853.000	32.65	16.59	49.24	74.00	-24.76	peak
5	16438.000	31.89	19.41	51.30	74.00	-22.70	peak
6	17285.000	29.59	21.79	51.38	74.00	-22.62	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.




HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9354.000	37.07	9.64	46.71	74.00	-27.29	peak
2	10069.000	36.48	10.59	47.07	74.00	-26.93	peak
3	11499.000	35.36	13.35	48.71	74.00	-25.29	peak
4	13809.000	32.16	16.99	49.15	74.00	-24.85	peak
5	15910.000	32.06	17.70	49.76	74.00	-24.24	peak
6	17219.000	29.81	21.34	51.15	74.00	-22.85	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9024.000	36.90	9.40	46.30	74.00	-27.70	peak
2	10388.000	36.64	11.18	47.82	74.00	-26.18	peak
3	11521.000	35.47	13.40	48.87	74.00	-25.13	peak
4	12896.000	34.47	15.14	49.61	74.00	-24.39	peak
5	14766.000	33.73	16.11	49.84	74.00	-24.16	peak
6	16438.000	31.98	19.41	51.39	74.00	-22.61	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9387.000	36.75	9.86	46.61	74.00	-27.39	peak
2	11356.000	35.99	12.51	48.50	74.00	-25.50	peak
3	12632.000	35.09	14.27	49.36	74.00	-24.64	peak
4	13908.000	34.48	16.16	50.64	74.00	-23.36	peak
5	16020.000	31.61	17.91	49.52	74.00	-24.48	peak
6	16900.000	31.84	20.10	51.94	74.00	-22.06	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9376.000	36.15	9.79	45.94	74.00	-28.06	peak
2	10564.000	35.91	12.06	47.97	74.00	-26.03	peak
3	12456.000	33.92	14.54	48.46	74.00	-25.54	peak
4	13050.000	34.57	15.20	49.77	74.00	-24.23	peak
5	14777.000	33.21	16.10	49.31	74.00	-24.69	peak
6	17021.000	30.29	20.69	50.98	74.00	-23.02	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9761.000	36.12	9.92	46.04	74.00	-27.96	peak
2	10553.000	35.81	11.93	47.74	74.00	-26.26	peak
3	12742.000	34.76	15.16	49.92	74.00	-24.08	peak
4	14370.000	33.26	16.59	49.85	74.00	-24.15	peak
5	16471.000	31.59	19.52	51.11	74.00	-22.89	peak
6	16933.000	30.80	20.28	51.08	74.00	-22.92	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

8.3.2. 802.11n HT20 MIMO MODE

UNII-1 BAND


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9376.000	36.80	9.79	46.59	74.00	-27.41	peak
2	10608.000	35.68	12.39	48.07	74.00	-25.93	peak
3	12665.000	34.16	14.35	48.51	74.00	-25.49	peak
4	13798.000	32.65	17.05	49.70	74.00	-24.30	peak
5	16009.000	32.01	17.85	49.86	74.00	-24.14	peak
6	17098.000	30.40	20.88	51.28	74.00	-22.72	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9783.000	36.10	9.95	46.05	74.00	-27.95	peak
2	10817.000	36.35	11.80	48.15	74.00	-25.85	peak
3	12665.000	34.29	14.35	48.64	74.00	-25.36	peak
4	13864.000	32.38	16.48	48.86	74.00	-25.14	peak
5	15998.000	32.00	17.80	49.80	74.00	-24.20	peak
6	16790.000	31.27	20.18	51.45	74.00	-22.55	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7836.000	36.76	7.96	44.72	74.00	-29.28	peak
2	10102.000	35.61	10.78	46.39	74.00	-27.61	peak
3	11499.000	35.62	13.35	48.97	74.00	-25.03	peak
4	13864.000	32.99	16.48	49.47	74.00	-24.53	peak
5	16460.000	30.79	19.49	50.28	74.00	-23.72	peak
6	17032.000	30.46	20.72	51.18	74.00	-22.82	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9354.000	36.26	9.64	45.90	74.00	-28.10	peak
2	10608.000	35.49	12.39	47.88	74.00	-26.12	peak
3	11378.000	35.69	12.63	48.32	74.00	-25.68	peak
4	13908.000	32.76	16.16	48.92	74.00	-25.08	peak
5	16427.000	31.46	19.37	50.83	74.00	-23.17	peak
6	17274.000	29.48	21.71	51.19	74.00	-22.81	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9365.000	37.25	9.72	46.97	74.00	-27.03	peak
2	10597.000	35.71	12.43	48.14	74.00	-25.86	peak
3	11752.000	35.81	13.15	48.96	74.00	-25.04	peak
4	13853.000	32.86	16.59	49.45	74.00	-24.55	peak
5	15195.000	33.15	16.14	49.29	74.00	-24.71	peak
6	17076.000	30.48	20.82	51.30	74.00	-22.70	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9354.000	36.67	9.64	46.31	74.00	-27.69	peak
2	10586.000	35.48	12.30	47.78	74.00	-26.22	peak
3	12588.000	34.36	14.27	48.63	74.00	-25.37	peak
4	14425.000	32.84	16.65	49.49	74.00	-24.51	peak
5	15998.000	31.54	17.80	49.34	74.00	-24.66	peak
6	17032.000	31.72	20.72	52.44	74.00	-21.56	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

UNII-2A BAND


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9387.000	35.99	9.86	45.85	74.00	-28.15	peak
2	10520.000	36.75	11.57	48.32	74.00	-25.68	peak
3	11499.000	35.29	13.35	48.64	74.00	-25.36	peak
4	13897.000	33.21	16.20	49.41	74.00	-24.59	peak
5	16460.000	31.54	19.49	51.03	74.00	-22.97	peak
6	16999.000	30.96	20.64	51.60	74.00	-22.40	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9156.000	36.18	9.15	45.33	74.00	-28.67	peak
2	10520.000	40.31	11.57	51.88	74.00	-22.12	peak
3	12588.000	34.85	14.27	49.12	74.00	-24.88	peak
4	13523.000	33.79	15.94	49.73	74.00	-24.27	peak
5	16471.000	30.91	19.52	50.43	74.00	-23.57	peak
6	17186.000	30.76	21.16	51.92	74.00	-22.08	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9365.000	36.81	9.72	46.53	74.00	-27.47	peak
2	10553.000	38.58	11.93	50.51	74.00	-23.49	peak
3	12599.000	34.36	14.19	48.55	74.00	-25.45	peak
4	13875.000	33.20	16.39	49.59	74.00	-24.41	peak
5	16020.000	31.49	17.91	49.40	74.00	-24.60	peak
6	17274.000	29.33	21.71	51.04	74.00	-22.96	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9365.000	36.18	9.72	45.90	74.00	-28.10	peak
2	10564.000	39.02	12.06	51.08	74.00	-22.92	peak
3	11499.000	34.87	13.35	48.22	74.00	-25.78	peak
4	13589.000	33.32	16.08	49.40	74.00	-24.60	peak
5	15833.000	33.92	17.35	51.27	74.00	-22.73	peak
6	16845.000	31.14	20.15	51.29	74.00	-22.71	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.




HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7836.000	37.26	7.96	45.22	74.00	-28.78	peak
2	9376.000	36.74	9.79	46.53	74.00	-27.47	peak
3	10630.000	36.90	12.25	49.15	74.00	-24.85	peak
4	13611.000	33.54	16.10	49.64	74.00	-24.36	peak
5	15965.000	33.18	17.76	50.94	74.00	-23.06	peak
6	17087.000	30.31	20.85	51.16	74.00	-22.84	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9464.000	36.86	9.82	46.68	74.00	-27.32	peak
2	10641.000	39.31	12.16	51.47	74.00	-22.53	peak
3	12610.000	34.46	14.21	48.67	74.00	-25.33	peak
4	14777.000	34.63	16.10	50.73	74.00	-23.27	peak
5	15965.000	32.57	17.76	50.33	74.00	-23.67	peak
6	16746.000	31.36	20.11	51.47	74.00	-22.53	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

UNII-2C BAND


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9365.000	37.04	9.72	46.76	74.00	-27.24	peak
2	11499.000	35.21	13.35	48.56	74.00	-25.44	peak
3	12588.000	34.74	14.27	49.01	74.00	-24.99	peak
4	13886.000	33.58	16.30	49.88	74.00	-24.12	peak
5	16438.000	30.43	19.41	49.84	74.00	-24.16	peak
6	17219.000	29.92	21.34	51.26	74.00	-22.74	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9387.000	36.41	9.86	46.27	74.00	-27.73	peak
2	11004.000	35.89	12.63	48.52	74.00	-25.48	peak
3	11499.000	35.15	13.35	48.50	74.00	-25.50	peak
4	13534.000	34.21	15.97	50.18	74.00	-23.82	peak
5	14700.000	33.23	16.23	49.46	74.00	-24.54	peak
6	16504.000	32.49	19.61	52.10	74.00	-21.90	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9057.000	35.64	9.44	45.08	74.00	-28.92	peak
2	10113.000	36.36	10.74	47.10	74.00	-26.90	peak
3	11367.000	35.82	12.58	48.40	74.00	-25.60	peak
4	12764.000	33.50	15.54	49.04	74.00	-24.96	peak
5	14348.000	32.76	16.51	49.27	74.00	-24.73	peak
6	17208.000	30.24	21.26	51.50	74.00	-22.50	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9134.000	36.43	9.28	45.71	74.00	-28.29	peak
2	10542.000	36.50	11.83	48.33	74.00	-25.67	peak
3	12698.000	34.65	14.44	49.09	74.00	-24.91	peak
4	13611.000	32.71	16.10	48.81	74.00	-25.19	peak
5	15613.000	31.99	17.09	49.08	74.00	-24.92	peak
6	16812.000	30.96	20.18	51.14	74.00	-22.86	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7847.000	37.68	7.91	45.59	74.00	-28.41	peak
2	10619.000	34.76	12.32	47.08	74.00	-26.92	peak
3	11356.000	35.54	12.51	48.05	74.00	-25.95	peak
4	13622.000	33.01	16.08	49.09	74.00	-24.91	peak
5	15580.000	32.28	17.00	49.28	74.00	-24.72	peak
6	17054.000	30.73	20.76	51.49	74.00	-22.51	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7836.000	37.00	7.96	44.96	74.00	-29.04	peak
2	9662.000	36.47	9.77	46.24	74.00	-27.76	peak
3	11499.000	34.90	13.35	48.25	74.00	-25.75	peak
4	13457.000	33.31	16.02	49.33	74.00	-24.67	peak
5	14755.000	33.00	16.13	49.13	74.00	-24.87	peak
6	17087.000	31.80	20.85	52.65	74.00	-21.35	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

STRADDLE CHANNEL 144

ANTENNA 1 TEST RESULTS (WORST CASE)

HARMONICS AND SPURIOUS EMISSIONS (HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9464.000	37.18	9.82	47.00	74.00	-27.00	peak
2	10608.000	35.06	12.39	47.45	74.00	-26.55	peak
3	12511.000	33.72	14.80	48.52	74.00	-25.48	peak
4	14766.000	32.91	16.11	49.02	74.00	-24.98	peak
5	16812.000	30.81	20.18	50.99	74.00	-23.01	peak
6	17714.000	28.89	22.62	51.51	74.00	-22.49	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.



HARMONICS AND SPURIOUS EMISSIONS (VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9178.000	37.21	9.02	46.23	74.00	-27.77	peak
2	10553.000	35.41	11.93	47.34	74.00	-26.66	peak
3	12533.000	33.48	14.65	48.13	74.00	-25.87	peak
4	13853.000	32.69	16.59	49.28	74.00	-24.72	peak
5	15998.000	32.18	17.80	49.98	74.00	-24.02	peak
6	17164.000	30.07	21.09	51.16	74.00	-22.84	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

UNII-3 BAND


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9332.000	36.45	9.51	45.96	74.00	-28.04	peak
2	10311.000	36.47	11.29	47.76	74.00	-26.24	peak
3	12698.000	34.02	14.44	48.46	74.00	-25.54	peak
4	14392.000	33.22	16.65	49.87	74.00	-24.13	peak
5	16020.000	31.04	17.91	48.95	74.00	-25.05	peak
6	17098.000	29.90	20.88	50.78	74.00	-23.22	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9376.000	36.33	9.79	46.12	74.00	-27.88	peak
2	11488.000	35.20	13.29	48.49	74.00	-25.51	peak
3	13523.000	33.22	15.94	49.16	74.00	-24.84	peak
4	14766.000	32.99	16.11	49.10	74.00	-24.90	peak
5	16449.000	31.35	19.45	50.80	74.00	-23.20	peak
6	17252.000	30.42	21.56	51.98	74.00	-22.02	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7836.000	36.91	7.96	44.87	74.00	-29.13	peak
2	9354.000	37.33	9.64	46.97	74.00	-27.03	peak
3	11510.000	35.32	13.39	48.71	74.00	-25.29	peak
4	14425.000	32.97	16.65	49.62	74.00	-24.38	peak
5	16438.000	30.71	19.41	50.12	74.00	-23.88	peak
6	17351.000	31.91	21.71	53.62	74.00	-20.38	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9387.000	35.98	9.86	45.84	74.00	-28.16	peak
2	10608.000	36.50	12.39	48.89	74.00	-25.11	peak
3	12863.000	33.43	15.50	48.93	74.00	-25.07	peak
4	14227.000	33.01	16.47	49.48	74.00	-24.52	peak
5	16416.000	31.00	19.33	50.33	74.00	-23.67	peak
6	17329.000	29.75	21.78	51.53	74.00	-22.47	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9365.000	36.52	9.72	46.24	74.00	-27.76	peak
2	10432.000	36.36	11.23	47.59	74.00	-26.41	peak
3	11598.000	35.30	13.54	48.84	74.00	-25.16	peak
4	13798.000	33.08	17.05	50.13	74.00	-23.87	peak
5	14678.000	32.98	16.18	49.16	74.00	-24.84	peak
6	16856.000	31.28	20.13	51.41	74.00	-22.59	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9475.000	36.13	9.80	45.93	74.00	-28.07	peak
2	10597.000	35.33	12.43	47.76	74.00	-26.24	peak
3	12687.000	34.57	14.40	48.97	74.00	-25.03	peak
4	13908.000	33.23	16.16	49.39	74.00	-24.61	peak
5	16053.000	31.00	18.10	49.10	74.00	-24.90	peak
6	17065.000	31.14	20.79	51.93	74.00	-22.07	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

8.3.3. 802.11n HT40 MIMO MODE

UNII-1 BAND


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9387.000	36.36	9.86	46.22	74.00	-27.78	peak
2	10564.000	36.78	12.06	48.84	74.00	-25.16	peak
3	12533.000	34.50	14.65	49.15	74.00	-24.85	peak
4	13919.000	33.52	16.16	49.68	74.00	-24.32	peak
5	15998.000	31.72	17.80	49.52	74.00	-24.48	peak
6	17087.000	30.80	20.85	51.65	74.00	-22.35	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10564.000	35.55	12.06	47.61	74.00	-26.39	peak
2	11499.000	35.81	13.35	49.16	74.00	-24.84	peak
3	12544.000	34.47	14.57	49.04	74.00	-24.96	peak
4	13919.000	33.76	16.16	49.92	74.00	-24.08	peak
5	14810.000	33.22	16.07	49.29	74.00	-24.71	peak
6	16845.000	31.23	20.15	51.38	74.00	-22.62	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9332.000	37.74	9.51	47.25	74.00	-26.75	peak
2	10993.000	35.73	12.58	48.31	74.00	-25.69	peak
3	11620.000	35.11	13.44	48.55	74.00	-25.45	peak
4	13908.000	34.01	16.16	50.17	74.00	-23.83	peak
5	14821.000	33.31	16.09	49.40	74.00	-24.60	peak
6	17032.000	30.72	20.72	51.44	74.00	-22.56	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10311.000	35.52	11.29	46.81	74.00	-27.19	peak
2	11367.000	36.65	12.58	49.23	74.00	-24.77	peak
3	12698.000	34.38	14.44	48.82	74.00	-25.18	peak
4	13919.000	34.26	16.16	50.42	74.00	-23.58	peak
5	15987.000	31.80	17.79	49.59	74.00	-24.41	peak
6	17054.000	30.87	20.76	51.63	74.00	-22.37	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

UNII-2A BAND

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9145.000	36.68	9.22	45.90	74.00	-28.10	peak
2	10553.000	36.24	11.93	48.17	74.00	-25.83	peak
3	12544.000	34.61	14.57	49.18	74.00	-24.82	peak
4	13809.000	33.58	16.99	50.57	74.00	-23.43	peak
5	15998.000	32.20	17.80	50.00	74.00	-24.00	peak
6	17340.000	29.32	21.74	51.06	74.00	-22.94	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.




HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9376.000	36.44	9.79	46.23	74.00	-27.77	peak
2	10586.000	35.75	12.30	48.05	74.00	-25.95	peak
3	12566.000	34.72	14.42	49.14	74.00	-24.86	peak
4	15173.000	33.68	16.12	49.80	74.00	-24.20	peak
5	15998.000	32.47	17.80	50.27	74.00	-23.73	peak
6	16812.000	30.81	20.18	50.99	74.00	-23.01	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7836.000	37.07	7.96	45.03	74.00	-28.97	peak
2	10124.000	36.06	10.70	46.76	74.00	-27.24	peak
3	11367.000	36.29	12.58	48.87	74.00	-25.13	peak
4	13567.000	32.88	16.03	48.91	74.00	-25.09	peak
5	14667.000	33.37	16.16	49.53	74.00	-24.47	peak
6	17098.000	30.62	20.88	51.50	74.00	-22.50	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7814.000	37.06	8.10	45.16	74.00	-28.84	peak
2	9926.000	36.23	10.25	46.48	74.00	-27.52	peak
3	11719.000	34.99	13.09	48.08	74.00	-25.92	peak
4	13864.000	33.53	16.48	50.01	74.00	-23.99	peak
5	15965.000	31.54	17.76	49.30	74.00	-24.70	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.



UNII-2C BAND


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9354.000	36.74	9.64	46.38	74.00	-27.62	peak
2	10399.000	37.33	11.17	48.50	74.00	-25.50	peak
3	11378.000	36.23	12.63	48.86	74.00	-25.14	peak
4	13512.000	33.49	15.92	49.41	74.00	-24.59	peak
5	14799.000	34.47	16.06	50.53	74.00	-23.47	peak
6	17076.000	30.74	20.82	51.56	74.00	-22.44	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8980.000	36.46	9.23	45.69	74.00	-28.31	peak
2	10608.000	35.96	12.39	48.35	74.00	-25.65	peak
3	11862.000	35.72	13.35	49.07	74.00	-24.93	peak
4	13820.000	32.63	16.89	49.52	74.00	-24.48	peak
5	15602.000	32.83	17.11	49.94	74.00	-24.06	peak
6	17164.000	30.20	21.09	51.29	74.00	-22.71	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.




HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9200.000	36.97	8.89	45.86	74.00	-28.14	peak
2	10256.000	36.94	10.91	47.85	74.00	-26.15	peak
3	12291.000	34.43	14.16	48.59	74.00	-25.41	peak
4	13798.000	32.29	17.05	49.34	74.00	-24.66	peak
5	15943.000	31.71	17.73	49.44	74.00	-24.56	peak
6	17087.000	30.20	20.85	51.05	74.00	-22.95	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8111.000	37.87	8.21	46.08	74.00	-27.92	peak
2	10388.000	36.17	11.18	47.35	74.00	-26.65	peak
3	11521.000	35.42	13.40	48.82	74.00	-25.18	peak
4	13556.000	33.29	16.01	49.30	74.00	-24.70	peak
5	14744.000	34.20	16.16	50.36	74.00	-23.64	peak
6	17076.000	30.00	20.82	50.82	74.00	-23.18	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9365.000	37.28	9.72	47.00	74.00	-27.00	peak
2	11499.000	35.19	13.35	48.54	74.00	-25.46	peak
3	12533.000	34.39	14.65	49.04	74.00	-24.96	peak
4	14425.000	33.10	16.65	49.75	74.00	-24.25	peak
5	16438.000	31.57	19.41	50.98	74.00	-23.02	peak
6	17032.000	30.34	20.72	51.06	74.00	-22.94	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8848.000	37.21	8.48	45.69	74.00	-28.31	peak
2	10311.000	36.17	11.29	47.46	74.00	-26.54	peak
3	12698.000	34.73	14.44	49.17	74.00	-24.83	peak
4	13611.000	33.76	16.10	49.86	74.00	-24.14	peak
5	15987.000	31.73	17.79	49.52	74.00	-24.48	peak
6	17076.000	31.40	20.82	52.22	74.00	-21.78	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

STRADDLE CHANNEL 142

ANTENNA 1 TEST RESULTS (WORST CASE)


HARMONICS AND SPURIOUS EMISSIONS (HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9123.000	35.83	9.35	45.18	74.00	-28.82	peak
2	10597.000	35.35	12.43	47.78	74.00	-26.22	peak
3	11598.000	35.33	13.54	48.87	74.00	-25.13	peak
4	14403.000	32.44	16.68	49.12	74.00	-24.88	peak
5	15998.000	31.66	17.80	49.46	74.00	-24.54	peak
6	16900.000	31.12	20.10	51.22	74.00	-22.78	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

HARMONICS AND SPURIOUS EMISSIONS (VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8958.000	36.36	9.10	45.46	74.00	-28.54	peak
2	10102.000	36.81	10.78	47.59	74.00	-26.41	peak
3	12599.000	34.36	14.19	48.55	74.00	-25.45	peak
4	14777.000	33.43	16.10	49.53	74.00	-24.47	peak
5	16438.000	32.12	19.41	51.53	74.00	-22.47	peak
6	16845.000	31.47	20.15	51.62	74.00	-22.38	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.



UNII-3 BAND


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9431.000	35.99	9.87	45.86	74.00	-28.14	peak
2	10597.000	35.43	12.43	47.86	74.00	-26.14	peak
3	12599.000	34.41	14.19	48.60	74.00	-25.40	peak
4	13798.000	32.23	17.05	49.28	74.00	-24.72	peak
5	15987.000	31.45	17.79	49.24	74.00	-24.76	peak
6	17263.000	29.83	21.64	51.47	74.00	-22.53	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9343.000	36.42	9.57	45.99	74.00	-28.01	peak
2	10553.000	36.06	11.93	47.99	74.00	-26.01	peak
3	12544.000	34.51	14.57	49.08	74.00	-24.92	peak
4	14194.000	32.90	16.49	49.39	74.00	-24.61	peak
5	16449.000	31.32	19.45	50.77	74.00	-23.23	peak
6	17076.000	30.86	20.82	51.68	74.00	-22.32	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.


HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9057.000	36.88	9.44	46.32	74.00	-27.68	peak
2	9354.000	36.98	9.64	46.62	74.00	-27.38	peak
3	11642.000	34.95	13.33	48.28	74.00	-25.72	peak
4	13512.000	33.57	15.92	49.49	74.00	-24.51	peak
5	15987.000	31.44	17.79	49.23	74.00	-24.77	peak
6	16922.000	31.13	20.22	51.35	74.00	-22.65	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8969.000	35.87	9.18	45.05	74.00	-28.95	peak
2	9761.000	36.85	9.92	46.77	74.00	-27.23	peak
3	11609.000	34.51	13.50	48.01	74.00	-25.99	peak
4	14447.000	33.18	16.63	49.81	74.00	-24.19	peak
5	16438.000	31.41	19.41	50.82	74.00	-23.18	peak
6	17032.000	30.97	20.72	51.69	74.00	-22.31	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

8.3.4. 802.11ac VHT80 MIMO MODE

UNII-1 BAND

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9145.000	37.15	9.22	46.37	74.00	-27.63	peak
2	10454.000	36.45	11.27	47.72	74.00	-26.28	peak
3	11543.000	34.94	13.44	48.38	74.00	-25.62	peak
4	12533.000	34.47	14.65	49.12	74.00	-24.88	peak
5	15206.000	33.17	16.14	49.31	74.00	-24.69	peak
6	17032.000	30.30	20.72	51.02	74.00	-22.98	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.



HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9365.000	37.29	9.72	47.01	74.00	-26.99	peak
2	10498.000	36.16	11.35	47.51	74.00	-26.49	peak
3	12797.000	32.37	16.12	48.49	74.00	-25.51	peak
4	14656.000	33.37	16.13	49.50	74.00	-24.50	peak
5	15998.000	31.85	17.80	49.65	74.00	-24.35	peak
6	16845.000	31.00	20.15	51.15	74.00	-22.85	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

UNII-2A BAND


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9640.000	36.35	9.71	46.06	74.00	-27.94	peak
2	11092.000	35.33	12.65	47.98	74.00	-26.02	peak
3	12764.000	33.28	15.54	48.82	74.00	-25.18	peak
4	14700.000	34.30	16.23	50.53	74.00	-23.47	peak
5	16482.000	30.67	19.56	50.23	74.00	-23.77	peak
6	17076.000	30.23	20.82	51.05	74.00	-22.95	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9585.000	36.36	9.65	46.01	74.00	-27.99	peak
2	10586.000	35.86	12.30	48.16	74.00	-25.84	peak
3	12566.000	34.46	14.42	48.88	74.00	-25.12	peak
4	14810.000	33.97	16.07	50.04	74.00	-23.96	peak
5	16438.000	31.65	19.41	51.06	74.00	-22.94	peak
6	17065.000	31.05	20.79	51.84	74.00	-22.16	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.

UNII-2C BAND

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10102.000	36.07	10.78	46.85	74.00	-27.15	peak
2	11048.000	35.16	12.65	47.81	74.00	-26.19	peak
3	12599.000	34.85	14.19	49.04	74.00	-24.96	peak
4	13809.000	33.12	16.99	50.11	74.00	-23.89	peak
5	16449.000	30.91	19.45	50.36	74.00	-23.64	peak
6	17230.000	29.83	21.41	51.24	74.00	-22.76	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.
 6. Owing to the highest peak level of unwanted emission out of the restricted bands are lower than the line(54dBuV/m) in the graph, so all the peak test point was deemed to comply with the limits -27dBm/MHz (68.2dBuV/m) list in the standard.