



■ Report No.: DDT-R22062203-2E03

■ Issued Date: Sep. 21, 2022

FCC CERTIFICATION TEST REPORT

FOR

Applicant	:	Guangzhou Shirui Electronics Co., Ltd
Address	:	192 Kezhu Road, Sciencetech Park, Guangzhou Economic Technology Development District, Guangzhou, China
Equipment under Test	:	Integrated video conference terminal
Model No.	:	UC S15, MS*****(*=0-9,A-Z or blank), UC S*****(*=0-9,A-Z or blank)
Trade Mark	:	MAXHUB
FCC ID	:	2AFG6-UCS15
Manufacturer	:	Guangzhou Shirui Electronics Co., Ltd
Address	:	192 Kezhu Road, Sciencetech Park, Guangzhou Economic Technology Development District, Guangzhou, China

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,
Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

TABLE OF CONTENTS

	Test report declares.....	4
1.	Summary of test results	6
2.	General test information.....	7
2.1.	Description of EUT	7
2.2.	Accessories of EUT.....	7
2.3.	Assistant equipment used for test.....	8
2.4.	Block diagram of EUT configuration for test	8
2.5.	Deviations of test standard.....	8
2.6.	Test environment conditions	9
2.7.	Test laboratory	9
2.8.	Measurement uncertainty.....	9
3.	Equipment used during test	10
4.	6dB Bandwidth and 99% Bandwidth.....	11
4.1.	Block diagram of test setup.....	11
4.2.	Limits	11
4.3.	Test Procedure.....	11
4.4.	Test Result	12
4.5.	original test data	13
5.	Conducted peak Output Power.....	26
5.1.	Block diagram of test setup.....	26
5.2.	Limits	26
5.3.	Test Procedure.....	26
5.4.	Test Result	26
6.	Power Spectral Density.....	28
6.1.	Block diagram of test setup.....	28
6.2.	Limits	28
6.3.	Test Procedure.....	28
6.4.	Test Result	28
6.5.	original test data	29
7.	Band Edge Compliance (Conducted Method)	36
7.1.	Block diagram of test setup.....	36
7.2.	Limits	36
7.3.	Test procedure	36
7.4.	Test Result	36
7.5.	original test data	37
8.	Conducted Spurious Emissions (Conducted Method).....	42
8.1.	Block diagram of test setup.....	42

8.2.	Limits	42
8.3.	Test procedure	42
8.4.	Test Result	43
8.5.	original test data	43
9.	Radiated Spurious Emissions	62
9.1.	Block diagram of test setup	62
9.2.	Limit	63
9.3.	Test Procedure	64
9.4.	Test result	66
10.	Radiated Band Edge Compliance	81
10.1.	Block diagram of test setup	81
10.2.	Limit	81
10.3.	Test Procedure	81
10.4.	Test result	81
11.	Power Line Conducted Emission	106
11.1.	Block diagram of test setup	106
11.2.	Power Line Conducted Emission Limits (Class B)	106
11.3.	Test Procedure	106
11.4.	Test Result	107
12.	Antenna Requirements	110
12.1.	Limit	110
12.2.	Result	110
13.	Test setup photograph	111
14.	Photos of the EUT	113

TEST REPORT DECLARE

Applicant	:	Guangzhou Shirui Electronics Co., Ltd
Address	:	192 Kezhu Road, Sciencetech Park, Guangzhou Economic Technology Development District, Guangzhou, China
Equipment under Test	:	Integrated video conference terminal
Model No	:	UC S15, MS*****(*=0-9,A-Z or blank), UC S*****(*=0-9,A-Z or blank)
Trade Mark	:	MAXHUB
Manufacturer	:	Guangzhou Shirui Electronics Co., Ltd
Address	:	192 Kezhu Road, Sciencetech Park, Guangzhou Economic Technology Development District, Guangzhou, China

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C

Test procedure used:

ANSI C63.10:2013, 558074 D01 15.247 Meas Guidance v05r02

We Declare:

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC standards.

Report No:	DDT-R22062203-2E03		
Date of Receipt:	Aug. 02, 2022	Date of Test:	Aug. 02, 2022 ~ Sep. 20, 2022

Prepared By:

Johnny Wang

Johnny Wang/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Sep. 21, 2022	

1. Summary of test results

The EUT have been tested according to the applicable standards as referenced below.		
Description of Test Item	Standard	Results
6dB Bandwidth and 99% Bandwidth	FCC Part 15: 15.247 ANSI C63.10:2013	Pass
Conducted Output Power	FCC Part 15: 15.247 ANSI C63.10:2013	Pass
Power Spectral Density	FCC Part 15:15.247 ANSI C63.10:2013	Pass
Band-edge and Spurious Emissions (Conducted)	FCC Part 15: 15.209 FCC Part 15: 15.247 ANSI C63.10: 2013	Pass
Radiated Spurious Emissions	FCC Part 15: 15.247 ANSI C63.10:2013	Pass
Radiated Band Edge Compliance	FCC Part 15: 15.209 FCC Part 15: 15.247 ANSI C63.10: 2013	Pass
Power Line Conducted Emission	FCC Part 15: 15.207 ANSI C63.10: 2013	Pass
Antenna requirement	FCC Part 15: 15.203	Pass

2. General test information

2.1. Description of EUT

EUT* Name	: Integrated video conference terminal
Model Number	: UC S15, MS*****(*=0-9,A-Z or blank), UC S*****(*=0-9,A-Z or blank)
Difference of models	: Above models are identical in schematic and structure, only the name is different for all the models, therefore the test performed on the model UC S15.
EUT function description	: Please reference user manual of this device
Power supply	: Input: 100-240V ~ 50/60Hz
Radio Technology	: IEEE 802.11b/g/n/ax
FCC Operation frequency	: IEEE 802.11b: 2412MHz—2462MHz IEEE 802.11g: 2412MHz—2462MHz IEEE 802.11n HT20: 2412MHz—2462MHz IEEE 802.11n HT40: 2422MHz—2452MHz IEEE 802.11ax HE20: 2412MHz—2462MHz IEEE 802.11ax HE40: 2422MHz—2452MHz
Modulation	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20, HT40: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax HE20, HE40: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Transmitter rate	: IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps IEEE 802.11n HT20: up to 72.2 Mbps IEEE 802.11n HT40: up to 150 Mbps IEEE 802.11ax HE20: up to 143.4 Mbps IEEE 802.11ax HE40: up to 286.8 Mbps
Antenna Gain	: PCB antenna, maximum PK gain: 3.9 dBi
Sample Number	: S22062203-01 for conductive S22062203-02 for radiation

Note: EUT is the ab. of equipment under test.

Channel information					
CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447	/	/

2.2. Accessories of EUT

Assistant equipment	Manufacturer	Model number	Other
Switching adapter	Dong Guan City GangQi Electronic	GQ36-120300-AX	Input: 100-240V ~ 50/60Hz 1A MAX

	Co., Ltd.		Output: DC 12V3A 36W
HDMI cable	N/A	N/A	Length: 1.6m
Remote control	N/A	N/A	N/A
Type-C cable	N/A	N/A	Length: 3.0m

2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	EMC Compliance	SN
N/A	N/A	N/A	N/A	N/A

2.4. Block diagram of EUT configuration for test



Test software: SecureCRTPortable.exe

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table:

The pathloss of external cable: 0.5dB (According to the manufacturer's claims)

Tested mode, channel, setting Tx power and rand data rate information

Mode	Setting Tx Power	data rate (Mbps) (see Note)	Channel	Frequency (MHz)
	ANT1			
Tx mode 802.11b	/	1	LCH: CH1	2412
	/	1	MCH: CH6	2437
	/	1	HCH: CH11	2462
Tx mode 802.11g	/	6	LCH: CH1	2412
	/	6	MCH: CH6	2437
	/	6	HCH: CH11	2462
Tx mode 802.11n HT20	/	MCS 0	LCH: CH1	2412
	/	MCS 0	MCH: CH6	2437
	/	MCS 0	HCH: CH11	2462
Tx mode 802.11n HT40	/	MCS 0	LCH: CH3	2422
	/	MCS 0	MCH: CH6	2437
	/	MCS 0	HCH: CH9	2452
Tx mode 802.11ax HE20	/	MCS 0	LCH: CH1	2412
	/	MCS 0	MCH: CH6	2437
	/	MCS 0	HCH: CH11	2462
Tx mode 802.11ax HE40	/	MCS 0	LCH: CH3	2422
	/	MCS 0	MCH: CH6	2437
	/	MCS 0	HCH: CH9	2452

Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.

2.5. Deviations of test standard

No Deviation

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+21 °C to +25 °C
Humidity range:	40% to 75%
Pressure range:	86 kPa to 106 kPa

2.7. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2.8. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86 dB (10 MHz ≤ f < 3.6 GHz);
	1.38 dB (3.6 GHz ≤ f < 8 GHz)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB (10 MHz ≤ f < 3.6 GHz);
	1.38 dB (3.6 GHz ≤ f < 8 GHz)
Frequencies Stability	6.7 × 10 ⁻⁸ (Antenna couple method)
	5.5 × 10 ⁻⁸ (Conducted method)
Conducted spurious emissions	0.86 dB (10 MHz ≤ f < 3.6 GHz);
	1.40 dB (3.6 GHz ≤ f < 8 GHz)
	1.66 dB (8 GHz ≤ f < 22 GHz)
Uncertainty for radio frequency (RBW < 20 kHz)	3 × 10 ⁻⁸
Temperature	0.4 °C
Humidity	2%
Uncertainty for Radiation Emission test (30 MHz-1 GHz)	4.70 dB (Antenna Polarize: V)
	4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz-40 GHz)	4.10 dB (1-6 GHz)
	4.40 dB (6 GHz-18 GHz)
	3.54 dB (18 GHz-26 GHz)
	4.30 dB (26 GHz-40 GHz)
Uncertainty for Power line conduction emission test	3.32 dB (150 kHz-30 MHz)


Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. Equipment used during test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
☑RF Connected Test (Tonscend RF Measurement System 3#)					
SPECTRUM ANALYZER	R&S	FSV40	101407	Jul. 21, 2022	1 Year
Wideband Radio Communication tester	R&S	CMW500	117491	May 18, 2022	1 Year
Vector Signal Generator	Agilent	N5182A	MY19060405	May 18, 2022	1 Year
Vector Signal Generator	Agilent	N5182A	MY48180912	May 18, 2022	1 Year
RF Control Unit	Tonsend	JS0806-2	DDT-ZC01449	May 18, 2022	1 Year
Temp&Humi Programmable	ZHIXIANG	ZXGDJS-150L	ZX170110-A	May 26, 2022	1 Year
Test Software	JS Tonscend	JS1120-3	Ver.2.6.77.0518	N/A	N/A
☑Radiation 3#chamber					
EMI Test Receiver	R&S	ESU	100472	May 18, 2022	1 Year
Spectrum analyzer	Agilent	E4447A	MY50180031	May 18, 2022	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	Sep. 19, 2021	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	01429	Jul. 22, 2022	1 Year
Double Ridged Horn Antenna	Schwarzbeck	BBHA 9120 D	02468	Nov. 29, 2021	1 Year
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	May 06, 2022	1 Year
Pre-amplifier	COM-POWER	PAM-118A	18040084	Sep. 02, 2021	1 Year
Pre-amplifier	COM-POWER	PAM-118A	18040084	Aug. 27, 2022	1 Year
Pre-amplifier	COM-POWER	PAM-840A	461369	Apr. 11, 2022	1 Year
Test software	Audix	E3	V 6.1.1.1	N/A	N/A
☑Power Line Conducted Emissions Test 1#					
Test Receiver	R&S	ESCI	100551	Sep. 02, 2021	1 Year
Test Receiver	R&S	ESCI	100551	Aug. 26, 2022	1 Year
LISN 1	R&S	ENV216	101109	Sep. 07, 2021	1 Year
LISN 1	R&S	ENV216	101109	Aug. 26, 2022	1 Year
LISN 2	R&S	ESH2-Z5	100309	Sep. 07, 2021	1 Year
LISN 2	R&S	ESH2-Z5	100309	Aug. 26, 2022	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	Sep. 02, 2021	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	Aug. 26, 2022	1 Year
CE Cable 1	HUBSER	N/A	W10.01	Sep. 02, 2021	1 Year
CE Cable 1	HUBSER	N/A	W10.01	Aug. 26, 2022	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A

4. 6dB Bandwidth and 99% Bandwidth

4.1. Block diagram of test setup



4.2. Limits

For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz

4.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) 99% Bandwidth set the spectrum analyzer as follows:

RBW:	300 kHz
VBW:	1 MHz
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) 6dB Bandwidth set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(4) Allow the trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.4. Test Result


Test Mode	Test	Ant	6dB Bandwidth [MHz]	Limit [MHz]	Verdict
11B	2412	Ant1	8.04	0.5	Pass
11B	2437	Ant1	8.04	0.5	Pass
11B	2462	Ant1	8.04	0.5	Pass
11G	2412	Ant1	15.12	0.5	Pass
11G	2437	Ant1	16.32	0.5	Pass
11G	2462	Ant1	16.36	0.5	Pass
11N20SISO	2412	Ant1	15.08	0.5	Pass
11N20SISO	2437	Ant1	15.12	0.5	Pass
11N20SISO	2462	Ant1	16.04	0.5	Pass
11N40SISO	2422	Ant1	35.20	0.5	Pass
11N40SISO	2437	Ant1	35.36	0.5	Pass
11N40SISO	2452	Ant1	35.20	0.5	Pass
11AX20SISO	2412	Ant1	15.12	0.5	Pass
11AX20SISO	2437	Ant1	15.12	0.5	Pass
11AX20SISO	2462	Ant1	15.12	0.5	Pass
11AX40SISO	2422	Ant1	35.36	0.5	Pass
11AX40SISO	2437	Ant1	35.20	0.5	Pass
11AX40SISO	2452	Ant1	36.08	0.5	Pass




Test Mode	Test	Ant	99% OBW [MHz]	Limit [MHz]	Verdict
11B	2412	Ant1	12.468	---	Pass
11B	2437	Ant1	12.468	---	Pass
11B	2462	Ant1	12.428	---	Pass
11G	2412	Ant1	16.424	---	Pass
11G	2437	Ant1	16.424	---	Pass
11G	2462	Ant1	16.503	---	Pass
11N20SISO	2412	Ant1	17.582	---	Pass
11N20SISO	2437	Ant1	17.502	---	Pass
11N20SISO	2462	Ant1	17.502	---	Pass
11N40SISO	2422	Ant1	35.964	---	Pass
11N40SISO	2437	Ant1	35.964	---	Pass
11N40SISO	2452	Ant1	36.044	---	Pass
11AX20SISO	2412	Ant1	18.781	---	Pass
11AX20SISO	2437	Ant1	18.861	---	Pass
11AX20SISO	2462	Ant1	18.741	---	Pass
11AX40SISO	2422	Ant1	37.403	---	Pass


11AX40SISO	2437	Ant1	37.403	---	Pass
11AX40SISO	2452	Ant1	37.483	---	Pass

4.5. original test data


6 dB bandwidth:









11N20SISO_Ant1_2412




11N20SISO_Ant1_2437




11N20SISO_Ant1_2462




11N40SISO_Ant1_2422




11N40SISO_Ant1_2437




11N40SISO_Ant1_2452




11AX20SISO_Ant1_2412




11AX20SISO_Ant1_2437




11AX20SISO_Ant1_2462




11AX40SISO_Ant1_2422





11AX40SISO_Ant1_2437




11AX40SISO_Ant1_2452




99% bandwidth:




11B_Ant1_2462




11G_Ant1_2412




11G_Ant1_2437




11G_Ant1_2462




11N20SISO_Ant1_2412




11N20SISO_Ant1_2437




11N20SISO_Ant1_2462





11N40SISO_Ant1_2422



11N40SISO_Ant1_2437






11AX20SISO_Ant1_2462




Date: 31.AUG.2022 14:23:38

11AX40SISO_Ant1_2422




Date: 31.AUG.2022 14:29:17

11AX40SISO_Ant1_2437



Date: 31.AUG.2022 14:30:46



5. Conducted peak Output Power

5.1. Block diagram of test setup

Same as section 4.1

5.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.3. Test Procedure

Connect each EUT's antenna output to power sensor by RF cable and attenuator

Measure the PK output power of each antenna port by power meter.

5.4. Test Result

Test Mode	Test Channel	Ant	Conducted Output Power (dBm)	Limit [dBm]	Verdict
11B	2412	Ant1	17.09	30	Pass
11B	2437	Ant1	16.42	30	Pass
11B	2462	Ant1	16.17	30	Pass
11G	2412	Ant1	13.22	30	Pass
11G	2437	Ant1	12.54	30	Pass
11G	2462	Ant1	12.31	30	Pass
11N20SISO	2412	Ant1	13.10	30	Pass
11N20SISO	2437	Ant1	12.42	30	Pass
11N20SISO	2462	Ant1	12.07	30	Pass
11N40SISO	2422	Ant1	12.53	30	Pass
11N40SISO	2437	Ant1	12.12	30	Pass
11N40SISO	2452	Ant1	12.19	30	Pass
11AX20SISO	2412	Ant1	13.34	30	Pass
11AX20SISO	2437	Ant1	12.47	30	Pass
11AX20SISO	2462	Ant1	12.12	30	Pass
11AX40SISO	2422	Ant1	12.63	30	Pass
11AX40SISO	2437	Ant1	12.12	30	Pass
11AX40SISO	2452	Ant1	12.09	30	Pass

Test Mode	Test Channel	Ant	EIRP (dBm)	Limit [dBm]	Verdict
11B	2412	Ant1	20.99	36	Pass
11B	2437	Ant1	20.32	36	Pass
11B	2462	Ant1	20.07	36	Pass
11G	2412	Ant1	17.12	36	Pass
11G	2437	Ant1	16.44	36	Pass
11G	2462	Ant1	16.21	36	Pass
11N20SISO	2412	Ant1	17.00	36	Pass
11N20SISO	2437	Ant1	16.32	36	Pass
11N20SISO	2462	Ant1	15.97	36	Pass
11N40SISO	2422	Ant1	16.43	36	Pass
11N40SISO	2437	Ant1	16.02	36	Pass
11N40SISO	2452	Ant1	16.09	36	Pass
11AX20SISO	2412	Ant1	17.24	36	Pass
11AX20SISO	2437	Ant1	16.37	36	Pass
11AX20SISO	2462	Ant1	16.02	36	Pass
11AX40SISO	2422	Ant1	16.53	36	Pass
11AX40SISO	2437	Ant1	16.02	36	Pass
11AX40SISO	2452	Ant1	15.99	36	Pass

Note: EIRP (dBm)=Conducted Output Power (dBm)+ Antenna Gain (dBi)

6. Power Spectral Density

6.1. Block diagram of test setup

Same as section 4.1

6.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

6.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:

Center frequency	DTS Channel center frequency
RBW:	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW:	$\geq 3\text{RBW}$
Span	1.5 times the DTS bandwidth
Detector Mode:	RMS
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.


(4) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


6.4. Test Result

Test Mode	Test Channel	Ant	PSD [dBm]	Limit [dBm/3kHz]	Verdict
11B	2412	Ant1	-14.12	8.00	Pass
11B	2437	Ant1	-15.03	8.00	Pass
11B	2462	Ant1	-15.11	8.00	Pass
11G	2412	Ant1	-21.24	8.00	Pass
11G	2437	Ant1	-21.80	8.00	Pass
11G	2462	Ant1	-21.76	8.00	Pass
11N20SISO	2412	Ant1	-21.01	8.00	Pass
11N20SISO	2437	Ant1	-21.43	8.00	Pass
11N20SISO	2462	Ant1	-21.80	8.00	Pass
11N40SISO	2422	Ant1	-22.85	8.00	Pass
11N40SISO	2437	Ant1	-24.24	8.00	Pass
11N40SISO	2452	Ant1	-23.49	8.00	Pass


11AX20SISO	2412	Ant1	-19.11	8.00	Pass
11AX20SISO	2437	Ant1	-20.29	8.00	Pass
11AX20SISO	2462	Ant1	-20.99	8.00	Pass
11AX40SISO	2422	Ant1	-22.96	8.00	Pass
11AX40SISO	2437	Ant1	-24.06	8.00	Pass
11AX40SISO	2452	Ant1	-23.70	8.00	Pass

6.5. original test data







11G_Ant1_2412




11G_Ant1_2437




11G_Ant1_2462




11N20SISO_Ant1_2412




11N20SISO_Ant1_2437




11N20SISO_Ant1_2462




11N40SISO_Ant1_2422




11N40SISO_Ant1_2437




11N40SISO_Ant1_2452




11AX20SISO_Ant1_2412




11AX20SISO_Ant1_2437




11AX20SISO_Ant1_2462




11AX40SISO_Ant1_2422



11AX40SISO_Ant1_2437



11AX40SISO_Ant1_2452



7. Band Edge Compliance (Conducted Method)

7.1. Block diagram of test setup

Same as section 4.1

7.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

7.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Establish a reference level by using the following procedure:


RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold
- (3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
- (4) Then mark the maximum amplitude of all unwanted emissions outside of the authorized frequency band.

7.4. Test Result


EUT Set Mode	CH or Frequency	Result (dBm)	EUT Set Mode	CH or Frequency	Result (dBm)
11b	CH1	Pass	11n HT 40	CH3	Pass
	CH6	Pass		CH6	Pass
	CH11	Pass		CH9	Pass
11g	CH1	Pass	11ax HE 20	CH1	Pass
	CH6	Pass		CH6	Pass
	CH11	Pass		CH11	Pass
11n HT 20	CH1	Pass	11ax HE 40	CH3	Pass
	CH6	Pass		CH6	Pass
	CH11	Pass		CH9	Pass

7.5. original test data







11G_Ant1_High_2462




11N20SISO_Ant1_Low_2412




11N20SISO_Ant1_High_2462



11N40SISO_Ant1_Low_2422



11N40SISO_Ant1_High_2452



11AX20SISO_Ant1_Low_2412

