



■ Report No.: DDT-R22062203-2E27

■ Issued Date: Sep. 21, 2022

## RF EXPOSURE REPORT

### FOR

<b>Applicant</b>	:	Guangzhou Shirui Electronics Co., Ltd
<b>Address</b>	:	192 Kezhu Road, Sciencetech Park, guangzhou Economic Technology Development District, Guangzhou, China
<b>Equipment under Test</b>	:	Integrated video conference terminal
<b>Model No.</b>	:	UC S15, MS*****(*=0-9,A-Z or blank), UC S*****(*=0-9,A-Z or blank)
<b>Trade Mark</b>	:	MAXHUB
<b>FCC ID</b>	:	2AFG6-UCS15
<b>Manufacturer</b>	:	Guangzhou Shirui Electronics Co., Ltd
<b>Address</b>	:	192 Kezhu Road, Sciencetech Park, guangzhou Economic Technology Development District, Guangzhou, China

**Issued By: Dongguan Dongdian Testing Service Co., Ltd.**

**Add.:** No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,  
Dongguan City, Guangdong Province, China, 523808

**Tel.:** +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

# REPORT

### Table of Contents

	Test report declares.....	3
1.	General Information .....	5
1.1.	Description of equipment .....	5
1.2.	Assess laboratory.....	6
2.	RF Exposure Evaluation .....	6
2.1.	Requirement.....	6
2.2.	Calculation method .....	7
2.3.	Estimation result.....	7

## Test Report Declare

<b>Applicant</b>	:	Guangzhou Shirui Electronics Co., Ltd
<b>Address</b>	:	192 Kezhu Road, Scientech Park, Guangzhou Economic Technology Development District, Guangzhou, China
<b>Equipment under Test</b>	:	Integrated video conference terminal
<b>Model No.</b>	:	UC S15, MS*****(*=0-9,A-Z or blank), UC S*****(*=0-9,A-Z or blank)
<b>Trade mark</b>	:	MAXHUB
<b>Manufacturer</b>	:	Guangzhou Shirui Electronics Co., Ltd
<b>Address</b>	:	192 Kezhu Road, Scientech Park, Guangzhou Economic Technology Development District, Guangzhou, China

**Standard Used:** KDB447498 D01 General RF Exposure Guidance v06

**We Declare:**

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these assess.

**After evaluation, our opinion is that the equipment In Accordance with above standard.**

<b>Report No:</b>	DDT-R22062203-2E27		
<b>Date of Receipt:</b>	Aug. 02, 2022	<b>Date of Test:</b>	Aug. 02, 2022 ~ Sep. 20, 2022

**Prepared By:**

*Johnny Wang*

**Johnny Wang/Engineer**

**Approved By:**



**Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

### Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Sep. 21, 2022	

## 1. General Information

### 1.1. Description of equipment

EUT* Name	: Integrated video conference terminal
Model Number	: UC S15, MS*****(*=0-9,A-Z or blank), UC S*****(*=0-9,A-Z or blank)
Difference of models	: Above models are identical in schematic and structure, only the name is different for all the models, therefore the test performed on the model UC S15.
EUT function description	: Please reference user manual of this device
Power supply	: Input: 100-240V ~ 50/60Hz
8800:	
Radio Specification	: Bluetooth V5.1, IEEE802.11b/g/n/a/ac/ax
Operation frequency	: Bluetooth: 2402MHz-2480MHz IEEE802.11b/g/n/a/ac/ax: 2412MHz-2462MHz, 5180MHz-5350MHz, 5500MHz-5700MHz, 5745MHz-5850MHz
Modulation	: Bluetooth: GFSK, $\pi/4$ -DQPSK, 8DPSK IEEE 802.11b: DSSS (CCK, QPSK, BPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20, HT40: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: HT20, HT40: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax HE20, HE40: OFDMA(BPSK,QPSK,16QAM,64QAM,256QAM, 1024QAM)
Transmitter rate	: Bluetooth: 1Mbps, 2Mbps, 3Mbps IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps IEEE 802.11n HT20: up to 72.2 Mbps IEEE 802.11n HT40: up to 150 Mbps IEEE 802.11ac HT20: up to 86.6 Mbps IEEE 802.11ac HT40: up to 200 Mbps IEEE 802.11ax HE20: up to 143.4 Mbps IEEE 802.11ax HE40: up to 286.8 Mbps
Antenna Gain	: Bluetooth Antenna: maximum PK gain: 3.9 dBi 2.4G WIFI maximum PK gain: 3.9 dBi, 5G WIFI maximum PK gain: 5.17 dBi
8822:	
Radio Specification	: IEEE802.11n/ac
Operation frequency	: IEEE802.11n/ac: 2437MHz, 5190MHz
Modulation	: IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: HT40: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Transmitter rate	: IEEE 802.11n HT20: up to 144.4 Mbps IEEE 802.11ac HT40: up to 400 Mbps
Antenna Gain	: ANT1: 2.4G WIFI maximum PK gain: 3.9 dBi, 5G WIFI maximum PK gain: 5.17 dBi ANT2: 2.4G WIFI maximum PK gain: 3.9 dBi, 5G WIFI maximum PK gain: 5.17 dBi
Sample Type	: Series production
Sample Number	: S22062203-01 for conductive S22062203-02 for radiation

## 1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: [ddt@dgddt.com](mailto:ddt@dgddt.com).

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

## 2. RF Exposure Evaluation

### 2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time [E] <sup>2</sup> , [H] <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density



## 2.2. Calculation method

$$E(\text{V/m}) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(\text{mW/cm}^2) = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = Peak RF output power (mW)

**G** = EUT Antenna numeric gain (numeric)=

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance,  $d = 0.2$  m, as well as the gain of the used antenna, the RF power density can be obtained.

## 2.3. Estimation result

8800:

Mode	PK Output power (dBm)	Output power (mW)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
BT	3.47	2.22	3.90	2.45	0.00109	1
BLE	3.44	2.21	3.90	2.45	0.00108	1
2.4G WIFI	17.09	51.17	3.90	2.45	0.02500	1
5G WIFI	15.53	35.73	5.17	3.29	0.02339	1

8822:

Mode	PK Output power (dBm)	Output power (mW)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
2.4G WIFI	17.25	53.09	3.90	2.45	0.02594	1
5G WIFI	11.15	13.03	5.17	3.29	0.00853	1

Worst Simultaneous:

BT(8800)+WIFI(8822)=0.00109/1+0.02594/1=0.02703 < 1

WIFI(8800)+WIFI(8822)=0.02500/1+0.02594/1=0.05094 < 1

Note: The estimation distance is 20 cm

Conclusion: The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

**END OF REPORT**